

REFERENCE	DESIGNATION
PH380-1,5-2S-M	S 1,5KW 7A,150-450VDC/AC220V INPUT AND 0-220V AC OUTPUT
PH380-2,2-2S-M	S 2,2KW 9A,150-450VDC/AC220V INPUT AND 0-220V AC OUTPUT

REFERENCE	DESIGNATION
PH380-4,0-4T	4KW 9A,250-800VDC/AC380V INPUT AND 0-440V AC OUTPUT
PH380-5,5-4T	5,5KW 13A,250-800VDC/AC380V INPUT AND 0-440V AC OUTPUT
PH380-7,5-4T	7,5KW 17A,250-800VDC/AC380V INPUT AND 0-440V AC OUTPUT
PH380-11-4T	11KW 25A,250-800VDC/AC380V INPUT AND 0-440V AC OUTPUT
PH380-15-4T	15KW 32A,250-800VDC/AC380V INPUT AND 0-440V AC OUTPUT
PH380-18-4T	18KW 37A,250-800VDC/AC380V INPUT AND 0-440V AC OUTPUT
PH380-22-4T	22KW 45A,250-800VDC/AC380V INPUT AND 0-440V AC OUTPUT

REFERENCE	DESIGNATION
PH380-30-4T	30KW 60A,250-800VDC/AC380V INPUT AND 0-440V AC OUTPUT
PH380-37-4T	37KW 75A,250-800VDC/AC380V INPUT AND 0-440V AC OUTPUT
PH380-45-4T	45KW 91A,250-800VDC/AC380V INPUT AND 0-440V AC OUTPUT
PH380-55-4T	55KW 110A,250-800VDC/AC380V INPUT AND 0-440V AC OUTPUT
PH380-75-4T	75KW 150A,250-800VDC/AC380V INPUT AND 0-440V AC OUTPUT

