

# HEPTACHLOR

HTC

CAUTIONARY RESPONSE INFORMATION				4. FIRE HAZARDS	7. SHIPPING INFORMATION
Common Synonyms E3314 1,4,5,6,7,8a- Heptachlorodicyclopentadiene Velsicol	Solid Sinks in water.	White to light tan Camphor-like odor		<p><b>4.1 Flash Point:</b> Not flammable</p> <p><b>4.2 Flammable Limits in Air:</b> Not flammable</p> <p><b>4.3 Fire Extinguishing Agents:</b> Not pertinent</p> <p><b>4.4 Fire Extinguishing Agents Not to Be Used:</b> Not pertinent</p> <p><b>4.5 Special Hazards of Combustion Products:</b> Irritating hydrogen chloride fumes may form in fire.</p> <p><b>4.6 Behavior in Fire:</b> Currently not available</p> <p><b>4.7 Auto Ignition Temperature:</b> Not pertinent</p> <p><b>4.8 Electrical Hazards:</b> Not pertinent</p> <p><b>4.9 Burning Rate:</b> Not pertinent</p> <p><b>4.10 Adiabatic Flame Temperature:</b> Currently not available</p> <p><b>4.11 Stoichiometric Air to Fuel Ratio:</b> Not pertinent</p> <p><b>4.12 Flame Temperature:</b> Currently not available</p> <p><b>4.13 Combustion Molar Ratio (Reactant to Product):</b> Not pertinent</p> <p><b>4.14 Minimum Oxygen Concentration for Combustion (MOCC):</b> Not listed</p>	<p><b>7.1 Grades of Purity:</b> Commercial, 72+%</p> <p><b>7.2 Storage Temperature:</b> Ambient</p> <p><b>7.3 Inert Atmosphere:</b> No requirement</p> <p><b>7.4 Venting:</b> Open</p> <p><b>7.5 IMO Pollution Category:</b> Currently not available</p> <p><b>7.6 Ship Type:</b> Currently not available</p> <p><b>7.7 Barge Hull Type:</b> Currently not available</p>
KEEP PEOPLE AWAY. AVOID CONTACT WITH SOLID AND DUST. Wear goggles and self-contained breathing apparatus. Notify local health and pollution control agencies. Protect water intakes.					
Fire	Not flammable. Irritating gases may be produced when heated.				8. HAZARD CLASSIFICATIONS
Exposure	DUST POISONOUS IF INHALED. If inhaled will cause headache or loss of consciousness. If in eyes, hold eyelids open and flush with plenty of water. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen.  SOLID POISONOUS IF SWALLOWED. Irritating to skin and eyes. If swallowed will cause nausea and vomiting. Remove contaminated clothing and shoes. Flush affected areas with plenty of water. IF IN EYES, hold eyelids open and flush with plenty of water. IF SWALLOWED and victim is CONSCIOUS, have victim drink water or milk. IF SWALLOWED and victim is UNCONSCIOUS OR HAVING CONVULSIONS, do nothing except keep victim warm.				<p><b>8.1 49 CFR Category:</b> Not listed.</p> <p><b>8.2 49 CFR Class:</b> Not pertinent</p> <p><b>8.3 49 CFR Package Group:</b> Not listed.</p> <p><b>8.4 Marine Pollutant:</b> No</p> <p><b>8.5 NFPA Hazard Classification:</b> Not listed</p> <p><b>8.6 EPA Reportable Quantity:</b> 1 pound</p> <p><b>8.7 EPA Pollution Category:</b> X</p> <p><b>8.8 RCRA Waste Number:</b> P059</p> <p><b>8.9 EPA FWPCA List:</b> Yes</p>
Water Pollution	HARMFUL TO AQUATIC LIFE IN VERY LOW CONCENTRATIONS. May be dangerous if it enters water intakes. Notify local health and wildlife officials. Notify operators of nearby water intakes.				9. PHYSICAL & CHEMICAL PROPERTIES
1. CORRECTIVE RESPONSE ACTIONS Stop discharge Contain Collection Systems: Skim; Dredge		2. CHEMICAL DESIGNATIONS 2.1 CG Compatibility Group: Not listed. 2.2 Formula: C <sub>10</sub> H <sub>8</sub> Cl <sub>7</sub> 2.3 IMO/UN Designation: Not listed 2.4 DOT ID No.: Not listed 2.5 CAS Registry No.: 76-44-8 2.6 NAERG Guide No.: Not listed 2.7 Standard Industrial Trade Classification: 51139		5. CHEMICAL REACTIVITY	<p><b>9.1 Physical State at 15° C and 1 atm:</b> Solid</p> <p><b>9.2 Molecular Weight:</b> 373.5</p> <p><b>9.3 Boiling Point at 1 atm:</b> Not pertinent (decomposes)</p> <p><b>9.4 Freezing Point:</b> 115-165°F = 46-74°C = 319-347°K</p> <p><b>9.5 Critical Temperature:</b> Not pertinent</p> <p><b>9.6 Critical Pressure:</b> Not pertinent</p> <p><b>9.7 Specific Gravity:</b> 1.66 at 20°C (solid)</p> <p><b>9.8 Liquid Surface Tension:</b> Not pertinent</p> <p><b>9.9 Liquid Water Interfacial Tension:</b> Not pertinent</p> <p><b>9.10 Vapor (Gas) Specific Gravity:</b> Not pertinent</p> <p><b>9.11 Ratio of Specific Heats of Vapor (Gas):</b> Not pertinent</p> <p><b>9.12 Latent Heat of Vaporization:</b> Not pertinent</p> <p><b>9.13 Heat of Combustion:</b> Not pertinent</p> <p><b>9.14 Heat of Decomposition:</b> Not pertinent</p> <p><b>9.15 Heat of Solution:</b> Not pertinent</p> <p><b>9.16 Heat of Polymerization:</b> Not pertinent</p> <p><b>9.17 Heat of Fusion:</b> Currently not available</p> <p><b>9.18 Limiting Value:</b> Currently not available</p> <p><b>9.19 Reid Vapor Pressure:</b> Currently not available</p>
3. HEALTH HAZARDS					
<p><b>3.1 Personal Protective Equipment:</b> Protective respirator; rubber gloves; clean clothes</p> <p><b>3.2 Symptoms Following Exposure:</b> Inhalation of dust causes irritation, tremors, and collapse. Ingestion causes nausea, vomiting, diarrhea, and irritation of the gastrointestinal tract. Contact with dust causes irritation of eyes and moderate irritation of skin.</p> <p><b>3.3 Treatment of Exposure:</b> Get medical attention following all overexposure to heptachlor. INHALATION: move to fresh air; if exposure to dust was severe, get medical attention. INGESTION: lavage stomach with warm tap water (unless convulsions are imminent); fats and oils should be avoided, as they increase the rate of absorption of all chlorinated hydrocarbons. EYES: wash repeatedly with water. SKIN: flush with water, then wash with soap and water.</p> <p><b>3.4 TLV-TWA:</b> 0.05 mg/m<sup>3</sup></p> <p><b>3.5 TLV-STEL:</b> Not listed.</p> <p><b>3.6 TLV-Ceiling:</b> Not listed.</p> <p><b>3.7 Toxicity by Ingestion:</b> Grade 4; oral LD<sub>50</sub> = 40 mg/kg (rat)</p> <p><b>3.8 Toxicity by Inhalation:</b> Currently not available.</p> <p><b>3.9 Chronic Toxicity:</b> Liver damage may develop.</p> <p><b>3.10 Vapor (Gas) Irritant Characteristics:</b> Currently not available</p> <p><b>3.11 Liquid or Solid Characteristics:</b> Currently not available</p> <p><b>3.12 Odor Threshold:</b> 0.02 ppm</p> <p><b>3.13 IDLH Value:</b> 35 mg/m<sup>3</sup></p> <p><b>3.14 OSHA PEL-TWA:</b> 0.5 mg/m<sup>3</sup></p> <p><b>3.15 OSHA PEL-STEL:</b> Not listed.</p> <p><b>3.16 OSHA PEL-Ceiling:</b> Not listed.</p> <p><b>3.17 EPA AEGL:</b> Not listed</p>					
NOTES					

# HEPTACHLOR

HTC

9.20 SATURATED LIQUID DENSITY		9.21 LIQUID HEAT CAPACITY		9.22 LIQUID THERMAL CONDUCTIVITY		9.23 LIQUID VISCOSITY	
Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F	Temperature (degrees F)	British thermal unit inch per hour-square foot-F	Temperature (degrees F)	Centipoise
NOT PERTINENT			NOT PERTINENT		NOT PERTINENT		NOT PERTINENT

9.24 SOLUBILITY IN WATER		9.25 SATURATED VAPOR PRESSURE		9.26 SATURATED VAPOR DENSITY		9.27 IDEAL GAS HEAT CAPACITY	
Temperature (degrees F)	Pounds per 100 pounds of water	Temperature (degrees F)	Pounds per square inch	Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F
INSOLUBLE			NOT PERTINENT		NOT PERTINENT		NOT PERTINENT