

MYRCENE

MRE

CAUTIONARY RESPONSE INFORMATION				4. FIRE HAZARDS	7. SHIPPING INFORMATION				
Common Synonyms 3-Methylene-7-methyl 1,6-octadiene 2-Methyl-6-methylene-2,7-octadiene 1,6-Octadiene, 7-methyl-3-methylene	Oil	Yellow tinted	Pleasant odor	<p>4.1 Flash Point: 103°F C.C.</p> <p>4.2 Flammable Limits in Air: Currently not available</p> <p>4.3 Fire Extinguishing Agents: Water spray, carbon dioxide, dry chemical, alcohol foam.</p> <p>4.4 Fire Extinguishing Agents Not to Be Used: Water may be ineffective</p> <p>4.5 Special Hazards of Combustion Products: Vapor may travel considerable distance to a source of ignition and flashback.</p> <p>4.6 Behavior in Fire: Currently not available</p> <p>4.7 Auto Ignition Temperature: Currently not available</p> <p>4.8 Electrical Hazards: Currently not available</p> <p>4.9 Burning Rate: Currently not available</p> <p>4.10 Adiabatic Flame Temperature: Currently not available</p> <p>4.11 Stoichiometric Air to Fuel Ratio: 66.6 (calc.)</p> <p>4.12 Flame Temperature: Currently not available</p> <p>4.13 Combustion Molar Ratio (Reactant to Product): 18.0 (calc.)</p> <p>4.14 Minimum Oxygen Concentration for Combustion (MOCC): Not listed</p>	<p>7.1 Grades of Purity: Currently not available</p> <p>7.2 Storage Temperature: Currently not available</p> <p>7.3 Inert Atmosphere: Ambient</p> <p>7.4 Venting: Currently not available</p> <p>7.5 IMO Pollution Category: D</p> <p>7.6 Ship Type: Data not available</p> <p>7.7 Barge Hull Type: Currently not available</p>				
Call fire department. Avoid contact with liquid. Evacuate area. Stay upwind and use water spray to "knock down" vapor. Notify local health and pollution control agencies.				8. HAZARD CLASSIFICATIONS					
Fire	Combustible. Flashback along vapor trail may occur. Vapor may explode if ignited in an enclosed area. Extinguish with water, dry chemical, alcohol foam, or CO ₂ . Cool exposed containers with water.				<p>8.1 49 CFR Category: Not listed</p> <p>8.2 49 CFR Class: Not pertinent</p> <p>8.3 49 CFR Package Group: Not listed</p> <p>8.4 Marine Pollutant: No</p> <p>8.5 NFPA Hazard Classification: Not listed</p> <p>8.6 EPA Reportable Quantity: Not listed</p> <p>8.7 EPA Pollution Category: Not listed</p> <p>8.8 RCRA Waste Number: Not listed</p> <p>8.9 EPA FWPCA List: Not listed</p>				
Exposure	CALL FOR MEDICAL AID. LIQUID OR SOLID Irritating to skin and eyes. Remove contaminated clothing and shoes. Flush affected areas with plenty of water. IF IN EYES, hold eyelids open and flush with plenty of water.				9. PHYSICAL & CHEMICAL PROPERTIES				
Water Pollution	Effect of low concentrations on aquatic life is unknown. Fouling to shoreline. May be dangerous if it enters water intakes. Notify local health and wildlife officials. Notify operators of nearby water intakes.				<p>9.1 Physical State at 15°C and 1 atm: Liquid</p> <p>9.2 Molecular Weight: 136.24</p> <p>9.3 Boiling Point at 1 atm: 332.6°F = 167°C = 440.2°K</p> <p>9.4 Freezing Point: Currently not available</p> <p>9.5 Critical Temperature: Currently not available</p> <p>9.6 Critical Pressure: Currently not available</p> <p>9.7 Specific Gravity: 0.801</p> <p>9.8 Liquid Surface Tension: Currently not available</p> <p>9.9 Liquid Water Interfacial Tension: Currently not available</p> <p>9.10 Vapor (Gas) Specific Gravity: 4.7</p> <p>9.11 Ratio of Specific Heats of Vapor (Gas): Currently not available</p> <p>9.12 Latent Heat of Vaporization: Currently not available</p> <p>9.13 Heat of Combustion: Currently not available</p> <p>9.14 Heat of Decomposition: Currently not available</p> <p>9.15 Heat of Solution: Currently not available</p> <p>9.16 Heat of Polymerization: Currently not available</p> <p>9.17 Heat of Fusion: Currently not available</p> <p>9.18 Limiting Value: Currently not available</p> <p>9.19 Reid Vapor Pressure: 0.0891 psia</p>				
1. CORRECTIVE RESPONSE ACTIONS Stop discharge		2. CHEMICAL DESIGNATIONS 2.1 CG Compatibility Group: 30; Olefins 2.2 Formula: H ₂ CCH ₂ (=CH ₂)CH ₂ CH ₂ C(CH ₃) ₂ 2.3 IMO/UN Designation: Currently not available 2.4 DOT ID No.: Not listed 2.5 CAS Registry No.: 123-35-3 2.6 NAERG Guide No.: Not listed 2.7 Standard Industrial Trade Classification: 5119							
3. HEALTH HAZARDS									
<p>3.1 Personal Protective Equipment: Wear self-contained breathing apparatus, rubber boots and heavy rubber gloves.</p> <p>3.2 Symptoms Following Exposure: May be harmful by inhalation, ingestion or skin absorption.</p> <p>3.3 Treatment of Exposure: INHALATION: Call for medical aid. Remove the victim to fresh air. If not breathing give artificial respiration. If breathing is difficult give oxygen. SKIN: Wash with soap and copious amounts of water. EYES: Immediately flush with copious amounts of water. Insure adequate flushing of the eyes by holding the eyelids open with the fingers.</p> <p>3.4 TLV-TWA: Not listed.</p> <p>3.5 TLV-STEL: Not listed.</p> <p>3.6 TLV-Ceiling: Not listed.</p> <p>3.7 Toxicity by Ingestion: Currently not available</p> <p>3.8 Toxicity by Inhalation: Currently not available.</p> <p>3.9 Chronic Toxicity: Currently not available</p> <p>3.10 Vapor (Gas) Irritant Characteristics: Vapors cause moderate irritation such that personnel will find high concentrations unpleasant. The effect is temporary.</p> <p>3.11 Liquid or Solid Characteristics: Causes smarting of the skin and first-degree burns on short exposure; may cause second-degree burns on long exposure.</p> <p>3.12 Odor Threshold: Currently not available</p> <p>3.13 IDLH Value: Not listed.</p> <p>3.14 OSHA PEL-TWA: Not listed.</p> <p>3.15 OSHA PEL-STEL: Not listed.</p> <p>3.16 OSHA PEL-Ceiling: Not listed.</p> <p>3.17 EPA AEGL: Not listed</p>									
NOTES									

MYRCENE

MRE

9.20 SATURATED LIQUID DENSITY		9.21 LIQUID HEAT CAPACITY		9.22 LIQUID THERMAL CONDUCTIVITY		9.23 LIQUID VISCOSITY	
Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F	Temperature (degrees F)	British thermal unit inch per hour-square foot-F	Temperature (degrees F)	Centipoise
C U R R E N T L Y N O T A V A I L A B L E			C U R R E N T L Y N O T A V A I L A B L E		C U R R E N T L Y N O T A V A I L A B L E		C U R R E N T L Y N O T A V A I L A B L E

9.24 SOLUBILITY IN WATER		9.25 SATURATED VAPOR PRESSURE		9.26 SATURATED VAPOR DENSITY		9.27 IDEAL GAS HEAT CAPACITY	
Temperature (degrees F)	Pounds per 100 pounds of water	Temperature (degrees F)	Pounds per square inch	Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F
I N S O L U B L E		58 68 128 153 181 199 223 259 299 341	0.019 0.135 0.193 0.387 0.774 1.160 1.934 3.867 7.735 14.696		C U R R E N T L Y N O T A V A I L A B L E	0 25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600	0.314 0.328 0.342 0.356 0.369 0.383 0.396 0.408 0.421 0.433 0.445 0.457 0.468 0.479 0.491 0.501 0.512 0.522 0.533 0.543 0.552 0.562 0.571 0.581 0.590