

OCTYL EPOXY TALLATE

OET

CAUTIONARY RESPONSE INFORMATION				4. FIRE HAZARDS	7. SHIPPING INFORMATION
Common Synonyms Epoxidized tall oil, octyl ester	Liquid	Pale yellow	Mild odor	<p>4.1 Flash Point: 450°F O.C.</p> <p>4.2 Flammable Limits in Air: Not pertinent</p> <p>4.3 Fire Extinguishing Agents: Foam, dry chemical, carbon dioxide</p> <p>4.4 Fire Extinguishing Agents Not to Be Used: Water may be ineffective.</p> <p>4.5 Special Hazards of Combustion Products: Currently not available</p> <p>4.6 Behavior in Fire: Currently not available</p> <p>4.7 Auto Ignition Temperature: Currently not available</p> <p>4.8 Electrical Hazards: Currently not available</p> <p>4.9 Burning Rate: Currently not available</p> <p>4.10 Adiabatic Flame Temperature: Currently not available</p> <p>4.11 Stoichiometric Air to Fuel Ratio: Not pertinent</p> <p>4.12 Flame Temperature: Currently not available</p> <p>4.13 Combustion Molar Ratio (Reactant to Product): Not pertinent.</p> <p>4.14 Minimum Oxygen Concentration for Combustion (MOCC): Not listed</p>	<p>7.1 Grades of Purity: Commercial</p> <p>7.2 Storage Temperature: Ambient</p> <p>7.3 Inert Atmosphere: No requirement</p> <p>7.4 Venting: Open (flame arrester)</p> <p>7.5 IMO Pollution Category: Currently not available</p> <p>7.6 Ship Type: Currently not available</p> <p>7.7 Barge Hull Type: Currently not available</p>
Keep people away. Avoid contact with liquid. Notify local health and pollution control agencies. Protect water intakes.				8. HAZARD CLASSIFICATIONS	
Fire Combustible. Extinguish with dry chemicals, foam or carbon dioxide. Water may be ineffective on fire. Cool exposed containers with water.				<p>8.1 49 CFR Category: Not listed</p> <p>8.2 49 CFR Class: Not pertinent</p> <p>8.3 49 CFR Package Group: Not listed</p> <p>8.4 Marine Pollutant: No</p> <p>8.5 NFPA Hazard Classification: Not listed</p> <p>8.6 EPA Reportable Quantity: Not listed</p> <p>8.7 EPA Pollution Category: Not listed.</p> <p>8.8 RCRA Waste Number: Not listed</p> <p>8.9 EPA FWPCA List: Not listed</p>	
Exposure CALL FOR MEDICAL AID. LIQUID Irritating to skin and eyes. Harmful if swallowed. Remove contaminated clothing and shoes. Flush affected areas with plenty of water. IF IN EYES, hold eyelids open and flush with plenty of water. IF SWALLOWED and victim is CONSCIOUS, have victim drink water or milk. IF SWALLOWED and victim is UNCONSCIOUS OR HAVING CONVULSIONS, do nothing except keep victim warm.				9. PHYSICAL & CHEMICAL PROPERTIES	
Water Pollution Effect of low concentrations on aquatic life is unknown. Fouling to shoreline. May be dangerous if it enters water intakes. Notify local health and wildlife officials. Notify operators of nearby water intakes.				<p>9.1 Physical State at 15°C and 1 atm: Liquid</p> <p>9.2 Molecular Weight: 420 (approx.)</p> <p>9.3 Boiling Point at 1 atm: Not pertinent (decomposes)</p> <p>9.4 Freezing Point: Not pertinent</p> <p>9.5 Critical Temperature: Not pertinent</p> <p>9.6 Critical Pressure: Not pertinent</p> <p>9.7 Specific Gravity: (est.) 1.002 at 20°C (liquid)</p> <p>9.8 Liquid Surface Tension: 40.1 dynes/cm = 0.0401 N/m at 20°C</p> <p>9.9 Liquid Water Interfacial Tension: Currently not available</p> <p>9.10 Vapor (Gas) Specific Gravity: Not pertinent</p> <p>9.11 Ratio of Specific Heats of Vapor (Gas): Not pertinent</p> <p>9.12 Latent Heat of Vaporization: Currently not available</p> <p>9.13 Heat of Combustion: Currently not available</p> <p>9.14 Heat of Decomposition: Not pertinent</p> <p>9.15 Heat of Solution: Not pertinent</p> <p>9.16 Heat of Polymerization: Not pertinent</p> <p>9.17 Heat of Fusion: Currently not available</p> <p>9.18 Limiting Value: Currently not available</p> <p>9.19 Reid Vapor Pressure: Currently not available</p>	
<p>1. CORRECTIVE RESPONSE ACTIONS Stop discharge Contain Collection Systems: Skim Chemical and Physical Treatment: Absorb Clean shore line</p> <p>2. CHEMICAL DESIGNATIONS 2.1 CG Compatibility Group: 34; Ester 2.2 Formula: Mixture 2.3 IMO/UN Designation: Not listed 2.4 DOT ID No.: Not listed 2.5 CAS Registry No.: Currently not available 2.6 NAERG Guide No.: Not listed 2.7 Standard Industrial Trade Classification: 51615</p> <p>3. HEALTH HAZARDS</p> <p>3.1 Personal Protective Equipment: Chemical goggles; face shield; oil-resistant gloves</p> <p>3.2 Symptoms Following Exposure: Contact with eyes causes mild inflammation. Contact with skin may produce allergic response.</p> <p>3.3 Treatment of Exposure: EYES or SKIN: remove excess oil with cloth or absorbent paper; then wash with soapy water and flush with clear water; consult a physician.</p> <p>3.4 TLV-TWA: Not listed.</p> <p>3.5 TLV-STEL: Not listed.</p> <p>3.6 TLV-Ceiling: Not listed.</p> <p>3.7 Toxicity by Ingestion: Grade 0; LD₅₀ >15 g/kg</p> <p>3.8 Toxicity by Inhalation: Currently not available.</p> <p>3.9 Chronic Toxicity: Currently not available</p> <p>3.10 Vapor (Gas) Irritant Characteristics: Currently not available</p> <p>3.11 Liquor or Solid Characteristics: Currently not available</p> <p>3.12 Odor Threshold: Currently not available</p> <p>3.13IDLH Value: Not listed.</p> <p>3.14 OSHA PEL-TWA: Not listed.</p> <p>3.15 OSHA PEL-STEL: Not listed.</p> <p>3.16 OSHA PEL-Ceiling: Not listed.</p> <p>3.17 EPA AEGL: Not listed</p>				6. WATER POLLUTION	
				<p>6.1 Aquatic Toxicity: Currently not available</p> <p>6.2 Waterfowl Toxicity: Currently not available</p> <p>6.3 Biological Oxygen Demand (BOD): Currently not available</p> <p>6.4 Food Chain Concentration Potential: None</p> <p>6.5 GESAMP Hazard Profile: Bioaccumulation: - Damage to living resources: - Human Oral hazard: 0 Human Contact hazard: - Reduction of amenities: X</p>	
NOTES					

OCTYL EPOXY TALLATE

OET

9.20 SATURATED LIQUID DENSITY		9.21 LIQUID HEAT CAPACITY		9.22 LIQUID THERMAL CONDUCTIVITY		9.23 LIQUID VISCOSITY	
Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F	Temperature (degrees F)	British thermal unit inch per hour-square foot-F	Temperature (degrees F)	Centipoise
52	58.550		N O T		N O T	77	
54	58.480						35.000
56	58.410						
58	58.340		P E R T I N E N T		P E R T I N E N T		
60	58.270						
62	58.200						
64	58.130						
66	58.060						
68	57.990						
70	57.920						
72	57.850						
74	57.780						
76	57.710						
78	57.640						
80	57.570						
82	57.500						
84	57.440						
86	57.370						

9.24 SOLUBILITY IN WATER		9.25 SATURATED VAPOR PRESSURE		9.26 SATURATED VAPOR DENSITY		9.27 IDEAL GAS HEAT CAPACITY	
Temperature (degrees F)	Pounds per 100 pounds of water	Temperature (degrees F)	Pounds per square inch	Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F
	I N S O L U B L E		N O T P E R T I N E N T		N O T P E R T I N E N T		N O T P E R T I N E N T