

BARIUM CARBONATE

BRCA

CAUTIONARY RESPONSE INFORMATION			
Common Synonyms	Solid crystals or powder	White	Odorless
Sinks in water.			
Notify local health and pollution control agencies. Protect water intakes.			
Fire	Not flammable.		
Exposure	CALL FOR MEDICAL AID. SOLID If swallowed, will cause nausea and vomiting. IF SWALLOWED and victim is CONSCIOUS, have victim drink water or milk.		
Water Pollution	HARMFUL TO AQUATIC LIFE IN VERY LOW CONCENTRATIONS. Fouling to shoreline. May be dangerous if it enters water intakes. Notify local health and wildlife officials. Notify operators of nearby water intakes.		

1. CORRECTIVE RESPONSE ACTIONS	2. CHEMICAL DESIGNATIONS	3. HEALTH HAZARDS	4. FIRE HAZARDS	5. CHEMICAL REACTIVITY	6. WATER POLLUTION	7. SHIPPING INFORMATION	8. HAZARD CLASSIFICATIONS	9. PHYSICAL & CHEMICAL PROPERTIES
<p>Stop discharge Contain Collection Systems: Dredge Clean shore line</p> <p>3.1 Personal Protective Equipment: Dust respirator</p> <p>3.2 Symptoms Following Exposure: (INGESTION ONLY): excessive salivation, vomiting, severe abdominal pain, and violent purging with watery and bloody stools; a slow and often irregular pulse and a transient elevation in arterial blood pressure; tinnitus, giddiness and vertigo; muscle twitches, progressing to convulsions and/or paralysis; dilated pupils with impaired accommodation; confusion and increasing somnolence, without coma; collapse and death from respiratory failure and cardiac arrest.</p> <p>3.3 Treatment of Exposure: Rapid oral administration of a soluble sulfate in water, such as magnesium or sodium sulfate (2 oz), alum (4 gm), or very dilute sulfuric acid (30 ml of a 10% solution diluted to 1 qt). These agents precipitate barium as the insoluble sulfate. Gastric lavage or induced emesis. Seek medical attention.</p> <p>3.4 TLV-TWA: 0.5 mg/m³ as Ba</p> <p>3.5 TLV-STEL: Not listed.</p> <p>3.6 TLV-Ceiling: Not listed.</p> <p>3.7 Toxicity by Ingestion: Grade 2; LD₅₀ = 0.5 to 5 g/kg (rabbit, rat, guinea pig)</p> <p>3.8 Toxicity by Inhalation: Currently not available.</p> <p>3.9 Chronic Toxicity: None observed.</p> <p>3.10 Vapor (Gas) Irritant Characteristics: Not pertinent</p> <p>3.11 Liquid or Solid Characteristics: None</p> <p>3.12 Odor Threshold: Odorless</p> <p>3.13 IDLH Value: 50 mg/m³ as barium.</p> <p>3.14 OSHA PEL-TWA: 0.5 mg/m³ as barium.</p> <p>3.15 OSHA PEL-STEL: Not listed.</p> <p>3.16 OSHA PEL-Ceiling: Not listed.</p> <p>3.17 EPA AEGL: Not listed</p>	<p>2.1 CG Compatibility Group: Not listed.</p> <p>2.2 Formula: BaCO₃</p> <p>2.3 IMO/UN Designation: 6.1/1564</p> <p>2.4 DOT ID No.: 1564</p> <p>2.5 CAS Registry No.: 513-77-9</p> <p>2.6 NAERG Guide No.: 154</p> <p>2.7 Standard Industrial Trade Classification: 52379</p>	<p>3.1 Personal Protective Equipment: Dust respirator</p> <p>3.2 Symptoms Following Exposure: (INGESTION ONLY): excessive salivation, vomiting, severe abdominal pain, and violent purging with watery and bloody stools; a slow and often irregular pulse and a transient elevation in arterial blood pressure; tinnitus, giddiness and vertigo; muscle twitches, progressing to convulsions and/or paralysis; dilated pupils with impaired accommodation; confusion and increasing somnolence, without coma; collapse and death from respiratory failure and cardiac arrest.</p> <p>3.3 Treatment of Exposure: Rapid oral administration of a soluble sulfate in water, such as magnesium or sodium sulfate (2 oz), alum (4 gm), or very dilute sulfuric acid (30 ml of a 10% solution diluted to 1 qt). These agents precipitate barium as the insoluble sulfate. Gastric lavage or induced emesis. Seek medical attention.</p> <p>3.4 TLV-TWA: 0.5 mg/m³ as Ba</p> <p>3.5 TLV-STEL: Not listed.</p> <p>3.6 TLV-Ceiling: Not listed.</p> <p>3.7 Toxicity by Ingestion: Grade 2; LD₅₀ = 0.5 to 5 g/kg (rabbit, rat, guinea pig)</p> <p>3.8 Toxicity by Inhalation: Currently not available.</p> <p>3.9 Chronic Toxicity: None observed.</p> <p>3.10 Vapor (Gas) Irritant Characteristics: Not pertinent</p> <p>3.11 Liquid or Solid Characteristics: None</p> <p>3.12 Odor Threshold: Odorless</p> <p>3.13 IDLH Value: 50 mg/m³ as barium.</p> <p>3.14 OSHA PEL-TWA: 0.5 mg/m³ as barium.</p> <p>3.15 OSHA PEL-STEL: Not listed.</p> <p>3.16 OSHA PEL-Ceiling: Not listed.</p> <p>3.17 EPA AEGL: Not listed</p>	<p>4.1 Flash Point: Not flammable</p> <p>4.2 Flammable Limits in Air: Not flammable</p> <p>4.3 Fire Extinguishing Agents: Not pertinent</p> <p>4.4 Fire Extinguishing Agents Not to Be Used: Not pertinent</p> <p>4.5 Special Hazards of Combustion Products: Not pertinent</p> <p>4.6 Behavior in Fire: Not pertinent</p> <p>4.7 Auto Ignition Temperature: Not flammable</p> <p>4.8 Electrical Hazards: Not pertinent</p> <p>4.9 Burning Rate: Not flammable</p> <p>4.10 Adiabatic Flame Temperature: Currently not available</p> <p>4.11 Stoichiometric Air to Fuel Ratio: Not pertinent</p> <p>4.12 Flame Temperature: Currently not available</p> <p>4.13 Combustion Molar Ratio (Reactant to Product): Not pertinent</p> <p>4.14 Minimum Oxygen Concentration for Combustion (MOCC): Not listed</p>	<p>5.1 Reactivity with Water: No reaction</p> <p>5.2 Reactivity with Common Materials: No reaction</p> <p>5.3 Stability During Transport: Stable</p> <p>5.4 Neutralizing Agents for Acids and Caustics: Not pertinent</p> <p>5.5 Polymerization: Not pertinent</p> <p>5.6 Inhibitor of Polymerization: Not pertinent</p>	<p>6.1 Aquatic Toxicity: Currently not available</p> <p>6.2 Waterfowl Toxicity: Currently not available</p> <p>6.3 Biological Oxygen Demand (BOD): None</p> <p>6.4 Food Chain Concentration Potential: Currently not available</p> <p>6.5 GESAMP Hazard Profile: Not listed</p>	<p>7.1 Grades of Purity: Reagent grade-99.0%; Ceramic grade-99.1%; Ceramic and chemical grade-99.3%; Glass grade- 98.8%; Electronic ceramic grade-99.6%</p> <p>7.2 Storage Temperature: Currently not available</p> <p>7.3 Inert Atmosphere: Currently not available</p> <p>7.4 Venting: Currently not available</p> <p>7.5 IMO Pollution Category: Currently not available</p> <p>7.6 Ship Type: Currently not available</p> <p>7.7 Barge Hull Type: Currently not available</p>	<p>8.1 49 CFR Category: Poison</p> <p>8.2 49 CFR Class: 6.1</p> <p>8.3 49 CFR Package Group: II</p> <p>8.4 Marine Pollutant: No</p> <p>8.5 NFPA Hazard Classification: Not listed</p> <p>8.6 EPA Reportable Quantity: Not listed.</p> <p>8.7 EPA Pollution Category: Not listed.</p> <p>8.8 RCRA Waste Number: Not listed</p> <p>8.9 EPA FWPCA List: Not listed</p>	<p>9.1 Physical State at 15° C and 1 atm: Solid</p> <p>9.2 Molecular Weight: 197.35</p> <p>9.3 Boiling Point at 1 atm: Not pertinent</p> <p>9.4 Freezing Point: Not pertinent</p> <p>9.5 Critical Temperature: Not pertinent</p> <p>9.6 Critical Pressure: Not pertinent</p> <p>9.7 Specific Gravity: 4.3 at 20°C (solid)</p> <p>9.8 Liquid Surface Tension: Not pertinent</p> <p>9.9 Liquid Water Interfacial Tension: Not pertinent</p> <p>9.10 Vapor (Gas) Specific Gravity: Not pertinent</p> <p>9.11 Ratio of Specific Heats of Vapor (Gas): Not pertinent</p> <p>9.12 Latent Heat of Vaporization: Not pertinent</p> <p>9.13 Heat of Combustion: Not pertinent</p> <p>9.14 Heat of Decomposition: Not pertinent</p> <p>9.15 Heat of Solution: Not pertinent</p> <p>9.16 Heat of Polymerization: Not pertinent</p> <p>9.17 Heat of Fusion: Currently not available</p> <p>9.18 Limiting Value: Currently not available</p> <p>9.19 Reid Vapor Pressure: Currently not available</p>

NOTES

BARIUM CARBONATE

BRC

9.20 SATURATED LIQUID DENSITY		9.21 LIQUID HEAT CAPACITY		9.22 LIQUID THERMAL CONDUCTIVITY		9.23 LIQUID VISCOSITY	
Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F	Temperature (degrees F)	British thermal unit inch per hour-square foot-F	Temperature (degrees F)	Centipoise
NOT PERTINENT			NOT PERTINENT		NOT PERTINENT		NOT PERTINENT

9.24 SOLUBILITY IN WATER		9.25 SATURATED VAPOR PRESSURE		9.26 SATURATED VAPOR DENSITY		9.27 IDEAL GAS HEAT CAPACITY	
Temperature (degrees F)	Pounds per 100 pounds of water	Temperature (degrees F)	Pounds per square inch	Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F
68	0.025		NOT PERTINENT		NOT PERTINENT		NOT PERTINENT