

AMYL PHTHALATE

ATL

CAUTIONARY RESPONSE INFORMATION				4. FIRE HAZARDS	7. SHIPPING INFORMATION								
Common Synonyms 1,2-Benzenedicarboxylic acid, dipentyl ester Dipentyl phthalate Phthalic acid, diethyl ester Phthalic acid, dipentyl ester	Liquid Floats on water.	Colorless	Odorless	<p>4.1 Flash Point: 245°F C.C.</p> <p>4.2 Flammable Limits in Air: Currently not available</p> <p>4.3 Fire Extinguishing Agents: Dry chemical, carbon dioxide</p> <p>4.4 Fire Extinguishing Agents Not to Be Used: Water or foam may cause frothing.</p> <p>4.5 Special Hazards of Combustion Products: Currently not available</p> <p>4.6 Behavior in Fire: Currently not available</p> <p>4.7 Auto Ignition Temperature: Currently not available</p> <p>4.8 Electrical Hazards: Currently not available</p> <p>4.9 Burning Rate: Currently not available</p> <p>4.10 Adiabatic Flame Temperature: Currently not available</p> <p>4.11 Stoichiometric Air to Fuel Ratio: 111.9 (calc.)</p> <p>4.12 Flame Temperature: Currently not available</p> <p>4.13 Combustion Molar Ratio (Reactant to Product): 32.0 (calc.)</p> <p>4.14 Minimum Oxygen Concentration for Combustion (MOCC): Not listed</p>	<p>7.1 Grades of Purity: Technical</p> <p>7.2 Storage Temperature: Ambient</p> <p>7.3 Inert Atmosphere: No requirement</p> <p>7.4 Venting: Open</p> <p>7.5 IMO Pollution Category: Currently not available</p> <p>7.6 Ship Type: Currently not available</p> <p>7.7 Barge Hull Type: Currently not available</p>								
<p>Keep people away. Shut off ignition sources. Call fire department. Avoid contact with liquid and vapor. Notify local health and pollution control agencies. Protect water intakes.</p>				<p>8. HAZARD CLASSIFICATIONS</p> <p>8.1 49 CFR Category: Not listed</p> <p>8.2 49 CFR Class: Not pertinent</p> <p>8.3 49 CFR Package Group: Not listed</p> <p>8.4 Marine Pollutant: No</p> <p>8.5 NFPA Hazard Classification:</p> <table> <tr> <td>Category</td> <td>Classification</td> </tr> <tr> <td>Health Hazard (Blue).....</td> <td>0</td> </tr> <tr> <td>Flammability (Red).....</td> <td>1</td> </tr> <tr> <td>Instability (Yellow).....</td> <td>0</td> </tr> </table>		Category	Classification	Health Hazard (Blue).....	0	Flammability (Red).....	1	Instability (Yellow).....	0
Category	Classification												
Health Hazard (Blue).....	0												
Flammability (Red).....	1												
Instability (Yellow).....	0												
<p>Fire Combustible Water and foam may be ineffective on fire. Extinguish with dry chemicals or carbon dioxide. Cool exposed containers with water.</p>				<p>8.6 EPA Reportable Quantity: Not listed.</p> <p>8.7 EPA Pollution Category: Not listed.</p> <p>8.8 RCRA Waste Number: Not listed</p> <p>8.9 EPA FWC List: Not listed</p>									
<p>Exposure CALL FOR MEDICAL AID. VAPOR Irritating to eyes, nose and throat. If inhaled will cause headache, coughing, or difficult breathing. If in eyes, hold eyelids open and flush with plenty of water. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen. LIQUID Irritating to skin and eyes. Harmful if swallowed. Remove contaminated clothing and shoes. Flush affected areas with plenty of water. IF IN EYES, hold open and flush with plenty of water. IF SWALLOWED and victim is CONSCIOUS, have victim drink water or milk. IF SWALLOWED and victim is UNCONSCIOUS OR HAVING CONVULSIONS, do nothing except keep victim warm.</p>				<p>9. PHYSICAL & CHEMICAL PROPERTIES</p> <p>9.1 Physical State at 15°C and 1 atm: Liquid</p> <p>9.2 Molecular Weight: 306.4</p> <p>9.3 Boiling Point at 1 atm: 631°F = 333°C = 606°K</p> <p>9.4 Freezing Point: Currently not available</p> <p>9.5 Critical Temperature: Not pertinent</p> <p>9.6 Critical Pressure: Not pertinent</p> <p>9.7 Specific Gravity: 0.82 at 20°C (liquid)</p> <p>9.8 Liquid Surface Tension: 31.5 dynes/cm = 0.0315 N/m at 20°C</p> <p>9.9 Liquid Water Interfacial Tension: Currently not available</p> <p>9.10 Vapor (Gas) Specific Gravity: 10.5</p> <p>9.11 Ratio of Specific Heats of Vapor (Gas): Not pertinent</p> <p>9.12 Latent Heat of Vaporization: 140 Btu/lb = 76 cal/g = 3.2 x 10⁵ J/kg</p> <p>9.13 Heat of Combustion: 13,900 Btu/lb = -7,720 cal/g = -323 x 10⁵ J/kg</p> <p>9.14 Heat of Decomposition: Not pertinent</p> <p>9.15 Heat of Solution: Not pertinent</p> <p>9.16 Heat of Polymerization: Not pertinent</p> <p>9.17 Heat of Fusion: Currently not available</p> <p>9.18 Limiting Value: Currently not available</p> <p>9.19 Reid Vapor Pressure: Currently not available</p>									
<p>Water Pollution Effect of low concentrations on aquatic life is unknown. Fouling to shoreline. May be dangerous if it enters water intakes. Notify local health and wildlife officials. Notify operators of nearby water intakes.</p>				<p>6. WATER POLLUTION</p> <p>6.1 Aquatic Toxicity: Currently not available</p> <p>6.2 Waterfowl Toxicity: Currently not available</p> <p>6.3 Biological Oxygen Demand (BOD): Currently not available</p> <p>6.4 Food Chain Concentration Potential: None</p> <p>6.5 GESAMP Hazard Profile: Not listed</p>									
<p>1. CORRECTIVE RESPONSE ACTIONS Stop discharge Dilute and disperse Chemical and Physical Treatment: Burn</p> <p>2. CHEMICAL DESIGNATIONS</p> <p>2.1 CG Compatibility Group: 34; Esters</p> <p>2.2 Formula: $C_8H_6(COOC_2H_5)_2$</p> <p>2.3 IMO/UN Designation: Not listed</p> <p>2.4 DOT ID No.: Not listed</p> <p>2.5 CAS Registry No.: 131-18-0</p> <p>2.6 NAERG Guide No.: Not listed</p> <p>2.7 Standard Industrial Trade Classification: 51129</p>				<p>NOTES</p>									
<p>3. HEALTH HAZARDS</p> <p>3.1 Personal Protective Equipment: Goggles or face shield; rubber gloves</p> <p>3.2 Symptoms Following Exposure: Inhalation of vapors from very hot material may cause headache, drowsiness, and convulsions. Hot vapors may irritate eyes.</p> <p>3.3 Treatment of Exposure: INHALATION: Move to fresh air. EYES: Flush with water. SKIN: Wipe off; flush with water; wash with soap and water.</p> <p>3.4 TLV-TWA: Not listed.</p> <p>3.5 TLV-STEL: Not listed.</p> <p>3.6 TLV-Ceiling: Not listed.</p> <p>3.7 Toxicity by Ingestion: Grade 2; $TD_{lo} = 2.2$ g/kg (rat)</p> <p>3.8 Toxicity by Inhalation: Currently not available.</p> <p>3.9 Chronic Toxicity: Causes birth defects in rats (skeletal and gross abnormalities)</p> <p>3.10 Vapor (Gas) Irritant Characteristics: Currently not available</p> <p>3.11 Liquid or Solid Characteristics: Currently not available</p> <p>3.12 Odor Threshold: Currently not available</p> <p>3.13 IDLH Value: Not listed.</p> <p>3.14 OSHA PEL-TWA: Not listed.</p> <p>3.15 OSHA PEL-STEL: Not listed.</p> <p>3.16 OSHA PEL-Ceiling: Not listed.</p> <p>3.17 EPA A EGL: Not listed</p>													

AMYL PHTHALATE

ATL

9.20 SATURATED LIQUID DENSITY		9.21 LIQUID HEAT CAPACITY		9.22 LIQUID THERMAL CONDUCTIVITY		9.23 LIQUID VISCOSITY	
Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F	Temperature (degrees F)	British thermal unit inch per hour-square foot-F	Temperature (degrees F)	Centipoise
68	51.190		C U R R E N T T L Y N O T A V A I L A B L E	C U R R E N T T L Y N O T A V A I L A B L E	70 75 80 85 90 95 100 105 110 115 120 125 130 135 140 145 150 155 160 165 170 175 180 185 190	32.483 29.311 26.536 24.087 21.910 19.963 18.210 16.624 15.182 13.866 12.659 11.549 10.524 9.576 8.695 7.874 7.109 6.392 5.721 5.090 4.497 3.937 3.408 2.908 2.434	

9.24 SOLUBILITY IN WATER		9.25 SATURATED VAPOR PRESSURE		9.26 SATURATED VAPOR DENSITY		9.27 IDEAL GAS HEAT CAPACITY	
Temperature (degrees F)	Pounds per 100 pounds of water	Temperature (degrees F)	Pounds per square inch	Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound- $^{\circ}$ F
68	0.010	125	0.000	125	0.00000		C
		130	0.000	130	0.00000		U
		135	0.000	135	0.00000		R
		140	0.000	140	0.00000		R
		145	0.000	145	0.00000		E
		150	0.000	150	0.00000		N
		155	0.000	155	0.00000		T
		160	0.000	160	0.00000		L
		165	0.000	165	0.00000		A
		170	0.000	170	0.00001		N
		175	0.000	175	0.00001		O
		180	0.000	180	0.00001		I
		185	0.000	185	0.00002		A
		190	0.000	190	0.00002		V
		195	0.001	195	0.00002		A
		200	0.001	200	0.00002		I
		205	0.001	205	0.00003		L
		210	0.001	210	0.00003		A
		215	0.001	215	0.00003		B
		220	0.001	220	0.00004		B
		225	0.001	225	0.00004		L
		230	0.001	230	0.00004		E
		235	0.001	235	0.00004		N
		240	0.001	240	0.00005		T
		245	0.001	245	0.00005		O
		250	0.001	250	0.00005		L