

# M-TOLUIDINE

TOI

CAUTIONARY RESPONSE INFORMATION				4. FIRE HAZARDS	7. SHIPPING INFORMATION								
Common Synonyms 3-Amino-1-methylbenzene 3-Aminotoluene 3-Methylaniline m-Methylaniline 3-Methylbenzeneamine	Liquid  May float or sink in water.	Colorless to yellow-brown  Aniline-like aromatic odor		<p>4.1 Flash Point: 186°F C.C.</p> <p>4.2 Flammable Limits in Air: 1.1 - 6.6 %</p> <p>4.3 Fire Extinguishing Agents: Foam, dry chemical, or carbon dioxide</p> <p>4.4 Fire Extinguishing Agents Not to Be Used: Not pertinent</p> <p>4.5 Special Hazards of Combustion Products: Toxic oxides of nitrogen and flammable vapors may form in fire.</p> <p>4.6 Behavior in Fire: Currently not available</p> <p>4.7 Auto Ignition Temperature: 899°F</p> <p>4.8 Electrical Hazards: Currently not available</p> <p>4.9 Burning Rate: Currently not available</p> <p>4.10 Adiabatic Flame Temperature: Currently not available</p> <p>4.11 Stoichiometric Air to Fuel Ratio: 48.8 (calc.)</p> <p>4.12 Flame Temperature: Currently not available</p> <p>4.13 Combustion Molar Ratio (Reactant to Product): 12.5 (calc.)</p> <p>4.14 Minimum Oxygen Concentration for Combustion (MOCC): Not listed</p>	<p>7.1 Grades of Purity: Commercial, 99.5 + %</p> <p>7.2 Storage Temperature: Ambient</p> <p>7.3 Inert Atmosphere: Currently not available</p> <p>7.4 Venting: Currently not available</p> <p>7.5 IMO Pollution Category: C</p> <p>7.6 Ship Type: 2</p> <p>7.7 Barge Hull Type: Currently not available</p>								
<p>Keep people away. Avoid contact with liquid and vapor. Shut off ignition sources. Call fire department. Notify local health and pollution control agencies. Protect water intakes.</p>				8. HAZARD CLASSIFICATIONS									
Fire	<p>Combustible. POISONOUS GASES MAY BE PRODUCED IN FIRE. Wear goggles and self-contained breathing apparatus. Extinguish with dry chemicals, alcohol or polymer foam or carbon dioxide. Cool exposed containers with water.</p>				<p>8.1 49 CFR Category: Poison</p> <p>8.2 49 CFR Class: 6.1</p> <p>8.3 49 CFR Package Group: II</p> <p>8.4 Marine Pollutant: No</p> <p>8.5 NFPA Hazard Classification:</p> <table> <thead> <tr> <th>Category</th> <th>Classification</th> </tr> </thead> <tbody> <tr> <td>Health Hazard (Blue)</td> <td>2</td> </tr> <tr> <td>Flammability (Red)</td> <td>2</td> </tr> <tr> <td>Instability (Yellow)</td> <td>0</td> </tr> </tbody> </table>	Category	Classification	Health Hazard (Blue)	2	Flammability (Red)	2	Instability (Yellow)	0
Category	Classification												
Health Hazard (Blue)	2												
Flammability (Red)	2												
Instability (Yellow)	0												
Exposure	<p>CALL FOR MEDICAL AID.</p> <p>LIQUID Irritating to skin and eyes. If swallowed will cause nausea, vomiting or loss of consciousness. Remove contaminated clothing and shoes. Flush affected areas with plenty of water. IF IN EYES, hold eyelids open and flush with plenty of water. IF SWALLOWED and victim is CONSCIOUS, have victim drink water or milk and induce vomiting. IF SWALLOWED and victim is UNCONSCIOUS OR HAVING CONVULSIONS, do nothing except keep victim warm.</p>				<p>8.6 EPA Reportable Quantity: Not listed.</p> <p>8.7 EPA Pollution Category: Not listed.</p> <p>8.8 RCRA Waste Number: Not listed</p> <p>8.9 EPA FWCNA List: Not listed</p>								
Water Pollution	<p>Effect of low concentration on aquatic life is unknown. Fouling to shoreline. May be dangerous if it enters water intakes. Notify local health and wildlife officials. Notify operators of nearby water intakes.</p>				9. PHYSICAL & CHEMICAL PROPERTIES								
1. CORRECTIVE RESPONSE ACTIONS Stop discharge Collection Systems: Skim; Pump Do not burn		<p>2. CHEMICAL DESIGNATIONS</p> <p>2.1 CG Compatibility Group: Not listed.</p> <p>2.2 Formula: 3-CH<sub>2</sub>CH<sub>2</sub>NH<sub>2</sub></p> <p>2.3 IMO/UN Designation: 6.1/1708</p> <p>2.4 DOT ID No.: 1708</p> <p>2.5 CAS Registry No.: 108-44-1</p> <p>2.6 NAERG Guide No.: 153</p> <p>2.7 Standard Industrial Trade Classification: 51454</p> <p>3. HEALTH HAZARDS</p> <p>3.1 Personal Protective Equipment: Chemical safety goggles; face shield; approved respirator; butyl rubber gloves</p> <p>3.2 Symptoms Following Exposure: Absorption of toxic quantities by any route causes cyanosis (blue discoloration of lips, nails, skin); nausea, vomiting, and coma may follow. Repeated inhalation of low concentrations may cause pallor, low-grade secondary anemia, fatigability, and loss of appetite. Contact with eyes causes irritation.</p> <p>3.3 Treatment of Exposure: Get medical attention following all exposures to this compound. INHALATION: move to fresh air. INGESTION: if victim is conscious, promptly induce vomiting EYES: flush with copious amounts of water for at least 15 min., holding lids apart. SKIN: remove all contaminated clothing; wash affected areas immediately and thoroughly with plenty of warm water and soap.</p> <p>3.4 TLV-TWA: 2 ppm (skin)</p> <p>3.5 TLV-STEL: Not listed.</p> <p>3.6 TLV-Ceiling: Not listed.</p> <p>3.7 Toxicity by Ingestion: Grade 3; LD<sub>50</sub> = 450 mg/kg (rat)</p> <p>3.8 Toxicity by Inhalation: Currently not available.</p> <p>3.9 Chronic Toxicity: Currently not available</p> <p>3.10 Vapor (Gas) Irritant Characteristics: Vapors are moderately irritating such that personnel will not tolerate moderate or high concentrations.</p> <p>3.11 Liquid or Solid Characteristics: Causes smarting of the skin and first-degree burns on short exposure; may cause second-degree burns on long exposure.</p> <p>3.12 Odor Threshold: Currently not available</p> <p>3.13 IDLH Value: Not listed.</p> <p>3.14 OSHA PEL-TWA: Not listed.</p> <p>3.15 OSHA PEL-STEL: Not listed.</p> <p>3.16 OSHA PEL-Ceiling: Not listed.</p> <p>3.17 EPA AEGL: Not listed</p>				<p>9.1 Physical State at 15°C and 1 atm: Liquid</p> <p>9.2 Molecular Weight: 107.2</p> <p>9.3 Boiling Point at 1 atm: 398.1°F = 203.4°C = 476.6°K</p> <p>9.4 Freezing Point: -22.7°F = -30.4°C = 242.8°K</p> <p>9.5 Critical Temperature: Currently not available</p> <p>9.6 Critical Pressure: Currently not available</p> <p>9.7 Specific Gravity: 0.989 at 20°C (liquid)</p> <p>9.8 Liquid Surface Tension: 36.9 dynes/cm = .037 N/m at 20°C</p> <p>9.9 Liquid Water Interfacial Tension: Currently not available</p> <p>9.10 Vapor (Gas) Specific Gravity: 3.9 (est)</p> <p>9.11 Ratio of Specific Heats of Vapor (Gas): Not pertinent</p> <p>9.12 Latent Heat of Vaporization: Currently not available</p> <p>9.13 Heat of Combustion: -15,883 Btu/lb = -8,824 cal/g = -369 x 10<sup>5</sup> J/kg</p> <p>9.14 Heat of Decomposition: Not pertinent</p> <p>9.15 Heat of Solution: Not pertinent</p> <p>9.16 Heat of Polymerization: Not pertinent</p> <p>9.17 Heat of Fusion: Currently not available</p> <p>9.18 Limiting Value: Currently not available</p> <p>9.19 Reid Vapor Pressure: Very Low</p>							
NOTES													

# M-TOLUIDINE

TOI

9.20 SATURATED LIQUID DENSITY		9.21 LIQUID HEAT CAPACITY		9.22 LIQUID THERMAL CONDUCTIVITY		9.23 LIQUID VISCOSITY	
Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F	Temperature (degrees F)	British thermal unit inch per hour-square foot-F	Temperature (degrees F)	Centipoise
68	61.740		C U R R E N T L Y  N O T  A V A I L A B L E		C U R R E N T L Y  N O T  A V A I L A B L E	59 60 61 62 63 64 65 66 67 68	4,420 4,343 4,268 4,196 4,126 4,059 3,994 3,931 3,869 3,810

9.24 SOLUBILITY IN WATER		9.25 SATURATED VAPOR PRESSURE		9.26 SATURATED VAPOR DENSITY		9.27 IDEAL GAS HEAT CAPACITY	
Temperature (degrees F)	Pounds per 100 pounds of water	Temperature (degrees F)	Pounds per square inch	Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F
	C U R R E N T L Y  N O T  A V A I L A B L E	120 140 160 180 200 220 240 260 280 300 320 340 360 380	0.031 0.067 0.130 0.234 0.397 0.639 0.988 1.475 2.137 3.019 4.169 5.647 7.517 9.853		C U R R E N T L Y  N O T  A V A I L A B L E	0 25 50 75 100 125 150 175 200 225 250 275 300 325 350 375 400 425 450 475 500 525 550 575 600	0.259 0.270 0.281 0.292 0.304 0.315 0.326 0.338 0.349 0.360 0.371 0.383 0.394 0.405 0.417 0.428 0.439 0.450 0.462 0.473 0.484 0.495 0.507 0.518 0.529