

LEAD FLUORIDE

LFR

| CAUTIONARY RESPONSE INFORMATION | | | | 4. FIRE HAZARDS | 7. SHIPPING INFORMATION |
|---|--|---|----------|---|--|
| Common Synonyms Lead difluoride Plumbous fluoride | Solid | White | Odorless | <p>4.1 Flash Point: Not flammable</p> <p>4.2 Flammable Limits in Air: Not flammable</p> <p>4.3 Fire Extinguishing Agents: Not pertinent</p> <p>4.4 Fire Extinguishing Agents Not to Be Used: Not pertinent</p> <p>4.5 Special Hazards of Combustion Products: Currently not available</p> <p>4.6 Behavior in Fire: Currently not available</p> <p>4.7 Auto Ignition Temperature: Not pertinent</p> <p>4.8 Electrical Hazards: Not pertinent</p> <p>4.9 Burning Rate: Not pertinent</p> <p>4.10 Adiabatic Flame Temperature: Currently not available</p> <p>4.11 Stoichiometric Air to Fuel Ratio: Not pertinent</p> <p>4.12 Flame Temperature: Currently not available</p> <p>4.13 Combustion Molar Ratio (Reactant to Product): Not pertinent</p> <p>4.14 Minimum Oxygen Concentration for Combustion (MOCC): Not listed</p> | <p>7.1 Grades of Purity: Technical; C.P.; Optical grade</p> <p>7.2 Storage Temperature: Ambient</p> <p>7.3 Inert Atmosphere: No requirement</p> <p>7.4 Venting: Open</p> <p>7.5 IMO Pollution Category: Currently not available</p> <p>7.6 Ship Type: Currently not available</p> <p>7.7 Barge Hull Type: Currently not available</p> |
| <p>KEEP PEOPLE AWAY. AVOID CONTACT WITH SOLID AND DUST. Wear dust respirator. Notify local health and pollution control agencies.</p> | | | | | |
| Fire | Not flammable. | | | | |
| Exposure | <p>CALL FOR MEDICAL AID. DUST POISONOUS IF INHALED. If inhaled will cause dizziness or loss of consciousness. If in eyes, hold eyelids open and flush with plenty of water. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen.</p> <p>SOLID Irritating to skin and eyes. If swallowed will cause nausea, vomiting or loss of consciousness. Remove contaminated clothing and shoes. Flush affected areas with plenty of water. IF IN EYES, hold eyelids open and flush with plenty of water. IF SWALLOWED and victim is CONSCIOUS have victim drink water or milk and have victim induce vomiting. IF SWALLOWED and victim is UNCONSCIOUS OR HAVING CONVULSIONS, do nothing except keep victim warm.</p> | | | | |
| Water Pollution | <p>Dangerous to aquatic life in high concentrations. May be dangerous if it enters water intakes. Notify local health and wildlife officials. Notify operators of nearby water intakes.</p> | | | | |
| 1. CORRECTIVE RESPONSE ACTIONS Stop discharge Collection Systems: Dredge | | 2. CHEMICAL DESIGNATIONS 2.1 CG Compatibility Group: Not listed. 2.2 Formula: PbF ₂ 2.3 IMO/UN Designation: Not listed 2.4 DOT ID No.: 2291 2.5 CAS Registry No.: 7783-46-2 2.6 NAERG Guide No.: 154 2.7 Standard Industrial Trade Classification: 52310 | | | |
| 3. HEALTH HAZARDS <p>3.1 Personal Protective Equipment: Dust and fumes of all but the most insoluble lead compounds are readily absorbed on inhalation and, to a lesser degree, after ingestion. Respirator for heavy dust exposure; safety goggles</p> <p>3.2 Symptoms Following Exposure: Not irritating to skin or mucous membranes; protect against chronic poisoning. Early symptoms of lead intoxication via inhalation or ingestion are most commonly gastrointestinal disorders, colic, constipation, etc.; weakness, which may go on to paralysis chiefly of the extensor muscles of the wrists and less often the ankles, is noticeable in the most serious cases. Ingestion of a large amount causes local irritation of the alimentary tract; pain, leg cramps, muscle weakness, paresthesias, depression, coma, and death may follow in 1 or 2 days. Contact with eyes causes irritation.</p> <p>3.3 Treatment of Exposure: Remove at once all cases of lead intoxication from further exposure until the blood level is reduced to a safe value; immediately place the individual under medical care. INGESTION: give gastric lavage using 1% solution of sodium or magnesium sulfate; leave 15-30 gm magnesium sulfate in 6-8 oz. of water in the stomach as antidote and cathartic; egg white, milk, and tannin are useful demulcents; atropine sulfate and other antispasmodics may relieve abdominal pain, but morphine may be necessary. EYES or SKIN: flush with water.</p> <p>3.4 TLV-TWA: 0.05 mg/m³ (as lead)</p> <p>3.5 TLV-STEL: Not listed.</p> <p>3.6 TLV-Ceiling: Not listed.</p> <p>3.7 Toxicity by Ingestion: Grade 2; LD₅₀ = 0.5-5 g/kg</p> <p>3.8 Toxicity by Inhalation: Currently not available.</p> <p>3.9 Chronic Toxicity: Currently not available</p> <p>3.10 Vapor (Gas) Irritant Characteristics: Currently not available</p> <p>3.11 Liquor or Solid Characteristics: Currently not available</p> <p>3.12 Odor Threshold: Currently not available</p> <p>3.13 IDLH Value: 100 mg Pb/m³</p> <p>3.14 OSHA PEL-TWA: 0.05 mg/m³ (as lead).</p> <p>3.15 OSHA PEL-STEL: Not listed.</p> <p>3.16 OSHA PEL-Ceiling: Not listed.</p> <p>3.17 EPA AEGL: Not listed</p> | | | | | |
| 4. FIRE HAZARDS <p>4.1 Flash Point: Not flammable</p> <p>4.2 Flammable Limits in Air: Not flammable</p> <p>4.3 Fire Extinguishing Agents: Not pertinent</p> <p>4.4 Fire Extinguishing Agents Not to Be Used: Not pertinent</p> <p>4.5 Special Hazards of Combustion Products: Currently not available</p> <p>4.6 Behavior in Fire: Currently not available</p> <p>4.7 Auto Ignition Temperature: Not pertinent</p> <p>4.8 Electrical Hazards: Not pertinent</p> <p>4.9 Burning Rate: Not pertinent</p> <p>4.10 Adiabatic Flame Temperature: Currently not available</p> <p>4.11 Stoichiometric Air to Fuel Ratio: Not pertinent</p> <p>4.12 Flame Temperature: Currently not available</p> <p>4.13 Combustion Molar Ratio (Reactant to Product): Not pertinent</p> <p>4.14 Minimum Oxygen Concentration for Combustion (MOCC): Not listed</p> | | | | | |
| 5. CHEMICAL REACTIVITY <p>5.1 Reactivity with Water: No reaction</p> <p>5.2 Reactivity with Common Materials: Currently not available</p> <p>5.3 Stability During Transport: Stable</p> <p>5.4 Neutralizing Agents for Acids and Caustics: Not pertinent</p> <p>5.5 Polymerization: Not pertinent</p> <p>5.6 Inhibitor of Polymerization: Not pertinent</p> | | | | | |
| 6. WATER POLLUTION <p>6.1 Aquatic Toxicity: 7.48 mg/l(as Pb)/4 days/minnow/TL_m/soft water</p> <p>6.2 Waterfowl Toxicity: May be toxic</p> <p>6.3 Biological Oxygen Demand (BOD): None</p> <p>6.4 Food Chain Concentration Potential: Bioconcentrative</p> <p>6.5 GESAMP Hazard Profile: Not listed</p> | | | | | |
| 7. SHIPPING INFORMATION <p>7.1 Grades of Purity: Technical; C.P.; Optical grade</p> <p>7.2 Storage Temperature: Ambient</p> <p>7.3 Inert Atmosphere: No requirement</p> <p>7.4 Venting: Open</p> <p>7.5 IMO Pollution Category: Currently not available</p> <p>7.6 Ship Type: Currently not available</p> <p>7.7 Barge Hull Type: Currently not available</p> | | | | | |
| 8. HAZARD CLASSIFICATIONS <p>8.1 49 CFR Category: Keep Away From Food</p> <p>8.2 49 CFR Class: 6.1</p> <p>8.3 49 CFR Package Group: III</p> <p>8.4 Marine Pollutant: Yes</p> <p>8.5 NFPA Hazard Classification: Not listed</p> <p>8.6 EPA Reportable Quantity: 10 pounds</p> <p>8.7 EPA Pollution Category: A</p> <p>8.8 RCRA Waste Number: Not listed</p> <p>8.9 EPA FWPCA List: Yes</p> | | | | | |
| 9. PHYSICAL & CHEMICAL PROPERTIES <p>9.1 Physical State at 15° C and 1 atm: Solid</p> <p>9.2 Molecular Weight: 245.19</p> <p>9.3 Boiling Point at 1 atm: Not pertinent</p> <p>9.4 Freezing Point: Not pertinent</p> <p>9.5 Critical Temperature: Not pertinent</p> <p>9.6 Critical Pressure: Not pertinent</p> <p>9.7 Specific Gravity: 8.24 at 20°C (solid)</p> <p>9.8 Liquid Surface Tension: Not pertinent</p> <p>9.9 Liquid Water Interfacial Tension: Not pertinent</p> <p>9.10 Vapor (Gas) Specific Gravity: Not pertinent</p> <p>9.11 Ratio of Specific Heats of Vapor (Gas): Not pertinent</p> <p>9.12 Latent Heat of Vaporization: Not pertinent</p> <p>9.13 Heat of Combustion: Not pertinent</p> <p>9.14 Heat of Decomposition: Not pertinent</p> <p>9.15 Heat of Solution: Not pertinent</p> <p>9.16 Heat of Polymerization: Not pertinent</p> <p>9.17 Heat of Fusion: 7.6 cal/g</p> <p>9.18 Limiting Value: Currently not available</p> <p>9.19 Reid Vapor Pressure: Currently not available</p> | | | | | |
| NOTES | | | | | |

LEAD FLUORIDE

LFR

| 9.20 SATURATED LIQUID DENSITY | | 9.21 LIQUID HEAT CAPACITY | | 9.22 LIQUID THERMAL CONDUCTIVITY | | 9.23 LIQUID VISCOSITY | |
|----------------------------------|-----------------------|------------------------------|-------------------------------------|-------------------------------------|---|----------------------------|------------------|
| Temperature (degrees F) | Pounds per cubic foot | Temperature (degrees F) | British thermal unit per pound-F | Temperature (degrees F) | British thermal unit inch per hour-square foot-F | Temperature (degrees F) | Centipoise |
| | NOT PERTINENT | | NOT PERTINENT | | NOT PERTINENT | | NOT PERTINENT |

| 9.24 SOLUBILITY IN WATER | | 9.25 SATURATED VAPOR PRESSURE | | 9.26 SATURATED VAPOR DENSITY | | 9.27 IDEAL GAS HEAT CAPACITY | |
|-----------------------------|-----------------------------------|----------------------------------|------------------------|---------------------------------|-----------------------|---------------------------------|-------------------------------------|
| Temperature (degrees F) | Pounds per 100 pounds of water | Temperature (degrees F) | Pounds per square inch | Temperature (degrees F) | Pounds per cubic foot | Temperature (degrees F) | British thermal unit per pound-F |
| 34 | 0.064 | | | | NOT | | NOT |
| 36 | 0.064 | | | | PERTINENT | | PERTINENT |
| 38 | 0.064 | | | | NOT | | NOT |
| 40 | 0.064 | | | | PERTINENT | | PERTINENT |
| 42 | 0.064 | | | | NOT | | NOT |
| 44 | 0.064 | | | | PERTINENT | | PERTINENT |
| 46 | 0.064 | | | | NOT | | NOT |
| 48 | 0.064 | | | | PERTINENT | | PERTINENT |
| 50 | 0.064 | | | | NOT | | NOT |
| 52 | 0.064 | | | | PERTINENT | | PERTINENT |
| 54 | 0.064 | | | | NOT | | NOT |
| 56 | 0.064 | | | | PERTINENT | | PERTINENT |
| 58 | 0.064 | | | | NOT | | NOT |
| 60 | 0.064 | | | | PERTINENT | | PERTINENT |
| 62 | 0.064 | | | | NOT | | NOT |
| 64 | 0.064 | | | | PERTINENT | | PERTINENT |
| 66 | 0.064 | | | | NOT | | NOT |
| 68 | 0.064 | | | | PERTINENT | | PERTINENT |
| 70 | 0.064 | | | | NOT | | NOT |
| 72 | 0.064 | | | | PERTINENT | | PERTINENT |
| 74 | 0.064 | | | | NOT | | NOT |
| 76 | 0.064 | | | | PERTINENT | | PERTINENT |
| 78 | 0.064 | | | | NOT | | NOT |
| 80 | 0.064 | | | | PERTINENT | | PERTINENT |
| 82 | 0.064 | | | | NOT | | NOT |
| 84 | 0.064 | | | | PERTINENT | | PERTINENT |