

# ETHYLENE GLYCOL PROPYL ETHER

EGP

CAUTIONARY RESPONSE INFORMATION				4. FIRE HAZARDS	7. SHIPPING INFORMATION
Common Synonyms Ektasolve EP Ethylene glycol monopropyl ether	Liquid Floats and mixes with water.	Colorless Mild rancid odor		<p>4.1 Flash Point: 120°F C.C.</p> <p>4.2 Flammable Limits in Air: LEL: 1.26% @ 69°C; UEL: 15.8% @ 127°C</p> <p>4.3 Fire Extinguishing Agents: Alcohol foam, water spray, dry chemical or carbon dioxide.</p> <p>4.4 Fire Extinguishing Agents Not to Be Used: Water.</p> <p>4.5 Special Hazards of Combustion Products: Carbon dioxide and carbon monoxide may be produced in a fire.</p> <p>4.6 Behavior in Fire: Currently not available</p> <p>4.7 Auto Ignition Temperature: Currently not available</p> <p>4.8 Electrical Hazards: Not listed.</p> <p>4.9 Burning Rate: Currently not available</p> <p>4.10 Adiabatic Flame Temperature: Currently not available</p> <p>4.11 Stoichiometric Air to Fuel Ratio: 33.3 (calc.)</p> <p>4.12 Flame Temperature: Currently not available</p> <p>4.13 Combustion Molar Ratio (Reactant to Product): 11.0 (calc.)</p> <p>4.14 Minimum Oxygen Concentration for Combustion (MOCC): Not listed</p>	<p>7.1 Grades of Purity: Commercial.</p> <p>7.2 Storage Temperature: Ambient.</p> <p>7.3 Inert Atmosphere: No requirement.</p> <p>7.4 Venting: Not listed.</p> <p>7.5 IMO Pollution Category: D</p> <p>7.6 Ship Type: 3</p> <p>7.7 Barge Hull Type: 3</p>
<p>Remove all ignition sources. Call fire department. Avoid contact with liquid. Notify local health and pollution control agencies. Protect water intakes.</p>				<p>8. HAZARD CLASSIFICATIONS</p> <p>8.1 49 CFR Category: Not listed.</p> <p>8.2 49 CFR Class: Not pertinent.</p> <p>8.3 49 CFR Package Group: Not listed.</p> <p>8.4 Marine Pollutant: No</p> <p>8.5 NFPA Hazard Classification: Not listed</p> <p>8.6 EPA Reportable Quantity: Not listed.</p> <p>8.7 EPA Pollution Category: Not listed.</p> <p>8.8 RCRA Waste Number: Not listed</p> <p>8.9 EPA FWPCA List: Not listed</p>	
Fire	<p>Combustible. Extinguish with dry chemical, alcohol foam, or carbon dioxide. Cool exposed containers with water.</p>				<p>9. PHYSICAL &amp; CHEMICAL PROPERTIES</p> <p>9.1 Physical State at 15° C and 1 atm: Liquid</p> <p>9.2 Molecular Weight: 104.15</p> <p>9.3 Boiling Point at 1 atm: 301°F = 149.5°C = 422.5°K</p> <p>9.4 Freezing Point: Currently not available</p> <p>9.5 Critical Temperature: Currently not available</p> <p>9.6 Critical Pressure: Currently not available</p> <p>9.7 Specific Gravity: 0.908 at 73°F</p> <p>9.8 Liquid Surface Tension: Currently not available</p> <p>9.9 Liquid Water Interfacial Tension: Currently not available</p> <p>9.10 Vapor (Gas) Specific Gravity: 3.6</p> <p>9.11 Ratio of Specific Heats of Vapor (Gas): Currently not available</p> <p>9.12 Latent Heat of Vaporization: Currently not available</p> <p>9.13 Heat of Combustion: Currently not available</p> <p>9.14 Heat of Decomposition: Currently not available</p> <p>9.15 Heat of Solution: Currently not available</p> <p>9.16 Heat of Polymerization: Not pertinent.</p> <p>9.17 Heat of Fusion: Currently not available</p> <p>9.18 Limiting Value: Currently not available</p> <p>9.19 Reid Vapor Pressure: Currently not available</p>
Exposure	<p>CALL FOR MEDICAL AID.</p> <p>LIQUID Irritating to skin and eyes. Harmful if swallowed. Remove contaminated clothing and shoes. Flush affected areas with plenty of water. IF IN EYES, hold eyelids open and flush with plenty of water.</p>				<p>5. CHEMICAL REACTIVITY</p> <p>5.1 Reactivity with Water: No reaction.</p> <p>5.2 Reactivity with Common Materials: Incompatible with oxidizing materials.</p> <p>5.3 Stability During Transport: Stable.</p> <p>5.4 Neutralizing Agents for Acids and Caustics: Not pertinent.</p> <p>5.5 Polymerization: Will not polymerize.</p> <p>5.6 Inhibitor of Polymerization: Not pertinent.</p>
Water Pollution	<p>Effect of low concentrations on aquatic life is unknown. May be dangerous if it enters water intakes. Notify local health and wildlife officials. Notify operators of nearby water intakes.</p>				<p>6. WATER POLLUTION</p> <p>6.1 Aquatic Toxicity: Currently not available</p> <p>6.2 Waterfowl Toxicity: Currently not available</p> <p>6.3 Biological Oxygen Demand (BOD): Currently not available</p> <p>6.4 Food Chain Concentration Potential: None.</p> <p>6.5 GESAMP Hazard Profile: Not listed</p>
<p>1. CORRECTIVE RESPONSE ACTIONS Stop discharge Dilute and disperse</p> <p>2. CHEMICAL DESIGNATIONS 2.1 CG Compatibility Group: 40; Glycol ethers 2.2 Formula: CH<sub>2</sub>CH<sub>2</sub>CH<sub>2</sub>OCH<sub>2</sub>CH<sub>2</sub>OH 2.3 IMO/UN Designation: Not listed. 2.4 DOT ID No.: Not listed. 2.5 CAS Registry No.: 2807-30-9 2.6 NAERG Guide No.: Not listed 2.7 Standard Industrial Trade Classification: 51616</p> <p>3. HEALTH HAZARDS</p> <p>3.1 Personal Protective Equipment: Approved respirator; rubber gloves; goggles; clothing to prevent body contact with liquid.</p> <p>3.2 Symptoms Following Exposure: Vapors irritate eyes and nose. Can cause corneal damage. Inhalation or skin contact can cause toxic effects.</p> <p>3.3 Treatment of Exposure: Call for medical aid. INHALATION: Remove to fresh air. SKIN OR EYES: Immediately flush with plenty of water.</p> <p>3.4 TLV-TWA: Not listed.</p> <p>3.5 TLV-STEL: Not listed.</p> <p>3.6 TLV-Ceiling: Not listed.</p> <p>3.7 Toxicity by Ingestion: Currently not available</p> <p>3.8 Toxicity by Inhalation: Currently not available.</p> <p>3.9 Chronic Toxicity: May cause anemia and kidney damage.</p> <p>3.10 Vapor (Gas) Irritant Characteristics: Vapors cause a slight smarting of the eyes or respiratory system if present in high concentrations. The effect is temporary.</p> <p>3.11 Liquid or Solid Characteristics: Minimum hazard. If spilled on clothing and allowed to remain, may cause smarting and reddening of the skin.</p> <p>3.12 Odor Threshold: Currently not available</p> <p>3.13 IDLH Value: Not listed.</p> <p>3.14 OSHA PEL-TWA: Not listed.</p> <p>3.15 OSHA PEL-STEL: Not listed.</p> <p>3.16 OSHA PEL-Ceiling: Not listed.</p> <p>3.17 EPA AEGL: Not listed</p>				NOTES	

# ETHYLENE GLYCOL PROPYL ETHER

EGP

9.20 SATURATED LIQUID DENSITY		9.21 LIQUID HEAT CAPACITY		9.22 LIQUID THERMAL CONDUCTIVITY		9.23 LIQUID VISCOSITY	
Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F	Temperature (degrees F)	British thermal unit inch per hour-square foot-F	Temperature (degrees F)	Centipoise
73	7.580		C U R R E N T L Y  N O T  A V A I L A B L E		C U R R E N T L Y  N O T  A V A I L A B L E		C U R R E N T L Y  N O T  A V A I L A B L E

9.24 SOLUBILITY IN WATER		9.25 SATURATED VAPOR PRESSURE		9.26 SATURATED VAPOR DENSITY		9.27 IDEAL GAS HEAT CAPACITY	
Temperature (degrees F)	Pounds per 100 pounds of water	Temperature (degrees F)	Pounds per square inch	Temperature (degrees F)	Pounds per cubic foot	Temperature (degrees F)	British thermal unit per pound-F
	M I S C I B L E	77	0.025	77	0.00045		C U R R E N T L Y  N O T  A V A I L A B L E