

D = DRUCKSTUTZEN
DISCHARGE NOZZLE TEMP.= 45 °C

LEITUNGEN SPANNUNGSFREI ANSCHLIESSEN!

ZULAESSIGE MASSABWEICHUNGEN FOUR.

ALISHOEREN FUER MASCHINEN

MASSE OMER TOLERANZAMGBE - GRAUGUSSTEILE

DIN 188 GT818

ALISHOEN SPANNUNGSF FOR PAKEHINES

COMMETTION DIMENSIONS FOR PUMPS

MASSE OMER TOLERANZAMGBE - GRAUGUSSTEILE

DIN 188 GT818

DIN 189 GT818

ALIGEMEINTOLERANZAMGBE - GRAUGUSSTEILE

DIN 180 ST818

DIN 180 ST818

GENERAL TOLERANZEN FUER BEARBEITETE TEILE


ALIGEMEINTOLERANZEN FUER BEARBEITETE TEILE


DIN 180 ST88-8

ZULAESSIGE KRAEFTE UND MOMENTE ENTSPRECHEN MIN. 2X API 610/8.
DIE ANGABEN GELTEN FUER STATISCHE ROHALEITUNGSLASTEN.
BEI UEBERSCHREITUNG IST NACHPRUFFUNG ERFORDERLICH.
ADMISSIBLE FORCES AND MOMENTS CORRESPOND TO MIN. 2X API 610/8.
DATA GIVEN BELOW ARE ONLY VALID FOR STATIC PIPING LOADS.
IF VALUES ARE EXCEEDED CHECK IS NECESSARY.

KRAEFTE, MOMENTE / FORCES, MOMENTS

		SAUGSTUTZEN SUCTION NOZZLE				DRUCKSTUTZEN DISCHARGE NOZZLE				
ſ	KRAEFTE FORCES (N)	Fx	Fz	Fy	Fres	Fx	Fz	Fy	Fres	
l		1780	1160	1430	2560	1430	1780	1160	25,60	
I	MOMENTE MOMENTS (Nm)	Mx	Mz	Му	Mres	Мx	Mz	Му	Mres	
		920	710	460	1250	920	710	460	1250	





OWNER DWG. NO. 10-VD-A1-RE-011-037-L P.O. NO. 2PB434

LNOE DWG. NO. M-ZA 50046 LINGE JOB CODE / PROJ. NO.

NATIONAL PETROCHEMICAL COMPANY MARUN PETROCHEMICAL COMPANY

F 103580

SHEET 1 OF 4

C2+ RECOVERY AND GAS CRACKING PLANTS

UNG.	LINCE DISPERSING AND CONTRACTING DIVISION			NARGAN COMPANY of Design
/DRAWING NO.	2001-10-18	KOSMAK	GEPR.	BESTELLER-MI./PURCHASER MI.
-	2001-10-18	DRESSEL	1	ITEM-NO. : 10-P-2774
€ 1 0	2001-08-02	DRESSEL		-
=1	DATIM COATE			

CAD RPH 40-180 AUFSTELLUNGSPLAN INSTALLATION PLAN KSB **b.**

6-N27-503918

24A ASME B16.5 [L.300RF NPS1/2" QUENCH OUT FLANGE API PLAN 62 24E ASME B16.5 CL.300RF NPS1/2" QUENCH IN FLANGE API PLAN 62 6B ASME B16.5 CL.300RF NPS1" PUMP DRAIN FLANGE DN2 ASME B16.5 CL.300RF NPS1-1/2" PUMP DISCHARGE FLANGE DN1 ASME B16.5 CL.300RF NPS2" PUMP SUCTION FLANGE ANSCHLUSS AUSFUEHRUNG REMARKS CONNECTION DESIGN FLANSCHE / FLANGES

GRUNDPLATTENGROESSE BASEPLATE SIZE	ZN24259-7S
MOTORGROESSE	SCHORCH KA7 167M-AB01G-V
MOTOR SIZE	2900RPM 7,5kW
KUPPLUNGSGROESSE	FLENDER N-EUPEX H
COUPLING SIZE	95-140

PUMPE	PUMP	122
GRUNDPLATTE	BASEPLATE	222
KUPPLUNG	COUPLING	9
ANTRIEB	ORIVE	85
		-
-		-
GESAMT	TOTAL	438
GEWICHTE	/ WEIGHTS	KG

