```
sql  -h localhost -u amioda -p

c:¥xampp
 -u root
DB monitor.  Commands end with ; or ¥g.
ion id is 6
.32-MariaDB mariadb.org binary distribution

2018, Oracle, MariaDB Corporation Ab and others.

  for help. Type '¥c' to clear the current input statement.

REATE DATABASE Challenge_db;
cted (0.00 sec)

RANT ALL ON base.* TO 'amioda'@'localhost';
ected (0.00 sec)

xit;

c:¥xampp
 -u amioda -p
***
DB monitor.  Commands end with ; or ¥g.
ion id is 7
.32-MariaDB mariadb.org binary distribution

2018, Oracle, MariaDB Corporation Ab and others.

  for help. Type '¥c' to clear the current input statement.

E Challenge_db
 Access denied for user 'amioda'@'localhost' to database 'challenge_db'
E Challenge_db;
 Access denied for user 'amioda'@'localhost' to database 'challenge_db'
xit;

c:¥xampp
 -u root
DB monitor.  Commands end with ; or ¥g.
ion id is 8
.32-MariaDB mariadb.org binary distribution

2018, Oracle, MariaDB Corporation Ab and others.

  for help. Type '¥c' to clear the current input statement.

E Challenge_db;
```

```
sql  -h localhost -u amioda -p

E Challenge_db;

lb]> exit;

c:¥xampp
 -u root
DB monitor.  Commands end with ; or ¥g.
ion id is 9
.32-MariaDB mariadb.org binary distribution

2018, Oracle, MariaDB Corporation Ab and others.

 for help. Type '¥c' to clear the current input statement.

RANT ALL ON Challenge_db.* TO 'amioda'@'localhost';
ected (0.00 sec)

xit;

c:¥xampp
 -u amioda -p
***
DB monitor.  Commands end with ; or ¥g.
ion id is 10
.32-MariaDB mariadb.org binary distribution

2018, Oracle, MariaDB Corporation Ab and others.

 for help. Type '¥c' to clear the current input statement.

E Challenge_db;

lb]> create table user(
;
me varchar(255),
varchar(255),
rd char(30)

You have an error in your SQL syntax; check the manual that corresponds to your MariaDB server version for the right syntax to use near '-> id int,
har(255),
(255),
e 2
lb]> create table profiles(

t,
255),
55),
```

```
sql -h localhost -u amioda -p

You have an error in your SQL syntax; check the manual that corresponds to your MariaDB server version for the right syntax to use near 'varchar(255),

b]> create table profiles(
nt,
(255),
255),

e

ected (0.30 sec)

b]> INSERT INTO Challenge_db (profilesID, name, tel, age, birthday) VALUES (1, '田中　実', 012-345-6789, 30, 1994-02-01);
Table 'challenge_db.challenge_db' doesn't exist
b]> INSERT INTO profiles (profilesID, name, tel, age, birthday) VALUES (1, '田中　実', 012-345-6789, 30, 1994-02-01);
ected, 1 warning (0.18 sec)

b]> INSERT INTO profiles (profilesID, name, tel, age, birthday) VALUES (2, '鈴木　茂', 090-1122-3344, 37, 1987-08-12);
ected, 1 warning (0.14 sec)

b]> INSERT INTO profiles (profilesID, name, tel, age, birthday) VALUES (3, '鈴木　実', 080-5566-7788, 24, 2000-12-24);
ected, 1 warning (0.14 sec)

b]> INSERT INTO profiles (profilesID, name, tel, age, birthday) VALUES (4, '佐藤　清', 012-0987-6543, 19, 2005-08-01);
ected, 1 warning (0.14 sec)

b]> INSERT INTO profiles (profilesID, name, tel, age, birthday) VALUES (5, '高橋　清', 090-9900-1234, 24, 2000-12-24);
ected, 1 warning (0.12 sec)

b]> SELECT profilesID, name, tel, age, birthday FROM profiles;
-----+---------+------+------------+
     | tel     | age  | birthday   |
-----+---------+------+------------+
実   | -7122   |   30 | 0000-00-00 |
茂   | -4376   |   37 | 0000-00-00 |
実   | -13274  |   24 | 0000-00-00 |
清   | -7518   |   19 | 0000-00-00 |
清   | -11044  |   24 | 0000-00-00 |
-----+---------+------+------------+
sec)

b]> UPDATE profiles SET tel = '012-345-6789' WHERE profilesID = 1;
ected (0.08 sec)
nged: 1  Warnings: 0

b]> SELECT profilesID, name, tel, age, birthday FROM profiles;
```

て検索

```
sql  -h localhost -u amioda -p

b]> SELECT profilesID, name, tel, age, birthday FROM profiles;
     | tel           | age  | birthday   |
     +------------+------+----------+
実 | 012-345-6789  |   30 | 0000-00-00 |
茂 | -4376         |   37 | 0000-00-00 |
実 | -13274        |   24 | 0000-00-00 |
清 | -7518         |   19 | 0000-00-00 |
清 | -11044        |   24 | 0000-00-00 |
     +------------+------+----------+
sec)

b]> UPDATE profiles SET tel = '090-1122-3344' WHERE profilesID = 2;
cted (0.06 sec)
nged: 1  Warnings: 0

b]> UPDATE profiles SET tel = '080-5566-7788' WHERE profilesID = 3;
cted (0.14 sec)
nged: 1  Warnings: 0

b]> UPDATE profiles SET tel = '012-0987-6543' WHERE profilesID = 4;
cted (0.07 sec)
nged: 1  Warnings: 0

b]> UPDATE profiles SET tel = '090-9900-1234' WHERE profilesID = 5;
cted (0.14 sec)
nged: 1  Warnings: 0

b]> SELECT profilesID, name, tel, age, birthday FROM profiles;
     +------------+------+----------+
     | tel           | age  | birthday   |
     +------------+------+----------+
実 | 012-345-6789  |   30 | 0000-00-00 |
茂 | 090-1122-3344 |   37 | 0000-00-00 |
実 | 080-5566-7788 |   24 | 0000-00-00 |
清 | 012-0987-6543 |   19 | 0000-00-00 |
清 | 090-9900-1234 |   24 | 0000-00-00 |
     +------------+------+----------+
sec)

b]> UPDATE profiles SET birthday = '1994-02-01' WHERE profilesID = 1;
cted (0.12 sec)
nged: 1  Warnings: 0

b]> SELECT profilesID, name, tel, age, birthday FROM profiles;
     +------------+------+----------+
     | tel           | age  | birthday   |
     +------------+------+----------+
実 | 012-345-6789  |   30 | 1994-02-01 |
```

て検索

```
sql -h localhost -u amioda -p
清 | 012-0987-6543 |    19 | 0000-00-00 |
清 | 090-9900-1234 |    24 | 0000-00-00 |
----+--------------+------+------------+

sec)

lb]> UPDATE profiles SET birthday = '1994-02-01' WHERE profilesID = 1;
cted (0.12 sec)
nged: 1  Warnings: 0

lb]> SELECT profilesID, name, tel, age, birthday FROM profiles;
----+--------------+------+------------+
    | tel          | age  | birthday   |
----+--------------+------+------------+
実 | 012-345-6789 |    30 | 1994-02-01 |
茂 | 090-1122-3344 |    37 | 0000-00-00 |
実 | 080-5566-7788 |    24 | 0000-00-00 |
清 | 012-0987-6543 |    19 | 0000-00-00 |
清 | 090-9900-1234 |    24 | 0000-00-00 |
----+--------------+------+------------+

sec)

lb]> UPDATE profiles SET birthday = '1987-08-12' WHERE profilesID = 2;
cted (0.05 sec)
nged: 1  Warnings: 0

lb]> UPDATE profiles SET birthday = '2000-12-24' WHERE profilesID = 3;
cted (0.07 sec)
nged: 1  Warnings: 0

lb]> UPDATE profiles SET birthday = '2005-08-01' WHERE profilesID = 4;
cted (0.05 sec)
nged: 1  Warnings: 0

lb]> UPDATE profiles SET birthday = '2000-12-24' WHERE profilesID = 5;
cted (0.05 sec)
nged: 1  Warnings: 0

lb]> SELECT profilesID, name, tel, age, birthday FROM profiles;
----+--------------+------+------------+
    | tel          | age  | birthday   |
----+--------------+------+------------+
実 | 012-345-6789 |    30 | 1994-02-01 |
茂 | 090-1122-3344 |    37 | 1987-08-12 |
実 | 080-5566-7788 |    24 | 2000-12-24 |
清 | 012-0987-6543 |    19 | 2005-08-01 |
清 | 090-9900-1234 |    24 | 2000-12-24 |
----+--------------+------+------------+

sec)

lb]>
```

て検索

```
iaDB [Challenge_db]> UPDATE profiles SET birthday = '2000-12-24' WHERE profilesID = 5;
ry OK, 1 row affected (0.05 sec)
s matched: 1  Changed: 1  Warnings: 0

iaDB [Challenge_db]> SELECT profilesID, name, tel, age, birthday FROM profiles;
---------+---------+---------------+------+------------+
rofilesID | name    | tel           | age  | birthday   |
---------+---------+---------------+------+------------+
      1 | 田中  実 | 012-345-6789   |   30 | 1994-02-01 |
      2 | 鈴木  茂 | 090-1122-3344  |   37 | 1987-08-12 |
      3 | 鈴木  実 | 080-5566-7788  |   24 | 2000-12-24 |
      4 | 佐藤  清 | 012-0987-6543  |   19 | 2005-08-01 |
      5 | 高橋  清 | 090-9900-1234  |   24 | 2000-12-24 |
---------+---------+---------------+------+------------+
ows in set (0.00 sec)

iaDB [Challenge_db]> _
```

ショッ

ショッ

🎋 課題を提出する