

Parser conflicts + JSON parser

Lab assignment

In this lab we will observe RR and SR conflicts + write a JSON parser

JSON

Notice the recursive structure!

```
{
  "glossary": {
    "title": "example glossary",
    "GlossDiv": {
      "title": "S",
      "GlossList": {
        "GlossEntry": {
          "ID": "SGML",
          "SortAs": "SGML",
          "GlossTerm": "Standard Generalized Markup Language",
          "Acronym": "SGML",
          "Abbrev": "ISO 8879:1986",
          "GlossDef": {
            "para": "A meta-markup language, used to create markup languages such as DocBook.",
            "GlossSeeAlso": [
              "GML",
              "XML"
            ]
          },
          "GlossSee": "markup"
        }
      }
    }
  }
}
```

LR(1) parser

"1" is referring to 1 lookahead symbol. It is a data being passed along while transitioning the parser states.

- Basically we can reduce if the lookahead symbol is the symbol we intended it to be.
- lookahead symbol b in production $A \rightarrow \cdot Bc$, b should be $\in \text{FOLLOW}(A)$

SR non-terminals

header
nullable: No
firsts: IDENTIFIER
follows: \$end
Productions: 1 2

params
nullable: No
firsts: IDENTIFIER
follows:),,
Productions: 3 4

param
nullable: No
firsts: IDENTIFIER
follows:),,
Productions: 5

ids
nullable: No
firsts: IDENTIFIER
follows: ,,)
Productions: 6 7

type
nullable: No
firsts: IDENTIFIER
follows: IDENTIFIER
Productions: 8

id
nullable: No
firsts: IDENTIFIER
follows: (,),,
Productions: 9

\$accept
nullable: No
firsts: IDENTIFIER
follows:
Productions: 0

SR LR(1) productions

- 0) `$accept -> header $end`
- 1) `header -> type id (params)`
- 2) `header -> type id ()`
- 3) `params -> param`
- 4) `params -> params , param`
- 5) `param -> type ids`
- 6) `ids -> id`
- 7) `ids -> ids , id`
- 8) `type -> IDENTIFIER`
- 9) `id -> IDENTIFIER`

SR LR(1) parse table

states	\$end	()	,	IDENTIFIER	header	id	ids	param	params	type
0					s3	<u>1</u>					<u>2</u>
1	a										
2					s5		<u>4</u>				
3					r8						
4		s6									
5		r9									
6			s8		s3				<u>9</u>	<u>7</u>	<u>10</u>
7			s11	s12							
8	r2										
9			r3	r3							
10					s15		<u>14</u>	<u>13</u>			
11	r1										
12					s3				<u>16</u>		<u>10</u>
13			r5	s17, r5 - Shift , then <u>Go to state 17</u> - Reduce by 5) param -> type ids							
14			r6	r6							
15			r9	r9							
16			r4	r4							
17					s15		<u>18</u>				
18			r7	r7							

RR LR(1) productions

- 0) `$accept -> exp $end`
- 1) `exp -> exp - sub_exp`
- 2) `exp -> sub_exp`
- 3) `sub_exp -> (type) sub_exp`
- 4) `sub_exp -> - sub_exp`
- 5) `sub_exp -> IDENTIFIER`
- 6) `sub_exp -> (exp)`
- 7) `type -> IDENTIFIER`

RR LR1(1) non-terminals

exp
nullable: No
firsts: (, -, IDENTIFIER
follows: \$end, -,)
Productions: 1 2

sub_exp
nullable: No
firsts: (, -, IDENTIFIER
follows: -, \$end,)
Productions: 3 4 5 6

type
nullable: No
firsts: IDENTIFIER
follows:)
Productions: 7

\$accept
nullable: No
firsts: (, -, IDENTIFIER
follows:
Productions: 0

RR LR(1) parse table

states	\$end	()	-	IDENTIFIER	exp	sub_exp	type
0		s3		s4	s5	<u>1</u>	<u>2</u>	
1	a			s6				
2	r2			r2				
3		s11		s12	s9	<u>8</u>	<u>10</u>	<u>7</u>
4		s3		s4	s5		<u>13</u>	
5	r5			r5				
6		s3		s4	s5		<u>14</u>	
7		s15						
8		s16		s17				
9		r7, r5 - Reduce by 7) type -> IDENTIFIER - Reduce by 5) sub_exp -> IDENTIFIER		r5				
10		r2		r2				
11		s11		s12	s9	<u>19</u>	<u>10</u>	<u>18</u>
12		s11		s12	s21		<u>20</u>	
13	r4			r4				
14	r1			r1				
15		s3		s4	s5		<u>22</u>	
16	r6			r6				
17		s11		s12	s21		<u>23</u>	
18		s24						
19		s25		s17				
20		r4		r4				
21		r5		r5				
22	r3			r3				
23		r1		r1				
24		s11		s12	s21		<u>26</u>	
25		r6		r6				
26		r3		r3				