

CodeGen.scala

Generating MIPS code given a AST

MIPS Registers

MIPS instruction uses 5 bits for register addressing, so there can be $2^5 = 32$ registers

Number	Name	Use	Preserved across function calls?
0	\$zero	constant 0	—
1	\$at	assembler temporary	no
2, 3	\$v0, \$v1	function return values	no
4 - 7	\$a0 - \$a3	function arguments	no
8 - 15	\$t0 - \$t7	temporaries	no
16 - 23	\$s0 - \$s7	temporaries	yes
24 - 31	\$t0 - \$t0	temporaries	no

MIPS Review

```
# Hello, World! program
.data ## Data declaration section
    ## String to be printed:
    out_string: .asciiz "\nHello, World!\n"
.text ## Assembly language instructions go in text segment
main: ## Start of code section
    li $v0, 4 # system call code for printing string = 4
    la $a0, out_string # load address of string to be printed into $a0
    syscall # call operating system to perform operation
            # specified in $v0
            # syscall takes its arguments from $a0, $a1, ...
    li $v0, 10 # terminate program
    syscall
```

Concerning `cint_lit`

In the code generation phase, we need to dump the all the literals in `.data` section

```
.word -1          # for garbage collector
int_lit13:        # 13 was incrementor, starting from 0
.word 5           # class tag number
.word 4           # object size, 4 bytes
.word Int_dispTab # int's dispatch table label
.word 20          # 20 was the value of the Int object? not sure here
.word -1          # next one ..
```

Concerning `Cstring_lit`

The same here, for strings it similar layout, except that for non-printable characters we need to use their ASCII representation. Also, we should not forget 0 to tell assembler that string ended.

```
.word -1                # for garbage collector
string_lit22:           # 22 was incrementor, starting from 0
.word 3                 # class tag number
.word 10                # object size, 10 bytes
.word String_dispTab    # String dispatch table label
.word int_lit13          # length label of string
.ascii "Done with 8 queens!" # text
.byte 10                 # non-printable character being
                        # to Int (i.e. '\n'.toInt)

.byte 0                 # \0
.align 2                 # align data to 2^n bytes (i.e. 2^2)
```

What does `.align` mean?

Concerning `.align`

The "word"s should be in a *word boundary* meaning in MIPS which is a 32 bit we need to have words as 4 bytes, next word as the next 4 bytes and etc.

ClassnameTable

Table of class names used in the program

```
class_nameTab:  
  .word string_lit1  
  .word string_lit13  
  .word string_lit11  
  .word string_lit10  
  .word string_lit7  
  .word string_lit6  
  .word string_lit5  
  .word string_lit3  
  .word string_lit15  
  .word string_lit21  
  .word string_lit14
```

Dispatch table for `Symbol`

`Symbol_dispTab:`

```
.word Any.Any          # base class constructor
.word Symbol.toString  # toString method that Symbol overrode
.word Any.equals       # base class equals method
.word Symbol.Symbol    # Symbol constructor
.word Symbol.hashCode  # hashCode method of Symbol
```


Object prototype for `Symbol` or attribute table

```
.word -1          # garbage collector tag
Symbol_protObj:
.word 2           # class tag
.word 6           # object size
.word Symbol_dispTab # dispatch table of symbol
.word 0           # attribute #1
.word 0           # attribute #2
.word int_lit0    # attribute #2
```

```
class Symbol() {
  var next = native;
  var name: String = "";
  var hash: Int = 0;
}
```

How to use class prototype to create the new object

```
override def visit_alloc(calloc: Calloc, type_name: Symbol) = {  
  // get the name of the symbol  
  val name: String = output.symbol_name(type_name)  
  // load the address of the class name prototype label into $ac  
  emitter.opc("la").opn(emitter.s_ACC()).opn(name + emitter.s_PROTOBJ()).endl(calloc)  
  // jump and link to Any.Clone method which is a built-in method to cool runtime  
  emitter.opc("jal").opn(emitter.s_ANYCLONE).endl(calloc)  
};
```

Offsets

We use the combination of offsets and labels to use the static data (i.e. dispatch table, class table and etc.).

- Note that addresses are in bytes in MIPS

```
.word -1      # offset -4 with respect to "label" (or label's address + (-4))
label:
.word 2       # offset 0 (or label's address + 0)
.word 3       # offset 4 (or label's address + 4)
```