

Efficient AI with Rust Lab  
Rapid Time Series Datasets Library  
RWTH Aachen University  
Group 1

Marius Kaufmann<sup>1</sup>   Amir Ali Aali<sup>2</sup>   Kilian Fin Braun<sup>1</sup>

<sup>1</sup>Masters of Computer Science

<sup>2</sup>Masters of Data Science

19<sup>th</sup> Jul, 2025



# Marius's Part

# Downsampling I

**Goal:** Reduce the number of data points in a time series dataset.

# Downsampling I

**Goal:** Reduce the number of data points in a time series dataset.

**Benefits:**

- ▶ Reduces memory usage

# Downsampling I

**Goal:** Reduce the number of data points in a time series dataset.

## Benefits:

- ▶ Reduces memory usage
- ▶ Speeds up processing time

# Downsampling I

**Goal:** Reduce the number of data points in a time series dataset.

## Benefits:

- ▶ Reduces memory usage
- ▶ Speeds up processing time

## Necessary parameter when downsampling:

- ▶ Downsampling factor: How many data points to skip

# Downsampling I

**Goal:** Reduce the number of data points in a time series dataset.

## Benefits:

- ▶ Reduces memory usage
- ▶ Speeds up processing time


## Necessary parameter when downsampling:

- ▶ Downsampling factor: How many data points to skip

## Example:

- ▶ Downsampling factor of 2: Every second data point is kept as shown in Figure 1

## Downsampling II



Downsampling example with a factor of 2



# Downsampling III

## How it works:

- ▶ The downsampling function takes a time series dataset and a downsampling factor as input.

# Downsampling III

## How it works:

- ▶ The downsampling function takes a time series dataset and a downsampling factor as input.
- ▶ It iterates over the dataset and keeps every  $n$ -th data point, where  $n$  is the downsampling factor.

# Downsampling III

## How it works:

- ▶ The downsampling function takes a time series dataset and a downsampling factor as input.
- ▶ It iterates over the dataset and keeps every  $n$ -th data point, where  $n$  is the downsampling factor.

## Bottleneck of passing the data by reference:

- ▶ Not possible. A copy is needed.

# Downsampling III

## How it works:

- ▶ The downsampling function takes a time series dataset and a downsampling factor as input.
- ▶ It iterates over the dataset and keeps every  $n$ -th data point, where  $n$  is the downsampling factor.

## Bottleneck of passing the data by reference:

- ▶ Not possible. A copy is needed.
- ▶ Creating view only possible on contiguous data.

# Downsampling III

## How it works:

- ▶ The downsampling function takes a time series dataset and a downsampling factor as input.
- ▶ It iterates over the dataset and keeps every  $n$ -th data point, where  $n$  is the downsampling factor.

## Bottleneck of passing the data by reference:

- ▶ Not possible. A copy is needed.
- ▶ Creating view only possible on contiguous data.
- ▶ Downsampling does not yield a contiguous data structure.

## Kilian's Part