

Efficient AI with Rust Lab  
Rapid Time Series Datasets Library  
RWTH Aachen University  
Group 1

Marius Kaufmann<sup>1</sup>   Amir Ali Aali<sup>2</sup>   Kilian Fin Braun<sup>1</sup>

<sup>1</sup>Masters of Computer Science

<sup>2</sup>Masters of Data Science

20<sup>th</sup> Jul, 2025



# Overview

## Goal

- ▶ Preprocessing of time series datasets

# Overview

## Goal

- ▶ Preprocessing of time series datasets
- ▶ Python package implemented in Rust

# Overview

## Goal

- ▶ Preprocessing of time series datasets
- ▶ Python package implemented in Rust
- ▶ Passing data by reference

# Overview

## Goal

- ▶ Preprocessing of time series datasets
- ▶ Python package implemented in Rust
- ▶ Passing data by reference
  - ▶ Using `numpy` crate

# Overview

## Goal

- ▶ Preprocessing of time series datasets
- ▶ Python package implemented in Rust
- ▶ Passing data by reference
  - ▶ Using `numpy` crate

## Scope

- ▶ Two types of datasets

# Overview

## Goal

- ▶ Preprocessing of time series datasets
- ▶ Python package implemented in Rust
- ▶ Passing data by reference
  - ▶ Using `numpy` crate

## Scope

- ▶ Two types of datasets
  - ▶ `ForecastingDataSet`

# Overview

## Goal

- ▶ Preprocessing of time series datasets
- ▶ Python package implemented in Rust
- ▶ Passing data by reference
  - ▶ Using `numpy` crate

## Scope

- ▶ Two types of datasets
  - ▶ `ForecastingDataSet`
  - ▶ `ClassificationDataSet`



# Overview

## Goal

- ▶ Preprocessing of time series datasets
- ▶ Python package implemented in Rust
- ▶ Passing data by reference
  - ▶ Using `numpy` crate

## Scope

- ▶ Two types of datasets
  - ▶ `ForecastingDataSet`
  - ▶ `ClassificationDataSet`
- ▶ Functionality
  - ▶ `impute()`

# Overview

## Goal

- ▶ Preprocessing of time series datasets
- ▶ Python package implemented in Rust
- ▶ Passing data by reference
  - ▶ Using `numpy` crate

## Scope

- ▶ Two types of datasets
  - ▶ `ForecastingDataSet`
  - ▶ `ClassificationDataSet`
- ▶ Functionality
  - ▶ `impute()`
  - ▶ `downsample()`

# Overview

## Goal

- ▶ Preprocessing of time series datasets
- ▶ Python package implemented in Rust
- ▶ Passing data by reference
  - ▶ Using `numpy` crate

## Scope

- ▶ Two types of datasets
  - ▶ `ForecastingDataSet`
  - ▶ `ClassificationDataSet`
- ▶ Functionality
  - ▶ `impute()`
  - ▶ `downsample()`
  - ▶ `split()`

# Overview

## Goal

- ▶ Preprocessing of time series datasets
- ▶ Python package implemented in Rust
- ▶ Passing data by reference
  - ▶ Using `numpy` crate

## Scope

- ▶ Two types of datasets
  - ▶ `ForecastingDataSet`
  - ▶ `ClassificationDataSet`
- ▶ Functionality
  - ▶ `impute()`
  - ▶ `downsample()`
  - ▶ `split()`
  - ▶ `normalize()` / `standardize()`

# Data Input Format

**Input 3D numpy array:**

# Data Input Format

## Input 3D numpy array:

- ▶ **First dimension:** Instances

# Data Input Format

## Input 3D numpy array:

- ▶ **First dimension:** Instances
- ▶ **Second dimension:** Timesteps

# Data Input Format

## Input 3D numpy array:

- ▶ **First dimension:** Instances
- ▶ **Second dimension:** Timesteps
- ▶ **Third dimension:** Features



# Data Input Format

## Input 3D numpy array:


- ▶ **First dimension:** Instances
- ▶ **Second dimension:** Timesteps
- ▶ **Third dimension:** Features

Row	Features
1	...
2	...
3	...
4	...
.	
.	
.	
n-1	...
n	...

# Data Input Format

## Input 3D numpy array:

- ▶ **First dimension:** Instances
- ▶ **Second dimension:** Timesteps
- ▶ **Third dimension:** Features

The diagram illustrates a 3D numpy array structure. It shows a stack of multiple 2D tables, representing different instances. The top-most table is clearly visible, with a header row containing 'Row' and 'Features'. Below the header, the rows are numbered 1, 2, 3, 4, followed by a large grey block representing intermediate rows, and then n-1, n, and a final row with double quotes. Each row in this table is a different color: blue for row 1, green for row 2, orange for row 3, yellow for row 4, light grey for the intermediate block, pink for row n-1, and purple for row n. The subsequent tables in the stack are offset to the left and bottom, showing they follow the same structure but are not fully visible. The 'Features' column in all visible rows contains an ellipsis (...).

Row	Features
1	...
2	...
3	...
4	...
...	
n-1	...
n	...
"	...
"	...


# Data Input Format

## Input 3D numpy array:

- ▶ **First dimension:** Instances
- ▶ **Second dimension:** Timesteps
- ▶ **Third dimension:** Features

## In practice

- ▶ Forecasting datasets:
  - ▶ One instance



The diagram illustrates a 3D numpy array structure for forecasting datasets. It shows a stack of 2D arrays, each representing an instance. The first instance (top) has rows 1, 2, 3, 4, and a large block of rows (indicated by three dots), followed by rows n-1 and n. The second instance (middle) has rows 1, 2, 3, 4, and a large block of rows (indicated by three dots), followed by rows n-1 and n. The third instance (bottom) has rows 1, 2, 3, 4, and a large block of rows (indicated by three dots), followed by rows n-1 and n. The rows are color-coded: blue for row 1, green for row 2, orange for row 3, yellow for row 4, light grey for the large block, red for row n-1, and purple for row n. The columns are labeled 'Row' and 'Features'.

Row	Features
1	...
2	...
3	...
4	...
...	...
n-1	...
n	...


# Data Input Format

## Input 3D numpy array:

- ▶ **First dimension:** Instances
- ▶ **Second dimension:** Timesteps
- ▶ **Third dimension:** Features

## In practice

- ▶ Forecasting datasets:
  - ▶ One instance
- ▶ Classification datasets:
  - ▶ Multiple instances



The diagram illustrates a 3D numpy array structure. It shows a stack of multiple 2D tables. The top-most table is highlighted with a white background and black borders. It has two columns: 'Row' and 'Features'. The 'Row' column contains the values 1, 2, 3, 4, followed by three dots, then n-1, n, and another three dots. The 'Features' column contains three dots for each row. The tables below the top one are shown in various colors (light blue, light green, light orange, light yellow, light grey, light red, light purple) and are slightly offset to the left and bottom, indicating they are part of a stack. The 'Row' column of the bottom-most table is labeled with 'n' and a double quote, suggesting a sequence of instances.

Row	Features
1	...
2	...
3	...
4	...
...	...
n-1	...
n	...
...	...

# Performance considerations

## Copying

- ▶ Copying data is expensive

# Performance considerations

## Copying

- ▶ Copying data is expensive
- ▶ Avoid unnecessary copies

# Performance considerations

## Copying

- ▶ Copying data is expensive
- ▶ Avoid unnecessary copies
- ▶ Copy only when absolutely necessary

# Performance considerations

## Copying

- ▶ Copying data is expensive
- ▶ Avoid unnecessary copies
- ▶ Copy only when absolutely necessary
  - ▶ Only once



# Performance considerations

## Copying

- ▶ Copying data is expensive
- ▶ Avoid unnecessary copies
- ▶ Copy only when absolutely necessary
  - ▶ Only once

## When to copy?

# Performance considerations

## Copying

- ▶ Copying data is expensive
- ▶ Avoid unnecessary copies
- ▶ Copy only when absolutely necessary
  - ▶ Only once

## When to copy?

- ▶ For `ForecastingDataSet`:

# Performance considerations

## Copying

- ▶ Copying data is expensive
- ▶ Avoid unnecessary copies
- ▶ Copy only when absolutely necessary
  - ▶ Only once

## When to copy?

- ▶ For `ForecastingDataSet`:
  - ▶ Windowed format in final step

# Performance considerations

## Copying

- ▶ Copying data is expensive
- ▶ Avoid unnecessary copies
- ▶ Copy only when absolutely necessary
  - ▶ Only once

## When to copy?

- ▶ For `ForecastingDataSet`:
  - ▶ Windowed format in final step
  - ▶ Copying unavoidable

# Performance considerations

## Copying

- ▶ Copying data is expensive
- ▶ Avoid unnecessary copies
- ▶ Copy only when absolutely necessary
  - ▶ Only once

## When to copy?

- ▶ For `ForecastingDataSet`:
  - ▶ Windowed format in final step
  - ▶ Copying unavoidable
- ▶ For `ClassificationDataSet`:

# Performance considerations

## Copying

- ▶ Copying data is expensive
- ▶ Avoid unnecessary copies
- ▶ Copy only when absolutely necessary
  - ▶ Only once

## When to copy?

- ▶ For `ForecastingDataSet`:
  - ▶ Windowed format in final step
  - ▶ Copying unavoidable
- ▶ For `ClassificationDataSet`:
  - ▶ Random splitting strategy offered

# Performance considerations

## Copying

- ▶ Copying data is expensive
- ▶ Avoid unnecessary copies
- ▶ Copy only when absolutely necessary
  - ▶ Only once

## When to copy?


- ▶ For `ForecastingDataSet`:
  - ▶ Windowed format in final step
  - ▶ Copying unavoidable
- ▶ For `ClassificationDataSet`:
  - ▶ Random splitting strategy offered
  - ▶ Copying unavoidable

# Data-flow

Forecasting Dataset Data-Flow    Classification Dataset Data-Flow

Original Data  
(NumPy Array)




Original Data  
(NumPy Array)








# Data-flow

Forecasting Dataset Data-Flow    Classification Dataset Data-Flow






# Data-flow

## Forecasting Dataset Data-Flow    Classification Dataset Data-Flow






# Data-flow

## Forecasting Dataset Data-Flow    Classification Dataset Data-Flow




# Data-flow

## Forecasting Dataset Data-Flow    Classification Dataset Data-Flow




# Data-flow

Forecasting Dataset Data-Flow      Classification Dataset Data-Flow




# Data-flow

## Forecasting Dataset Data-Flow    Classification Dataset Data-Flow



# Data-flow

## Forecasting Dataset Data-Flow    Classification Dataset Data-Flow



# Pipeline Design

## ForecastingDataSet

```
# Create instance
fore = ForecastingDataSet(
    data, 0.7, 0.2, 0.1
)

# call the pipeline methods
fore.impute(
    ImputeStrategy.Median
)

fore.downsample(2)
fore.split()

fore.normalize()
fore.standardize()

# collect the results
fore_res = fore.collect(3, 1, 1)
```



# Pipeline Design

## ForecastingDataSet

```
# Create instance
fore = ForecastingDataSet(
    data, 0.7, 0.2, 0.1
)

# call the pipeline methods
fore.impute(
    ImputeStrategy.Median
)
fore.downsample(2)
fore.split()

fore.normalize()
fore.standardize()

# collect the results
fore_res = fore.collect(3, 1, 1)
```

## ClassificationDataSet

```
# create instance
clas = ClassificationDataSet(
    data, labels, 0.7, 0.2, 0.1
)

# call the pipeline methods
clas.impute(
    ImputeStrategy.Median
)
clas.downsample(2)
clas.split(
    SplittingStrategy.Random
)
clas.normalize()
clas.standardize()

# collect the results
clas_res = clas.collect()
```

# Downsampling I

**Goal:** Reduce the number of data points in a time series dataset.

# Downsampling I

**Goal:** Reduce the number of data points in a time series dataset.

**Benefits:**

- ▶ Reduces memory usage

# Downsampling I

**Goal:** Reduce the number of data points in a time series dataset.

## Benefits:

- ▶ Reduces memory usage
- ▶ Speeds up processing time

# Downsampling I

**Goal:** Reduce the number of data points in a time series dataset.

## Benefits:

- ▶ Reduces memory usage
- ▶ Speeds up processing time

## Necessary parameter when downsampling:

- ▶ Downsampling factor: How many data points to skip

# Downsampling I

**Goal:** Reduce the number of data points in a time series dataset.

## Benefits:

- ▶ Reduces memory usage
- ▶ Speeds up processing time


## Necessary parameter when downsampling:

- ▶ Downsampling factor: How many data points to skip

## Example:

- ▶ Downsampling factor of 2: Every second data point is kept

## Downsampling II



Downsampling example with a factor of 2

## Downsampling III

### How it works:

- ▶ The downsampling function takes a time series dataset and a downsampling factor as input.



# Downsampling III

## How it works:

- ▶ The downsampling function takes a time series dataset and a downsampling factor as input.
- ▶ It iterates over the dataset and keeps every  $n$ -th data point, where  $n$  is the downsampling factor.

# Downsampling III

## How it works:

- ▶ The downsampling function takes a time series dataset and a downsampling factor as input.
- ▶ It iterates over the dataset and keeps every  $n$ -th data point, where  $n$  is the downsampling factor.

## Bottleneck of passing the data by reference:

- ▶ Not possible. A copy is needed.

# Downsampling III

## How it works:

- ▶ The downsampling function takes a time series dataset and a downsampling factor as input.
- ▶ It iterates over the dataset and keeps every  $n$ -th data point, where  $n$  is the downsampling factor.

## Bottleneck of passing the data by reference:

- ▶ Not possible. A copy is needed.
- ▶ Creating view only possible on contiguous data.

# Downsampling III

## How it works:

- ▶ The downsampling function takes a time series dataset and a downsampling factor as input.
- ▶ It iterates over the dataset and keeps every  $n$ -th data point, where  $n$  is the downsampling factor.

## Bottleneck of passing the data by reference:

- ▶ Not possible. A copy is needed.
- ▶ Creating view only possible on contiguous data.
- ▶ Downsampling does not yield a contiguous data structure.

## Splitting I

**Goal:** Split a time series dataset into three parts: training, validation, and test.

# Splitting I

**Goal:** Split a time series dataset into three parts: training, validation, and test.

## Different splitting strategies:

- ▶ Random split (Classification Data)

# Splitting I

**Goal:** Split a time series dataset into three parts: training, validation, and test.

## Different splitting strategies:

- ▶ Random split (Classification Data)
- ▶ In-Order split (Classification Data)

# Splitting I

**Goal:** Split a time series dataset into three parts: training, validation, and test.

## Different splitting strategies:

- ▶ Random split (Classification Data)
- ▶ In-Order split (Classification Data)
- ▶ Temporal split (Forecasting Data)



# Splitting I

**Goal:** Split a time series dataset into three parts: training, validation, and test.

## Different splitting strategies:

- ▶ Random split (Classification Data)
- ▶ In-Order split (Classification Data)
- ▶ Temporal split (Forecasting Data)

## Necessary parameter when splitting:

- ▶ Training set ratio

# Splitting I

**Goal:** Split a time series dataset into three parts: training, validation, and test.

## Different splitting strategies:

- ▶ Random split (Classification Data)
- ▶ In-Order split (Classification Data)
- ▶ Temporal split (Forecasting Data)

## Necessary parameter when splitting:

- ▶ Training set ratio
- ▶ Validation set ratio

# Splitting I

**Goal:** Split a time series dataset into three parts: training, validation, and test.

## Different splitting strategies:

- ▶ Random split (Classification Data)
- ▶ In-Order split (Classification Data)
- ▶ Temporal split (Forecasting Data)

## Necessary parameter when splitting:

- ▶ Training set ratio
- ▶ Validation set ratio
- ▶ Test set ratio

## Splitting II (Random Split - Classification Data)

### How it works:

1. Validate the proportions of train, validation, and test sets.

## Splitting II (Random Split - Classification Data)

### How it works:

1. Validate the proportions of train, validation, and test sets.
2. Shuffle the instances of the dataset randomly.

## Splitting II (Random Split - Classification Data)

### How it works:

1. Validate the proportions of train, validation, and test sets.
2. Shuffle the instances of the dataset randomly.
3. Compute the split offsets based on the proportions.

## Splitting II (Random Split - Classification Data)

### How it works:

1. Validate the proportions of train, validation, and test sets.
2. Shuffle the instances of the dataset randomly.
3. Compute the split offsets based on the proportions.
4. Split the instances into three sets.


## Splitting II (Random Split - Classification Data)

### How it works:

1. Validate the proportions of train, validation, and test sets.
2. Shuffle the instances of the dataset randomly.
3. Compute the split offsets based on the proportions.
4. Split the instances into three sets.
5. Return the three sets as separate datasets.




## Splitting III (Random Split - Classification Data)



Random split example

## Splitting IV (In-Order Split - Classification Data)


Works very similar to the random split, but it **doesn't shuffle** the dataset anymore.



In-Order split example

## Splitting V (Temporal Split - Forecasting Data)

Similar to the in-order split, but this time we are dealing with forecasting data, which in most cases is only one instance and we split over **timesteps** and not instances anymore.



Temporal split example

## Standardization

**Goal:** Transform each feature in a time series dataset to have a **mean** of **0** and a **standard deviation** of **1**.

## Standardization

**Goal:** Transform each feature in a time series dataset to have a **mean** of **0** and a **standard deviation** of **1**.

### How it works

- ▶ Compute the mean and standard deviation for each feature column in the **training** dataset.

## Standardization

**Goal:** Transform each feature in a time series dataset to have a **mean** of **0** and a **standard deviation** of **1**.

### How it works

- ▶ Compute the mean and standard deviation for each feature column in the **training** dataset.
- ▶ Through a for-loop iterate over each feature and apply the standardization formula:

$$x' = \frac{x - \text{mean}}{\text{std}} \quad (1)$$

## Standardization

**Goal:** Transform each feature in a time series dataset to have a **mean** of **0** and a **standard deviation** of **1**.

### How it works

- ▶ Compute the mean and standard deviation for each feature column in the **training** dataset.
- ▶ Through a for-loop iterate over each feature and apply the standardization formula:

$$x' = \frac{x - \text{mean}}{\text{std}} \quad (1)$$

- ▶ Apply the same mean and standard deviation to the **validation** and **test** sets.

## Min-Max Normalization

**Goal:** Transform each feature in a time series dataset to a range between **0** and **1**.



## Min-Max Normalization

**Goal:** Transform each feature in a time series dataset to a range between **0** and **1**.

### How it works

- ▶ Compute the minimum and maximum for each feature in the **training** dataset.

## Min-Max Normalization

**Goal:** Transform each feature in a time series dataset to a range between **0** and **1**.

### How it works

- ▶ Compute the minimum and maximum for each feature in the **training** dataset.
- ▶ Through a for-loop iterate over each feature and apply the min-max normalization formula:

$$x' = \frac{x - \min}{\max - \min} \quad (2)$$

## Min-Max Normalization

**Goal:** Transform each feature in a time series dataset to a range between **0** and **1**.

### How it works

- ▶ Compute the minimum and maximum for each feature in the **training** dataset.
- ▶ Through a for-loop iterate over each feature and apply the min-max normalization formula:

$$x' = \frac{x - \min}{\max - \min} \quad (2)$$

- ▶ Apply the same min and max to the **validation** and **test** sets.

## Unit Tests I

**Goal:** Ensure the correctness of the implemented methods.

## Unit Tests I

**Goal:** Ensure the correctness of the implemented methods.

**Bottleneck:**

- ▶ Rust code is tightly integrated with PyO3.

## Unit Tests I

**Goal:** Ensure the correctness of the implemented methods.

**Bottleneck:**

- ▶ Rust code is tightly integrated with PyO3.
- ▶ PyO3 is not compatible with the standard Rust testing framework.

## Unit Tests I

**Goal:** Ensure the correctness of the implemented methods.

### Bottleneck:

- ▶ Rust code is tightly integrated with PyO3.
- ▶ PyO3 is not compatible with the standard Rust testing framework.
- ▶ PyO3 is a Rust crate that allows Rust code to be called from Python.

## Unit Tests I

**Goal:** Ensure the correctness of the implemented methods.

### Bottleneck:

- ▶ Rust code is tightly integrated with PyO3.
- ▶ PyO3 is not compatible with the standard Rust testing framework.
- ▶ PyO3 is a Rust crate that allows Rust code to be called from Python.
- ▶ PyO3 provides a way to write Python bindings for Rust code.



## Unit Tests I

**Goal:** Ensure the correctness of the implemented methods.

### Bottleneck:

- ▶ Rust code is tightly integrated with PyO3.
- ▶ PyO3 is not compatible with the standard Rust testing framework.
- ▶ PyO3 is a Rust crate that allows Rust code to be called from Python.
- ▶ PyO3 provides a way to write Python bindings for Rust code.

### Solution:

- ▶ Use the PyO3 testing framework.

## Unit Tests I

**Goal:** Ensure the correctness of the implemented methods.

### Bottleneck:

- ▶ Rust code is tightly integrated with PyO3.
- ▶ PyO3 is not compatible with the standard Rust testing framework.
- ▶ PyO3 is a Rust crate that allows Rust code to be called from Python.
- ▶ PyO3 provides a way to write Python bindings for Rust code.

### Solution:

- ▶ Use the PyO3 testing framework.
- ▶ Mimic the Python API in Rust.

## Unit Tests I

**Goal:** Ensure the correctness of the implemented methods.

### Bottleneck:

- ▶ Rust code is tightly integrated with PyO3.
- ▶ PyO3 is not compatible with the standard Rust testing framework.
- ▶ PyO3 is a Rust crate that allows Rust code to be called from Python.
- ▶ PyO3 provides a way to write Python bindings for Rust code.

### Solution:

- ▶ Use the PyO3 testing framework.
- ▶ Mimic the Python API in Rust.
- ▶ Write unit tests in Rust that can be called from Python.

## Unit Tests I

**Goal:** Ensure the correctness of the implemented methods.

### Bottleneck:

- ▶ Rust code is tightly integrated with PyO3.
- ▶ PyO3 is not compatible with the standard Rust testing framework.
- ▶ PyO3 is a Rust crate that allows Rust code to be called from Python.
- ▶ PyO3 provides a way to write Python bindings for Rust code.

### Solution:

- ▶ Use the PyO3 testing framework.
- ▶ Mimic the Python API in Rust.
- ▶ Write unit tests in Rust that can be called from Python.
- ▶ Use the PyO3 testing framework to run the tests.

## Unit Tests II

**Example:** Testing the `impute()` method.

**How it works:**

- ▶ Create a simple numpy array with missing values.

## Unit Tests II

**Example:** Testing the `impute()` method.

### How it works:

- ▶ Create a simple numpy array with missing values.
- ▶ Call the `impute()` method with a specific strategy.

## Unit Tests II

**Example:** Testing the `impute()` method.

### How it works:

- ▶ Create a simple numpy array with missing values.
- ▶ Call the `impute()` method with a specific strategy.
- ▶ Check if the missing values are filled correctly.

## Unit Tests II

**Example:** Testing the `impute()` method.

### How it works:

- ▶ Create a simple numpy array with missing values.
- ▶ Call the `impute()` method with a specific strategy.
- ▶ Check if the missing values are filled correctly.

### Coverage:

- ▶ The unit tests cover most of the implemented methods.



## Unit Tests II

**Example:** Testing the `impute()` method.

### How it works:

- ▶ Create a simple numpy array with missing values.
- ▶ Call the `impute()` method with a specific strategy.
- ▶ Check if the missing values are filled correctly.

### Coverage:

- ▶ The unit tests cover most of the implemented methods.
- ▶ Since tests are not native Rust tests, we couldn't use the standard Rust coverage tools.

## Unit Tests II

**Example:** Testing the `impute()` method.

### How it works:

- ▶ Create a simple numpy array with missing values.
- ▶ Call the `impute()` method with a specific strategy.
- ▶ Check if the missing values are filled correctly.

### Coverage:

- ▶ The unit tests cover most of the implemented methods.
- ▶ Since tests are not native Rust tests, we couldn't use the standard Rust coverage tools.
- ▶ We used the PyO3 testing framework to run the tests and check the coverage.

## Unit Tests II

**Example:** Testing the `impute()` method.

### How it works:

- ▶ Create a simple numpy array with missing values.
- ▶ Call the `impute()` method with a specific strategy.
- ▶ Check if the missing values are filled correctly.

### Coverage:

- ▶ The unit tests cover most of the implemented methods.
- ▶ Since tests are not native Rust tests, we couldn't use the standard Rust coverage tools.
- ▶ We used the PyO3 testing framework to run the tests and check the coverage.
- ▶ The coverage is not as detailed as with the standard Rust testing framework, but it is sufficient for our needs.

## Unit Tests III

### How we calculated the coverage:

- ▶ We used the PyO3 testing framework to run the tests.

## Unit Tests III

### How we calculated the coverage:

- ▶ We used the PyO3 testing framework to run the tests.
- ▶ Counted the number of all methods.

## Unit Tests III

### How we calculated the coverage:

- ▶ We used the PyO3 testing framework to run the tests.
- ▶ Counted the number of all methods.
- ▶ Counted the number of methods that were called during the tests.

## Unit Tests III

### How we calculated the coverage:

- ▶ We used the PyO3 testing framework to run the tests.
- ▶ Counted the number of all methods.
- ▶ Counted the number of methods that were called during the tests.
- ▶ Calculated the coverage as a percentage.

## Unit Tests III

### How we calculated the coverage:

- ▶ We used the PyO3 testing framework to run the tests.
- ▶ Counted the number of all methods.
- ▶ Counted the number of methods that were called during the tests.
- ▶ Calculated the coverage as a percentage.

### Results:

- ▶ Number of all methods: 47



## Unit Tests III

### How we calculated the coverage:

- ▶ We used the PyO3 testing framework to run the tests.
- ▶ Counted the number of all methods.
- ▶ Counted the number of methods that were called during the tests.
- ▶ Calculated the coverage as a percentage.

### Results:

- ▶ Number of all methods: 47
- ▶ Number of methods called during tests: 40

## Unit Tests III

### How we calculated the coverage:

- ▶ We used the PyO3 testing framework to run the tests.
- ▶ Counted the number of all methods.
- ▶ Counted the number of methods that were called during the tests.
- ▶ Calculated the coverage as a percentage.

### Results:

- ▶ Number of all methods: 47
- ▶ Number of methods called during tests: 40
- ▶ Coverage: 85.1%

## Kilian's Part