

Recursive implementation:

```
function DEPTH-LIMITED-SEARCH( problem, limit) returns soln/fail/cutoff
    RECURSIVE-DLS(MAKE-NODE(INITIAL-STATE[problem]), problem, limit)

function RECURSIVE-DLS(node, problem, limit) returns soln/fail/cutoff
    cutoff-occurred?  $\leftarrow$  false
    if GOAL-TEST[problem](STATE[node]) then return SOLUTION(node)
    else if DEPTH[node] = limit then return cutoff
    else for each successor in EXPAND(node, problem) do
        result  $\leftarrow$  RECURSIVE-DLS(successor, problem, limit)
        if result = cutoff then cutoff-occurred?  $\leftarrow$  true
        else if result  $\neq$  failure then return result
    if cutoff-occurred? then return cutoff else return failure
```

Graph search

```
function GRAPH-SEARCH(problem, fringe) returns a solution, or failure
  closed ← an empty set
  fringe ← INSERT(MAKE-NODE(INITIAL-STATE[problem]), fringe)
  loop do
    if fringe is empty then return failure
    node ← REMOVE-FRONT(fringe)
    if GOAL-TEST[problem](STATE[node]) then return SOLUTION(node)
    if STATE[node] is not in closed then
      add STATE[node] to closed
      fringe ← INSERTALL(EXPAND(node, problem), fringe)
```

function ITERATIVE-DEEPENING-SEARCH(*problem*) **returns** a solution, or failure

inputs: *problem*, a problem

for *depth* \leftarrow 0 **to** ∞ **do**

result \leftarrow DEPTH-LIMITED-SEARCH(*problem*, *depth*)

if *result* \neq cutoff **then return** *result*