

HSC-00 REVISION 12

COMPREHENSIVE ENGINEERING BASELINE

26,000 kg | Main Rotor 26.0 m | Tail Rotor 4.0 m | Capsule 7,000 kg

Founder: Amirbahador Atai

Revision 12 applies only the following controlled numerical updates: design mass **26,000 kg**; main rotor diameter **26.0 m**; tail rotor diameter **4.0 m**; with recalculated disk areas, disk loading, hover-power study figures and mass-accounting tables closed to 26,000 kg. All other narrative is retained without summarisation. Font size increased for readability.

TOP-LEVEL TECHNICAL BASELINE (REV 12)

Parameter	Rev 12 Value	Status
Design mass	26,000 kg	[TARGET]
Main rotor diameter	26.0 m	[TARGET]
Main rotor disk area	530.93 m²	[CALC]
Disk loading	48.97 kg/m²	[CALC]
Tail rotor diameter	4.0 m	[TARGET]
Tail rotor disk area	12.57 m²	[CALC]
Capsule mass	7,000 kg	[TARGET]
Range target	1,000 km	[TARGET]
Ideal hover power (study)	≈ 3.57 MW	[CALC]
Shaft power @ FM 0.75	≈ 4.76 MW	[CALC]
Occupancy	10–12 persons	[TARGET / STUDY]
Propulsion	Two turboshaft engines	[REQ / STUDY]

MASS ACCOUNTING — 26,000 kg

Mass Group	Planning Mass	Status
Survival capsule, complete	7,000 kg	TARGET
Main airframe excluding capsule	5,000 kg	ASSUMPTION / STUDY
Main rotor, hub and controls	2,100 kg	ASSUMPTION / STUDY
Tail rotor, gearbox and drive	480 kg	ASSUMPTION / STUDY
Engines, transmission, gearboxes and mounts	3,100 kg	ASSUMPTION / STUDY
Fuel system + full usable fuel	3,400 kg	ASSUMPTION / STUDY
Rapid separation system	1,000 kg	ASSUMPTION / STUDY
Avionics, electrical, hydraulic, thermal, control	1,600 kg	ASSUMPTION / STUDY
Operating fluids and consumables	320 kg	ASSUMPTION / STUDY
Growth / configuration reserve	2,000 kg	PROGRAM RESERVE
TOTAL	26,000 kg	CALC / CLOSURE

CAPSULE COMPONENT MASS — 7,000 kg

Capsule Component	Mass
Primary crashworthy cell / internal roll-cage	1,950 kg
Outer capsule shell / fairing / thermal protection	500 kg
Eight fixed landing supports + energy absorbers	850 kg
Crashworthy seats + restraints, 10–12 positions	700 kg
Emergency exits / doors, frames and seals	250 kg
Distributed multi-canopy recovery system	650 kg
Independent emergency power + batteries	250 kg
Life support / oxygen / environmental	200 kg
Avionics / sensing / communications / locator	250 kg
Separation interfaces + release hardware	350 kg
Internal secondary structure / floor / padding	500 kg
Fire / smoke detection and suppression	150 kg
Water landing / flotation / sealing	150 kg
Inspection / access / replaceable protection	100 kg
Capsule configuration growth allowance	150 kg
TOTAL	7,000 kg

Founder: Amirbahador Atai HSC Generation 1 — Document 00 —
Preliminary Controlled Engineering Baseline Page 1

HEAVY SAFE HELICOPTER (HSC) DOCUMENT 00 —
COMPREHENSIVE ENGINEERING BASELINE Generation 1 — HSC
Generation 1 26-TON-CLASS INTEGRATED SURVIVAL HELICOPTER
Separable Occupied Survival Capsule + Controlled Rapid Separation +
Multi-Mode Recovery Architecture Document Title HSC Generation 1 —
Comprehensive Engineering Baseline Document Number HSC-00
Document Type Master Engineering Specification — Conceptual / IP
Baseline Document Class Conceptual Engineering / Intellectual
Property Development Record Revision Rev 12 — Generation 1,
26-ton-class baseline Status [PROPOSED] Preliminary Controlled
Engineering Baseline Development Stage Pre-Simulation /
Pre-Hardware / Pre-Prototype Language English Confidentiality
Proprietary Concept Development Material Founder Amirbahador Atai
Engineering integrity statement: This document defines a controlled
conceptual baseline. Numerical values marked TARGET,
ASSUMPTION, STUDY, CALC or OPEN are not demonstrated
performance, certification results, or flight-proven values. Critical claims
require analytical closure, simulation, ground testing, integrated testing
and, where applicable, flight-test evidence. Revision intent: supersede
the previous Generation 1 planning baseline of 15,000 kg / 15 m main
rotor / 2.7 m tail rotor / 750–900 km range with a new controlled HSC
Generation 1 study baseline of 26,000 kg / 26.0 m main rotor / 4.0 m tail
rotor / 1,000 km range target, while preserving and strengthening the
survival-capsule, rapid-separation and independent-safety architecture.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 1

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 2

1. PURPOSE AND SCOPE HSC Generation 1 Generation 1 defines the system-level architecture for a 26-ton-class single-main-rotor helicopter whose primary distinguishing engineering concept is an occupied survival capsule that can become the final landing boundary during a catastrophic emergency. The aircraft is designed around a layered survival chain rather than reliance on a single emergency device. The V4.0 baseline covers the aircraft, occupied survival capsule, rapid selective separation system, safety initiation paths, deterministic safety authorization, stabilization, recovery systems, impact attenuation, post-event survival and the interfaces required to verify the complete chain. The design philosophy is not 'separate everything whenever the aircraft starts descending'. Separation is a controlled emergency mode authorized only when defined conditions are satisfied. The system must account for altitude, airspeed, attitude, angular rates, structural state, fire state, rotor state, available recovery modes, capsule clearance and downstream hazards. The survival architecture is intended to support multiple emergency outcomes: conventional flight recovery where possible, autorotation where applicable, selective hazard/mass reduction, capsule separation, parachute-assisted descent, energy-absorbing landing and post-landing rescue. The architecture must not require the most extreme survival mode for every failure. The baseline also preserves human emergency authority. Automatic systems may initiate or recommend a survival sequence only within defined authorization envelopes; the crew must retain an independent

means to command, inhibit or terminate automatic action where technically and physically possible. This document is an engineering/IP baseline, not a certification approval. Airworthiness, structural substantiation, parachute qualification, release reliability, occupant injury criteria, flight performance and global patent novelty remain open work items.

2. BASELINE STATUS AND CONFIGURATION CONTROL Status Label Meaning in this document [LOCKED CONCEPT] Architecture intentionally retained as a baseline design principle; implementation remains subject to engineering verification. [REQ] Top-level requirement proposed for subsequent requirement allocation. [TARGET] Numerical or functional development objective; not demonstrated. [ASSUMPTION / STUDY] Working engineering assumption used for preliminary sizing/accounting. [CALC] Value calculated from stated assumptions and equations. [OPEN] Requires analysis, simulation, test, supplier data or design decision. [TBD — DEPENDENCY] Cannot be responsibly fixed until a dependent design activity closes. [PRIOR ART STATUS: NOT YET SEARCHED] No novelty conclusion is implied. The V4.0 baseline shall be configuration-controlled. Any change to MTOW, rotor diameter, capsule mass, occupant count,

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 2

separation sequence, parachute architecture, landing-support geometry or safety-layer independence shall trigger an impact assessment across mass properties, CG, inertia, dynamics, structures, controls, recovery and verification.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 3

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 3

3. GENERATION 1 V4.0 TOP-LEVEL TECHNICAL BASELINE
Parameter HSC Generation 1 Gen1 Status Maximum Take-Off / Design
Mass 26,000 kg [TARGET] Occupancy 10–12 persons [TARGET /
STUDY] Flight architecture Conventional single main rotor + tail rotor
[REQ / STUDY] Main rotor diameter

26.0 m [TARGET] Main rotor disk area 530.93 m² [CALC] Weight-based
disk loading 48.97 kg/m² (480 N/m²) [CALC] Tail rotor diameter

4.0 m [TARGET] Tail rotor disk area

12.57 m² [CALC] Propulsion architecture Two turboshaft-class engines
[REQ / STUDY] Landing gear No retractable wheeled gear; 8 short,
thick fixed mechanical supports integrated with capsule [TARGET /
CONCEPT] Range 1,000 km [TARGET] Hover endurance To be
derived after power/fuel/thermal closure [OPEN] Survival capsule
Dedicated occupied final landing boundary [REQ] Capsule preliminary
complete mass 7,000 kg [TARGET] Capsule recovery Distributed
multi-canopy system; 8-canopy architecture for preliminary study

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 4

[STUDY] Airframe recovery parachute Optional independent
residual-airframe trade study [OPTION / OPEN] Rapid separation
Selective separation of designated high-mass/fire-hazard components

[REQ / CONCEPT] Separation development objective ≤ 6 s from validated command to verified capsule-clear state [TARGET / OPEN]

The 26.0 m rotor is intentionally sized for the 26-ton class. At 26,000 kg, the resulting weight-based disk loading is approximately 48.97 kg/m², calculated from rotor disk area. This is a sizing indicator, not a guarantee of hover, climb, OEI or hot/high performance. Preliminary ideal hover power is approximately 3.57 MW at sea-level standard density. Applying an illustrative figure-of-merit assumption of 0.75 gives approximately 4.76 MW rotor power. This is a study calculation only. Installed engine power must be determined from a complete power-required/power-available model including profile power, induced power, transmission losses, control margins, temperature, density altitude, rotor speed, transients and OEI requirements. The 1,000 km range is a design target. It shall not be presented as achieved range until the mission model closes with aircraft drag, rotor performance, engine specific fuel consumption, fuel capacity, reserves, payload, temperature/altitude and operational constraints.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 5

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 4

4. AIRCRAFT GEOMETRY AND CONFIGURATION The V4.0 geometry below is a preliminary architecture sized around the 26-ton class. Dimensions other than rotor diameters are deliberately kept as ranges or open items until aerodynamic, structural, cabin, capsule and systems layouts are reconciled. Geometry Item V4.0 Preliminary Definition Status Overall length Approx. 16.5–18.0 m [TARGET /

STUDY] Maximum fuselage width Approx. 4.0–4.5 m [TARGET / STUDY] Overall height Approx. 4.8–5.3 m [TARGET / STUDY] Main rotor diameter

26.0 m [TARGET] Tail rotor diameter

4.0 m [TARGET] Rotor arrangement Single main rotor + tail rotor [REQ / STUDY] Landing supports 8 fixed short mechanical supports under capsule [TARGET] Retractable landing gear None [LOCKED CONCEPT] Capsule position Central occupied boundary integrated within primary airframe [LOCKED CONCEPT] Capsule normal-flight load path Dedicated primary attachment system with controlled emergency release [REQ] Capsule emergency load path Capsule becomes independent final landing element after verified clearance [REQ] The eight landing supports shall not be treated as simple struts attached to a thin capsule shell. The intended load path is: ground contact → foot/ground interface → progressive energy absorber → lower capsule load path → primary capsule structure → occupant restraint/seat energy management. Structural sizing shall consider vertical, longitudinal, lateral and torsional loads, slope, uneven terrain, soft soil, asymmetric touchdown and failed-leg cases. Fixed short supports eliminate the mechanical complexity and failure modes associated with retractable landing gear, but their

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 6

permanent external geometry must be included in aerodynamic drag, ground clearance, rotor downwash, structural loads and emergency separation analyses.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 7

HSC Generation 1 — Document 00 — Comprehensive Engineering Baseline Page 5

5. PRELIMINARY MASS ACCOUNTING — 26,000 KG BASELINE The following accounting model is intentionally a planning model. It is constructed to close to 26,000 kg and must not be interpreted as a verified mass properties report. The complete capsule allocation of 7,000 kg is a preliminary target and includes the survival structure, seats/restraints, eight landing supports and energy absorbers, recovery parachute system, separation interfaces, internal emergency systems and essential post-landing survival provisions. The detailed capsule mass shall later be decomposed bottom-up. The 2,900 kg fuel-system/full-usable-fuel allocation is a study allocation only. It must be reconciled against actual fuel density, tank geometry, usable volume, unusable fuel, system mass, reserve policy and the 1,000 km mission model. No specific fuel volume is locked by this document. The 900 kg rapid-separation allocation is also a study value. It includes release mechanisms, local structural reinforcement, independent actuation power/signalling, locking/inhibit hardware, sensors and associated wiring/plumbing. It shall be refined after the actual jettison architecture is defined. Mass properties shall be maintained for: normal design/gross mass, minimum mission mass, maximum fuel, minimum fuel, forward/aft CG, lateral CG, capsule-attached configuration, partial separation, asymmetric separation, failed release, capsule-only descent and post-landing configuration. The 26,000 kg figure is an accounting closure, not a weighed aircraft. If detailed engineering exceeds the planning mass, the increase shall be reported and the configuration

shall be rebalanced under configuration control rather than artificially forcing the design back to 26,000 kg.

Mass Group Planning Mass Status

Survival capsule, complete 7,000 kg TARGET

Main airframe excluding capsule 5,000 kg ASSUMPTION / STUDY

Main rotor, hub and controls 2,100 kg ASSUMPTION / STUDY

Tail rotor, gearbox and drive 480 kg ASSUMPTION / STUDY

Engines, transmission, gearboxes and mounts 3,100 kg ASSUMPTION / STUDY

Fuel system + full usable fuel allocation 3,400 kg ASSUMPTION / STUDY

Rapid separation system + independent hardware 1,000 kg ASSUMPTION / STUDY

Avionics, electrical, hydraulic, thermal and control equipment 1,600 kg ASSUMPTION / STUDY

Operating fluids and consumables 320 kg ASSUMPTION / STUDY

Growth / configuration reserve 2,000 kg PROGRAM RESERVE

TOTAL 26,000 kg CALC / ACCOUNTING CLOSURE

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 8

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 6

6. PROPULSION, ROTOR AND PERFORMANCE CLOSURE 6.1

Propulsion architecture ● Two turboshaft-class engines are retained as the Generation 1 baseline architecture. ● No engine model or exact shaft power is locked in Document 00 V4.0. ● Engine selection shall be based on total installed power, OEI capability, hot/high operation, transient response, fuel consumption, thermal margins, transmission compatibility, maintenance and availability. ● The engine installation shall support controlled emergency isolation and, where technically justified, separation from the survival capsule. ● Fuel isolation must be coordinated with emergency separation and fire containment; separation shall not create a new uncontrolled fuel hazard.

6.2 Main rotor ● Nominal main rotor diameter: 26.0 m [TARGET]. ● Disk area: 530.93 m² [CALC]. ● Weight-based disk loading at 26,000 kg: 48.97 kg/m² [CALC]. ● Rotor blade mass, chord, twist, solidity, tip speed, rotor RPM, airfoil family and control authority remain [OPEN]. ● The rotor shall be analyzed for hover, climb, cruise, maneuver, autorotation, transient and emergency states. ● Any emergency rotor release concept is conditional. The main rotor shall not be designated universally jettisonable until structural, dynamic, aerodynamic, gyroscopic, trajectory, clearance and post-release control analyses demonstrate acceptability.

6.3 Tail rotor ● Nominal diameter: 4.0 m [TARGET]. ● Disk area: 12.57 m² [CALC]. ● Final tail rotor size shall be closed against main rotor torque, tail-arm geometry, anti-torque authority, directional control

margins, OEI states, crosswind and emergency configurations. ● Tail rotor, gearbox and drive may be candidates for controlled separation if the post-release dynamics are acceptable.

6.4 Performance closure requirements ● Power required versus power available over gross mass, altitude, temperature and rotor RPM. ● Hover ceiling and hot/high hover. ● Rate of climb and cruise performance.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 9

● One-engine-inoperative performance and safe operating envelope. ● Autorotation performance and rotor energy management. ● Transmission and gearbox thermal/torque limits. ● Rotor vibration and dynamic stability. ● Cruise drag and fuel flow. ● Mission fuel including reserves. ● 1,000 km range closure.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 10

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 7

7. 1,000 KM RANGE TARGET — MISSION DEFINITION The 1,000 km figure is retained as a high-value product requirement target, but the document deliberately does not fabricate a final cruise speed, fuel burn or reserve figure. These values depend on the selected rotor, airframe drag, engine, fuel system and mission profile. Mission Variable V4.0 Baseline Closure Requirement Design range 1,000 km [TARGET] Cruise speed TBD by aerodynamic/propulsion study [OPEN] Cruise altitude TBD by mission study [OPEN] Fuel quantity TBD by tank +

mission closure [OPEN] Reserve policy TBD by operational/certification basis [OPEN] Payload/occupancy 10–12 occupants + mission equipment [TARGET] Hot/high mission Required [REQ] OEI diversion/reserve case Required for safety assessment [REQ] The range model shall explicitly account for start/taxi or equivalent ground operation, climb, cruise, descent, loiter/diversion where applicable, reserve, unusable fuel, engine/transmission margins and environmental conditions. Range shall not be derived from fuel quantity alone.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 11

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 8

8. OCCUPIED SURVIVAL CAPSULE The occupied survival capsule is the central safety boundary of HSC Generation 1. During normal flight it is structurally integrated into the aircraft through controlled primary attachments. During a validated catastrophic survival sequence, it is intended to become an independent occupied landing element. Capsule Parameter V4.0 Definition Status Occupancy 10–12 persons [TARGET / STUDY] Complete capsule mass 7,000 kg planning target [TARGET] Primary structure Continuous CFRP roll-cage with metallic/titanium nodes and controlled joints [CONCEPT] Seats Energy-absorbing seats with five-point/appropriate restraints [TARGET] Landing supports 8 short, thick fixed mechanical supports with progressive energy absorption [TARGET] Parachute architecture Distributed multi-canopy; 8-canopy preliminary study architecture [STUDY] Capsule emergency systems Independent emergency power, sensing, locator, communications and essential life-support [TARGET] Capsule

clearance Verified before recovery deployment [REQ] Post-landing stability Eight-point support architecture with asymmetric/failed-leg analysis [REQ] The capsule shall be designed as a real structural system rather than a passenger cabin merely surrounded by a shell. The engineering program shall address load paths, crash loads, fatigue, damage tolerance, joints, attachment fittings, seat loads, floor loads, fire/smoke, environmental exposure, water/ditching provisions where required, emergency egress and occupant injury criteria. The capsule shall retain sufficient independent capability after separation to support recovery and rescue. Essential systems should not depend on the main airframe power bus after separation. Preliminary 7,000 kg capsule component-level planning allocation: Capsule Component — Mass Primary crashworthy protective cell / internal roll-cage structure — 1,950 kg Outer capsule shell / fairing / thermal protection — 500 kg Eight fixed landing supports + progressive energy absorbers — 850 kg

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 12

Crashworthy seats + occupant restraints, 10–12 positions — 700 kg Emergency exits / doors, frames and seals — 250 kg Distributed multi-canopy capsule recovery system — 650 kg Independent capsule emergency power + batteries — 250 kg Life support / emergency oxygen / environmental provisions — 200 kg Avionics / sensing / communications / locator / lighting — 250 kg Separation interfaces + capsule-side release hardware — 350 kg Internal secondary structure / floor / partitions / occupant padding — 500 kg Fire / smoke detection and suppression provisions — 150 kg Water landing / flotation / sealing provisions — 150 kg Inspection / access / replaceable protection

hardware — 100 kg Capsule configuration growth allowance — 150 kg
TOTAL — 7,000 kg

Capsule Component Mass

Primary crashworthy protective cell / internal roll-cage structure 1,950 kg

Outer capsule shell / fairing / thermal protection 500 kg

Eight fixed landing supports + progressive energy absorbers 850 kg

Crashworthy seats + occupant restraints, 10–12 positions 700 kg

Emergency exits / doors, frames and seals 250 kg

Distributed multi-canopy capsule recovery system 650 kg

Independent capsule emergency power + batteries 250 kg

Life support / emergency oxygen / environmental provisions 200 kg

Avionics / sensing / communications / locator / lighting 250 kg

Separation interfaces + capsule-side release hardware 350 kg

Internal secondary structure / floor / partitions / occupant padding 500 kg

Fire / smoke detection and suppression provisions 150 kg

Water landing / flotation / sealing provisions 150 kg

Inspection / access / replaceable protection hardware 100 kg

Capsule configuration growth allowance 150 kg

TOTAL 7,000 kg

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 13

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 9

9. EIGHT FIXED SHORT MECHANICAL LANDING SUPPORTS HSC Generation 1 uses eight short, thick, fixed mechanical supports located below the survival capsule. The concept is intentionally different from conventional retractable landing gear: the supports are part of the survival capsule's impact-attenuation system and remain with the occupants after separation. ● Eight supports provide load distribution and redundancy against uneven terrain and partial failure. ● Each support shall include a defined mechanical energy-absorption function rather than relying solely on elastic deformation. ● Replaceable or inspectable sacrificial/crush elements should be considered to improve post-event maintainability. ● The attachment system shall transmit controlled loads into the capsule's primary lower structure. ● The system shall be analyzed for vertical, lateral, longitudinal and combined impact loads. ● Asymmetric landing with one or more failed/degraded supports is a required analysis case. ● Terrain cases shall include hard flat ground, sloped ground, uneven ground and soft/low-bearing-strength surfaces. ● Ground clearance and rotor-downwash interaction shall be evaluated. ● Post-landing stability,

tipping resistance and rescue access shall be included. Preliminary capsule impact energy follows $E = 1/2 m v^2$. For a 7,000 kg capsule, illustrative kinetic energies are approximately 126.0 kJ at 6 m/s, 224.0 kJ at 8 m/s and 350.0 kJ at 10 m/s. These are not allowable impact energies; they are sizing illustrations only. Actual survival depends on energy absorption, occupant pulse, attitude/rates, terrain and structural response.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 14

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 10

10. SIX-LAYER SURVIVAL AND SAFETY ARCHITECTURE The V4.0 architecture retains and strengthens the six-layer functional survival philosophy from the previous LSH baseline. The layers are functionally distinct. Duplication alone shall never be used as evidence of independence. Independence shall be assessed for power, signal routing, sensors, processors, physical location, structural vulnerability, fire, EMI/lightning, common-cause failures and human interaction.

Layer	Function	Primary Purpose
L1	Primary automatic emergency detection and initiation	Detect catastrophic states and initiate a validated survival sequence when authorization conditions are met.
L2	Independent backup initiation	Provide a second physically/electrically segregated automatic path if L1 is unavailable.
L3	Independent manual/crew authority	Allow crew initiation, inhibit and emergency authority without dependence on L1/L2.
L4	Rapid selective physical separation	Separate designated mass/fire hazards from the capsule using controlled release mechanisms.
L5	Direct-impact survival	Protect occupants through

capsule structure, restraints, seats and eight energy-absorbing supports. L6 Recovery and post-event survival Deploy recovery system, stabilize landing, locate occupants and support post-landing survival/rescue. The architecture shall be evaluated as a chain, but it shall also be designed so that failure of one layer does not automatically eliminate all survival capability. For example, loss of automatic detection must not eliminate manual authority; loss of one release path must not necessarily eliminate all separation capability; and imperfect separation must not make the capsule structurally incapable of surviving residual loads. The design principle is: AI or advanced prediction may assist detection, classification and decision support; deterministic safety logic authorizes safety-critical actuation. Confidence or model output shall never be treated as equivalent to safety authorization.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 15

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 11

11. DETERMINISTIC SAFETY AUTHORIZATION AND SAFETY KERNEL The Safety Kernel is the deterministic authorization boundary between emergency detection/decision logic and physical survival actuation. Its purpose is to prevent a computationally complex or uncertain decision layer from directly commanding hazardous separation without satisfying explicit safety preconditions. The Safety Kernel shall evaluate, as applicable: ● Altitude above terrain and minimum recovery altitude. ● Airspeed and dynamic pressure envelope. ● Pitch, roll, yaw and angular-rate limits. ● Rotor RPM, rotor state and rotor control state. ● Engine/fire/fuel hazard state. ●

Structural health and confirmed structural failure state. ● Capsule attachment health and release readiness. ● Separation trajectory clearance. ● Potential collision between released components and capsule/parachutes. ● Parachute deployment envelope and recovery-system availability. ● Landing support availability and degraded configurations. ● Sensor validity and disagreement. ● Power availability for release and recovery systems. ● Communication availability where communication is part of the architecture. ● Manual crew authority and emergency override state. ● Rollback/fallback availability. If the safety conditions are not satisfied, the system shall inhibit the unsafe action or transition to a defined degraded mode. The design shall define what constitutes 'no safe optimal solution': safety and physical feasibility take priority over optimization or mission continuation. No software model, AI classifier, optimizer or predictive system shall bypass the Safety Kernel, aircraft protection systems, interlocks, equipment limits or human emergency authority.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 16

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 12

12. CONTROLLED RAPID SEPARATION SYSTEM 12.1 Separation philosophy The rapid separation system is a selective, staged, controlled mechanism for reducing the mass, fire load and rotating/energetic hardware that must remain associated with the occupied capsule during the final descent. It is not a blanket requirement to release every aircraft component in every emergency. The system shall use state-dependent release logic. Components shall

be designated as jettisonable only after structural, aerodynamic, dynamic, fire, control, trajectory and collision analysis demonstrates that release is acceptable within a defined envelope.

12.2 Candidate separable components ● Main engines and associated high-mass engine installation interfaces, where practical. ● Selected transmission/drive components where release is structurally and dynamically acceptable. ● Main rotor blades and/or hub components only if detailed dynamic and trajectory analysis demonstrates safe clearance; main rotor release is NOT universally locked. ● Tail rotor, tail-rotor gearbox and drive shafting where release is safe. ● Primary fuel tanks and major fuel lines that constitute a significant fire hazard, after safe fuel isolation. ● Selected external structural panels or high-mass attachments that do not form part of the capsule primary load path. ● Other components only through configuration-controlled hazard and trajectory analysis.

12.3 Mandatory release protections ● Positive mechanical retention during normal flight. ● Electrical/logic inhibits against inadvertent release. ● Independent command paths. ● Defined arm/fire sequence. ● Release-state sensing. ● Fuel and energy isolation before or coordinated with release. ● Asymmetric/partial-release detection. ● Post-release trajectory monitoring where practical. ● Capsule-clear verification before parachute authorization. ● Defined failed-release and rollback/fallback behavior.

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 13

13. PRELIMINARY SIX-SECOND SURVIVAL SEQUENCE The following sequence is a development objective inherited and strengthened from the prior LSH rapid-jettison baseline. It is intentionally aggressive and shall remain [OPEN] until mechanism tests and dynamic simulations demonstrate that timing, reliability and separation quality can be achieved. Time Action Safety Purpose
0.0–0.4 s Validate emergency state; arm authorized release path; isolate fuel/electrical/energy hazards Prevent release during an invalid or unsafe state. 0.4–2.2 s Stage primary high-mass/rotating-system release where authorized Reduce major mass and energy/fire hazards.

2.2–3.8 s Release tail-rotor/drive and primary fuel hazards where authorized Remove remaining major hazards.

3.8–5.4 s Release remaining designated airframe/capsule attachments Free the capsule from the main airframe.

5.4–6.0 s Verify capsule clearance and recovery envelope Prevent premature parachute deployment. After clearance Authorize capsule recovery system Transition to capsule-only or capsule-dominant survival state. The sequence shall not be treated as a fixed certification requirement. If the detailed architecture cannot safely achieve ≤ 6 s, the target shall be revised under configuration control rather than achieved by reducing verification rigor. Partial and asymmetric separation are first-class emergency states. The system shall not assume that every release mechanism functions perfectly. It must recognize which

components remain attached and determine whether the resulting state is survivable, whether another controlled action is permitted, or whether the capsule must proceed with degraded recovery.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 18

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 14

14. MULTI-MODE RECOVERY ARCHITECTURE The HSC Generation 1 recovery architecture is intentionally layered so that survival is not dependent on one device. Recovery Mode Use Case Status Controlled flight recovery Recoverable control/propulsion disturbance [REQ / STUDY] Autorotation Engine/power loss when altitude/rotor state permit [REQ / STUDY] Selective mass/hazard separation Fire, structural or combined emergency requiring reduction of carried hazard/mass [REQ / CONCEPT] Capsule separation Catastrophic state where independent occupied recovery is preferable [REQ / CONCEPT] Distributed capsule parachutes Primary post-separation vertical recovery [STUDY — 8 CANOPIES] Eight energy-absorbing supports Final ground impact attenuation [REQ / TARGET] Optional airframe recovery parachute Residual-airframe recovery or unmanned asset protection [OPTION / TRADE STUDY] Post-landing survival Locator, communications, lighting, emergency power and rescue interface [REQ] The capsule parachute system should be distributed rather than treated as a single-point canopy where practical. The final number, canopy size, deployment sequence, reefing, riser architecture, failure tolerance and inflation dynamics require parachute sizing and test. An independent parachute for the residual main airframe is retained as an optional trade

study, not a mandatory V4.0 requirement. It can be valuable for reducing ground hazard, protecting unmanned equipment or providing an additional recovery mode, but it introduces additional mass, drag, deployment hazards and potential interaction with the capsule. Its value shall therefore be established through system-level trade analysis.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 19

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 15

15. EMERGENCY STATE MACHINE HSC Generation 1 shall use an explicit emergency state machine rather than a single binary 'normal/emergency' flag.

- 1 NORMAL FLIGHT — all safety layers monitored; release hardware mechanically locked.
- 2 ANOMALY DETECTED — sensor/model detects a potential abnormal condition.
- 3 CONFIRMATION — independent evidence and validity checks determine whether the condition is real.
- 4 IMPACT ASSESSMENT — estimate control authority, altitude, airspeed, fire/structural risk, rotor/engine state and available recovery modes.
- 5 RECOVERY ATTEMPT — use conventional control, engine redundancy or autorotation where safe and appropriate.
- 6 SURVIVAL AUTHORIZATION — Safety Kernel evaluates whether selective separation/capsule recovery is permitted.
- 7 STAGED SEPARATION — execute only the designated release set for the specific emergency state.
- 8 CAPSULE CLEARANCE — verify physical separation and identify any attached components.
- 9 RECOVERY DEPLOYMENT — authorize parachute/recovery system within validated envelope.
- 10 DESCENT MANAGEMENT — monitor attitude, rates, canopy state and

landing-support readiness. 11 LANDING ATTENUATION — deploy/condition energy absorbers as required. 12 POST-LANDING SURVIVAL — stabilize, locate, communicate, protect occupants and support rescue. 13 AUDIT — preserve event data, release states, sensor states and command history for engineering analysis. Representative state-dependent behavior: an isolated engine failure should not automatically trigger capsule separation; a major fire may prioritize fuel isolation and selective separation; loss of control may require a different separation envelope; structural damage may require immediate transition; a combined catastrophic event may require the full survival chain.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 20

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 16

16. INDEPENDENCE, FAILURE MODES AND COMMON-CAUSE CONTROL The survival architecture introduces new hazards as well as new protections. The following failure classes shall be treated as explicit design cases. Failure / Hazard Required Design Response Unintended separation Mechanical locks, electrical inhibits, command validation, monitoring and quantitative safety objective. Partial separation State sensing, asymmetric-load analysis and defined degraded recovery mode. Asymmetric separation Dynamic analysis, CG/inertia update and post-release control assessment. Release mechanism failure Independent path or defined safe fallback; no assumption of perfect release. Sensor loss / bad data Validity monitoring, redundant/diverse sensing and safe-state logic. Automatic detection failure Independent

backup and manual crew initiation. Power-bus failure Independent survival power where required for critical functions. Communication loss Local deterministic safety logic; communication shall not be the sole authorization path. AI/model failure Deterministic safety logic remains authoritative. Fire during separation Fuel isolation, fire containment and release sequencing. Released component collision Trajectory analysis, clearance envelopes and controlled sequencing. Parachute deployment outside envelope Hard inhibits and validated deployment conditions. Landing-support failure Eight-support redundancy and asymmetric/failed-leg structural cases. Common-cause EMI/lightning/fire/structural damage Dedicated common-cause analysis and physical/electrical segregation. Independence is not established merely because two boxes, sensors or switches exist. The verification program shall assess common power, common wiring routes, common structure, common software, common sensor physics, common fire zones and common environmental vulnerabilities.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 21

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 17

17. INTELLIGENT MONITORING, PREDICTION AND CONTROL BOUNDARY HSC Generation 1 may incorporate advanced health monitoring, digital-twin estimation, predictive fault detection and AI-assisted decision support. These functions shall remain bounded by deterministic safety authorization. Recommended information/control chain: State / Health Estimation → Emergency Prediction / Forecast → Risk State → Candidate Recovery Actions → Resilience-First Decision

→ Deterministic Safety Validation → Interlock / Precondition Verification
→ Controlled Actuation → Post-Action Monitoring → Rollback / Fallback
→ Immutable Event Record ● AI may detect patterns, estimate degradation and rank candidate actions. ● AI may not directly bypass interlocks or safety limits. ● AI confidence shall not be treated as safety authorization. ● Deterministic protection and safety logic remains authoritative. ● Human emergency authority remains non-bypassable. ● Model failure shall lead to a defined degraded mode. ● Critical command paths shall have software/configuration integrity controls. ● All emergency decisions shall generate an auditable event record.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 22

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 18

18. PRINCIPAL SYSTEM INTERFACES Interface Definition Control Requirement CAP-AF Capsule ↔ airframe structural attachment Normal-flight load path + controlled emergency release + positive retention. CAP-PAR Capsule ↔ parachute system Deployment only after validated capsule state and clearance. CAP-LG Capsule ↔ eight landing supports Primary crash/landing load path with energy absorption. JET-PWR Independent release power Segregated from common single-point power failure where required. JET-CMD Automatic/backup/manual commands Independent paths and protected actuation. JET-SNS Release-state sensing Positive confirmation of attached/released state. FUEL-ISO Fuel isolation ↔ separation Isolation before or coordinated with release according to hazard analysis. REC-LOC Post-landing locator/communications Independent

emergency power and antenna strategy. AV-CTRL Avionics/control ↔ Safety Kernel Deterministic authorization boundary. All interfaces crossing survival boundaries shall be documented in Interface Control Documents and assessed for common-cause vulnerability. Connector, harness, hydraulic, fuel and structural interfaces shall be designed so that emergency separation does not create an uncontrolled hazard.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 23

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 19

19. VERIFICATION, VALIDATION AND EVIDENCE PROGRAM V4.0 deliberately separates conceptual definition from demonstrated performance. The following evidence gates are required before any high-confidence safety or performance claim is made. Gate Evidence Objective G0 Architecture Freeze Confirm safety philosophy, system boundaries, interfaces and emergency states. G1 Analytical Closure Mass, CG, inertia, rotor sizing, power, fuel, structural load paths and separation kinematics. G2 Subsystem Demonstration Release mechanisms, locks/inhibits, energy absorbers, parachute components, sensors and independent power. G3 Integrated Ground Demonstration End-to-end sequence without flight exposure; verify timing, state sensing and capsule clearance. G4 Dynamic / 6-DOF Simulation Vehicle and capsule dynamics through representative emergency states, partial/asymmetric release and parachute inflation. G5 Structural / Crash Testing Capsule, attachment points, seats, landing supports, energy absorbers and occupant-protection evidence. G6 Recovery System Testing Canopy deployment, inflation loads, failure cases,

stability and landing performance. G7 Flight Development Controlled flight tests within approved envelope; validate normal and emergency recovery behavior. G8 Certification / Qualification Evidence package against the selected certification basis and applicable standards. Terms shall be used carefully: 'specified' means defined in the design; 'analyzed' means a documented analytical result; 'simulated' means supported by a model; 'tested' means demonstrated in a defined test; 'verified' means evidence shows compliance with a requirement; 'validated' means suitability has been established for the intended use; 'qualified' and 'certified' require the applicable formal processes.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 24

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 20

20. 6-DOF EMERGENCY DYNAMICS PROGRAM A dedicated six-degree-of-freedom simulation shall be developed for the aircraft, separated capsule and relevant released components. The simulation shall include translation and rotation, component release impulses, aerodynamic forces, rotor/propulsor effects where relevant, parachute inflation and terrain interaction. ● Aircraft pre-release attitude, airspeed, altitude and angular-rate envelopes. ● Release impulse and mechanism timing. ● Component mass, CG and inertia before and after each release. ● Asymmetric and partial release configurations. ● Main rotor and tail rotor release cases only where under active study. ● Capsule aerodynamic coefficients across relevant attitudes. ● Parachute deployment and inflation transient loads. ● Canopy failure/degradation cases. ● Ground-contact kinematics with slope and

uneven terrain. ● Landing-support deformation and energy absorption. ● Occupant acceleration/pulse proxies for early screening. ● Collision envelopes between released hardware, capsule and parachutes. The 6-DOF model is a core verification tool, not a substitute for physical testing. Model uncertainty, sensitivity and correlation to test data shall be documented.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 25

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 21

21. ENGINEERING / IP VALUE SURFACES The following architecture elements are candidate IP extraction surfaces. Their legal novelty and patentability are NOT established by this document and require a professional prior-art search and claim analysis. Candidate IP Element Technical Content IP-ELEMENT-0001 Occupied survival boundary integrated into a 26-ton-class rotorcraft architecture. IP-ELEMENT-0002 State-dependent selective separation of high-mass and fire-hazard systems from an occupied survival capsule. IP-ELEMENT-0003 Deterministic Safety Kernel authorizing separation/recovery based on physical preconditions. IP-ELEMENT-0004 Six-layer survival architecture combining diverse initiation, physical separation, impact attenuation and post-event recovery. IP-ELEMENT-0005 Eight-support capsule-integrated impact attenuation architecture. IP-ELEMENT-0006 Coordinated multi-mode recovery chain: control recovery → autorotation → selective separation → capsule recovery → ground attenuation. IP-ELEMENT-0007 State-aware post-separation management for partial/asymmetric release states. IP-ELEMENT-0008

Optional coordinated residual-airframe recovery as a separate survival mode. IP-ELEMENT-0009 Immutable emergency event record linking detection, authorization, release states and recovery status.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 26

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 22

22. PROPOSED TOP-LEVEL REQUIREMENT SET ID Requirement / Target Status HSC-REQ-SYS-001 Aircraft shall provide 10–12 occupant provisions within the selected cabin/capsule configuration. [REQ / TARGET] HSC-REQ-SYS-002 Generation 1 shall use a single main rotor and tail rotor architecture. [REQ] HSC-REQ-SYS-003 Design mass shall be based on a 26,000 kg target configuration. [TARGET] HSC-REQ-ROT-001 Main rotor diameter target shall be 26.0 m. [TARGET] HSC-REQ-ROT-002 Tail rotor diameter target shall be 4.0 m. [TARGET] HSC-REQ-RNG-001 Design range target shall be 1,000 km subject to mission closure. [TARGET] HSC-REQ-CAP-001 Occupied survival capsule shall constitute the final landing boundary in capsule-recovery mode. [REQ] HSC-REQ-CAP-002 Capsule shall include structural protection, occupant restraint, impact attenuation and post-event survival provisions. [REQ] HSC-REQ-LG-001 Capsule shall use eight short fixed mechanical landing supports as the preliminary architecture. [TARGET] HSC-REQ-JET-001 Rapid separation shall be selective and state-dependent. [REQ] HSC-REQ-JET-002 Automatic initiation and independent manual initiation shall be provided. [REQ] HSC-REQ-JET-003 Unintended separation shall be treated as a catastrophic hazard. [REQ] HSC-REQ-JET-004 No component shall be

universally jettisonable without structural, dynamic, fire, control and collision analysis. [REQ] HSC-REQ-JET-005 Partial/asymmetric separation shall be explicitly modeled and detected. [REQ] HSC-REQ-SAF-001 Deterministic safety authorization shall be independent of AI confidence. [REQ]

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 27

HSC-REQ-SAF-002 Human emergency authority shall not be bypassable. [REQ] HSC-REQ-REC-001 Capsule recovery shall use a distributed multi-canopy architecture subject to sizing. [REQ / STUDY] HSC-TGT-JET-001 Validated command to verified capsule-clear state target ≤ 6 s. [TARGET / OPEN]

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 28

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 23

23. CRITICAL OPEN ITEMS — V4.0 1 Close the 26,000 kg mass model using component-level estimates and uncertainty. 2 Close the 10–12 occupant capsule geometry and bottom-up mass. 3 Select/size main rotor blade geometry, RPM, solidity, control system and transmission. 4 Close tail rotor sizing against torque and directional-control requirements. 5 Select candidate engines and close total installed power and OEI performance. 6 Develop 1,000 km mission fuel model including reserves. 7 Develop full 6-DOF aircraft/capsule/released-component model. 8 Define the exact set of jettisonable components for each emergency state. 9 Prove safe separation trajectories and post-jettison control for each candidate

component. 10 Develop independent automatic and manual command architecture and common-cause analysis. 11 Define Safety Kernel requirements and deterministic implementation boundary. 12 Size the distributed parachute system and establish canopy failure tolerance. 13 Evaluate optional residual-airframe parachute versus added mass, drag and deployment risk. 14 Size the eight landing supports and energy absorbers, including asymmetric failures. 15 Perform capsule structural, crash, fatigue and damage-tolerance analyses. 16 Define occupant injury criteria and test instrumentation. 17 Define emergency power and post-separation electrical architecture. 18 Define fire, fuel isolation and thermal protection architecture. 19 Define emergency egress, rescue, locator and communication provisions. 20 Establish certification basis and verification matrix. These open items are not weaknesses to be hidden; they are the correct engineering gates that separate a strong conceptual IP baseline from an unsupported performance claim.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 29

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 24

24. ENGINEERING BASIS AND EXTERNAL REFERENCE NOTES

The V4.0 baseline is derived primarily from the user's prior LSH Document 00 Rev3.2 and the higher-maturity rapid-jettison Generation 1 document. The previous baseline established the six-layer survival philosophy, independent automatic/manual initiation, controlled separation, eight landing supports, capsule-as-final-landing-boundary concept, six-second development objective and the need to treat partial/asymmetric separation as first-class states. The current V4.0

update changes the Generation 1 planning point to 26,000 kg, 26.0 m main rotor, 4.0 m tail rotor and 1,000 km range target. The numerical 26-ton mass accounting in this revision is a new preliminary study allocation and must be replaced by a bottom-up mass model during engineering development. Current EASA CS-29 material was reviewed as an external engineering reference. The EASA material emphasizes that jettisonable configurations require satisfactory separation characteristics, including clear trajectory, no damaging interaction, no adverse/uncontrollable aircraft reaction, acceptable post-jettison stability/control and acceptable post-jettison performance; the V4.0 verification program therefore treats these as core analysis/test concerns rather than assuming safe release. External reference: EASA, Easy Access Rules for Large Rotorcraft (CS-29), Amendment 12, March 2026. <https://www.easa.europa.eu/en/document-library/easy-access-rules/online-publications/easy-access-rules-large-rotorcraft-cs-29-12> Source baseline files used: LSH_00_Lightweight_Safe_Helicopter_Gen1_Rev3_2.pdf and USCC_Document_00_Lightweight_Jettison_Gen1_Rev1.3_HigherMaturity-2.pdf. The source documents explicitly state that their numerical performance values are preliminary and that independence, jettison timing, parachute sizing, impact loads and mass properties remain verification gates.

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 30

HSC Generation 1 — Document 00 — Preliminary Controlled Engineering Baseline Page 25

25. V4.0 DESIGN PHILOSOPHY — CONTROLLED SURVIVAL, NOT A SINGLE DEVICE The defining engineering proposition of HSC Generation 1 is the integration of multiple survival mechanisms into one state-aware architecture. The aircraft is not intended to depend solely on a parachute, solely on autorotation, solely on a detachable cabin or solely on automatic software. The intended chain is: PREVENT / MONITOR → DETECT → CONFIRM → ASSESS → RECOVER IF POSSIBLE → SAFETY AUTHORIZE → SELECTIVELY SEPARATE → VERIFY CAPSULE CLEARANCE → DEPLOY RECOVERY → MANAGE DESCENT → ABSORB IMPACT → SURVIVE / LOCATE / RESCUE → AUDIT The architecture becomes especially valuable when several failure mechanisms occur together. A single-engine failure may be handled by normal redundancy or autorotation; a fire may require fuel isolation and selective separation; a loss of control may require a different survival state; a combined fire/control/structural event may require the full capsule recovery chain. The V4.0 baseline therefore treats safety as a system architecture and verification problem. The strongest future evidence will come from a closed mass model, rotor/propulsion analysis, 6-DOF simulation, deterministic safety logic, separation mechanism tests, capsule structural tests, parachute tests and progressively integrated demonstrations. Document disposition: V4.0 is suitable as the controlled conceptual/master engineering baseline for the next engineering phase. It should not yet be presented as a certified aircraft specification or as proof of achieved 26-ton performance, 1,000 km range or survival probability. END OF DOCUMENT 00 — HSC Generation 1 GENERATION 1

HSC Generation 1 — Document 00 — Comprehensive Engineering Baseline

26. DETAILED AIRCRAFT MASS BREAKDOWN — HSC GENERATION 1 The following component-level allocation is a planning-level engineering decomposition of the 26,000 kg top-level accounting model. It is not a manufacturing BOM, weighed hardware result, or certification mass-properties report.

Main Airframe — 5,000 kg

- Fuselage primary load-bearing structure — 1,450 kg
- Frames, bulkheads and longerons — 650 kg
- Tail boom and tail structural assemblies — 520 kg
- Engine and transmission support structure — 380 kg
- Rotor mast/transmission support integration structure — 260 kg
- External skins, fairings and aerodynamic panels — 310 kg
- Doors, access panels and hinges — 190 kg
- Firewalls, barriers and structural fire protection — 170 kg
- Structural fittings, lugs, fasteners and local reinforcements — 260 kg
- Cabin/service floor structure outside capsule boundary — 210 kg

Main Rotor System — 2,100 kg

- Main rotor blades — 26.0 m system — 980 kg
- Rotor hub and blade retention/grips — 280 kg
- Mast and rotor-head structural components — 260 kg
- Swashplate and pitch-control hardware — 170 kg
- Pitch links, control rods and bearings — 110 kg
- Rotor vibration/dynamic-control hardware — 80 kg
- Rotor lubrication/inspection/access hardware — 40 kg

Configuration allowance — 40 kg

Tail Rotor System — 480 kg

- Tail rotor blades — 4.0 m system — 145 kg
- Tail rotor hub and blade retention — 65 kg
- Tail rotor gearbox — 95 kg
- Drive shafting, couplings and bearings — 60 kg
- Tail rotor controls and pitch mechanism — 35 kg
- Tail structure/interface hardware — 25 kg

Engines and Main Transmission System — 3,100 kg

- Engine #1

complete installed — 700 kg • Engine #2 complete installed — 700 kg • Engine accessories and engine-control hardware — 180 kg • Main gearbox / combining transmission — 650 kg • Intermediate/reduction transmission elements — 180 kg • Drive shafts and couplings — 100 kg • Lubrication, oil cooling and filtration — 80 kg • Engine/gearbox mounts and vibration isolation — 60 kg • Exhaust and hot-section installation hardware — 50 kg Fuel System + Full Usable Fuel — 3,400 kg • Usable fuel mass — 2,100 kg • Fuel tanks and crash/fire-resistant tank structure — 280 kg • Fuel pumps and boost/transfer units — 90 kg • Fuel lines, hoses, valves and fittings — 110 kg • Fuel filters, sensors and quantity measurement — 55 kg • Fuel isolation/emergency shutoff hardware — 75 kg • Venting, surge and inerting/fire-protection provisions — 70 kg • Unusable/residual fuel allocation — 120 kg Rapid Selective Separation System — 1,000 kg

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 32

- Primary capsule release mechanisms and locks — 240 kg • Independent backup release mechanisms — 150 kg • Local structural reinforcement and release fittings — 160 kg • Independent initiators/actuators — 90 kg • Release-state sensors and monitoring — 65 kg • Independent power/signalling and protected wiring — 70 kg • Fuel/energy isolation interfaces — 55 kg • Retention, inhibit and safety-interlock hardware — 50 kg • Configuration growth allowance — 20 kg Avionics / Electrical / Hydraulic / Thermal / Control — 1,600 kg • Flight-control computers/control electronics — 180 kg • Flight-control actuators/servo hardware — 210 kg • Navigation/air-data/flight sensors — 100 kg • Communications/mission avionics — 90 kg • Electrical

generation/distribution — 190 kg • Batteries/emergency electrical interfaces — 90 kg • Wiring/harnesses/connectors — 170 kg • Hydraulic pumps/reservoirs/lines/actuators — 180 kg • Thermal management/cooling — 100 kg • Environmental control/ventilation — 70 kg • Fire detection/warning/suppression interfaces — 55 kg • Health monitoring/data recording — 45 kg • Lighting/service/misc. — 20 kg
Operating Fluids & Consumables — 320 kg • Engine/transmission oil and other operating fluids — 180 kg • Hydraulic fluid — 35 kg • Coolant/thermal working fluid — 30 kg • Other trapped/operating consumables — 55 kg

Founder: Amirbahador Atai

HSC-00 Rev. 01 — Controlled Conceptual / IP Baseline Page 33

HSH (HEAVY SAFE HELICOPTER) DOCUMENT 00 — LARGE-FONT STRATEGIC LICENSING ENHANCEMENT Generation 1 | Founder: Amirbahador Atai 33-page original baseline retained unchanged; large-font version applies to the appended enhancement material only.

IMPORTANT: The original 33-page baseline is reproduced as-is in the integrated PDF. Only the newly appended licensing material is typeset in larger font.

01. EXECUTIVE LICENSING PROPOSITION HSH Generation 1 is positioned as a licensable conceptual and architectural IP package centred on an occupied survival capsule that can become the final landing boundary in a catastrophic emergency. The underlying 33-page HSC-00 V4.0 baseline defines a 26-ton-class single-main-rotor

helicopter, a 26.0 m main rotor target, a 4.0 m tail-rotor target, a 1,000 km range target, controlled selective separation, deterministic safety authorization, and multi-mode recovery.

Licensing interpretation: • Core IP proposition: the occupied survival boundary is treated as a dedicated survival system rather than only as a conventional cabin. • System-level differentiator: survival is organised as a chain of detection, authorization, selective separation, capsule protection, recovery and post-event survival. • Commercial proposition: a licensee receives access to an architectural starting point and controlled IP-development framework, not a certified production helicopter. • Buyer value: the architecture is structured so that engineering closure, verification evidence, certification work and future productisation can be managed as explicit workstreams. • License value should therefore be assessed against the reusable architecture, defined interfaces, candidate IP surfaces, verification roadmap and technology-transfer potential.

Status: [PROPOSED] Additive commercial/IP interpretation. No new performance claim is created by this section.

02. ARCHITECTURAL DIFFERENTIATION MAP For licensing discussion, the HSH architecture can be compared with conventional large rotorcraft by asking which emergency functions are explicitly designed into the aircraft architecture. This comparison is descriptive, not a claim of superior statistical safety or certification performance.

Licensing interpretation: • Occupied survival capsule as final landing boundary: HSH defines this as a core architectural requirement. •

State-dependent selective separation: HSH explicitly defines release as an authorized emergency mode rather than an indiscriminate jettison command.

- Deterministic Safety Kernel: the baseline establishes a safety authorization boundary between complex prediction/decision functions and physical survival actuation.
- Six-layer survival chain: initiation, independent backup/manual authority, selective separation, direct-impact survival and recovery/post-event survival are treated as distinct functional layers.
- Partial/asymmetric separation: the baseline explicitly treats incomplete release as a first-class emergency state requiring sensing, analysis and degraded recovery logic.
- Independent post-separation capability: the capsule domain includes independent emergency power, sensing, locator, communications and essential life-support provisions as target/requirement concepts.
- Multi-mode recovery: controlled flight recovery and autorotation remain available where appropriate, while separation and capsule recovery form additional emergency modes.

Status: [PROPOSED] Additive commercial/IP interpretation. No new performance claim is created by this section.

03. IP ARCHITECTURE / VALUE-SURFACE MAP The original HSC-00 Section 21 identifies nine candidate IP extraction surfaces. The table below adds a licensing interpretation without changing the underlying technical wording or legal status.

Licensing interpretation:

- IP-ELEMENT-0001 — Occupied survival boundary integrated into a 26-ton-class rotorcraft architecture: core product identity.
- IP-ELEMENT-0002 — State-dependent selective separation of high-mass and fire-hazard systems from an occupied

survival capsule: primary technical differentiator. • IP-ELEMENT-0003 — Deterministic Safety Kernel authorizing separation/recovery based on physical preconditions: safety-architecture differentiator. • IP-ELEMENT-0004 — Six-layer survival architecture combining diverse initiation, physical separation, impact attenuation and post-event recovery: system-level IP story. • IP-ELEMENT-0005 — Eight-support capsule-integrated impact attenuation architecture: hardware differentiation surface. • IP-ELEMENT-0006 — Coordinated multi-mode recovery chain: operational architecture surface. • IP-ELEMENT-0007 — State-aware post-separation management for partial/asymmetric release states: engineering differentiation surface. • IP-ELEMENT-0008 — Optional coordinated residual-airframe recovery: optional future value surface. • IP-ELEMENT-0009 — Immutable emergency event record: audit, traceability and engineering-analysis value surface. • Legal note: novelty, patentability, claim scope, validity and freedom-to-operate are not established by the baseline or this package. Professional prior-art and claim analysis remain required.

Status: [PROPOSED] Additive commercial/IP interpretation. No new performance claim is created by this section.

04. LICENSEE DUE-DILIGENCE & MATURITY ROADMAP A serious licensee should be able to distinguish what is defined from what is still open. The existing G0–G8 verification structure provides the backbone for that evaluation.

Licensing interpretation: • Architecture: Defined at conceptual baseline level. • Requirements: Top-level requirements and targets are defined, with allocation and closure still required. • Mass: 26,000 kg aircraft

accounting and 7,000 kg capsule allocation are planning values requiring bottom-up closure. • Dynamics: 6-DOF emergency dynamics, separation trajectories, partial/asymmetric release and parachute inflation remain open verification work. • Separation: Selective and staged architecture is defined conceptually; release mechanism reliability and safe trajectories require analysis and testing. • Recovery: Distributed multi-canopy architecture is a preliminary study concept requiring sizing, deployment and failure-case testing. • Structures: Capsule, attachments, landing supports and occupant protection require analytical and physical substantiation. • Certification: The applicable certification basis and formal qualification evidence are not yet established. • IP: Candidate surfaces are identified; novelty and freedom-to-operate require professional legal analysis. • Gate logic: G0 Architecture Freeze → G1 Analytical Closure → G2 Subsystem Demonstration → G3 Integrated Ground Demonstration → G4 Dynamic/6-DOF Simulation → G5 Structural/Crash Testing → G6 Recovery Testing → G7 Flight Development → G8 Certification/Qualification.

Status: [PROPOSED] Additive commercial/IP interpretation. No new performance claim is created by this section.

05. STAGED / MULTI-STAGE SEPARATION ARCHITECTURE The existing baseline already defines selective, state-dependent separation and a preliminary six-second development sequence. For commercial readability, that architecture can be expressed as three functional stages without replacing the original sequence.

Licensing interpretation:

- Stage A — Hazard Reduction: where authorized, isolate and separate designated high-mass, rotating or fire-hazard components while maintaining controlled capsule load paths and clearance constraints.
- Stage B — Capsule Liberation: release the remaining designated airframe-to-capsule attachments so the occupied capsule can become the independent final landing boundary.
- Stage C — Clearance Verification & Recovery: positively determine capsule-clear status, identify residual attached components and authorize the recovery system only within its validated envelope.
- The existing ≤ 6 s command-to-clear value remains a TARGET / OPEN development objective, not demonstrated performance.
- Partial and asymmetric release must remain explicitly represented in the state model. The architecture should never assume perfect mechanism operation.
- Any actual jettison set must be established through structural, aerodynamic, dynamic, fire, control, trajectory and collision analysis.

Status: [PROPOSED] Additive commercial/IP interpretation. No new performance claim is created by this section.

06. TECHNOLOGY PLATFORM & FUTURE PRODUCT FAMILY The underlying survival architecture can be treated as a potential technology platform, while keeping future variants clearly separated from the Generation 1 engineering baseline.

Licensing interpretation:

- HSH-G1 Heavy: the present 26-ton-class single-main-rotor baseline.
- HSH Utility: a potential utility-oriented configuration using the same survival-architecture principles with independent mass, CG, performance and certification closure.
- HSH

Rescue: a potential rescue-oriented configuration where capsule architecture, emergency access, locator capability and mission equipment would be re-optimised. • HSH Expedition: a potential long-endurance or remote-area configuration subject to independent fuel, thermal, structural and mission closure. • HSH Special Mission: a potential configuration for specialised operators where the survival architecture remains the common design philosophy. • These future families are conceptual opportunities only. They are not implied to be engineered, tested, certified or commercially available. • The reusable platform opportunity lies in architecture, interfaces, safety logic, survival-state management, verification methods and controlled configuration management, while vehicle-specific hardware must be re-engineered for each derivative.

Status: [PROPOSED] Additive commercial/IP interpretation. No new performance claim is created by this section.

07. STRATEGIC LICENSING PATH The proposed commercial path is deliberately staged so that technical confidence grows before the license scope is finalised. It also keeps the founder's IP position and the licensee's engineering due diligence aligned.

Licensing interpretation: • Phase 1 — NDA: establish confidentiality and permitted evaluation scope. • Phase 2 — Controlled Technical Data Room: provide the 33-page baseline, this additive package and the controlled document-tree material appropriate to the evaluation stage. • Phase 3 — Technical / IP Due Diligence: review requirements, mass model, interfaces, separation concept, safety architecture, verification roadmap and candidate IP surfaces. • Phase 4 — Exclusive Evaluation

Option: if commercially appropriate, define a time-limited evaluation or option period with controlled technical access. • Phase 5 — License Term Sheet: define territory, field of use, exclusivity, milestones, economics, sublicensing and improvement rights. • Phase 6 — Engineering Development Agreement: allocate responsibility for simulation, testing, qualification, certification and product definition. • Phase 7 — Commercial License / Product Development: transition the controlled IP package into the licensee's engineering and industrialisation system. • Commercial terms remain contractual matters and are not established by this engineering document.

Status: [PROPOSED] Additive commercial/IP interpretation. No new performance claim is created by this section.

08. LICENSEE'S FIRST 10 QUESTIONS A sophisticated buyer will usually want rapid answers to a small set of fundamental questions. The following list is intended to make the HSH package easier to evaluate without hiding open engineering work.

Licensing interpretation: • 1. What exactly is the IP? The candidate IP surfaces are explicitly identified in the underlying Document 00 and mapped to their technical roles. • 2. What is actually defined today? The architecture, major interfaces, safety philosophy, emergency state machine, candidate separation logic and verification structure are defined at conceptual-baseline level. • 3. What is not yet proven? Mass closure, detailed dynamics, separation reliability, parachute performance, structural qualification, flight behaviour, certification and patentability remain open. • 4. What is the core differentiator? The occupied survival capsule combined with controlled state-dependent

separation and deterministic safety authorization forms the central architectural proposition. • 5. Can the architecture scale? The survival principles can be considered as a platform opportunity, but every derivative requires independent engineering closure and certification. • 6. What prevents uncontrolled separation? The baseline specifies mechanical retention, electrical/logic inhibits, independent command paths, defined arming, release-state sensing and safety preconditions. • 7. What happens if separation is incomplete? Partial/asymmetric release is explicitly treated as an emergency state requiring state sensing and a defined degraded recovery strategy. • 8. How does AI interact with safety? AI may support detection, prediction and candidate-action ranking, while deterministic safety logic remains the authorization boundary. • 9. How does the buyer know when the concept becomes credible? Evidence gates G0–G8 define the progression from architecture through analysis, subsystem tests, integrated demonstrations, flight development and qualification.

• 10. What happens after licensing? The proposed path moves from controlled data-room evaluation into a term sheet and then a structured engineering-development programme.

Status: [PROPOSED] Additive commercial/IP interpretation. No new performance claim is created by this section.

END OF DOCUMENT 00 — HSC GENERATION 1 | REVISION 12

Capsule: 7,000 kg | Vehicle: 26 t | Main rotor: 26.0 m | Tail rotor: 4.0 m

Founder: Amirbahador Atai | Not a certification approval