

ATAI Ultimate Safe Capsule – Scalable Hybrid Lift Platform

Founder: Amirbahador ATAI

Date: 2026

Scalable Hybrid Lift Safety Capsule Platform

A scalable aerial safety capsule platform designed for resilient evacuation, disaster response, and aerial infrastructure.

Page 2 – Executive Overview

The ATAI Ultimate Safe Capsule is a large-scale airborne safety platform conceived as a hybrid lift system combining helium buoyancy with powered lift fans. The result is a scalable aerial vehicle architecture designed not as a conventional aircraft, but as a resilient airborne infrastructure platform capable of supporting emergency response, evacuation, temporary sheltering, and elevated logistics in extreme operating environments.

At its core, the concept addresses a growing need for multi-role aerial systems that can remain operational when ground infrastructure is damaged, flooded, blocked, or otherwise unavailable. The platform is intended to provide a stable, controllable, and highly redundant aerial volume that can serve as a safe capsule for people, essential equipment, communications, and mission-critical supplies.

The mission envelope includes:

- Emergency evacuation from flood zones, wildfire regions, earthquake-damaged cities, and conflict-affected areas
- Disaster resilience, including temporary command posts, medical support zones, and elevated shelter spaces
- Floating shelters for short- to medium-duration habitation in crisis conditions

- Aerial infrastructure, such as communications relays, power support, observation nodes, and logistics transfer points

Unlike conventional aircraft, the ATAI concept prioritizes stationary endurance, controlled vertical movement, passive safety, and load-bearing stability over speed. The helium system provides a baseline lift reserve, reducing power demand and enabling graceful failure modes. The fan system supplements buoyancy for hover, trimming, descent control, and landing operations.

The intended outcome is a scalable, modular aerospace platform that can be configured for different diameters and payload classes while preserving a common engineering philosophy: maximum survivability, low-risk operation, and mission adaptability.

Page 3 – Design Philosophy

The ATAI platform is defined by a safety-first architecture. Every major design decision is centered on survivability, controlled descent, structural redundancy, and operational resilience. The system is not optimized solely for aerodynamic efficiency; instead, it is optimized for dependable performance under degraded conditions and in environments where landing or evacuation options may be limited.

Safety-First Architecture

The capsule is engineered around the principle that critical functions must remain available even after partial system failure. This includes:

- Multiple independent lift sources
- Distributed control authority
- Compartmentalized buoyancy volume
- Redundant energy pathways
- Mechanical backup landing and descent systems

This approach reduces single-point failure risk and supports stable behavior in emergency scenarios.

Redundancy as a Core Requirement

Redundancy is incorporated at the structural, electrical, propulsion, and safety levels. The architecture assumes that mission continuity must be maintained even if one or more subsystems are compromised. As a result, the platform uses:

- Distributed lift fans rather than a single propulsion source
- Segmented helium cells rather than one large gas volume
- Parallel flight-control logic pathways
- Multiple emergency landing and descent devices
- Structural load redistribution routes across the shell and internal frame

Scalable Design Philosophy

The platform is intended to scale from smaller operational variants to very large airborne structures without changing the fundamental engineering logic. The same design language can support diameters from 30 m to 100 m, with proportional adjustments in buoyancy, fan capacity, energy storage, and structural reinforcement.

Modular Engineering

Modularity is a central manufacturing and maintenance strategy. Major elements are designed as replaceable or upgradeable modules:

- Buoyancy sections
- Fan pods
- Power units
- Landing assemblies
- Payload decks
- Safety systems

This reduces lifecycle complexity and allows different mission configurations to be assembled from a common platform family.

Materials and Stability

The platform emphasizes carbon fiber composite structure, lightweight aerospace materials, and a wide load base to maximize stiffness-to-mass ratio. Autonomy-assisted stabilization ensures that the vehicle can maintain attitude, manage drift, and perform controlled vertical operations with minimal pilot burden.

Page 4 – System Architecture

The ATAI platform is organized as an integrated hybrid system in which each subsystem supports a distinct operational role while contributing to overall flight stability and safety.

1. Helium Buoyancy Disk

A large helium buoyancy disk forms the core lifting volume. Its purpose is to provide a substantial fraction of total lift passively, reducing dependence on powered lift during hover and emergency operation.

2. Carbon Fiber Composite Structural Shell

A high-strength composite shell encloses and protects the internal architecture. It functions as the primary load-bearing enclosure, providing rigidity, aerodynamic shaping, and impact resistance while keeping structural mass low.

3. Lift Fan Propulsion System

The fan propulsion system provides controlled vertical lift, hover support, stabilization, and directional trim. It supplements buoyancy and enables maneuvering in wind and transition phases.

4. Hybrid Energy System

Power is delivered through a hybrid energy stack combining a turbo-generator and battery boost system. This configuration supports both continuous operation and short-duration high-power demand, especially during takeoff, hover, and emergency descent control.

5. Structural Landing Platform

The landing platform is designed to distribute ground loads through a set of heavy landing legs and energy-absorbing interfaces. It enables safe touchdown on prepared or semi-prepared surfaces.

6. Safety and Emergency Systems

The safety layer includes parachutes, redundant flight-control systems, emergency descent capability, and controlled landing mechanisms. These elements operate independently or in coordination depending on failure mode and mission state.

Integration of Subsystems

The system functions as a layered aerospace architecture:

- Helium supplies baseline lift
- Fans generate controlled lift and trim
- Structure transfers loads safely through the frame
- Power systems sustain fan operation and avionics
- Safety systems provide last-line survivability

This integration creates a platform that is neither purely buoyant nor purely powered, but a balanced hybrid optimized for resilience.

Page 5 – Structural Design

The structural concept relies on a carbon fiber composite shell supported by an internal frame and load-distribution architecture designed to manage both static and dynamic forces.

Carbon Fiber Composite Shell

The outer shell is envisioned as a lightweight aerospace composite structure with high stiffness, good fatigue resistance, and favorable strength-to-weight performance. Carbon fiber allows the capsule to maintain large-span geometry while limiting mass growth.

The shell serves several purposes:

- Forms the primary aerodynamic and environmental enclosure
- Protects internal systems from weather and debris
- Contributes to global stiffness
- Supports attachment of lift fans, landing gear, and payload modules

Internal Frame

Inside the shell, a structural frame carries local loads and routes them into the main load paths. The frame is designed to maintain geometry under pressurization, lift loading, ground contact, and asymmetric operational conditions.

Load Distribution Rings

Concentric load distribution rings are used to spread concentrated loads from propulsion units, landing legs, and payload compartments across the wider structure. This prevents local overstress and improves damage tolerance.

Modular Deck Structure

The internal volume includes modular deck segments for mission-specific payloads. These decks may support:

- Passenger evacuation modules
- Medical stations
- Communications equipment
- Power distribution cabinets
- Cargo and supply containers

Payload Compartments

Payload areas are isolated to maintain compartmental safety and operational flexibility. Compartments can be configured for personnel transport, sheltering, equipment storage, or temporary habitat functions.

Structural Redundancy and Materials

Redundancy is built into the load paths so that localized structural damage does not compromise the entire platform. The use of aerospace-grade composites, metallic inserts, and reinforced joints enables a strong yet lightweight structure suitable for scalable deployment.

Page 6 – Buoyancy System

The buoyancy system is the fundamental enabler of the ATAI hybrid platform. It uses helium buoyancy to produce a large fraction of the required lift while keeping power demand manageable.

Helium Buoyancy Chamber

The buoyancy chamber is configured as a large segmented helium volume integrated into the main disk-like body of the platform. The chamber is designed to be structurally integrated rather than merely suspended within the vehicle.

Estimated Lift Physics

In simplified terms, buoyancy is governed by the density difference between surrounding air and the helium gas volume. The lift generated by helium is a function of ambient atmospheric conditions, gas purity, structural enclosure mass, and system volume. At scale, the buoyancy system provides a substantial baseline lift reserve that reduces fan power requirements and enhances emergency survivability.

Volume Efficiency

The geometry is designed for approximately 85% usable internal volume efficiency, meaning that the main body maximizes effective buoyancy space while preserving room for structure, ducts, systems, and compartmentation. This is important because large-diameter platforms must balance lift volume against structural and payload demands.

Compartmentalized Gas Cells

To improve safety and fault tolerance, the helium volume is divided into multiple gas cells. This compartmentalization limits the consequences of puncture, leakage, or localized damage. A single cell failure should not cause catastrophic loss of buoyancy.

Buoyancy Stabilization

The buoyancy system is integrated with stability control logic and ballast management where applicable. By coordinating lift distribution with active fan control, the platform can maintain trim, reduce oscillation, and compensate for load shifts or wind disturbances.

The result is a buoyancy architecture that is passive in principle but actively managed in operation.

Page 7 – Propulsion and Lift Fan System

The propulsion architecture is built around a distributed lift fan arrangement designed to work in harmony with the helium buoyancy structure.

Primary Lift Fans

The platform uses 6 large primary lift fans mounted on the underside. These fans provide the main powered vertical thrust needed for:

- Vertical takeoff support
- Hover assistance
- Controlled altitude holding
- Emergency descent moderation
- Landing flare and stabilization

The primary fans are sized for high thrust efficiency and placed to distribute loads symmetrically across the structure.

Stabilization and Directional Control Fans

In addition to the primary fans, the platform uses 8 distributed control fans for stabilization and directional management. These fans provide:

- Roll and pitch correction
- Yaw control
- Crosswind compensation
- Fine hover trimming
- Thrust-vector management during transition phases

Hover Capability

Hover is achieved through combined buoyant support and fan-generated lift. Because helium carries part of the load, the fan system operates at reduced effective demand compared with a fully powered lift vehicle of similar size. This improves thermal margins, energy efficiency, and emergency endurance.

Controlled Descent

The fans can be used to manage descent rate and landing profile. Controlled descent is essential for safe operations under partial power or degraded conditions. The platform is designed so that descent remains controllable even when the system is not operating in full performance mode.

Thrust Vector Management

The hybrid architecture allows thrust to be distributed and adjusted across multiple fan units. This improves authority over attitude and lateral drift, especially in gusty or uneven atmospheric conditions. The distributed fan system provides a robust path to maintaining stability without reliance on a single propulsion element.

Page 8 – Energy and Power System

The power architecture is designed to support both continuous mission operation and short-duration high-power events associated with hover and landing.

Hybrid Power Architecture

The system uses a hybrid energy configuration consisting of:

- Turbo-generator
- Battery boost system
- Electrical distribution network

This architecture combines energy density, responsiveness, and operational resilience.

Turbo-Generator

The turbo-generator provides sustained electrical power for long-duration operation. It is intended to support fan operation, avionics, environmental control, communications, and auxiliary systems during extended missions.

Battery Boost System

A battery subsystem supplies high instantaneous power during peak demand. This is particularly important for:

- Lift fan startup
- Hover stabilization bursts
- Emergency maneuvering
- Power smoothing during transient load changes

The batteries provide rapid response and help absorb load fluctuations that would otherwise stress the generator or power electronics.

Electrical Distribution

A distributed electrical bus routes power to propulsion units, control systems, safety devices, and mission payloads. The distribution architecture is designed for fault isolation, allowing a fault in one branch to be contained without compromising the entire platform.

Short-Duration Hover Capability

The system is engineered for 3–5 minutes of emergency hover capability under battery-supported conditions when required. This window is intended to support emergency stabilization, controlled landing preparation, or survival hover during transient power anomalies.

The power architecture therefore reflects a deliberate balance between endurance, peak output, and fault tolerance.

Page 9 – Safety Systems

Safety is not treated as an accessory; it is an embedded design layer spanning descent, landing, control redundancy, and structural mitigation.

Multi-Layer Safety Architecture

The platform includes several independent safety systems that work together to improve survivability under off-nominal conditions.

Emergency Parachutes

The concept incorporates 16 emergency parachutes distributed to provide additional descent control and fail-safe load reduction. These parachutes are intended as a last-line safety feature to slow descent and improve survivability during severe failures.

Heavy Landing Legs with Shock Absorbers

The landing system includes 12 heavy landing legs equipped with shock absorbers. These legs are designed to spread touchdown loads and absorb vertical impact energy during landing on uneven, soft, or partially prepared surfaces.

Redundant Flight Control

Flight control is implemented with redundant processors, sensors, and command pathways. This redundancy supports continued operation following a partial avionics failure or sensor degradation. The control logic is intended to preserve attitude stability, fan coordination, and descent management.

Controlled Descent Capability

Even in abnormal conditions, the platform is designed to retain some degree of controlled descent capability through a combination of buoyancy reserve, fan

modulation, and backup systems. The design objective is to avoid uncontrolled falling behavior and to transition toward survivable landing modes.

Safety Philosophy

The overall philosophy is to ensure that no single malfunction should immediately compromise the entire vehicle. Safety is achieved through layered protection, distributed authority, and graceful degradation.

Page 10 – Scalable Platform Architecture

The ATAI concept is intentionally designed as a scalable engineering platform rather than a single fixed-size vehicle. The same architecture can be adapted across multiple diameter classes, supporting different mission payloads and operational envelopes.

Diameter Range

The platform family is envisioned across diameters from 30 m to 100 m. This wide range allows the design to address both regional support missions and large-scale infrastructure applications.

Scaling of Structural Modules

As diameter increases, the shell must manage greater bending loads, larger buoyant volume, and higher inertia. Accordingly, structural modules scale in the following ways:

- Thicker or more advanced composite laminates
- Larger or more numerous load rings
- Higher-capacity joining interfaces
- Expanded internal support framework

Scaling of Fan Power

Fan size and power scale with vehicle mass, desired hover margin, and aerodynamic losses. Larger variants require more distributed lift capacity and stronger electrical systems. The platform architecture is designed to allow fan clusters and electrical distribution to expand with the diameter class.

Scaling of Buoyancy

Buoyancy volume grows approximately with size, but the structural fraction also changes. The design must preserve usable helium volume while managing enclosure mass. Larger diameters offer greater lift potential, but also demand stronger compartmentalization and more careful load balancing.

Common Design Language

Despite the size differences, each variant shares a common design language:

- Hybrid lift principle
- Compartmented buoyancy
- Distributed propulsion
- Composite structural shell
- Multi-layer safety systems
- Modular payload interface

This commonality simplifies development, certification strategy, maintenance planning, and investment scaling.

Page 11 – Comparative Specification Table

Variant	Diameter	Helium Lift	Fan Lift	Total Lift Capacity	Operational Mass	Hover Power
ATAI-30	30 m	6 t	7 t	13 t	10 t	1.4 MW
ATAI-40	40 m	11 t	12 t	23 t	18 t	2.2 MW
ATAI-50	50 m	17 t	18 t	35 t	28 t	3 MW

Variant	Diameter	Helium Lift	Fan Lift	Total Lift Capacity	Operational Mass	Hover Power
ATAI-60	60 m	25 t	27 t	52 t	40 t	4.5 MW
ATAI-70	70 m	34 t	36 t	70 t	50 t	5.5 MW
ATAI-80	80 m	46 t	40 t	86 t	60 t	6.8 MW
ATAI-90	90 m	57 t	48 t	105 t	75 t	8 MW
ATAI-100	100 m	69 t	55 t	124 t	95 t	10 MW

Technical Interpretation

The table above illustrates the scaling logic of the ATAI family. As diameter increases, both helium lift and fan lift increase, enabling higher total lift capacity and supporting larger operational masses. The hover power requirement also grows, reflecting the increased energy demand of larger distributed lift systems.

The values show that the platform remains viable across a broad range of sizes while maintaining the same hybrid lift principle. This makes the concept suitable for mission-specific variants, ranging from compact emergency platforms to major airborne infrastructure nodes.

Page 12 – Future Development and Applications

The ATAI scalable airborne safety platform has broad potential across civil protection, infrastructure resilience, and advanced logistics.

Disaster Evacuation Platforms

In flood, wildfire, earthquake, or industrial disaster scenarios, the platform could serve as a high-capacity aerial refuge and evacuation node. Its ability to hover, land, and remain stable under degraded ground conditions makes it particularly relevant for emergency response.

Floating Emergency Habitats

With appropriate interior systems, the capsule can function as a temporary airborne habitat for displaced populations, field medical teams, or emergency command personnel. This expands the concept beyond transport into protected living and operations space.

Aerial Logistics Hubs

The platform can serve as a transfer station for supplies, medical loads, communications hardware, and critical equipment in areas where roads, airports, or harbors are unavailable.

Research Stations

The ATAI concept also supports environmental monitoring, atmospheric research, disaster mapping, and high-altitude observation. Its stable platform nature makes it valuable for sensor deployment and mission endurance.

Resilient Urban Aerial Infrastructure

In the long term, scaled versions of the platform could support resilient urban aerial infrastructure, including temporary communications coverage, elevated emergency services, and adaptive infrastructure during regional disruption.

Long-Term Vision

The long-term vision of ATAI is to establish a scalable airborne safety platform family that expands the role of aerospace engineering beyond transportation and into resilience, protection, and humanitarian infrastructure. The ATAI concept envisions a future where the sky itself becomes a dependable layer of safety, mobility, and support.