

HEAVY SAFE HELICOPTER (HSC)

DOCUMENT 00 — COMPREHENSIVE ENGINEERING

BASELINE

Generation 1 — HSC Generation 1

23-TON-CLASS INTEGRATED SURVIVAL HELICOPTER

Separable Occupied Survival Capsule + Controlled Rapid Separation +

Multi-Mode Recovery Architecture

Document Title

HSC Generation 1 — Comprehensive Engineering Baseline

Document Number

HSC-00

Document Type

Master Engineering Specification — Conceptual / IP Baseline

Document Class

Conceptual Engineering / Intellectual Property Development Record

Revision

V4.0 — Generation 1, 23-ton-class baseline

Status

[PROPOSED] Preliminary Controlled Engineering Baseline

Development Stage

Pre-Simulation / Pre-Hardware / Pre-Prototype

Language

English

Confidentiality

Proprietary Concept Development Material

Founder

Amirbahador Atai

Engineering integrity statement: This document defines a controlled conceptual baseline. Numerical values marked TARGET, ASSUMPTION, STUDY, CALC or OPEN are not demonstrated performance, certification results, or flight-proven values. Critical claims require analytical closure, simulation, ground testing, integrated testing and, where applicable, flight-test evidence.

Revision intent: supersede the previous Generation 1 planning baseline of 15,000 kg / 15 m main rotor / 2.7 m tail rotor / 750-900

km range with a new controlled HSC Generation 1 study baseline of 23,000 kg / 22 m main rotor / 3.6 m tail rotor / 1,000 km range target,

while preserving and strengthening the survival-capsule, rapid-separation and independent-safety architecture.

1. PURPOSE AND SCOPE

HSC Generation 1 Generation 1 defines the system-level architecture for a 23-ton-class single-main-rotor helicopter whose primary

distinguishing engineering concept is an occupied survival capsule that can become the final landing boundary during a catastrophic emergency. The aircraft is designed around a layered survival chain rather than reliance on a single emergency device.

The V4.0 baseline covers the aircraft, occupied survival capsule, rapid selective separation system, safety initiation paths, deterministic safety authorization, stabilization, recovery systems, impact attenuation, post-event survival and the interfaces

required to verify the complete chain.

The design philosophy is not 'separate everything whenever the aircraft starts descending'. Separation is a controlled emergency

mode authorized only when defined conditions are satisfied. The system must account for altitude, airspeed, attitude, angular

rates, structural state, fire state, rotor state, available recovery modes, capsule clearance and downstream hazards.

The survival architecture is intended to support multiple emergency outcomes: conventional flight recovery where possible, autorotation where applicable, selective hazard/mass reduction, capsule separation, parachute-assisted descent, energy-absorbing landing and post-landing rescue. The architecture must not require the most extreme survival mode for every

failure.

The baseline also preserves human emergency authority. Automatic systems may initiate or recommend a survival sequence only

within defined authorization envelopes; the crew must retain an independent means to command, inhibit or terminate automatic

action where technically and physically possible.

This document is an engineering/IP baseline, not a certification approval. Airworthiness, structural substantiation, parachute

qualification, release reliability, occupant injury criteria, flight performance and global patent novelty remain open work items.

2. BASELINE STATUS AND CONFIGURATION CONTROL

Status Label

Meaning in this document

[LOCKED CONCEPT]

Architecture intentionally retained as a baseline design principle; implementation remains subject to engineering verification.

[REQ]

Top-level requirement proposed for subsequent requirement allocation.

[TARGET]

Numerical or functional development objective; not demonstrated.

[ASSUMPTION / STUDY]

Working engineering assumption used for preliminary sizing/accounting.

[CALC]

Value calculated from stated assumptions and equations.

[OPEN]

Requires analysis, simulation, test, supplier data or design decision.

[TBD — DEPENDENCY]

Cannot be responsibly fixed until a dependent design activity closes.

[PRIOR ART STATUS: NOT YET SEARCHED]

No novelty conclusion is implied.

The V4.0 baseline shall be configuration-controlled. Any change to MTOW, rotor diameter, capsule mass, occupant count,

separation sequence, parachute architecture, landing-support geometry or safety-layer independence shall trigger an impact

assessment across mass properties, CG, inertia, dynamics, structures, controls, recovery and verification.

3. GENERATION 1 V4.0 TOP-LEVEL TECHNICAL BASELINE

Parameter

HSC Generation 1 Gen1

Status

Maximum Take-Off / Design Mass

23,000 kg

[TARGET]

Occupancy

10-12 persons

[TARGET / STUDY]

Flight architecture

Conventional single main rotor + tail rotor

[REQ / STUDY]

Main rotor diameter

22.0 m

[TARGET]

Main rotor disk area

380.13 m²

[CALC]

Weight-based disk loading

60.5 kg/m² (593 N/m²)

[CALC]

Tail rotor diameter

3.6 m

[TARGET]

Tail rotor disk area

10.18 m²

[CALC]

Propulsion architecture

Two turboshaft-class engines

[REQ / STUDY]

Landing gear

No retractable wheeled gear; 8 short, thick fixed mechanical supports integrated with capsule

[TARGET / CONCEPT]

Range

1,000 km

[TARGET]

Hover endurance

To be derived after power/fuel/thermal closure

[OPEN]

Survival capsule

Dedicated occupied final landing boundary

[REQ]

Capsule preliminary complete mass

7,000 kg

[TARGET]

Capsule recovery

Distributed multi-canopy system; 8-canopy architecture for preliminary study

[STUDY]

Airframe recovery parachute

Optional independent residual-airframe trade study

[OPTION / OPEN]

Rapid separation

Selective separation of designated high-mass/fire-hazard components

[REQ / CONCEPT]

Separation development objective

≤ 6 s from validated command to verified capsule-clear state

[TARGET / OPEN]

The 22 m rotor is intentionally larger than the previous 15 m planning rotor. At 23,000 kg, the resulting weight-based disk loading

is approximately 60.5 kg/m², calculated from rotor disk area. This is a sizing indicator, not a guarantee of hover, climb, OEI or

hot/high performance.

Preliminary ideal hover power is approximately 3.29 MW at sea-level standard density. Applying an illustrative figure-of-merit

assumption of 0.75 gives approximately 4.39 MW rotor power. This is a study calculation only. Installed engine power must be

determined from a complete power-required/power-available model including profile power, induced power, transmission losses,

control margins, temperature, density altitude, rotor speed, transients and OEI requirements.

The 1,000 km range is a design target. It shall not be presented as achieved range until the mission model closes with aircraft

drag, rotor performance, engine specific fuel consumption, fuel capacity, reserves, payload, temperature/altitude and operational

constraints.

4. AIRCRAFT GEOMETRY AND CONFIGURATION

The V4.0 geometry below is a preliminary architecture sized around the 23-ton class. Dimensions other than rotor diameters are

deliberately kept as ranges or open items until aerodynamic, structural, cabin, capsule and systems layouts are reconciled.

Geometry Item

V4.0 Preliminary Definition

Status

Overall length

Approx. 16.5–18.0 m

[TARGET / STUDY]

Maximum fuselage width

Approx. 4.0–4.5 m

[TARGET / STUDY]

Overall height

Approx. 4.8–5.3 m

[TARGET / STUDY]

Main rotor diameter

22.0 m

[TARGET]

Tail rotor diameter

3.6 m

[TARGET]

Rotor arrangement

Single main rotor + tail rotor

[REQ / STUDY]

Landing supports

8 fixed short mechanical supports under capsule

[TARGET]

Retractable landing gear

None

[LOCKED CONCEPT]

Capsule position

Central occupied boundary integrated within primary airframe

[LOCKED CONCEPT]

Capsule normal-flight load path

Dedicated primary attachment system with controlled emergency release

[REQ]

Capsule emergency load path

Capsule becomes independent final landing element after verified clearance

[REQ]

The eight landing supports shall not be treated as simple struts attached to a thin capsule shell. The intended load path is: ground

contact → foot/ground interface → progressive energy absorber → lower capsule load path → primary capsule structure → occupant restraint/seat energy management. Structural sizing shall consider vertical, longitudinal, lateral and torsional loads,

slope, uneven terrain, soft soil, asymmetric touchdown and failed-leg cases.

Fixed short supports eliminate the mechanical complexity and failure modes associated with retractable landing gear, but their

permanent external geometry must be included in aerodynamic drag, ground clearance, rotor downwash, structural loads and emergency separation analyses.

5. PRELIMINARY MASS ACCOUNTING — 23,000 KG BASELINE

The following accounting model is intentionally a planning model. It is constructed to close to 23,000 kg and must not be interpreted as a verified mass properties report.

The complete capsule allocation of 7,000 kg is a preliminary target and includes the survival structure, seats/restraints, eight landing supports and energy absorbers, recovery parachute system, separation interfaces, internal emergency systems and essential post-landing survival provisions. The detailed capsule mass shall later be decomposed bottom-up.

The 2,900 kg fuel-system/full-usable-fuel allocation is a study allocation only. It must be reconciled against actual fuel density, tank geometry, usable volume, unusable fuel, system mass, reserve policy and the 1,000 km mission model. No specific fuel volume is locked by this document.

The 900 kg rapid-separation allocation is also a study value. It includes release mechanisms, local structural reinforcement, independent actuation power/signalling, locking/inhibit hardware, sensors and associated wiring/plumbing. It shall be refined after the actual jettison architecture is defined.

Mass properties shall be maintained for: normal design/gross mass, minimum mission mass, maximum fuel, minimum fuel, forward/aft CG, lateral CG, capsule-attached configuration, partial separation, asymmetric separation, failed release, capsule-only descent and post-landing configuration.

The 23,000 kg figure is an accounting closure, not a weighed aircraft. If detailed engineering exceeds the planning mass, the increase shall be reported and the configuration shall be rebalanced under configuration control rather than artificially forcing the design back to 23,000 kg.

Mass Group	Planning Mass	Status
Survival capsule, complete	7,000 kg	TARGET
Main airframe excluding capsule	4,400 kg	ASSUMPTION / STUDY
Main rotor, hub and controls	1,800 kg	ASSUMPTION / STUDY
Tail rotor, gearbox and drive	400 kg	ASSUMPTION / STUDY
Engines, transmission, gearboxes and mounts	2,700 kg	ASSUMPTION / STUDY
Fuel system + full usable fuel allocation	2,900 kg	ASSUMPTION / STUDY
Rapid separation system + independent hardware	900 kg	ASSUMPTION / STUDY
Avionics, electrical, hydraulic, thermal and control equipment	1,500 kg	ASSUMPTION / STUDY
Operating fluids and consumables	300 kg	ASSUMPTION / STUDY
Growth / configuration reserve	1,100 kg	PROGRAM RESERVE
TOTAL	23,000 kg	CALC / ACCOUNTING CLOSURE

6. PROPULSION, ROTOR AND PERFORMANCE CLOSURE

6.1 Propulsion architecture

- Two turboshaft-class engines are retained as the Generation 1 baseline architecture.
- No engine model or exact shaft power is locked in Document 00 V4.0.
- Engine selection shall be based on total installed power, OEI capability, hot/high operation, transient response, fuel consumption, thermal margins, transmission compatibility, maintenance and availability.
- The engine installation shall support controlled emergency isolation and, where technically justified, separation from the survival capsule.
- Fuel isolation must be coordinated with emergency separation and fire containment; separation shall not create a new uncontrolled fuel hazard.

6.2 Main rotor

- Nominal main rotor diameter: 22.0 m [TARGET].
- Disk area: 380.13 m² [CALC].
- Weight-based disk loading at 23,000 kg: 60.5 kg/m² [CALC].
- Rotor blade mass, chord, twist, solidity, tip speed, rotor RPM, airfoil family and control authority remain [OPEN].
- The rotor shall be analyzed for hover, climb, cruise, maneuver, autorotation, transient and emergency states.
- Any emergency rotor release concept is conditional. The main rotor shall not be designated universally jettisonable until structural, dynamic, aerodynamic, gyroscopic, trajectory, clearance and post-release control analyses demonstrate acceptability.

6.3 Tail rotor

- Nominal diameter: 3.6 m [TARGET].
- Disk area: 10.18 m² [CALC].
- Final tail rotor size shall be closed against main rotor torque, tail-arm geometry, anti-torque authority, directional control margins, OEI states, crosswind and emergency configurations.
- Tail rotor, gearbox and drive may be candidates for controlled separation if the post-release dynamics are acceptable.

6.4 Performance closure requirements

- Power required versus power available over gross mass, altitude, temperature and rotor RPM.
- Hover ceiling and hot/high hover.
- Rate of climb and cruise performance.

- One-engine-inoperative performance and safe operating envelope.
- Autorotation performance and rotor energy management.
- Transmission and gearbox thermal/torque limits.
- Rotor vibration and dynamic stability.
- Cruise drag and fuel flow.
- Mission fuel including reserves.
- 1,000 km range closure.

7. 1,000 KM RANGE TARGET — MISSION DEFINITION

The 1,000 km figure is retained as a high-value product requirement target, but the document deliberately does not fabricate a

final cruise speed, fuel burn or reserve figure. These values depend on the selected rotor, airframe drag, engine, fuel system and

mission profile.

Mission Variable

V4.0 Baseline

Closure Requirement

Design range

1,000 km

[TARGET]

Cruise speed

TBD by aerodynamic/propulsion study

[OPEN]

Cruise altitude

TBD by mission study

[OPEN]

Fuel quantity

TBD by tank + mission closure

[OPEN]

Reserve policy

TBD by operational/certification basis

[OPEN]

Payload/occupancy

10-12 occupants + mission equipment

[TARGET]

Hot/high mission

Required

[REQ]

OEI diversion/reserve case

Required for safety assessment

[REQ]

The range model shall explicitly account for start/taxi or equivalent ground operation, climb, cruise, descent, loiter/diversion where

applicable, reserve, unusable fuel, engine/transmission margins and environmental conditions. Range shall not be derived from

fuel quantity alone.

8. OCCUPIED SURVIVAL CAPSULE

The occupied survival capsule is the central safety boundary of HSC Generation 1. During normal flight it is structurally integrated into the

aircraft through controlled primary attachments. During a validated catastrophic survival sequence, it is intended to become an

independent occupied landing element.

Capsule Parameter

V4.0 Definition

Status

Occupancy

10–12 persons

[TARGET / STUDY]

Complete capsule mass

7,000 kg planning target

[TARGET]

Primary structure

Continuous CFRP roll-cage with metallic/titanium nodes and controlled joints

[CONCEPT]

Seats

Energy-absorbing seats with five-point/appropriate restraints

[TARGET]

Landing supports

8 short, thick fixed mechanical supports with progressive energy absorption

[TARGET]

Parachute architecture

Distributed multi-canopy; 8-canopy preliminary study architecture

[STUDY]

Capsule emergency systems

Independent emergency power, sensing, locator, communications and essential life-support

[TARGET]

Capsule clearance

Verified before recovery deployment

[REQ]

Post-landing stability

Eight-point support architecture with asymmetric/failed-leg analysis

[REQ]

The capsule shall be designed as a real structural system rather than a passenger cabin merely surrounded by a shell. The engineering program shall address load paths, crash loads, fatigue, damage tolerance, joints, attachment fittings, seat loads, floor

loads, fire/smoke, environmental exposure, water/ditching provisions where required, emergency egress and occupant injury

criteria.

The capsule shall retain sufficient independent capability after separation to support recovery and rescue. Essential systems

should not depend on the main airframe power bus after separation.

Preliminary 7,000 kg capsule component-level planning allocation:

Capsule Component — Mass

Primary crashworthy protective cell / internal roll-cage structure — 1,950 kg

Outer capsule shell / fairing / thermal protection — 500 kg

Eight fixed landing supports + progressive energy absorbers — 850 kg

Crashworthy seats + occupant restraints, 10-12 positions — 700 kg
 Emergency exits / doors, frames and seals — 250 kg
 Distributed multi-canopy capsule recovery system — 650 kg
 Independent capsule emergency power + batteries — 250 kg
 Life support / emergency oxygen / environmental provisions — 200 kg
 Avionics / sensing / communications / locator / lighting — 250 kg
 Separation interfaces + capsule-side release hardware — 350 kg
 Internal secondary structure / floor / partitions / occupant padding — 500 kg
 Fire / smoke detection and suppression provisions — 150 kg
 Water landing / flotation / sealing provisions — 150 kg
 Inspection / access / replaceable protection hardware — 100 kg
 Capsule configuration growth allowance — 150 kg
 TOTAL — 7,000 kg

Capsule Component	Mass
Primary crashworthy protective cell / internal roll-cage structure	1,950 kg
Outer capsule shell / fairing / thermal protection	500 kg
Eight fixed landing supports + progressive energy absorbers	850 kg
Crashworthy seats + occupant restraints, 10-12 positions	700 kg
Emergency exits / doors, frames and seals	250 kg
Distributed multi-canopy capsule recovery system	650 kg
Independent capsule emergency power + batteries	250 kg
Life support / emergency oxygen / environmental provisions	200 kg
Avionics / sensing / communications / locator / lighting	250 kg
Separation interfaces + capsule-side release hardware	350 kg
Internal secondary structure / floor / partitions / occupant padding	500 kg
Fire / smoke detection and suppression provisions	150 kg
Water landing / flotation / sealing provisions	150 kg
Inspection / access / replaceable protection hardware	100 kg
Capsule configuration growth allowance	150 kg
TOTAL	7,000 kg

9. EIGHT FIXED SHORT MECHANICAL LANDING SUPPORTS

HSC Generation 1 uses eight short, thick, fixed mechanical supports located below the survival capsule. The concept is intentionally

different from conventional retractable landing gear: the supports are part of the survival capsule's impact-attenuation system and

remain with the occupants after separation.

●

Eight supports provide load distribution and redundancy against uneven terrain and partial failure.

●

Each support shall include a defined mechanical energy-absorption function rather than relying solely on elastic deformation.

●

Replaceable or inspectable sacrificial/crush elements should be considered to improve post-event maintainability.

●

The attachment system shall transmit controlled loads into the capsule's primary lower structure.

●

The system shall be analyzed for vertical, lateral, longitudinal and combined impact loads.

●

Asymmetric landing with one or more failed/degraded supports is a required analysis case.

●

Terrain cases shall include hard flat ground, sloped ground, uneven ground and soft/low-bearing-strength surfaces.

●

Ground clearance and rotor-downwash interaction shall be evaluated.

●

Post-landing stability, tipping resistance and rescue access shall be included.

Preliminary capsule impact energy follows $E = 1/2 m v^2$. For a 7,000 kg capsule, illustrative kinetic energies are approximately

126.0 kJ at 6 m/s, 224.0 kJ at 8 m/s and 350.0 kJ at 10 m/s. These are not allowable impact energies; they are sizing illustrations

only. Actual survival depends on energy absorption, occupant pulse, attitude/rates, terrain and structural response.

10. SIX-LAYER SURVIVAL AND SAFETY ARCHITECTURE

The V4.0 architecture retains and strengthens the six-layer functional survival philosophy from the previous LSH baseline. The

layers are functionally distinct. Duplication alone shall never be used as evidence of independence. Independence shall be assessed for power, signal routing, sensors, processors, physical location, structural vulnerability, fire, EMI/lightning, common-cause failures and human interaction.

Layer

Function

Primary Purpose

L1

Primary automatic emergency detection and initiation

Detect catastrophic states and initiate a validated survival sequence when authorization conditions are met.

L2

Independent backup initiation

Provide a second physically/electrically segregated automatic path if L1 is unavailable.

L3

Independent manual/crew authority

Allow crew initiation, inhibit and emergency authority without dependence on L1/L2.

L4

Rapid selective physical separation

Separate designated mass/fire hazards from the capsule using controlled release mechanisms.

L5

Direct-impact survival

Protect occupants through capsule structure, restraints, seats and eight energy-absorbing supports.

L6

Recovery and post-event survival

Deploy recovery system, stabilize landing, locate occupants and support post-landing survival/rescue.

The architecture shall be evaluated as a chain, but it shall also be designed so that failure of one layer does not automatically

eliminate all survival capability. For example, loss of automatic detection must not eliminate manual authority; loss of one release

path must not necessarily eliminate all separation capability; and imperfect separation must not make the capsule structurally

incapable of surviving residual loads.

The design principle is: AI or advanced prediction may assist detection, classification and decision support; deterministic safety logic authorizes safety-critical actuation. Confidence or model output shall never be treated as equivalent to safety authorization.

11. DETERMINISTIC SAFETY AUTHORIZATION AND SAFETY KERNEL

The Safety Kernel is the deterministic authorization boundary between emergency detection/decision logic and physical survival

actuation. Its purpose is to prevent a computationally complex or uncertain decision layer from directly commanding hazardous

separation without satisfying explicit safety preconditions.

The Safety Kernel shall evaluate, as applicable:

- Altitude above terrain and minimum recovery altitude.
- Airspeed and dynamic pressure envelope.
- Pitch, roll, yaw and angular-rate limits.
- Rotor RPM, rotor state and rotor control state.
- Engine/fire/fuel hazard state.
- Structural health and confirmed structural failure state.
- Capsule attachment health and release readiness.
- Separation trajectory clearance.
- Potential collision between released components and capsule/parachutes.
- Parachute deployment envelope and recovery-system availability.
- Landing support availability and degraded configurations.
- Sensor validity and disagreement.
- Power availability for release and recovery systems.
- Communication availability where communication is part of the architecture.
- Manual crew authority and emergency override state.
- Rollback/fallback availability.

If the safety conditions are not satisfied, the system shall inhibit the unsafe action or transition to a defined degraded mode. The

design shall define what constitutes 'no safe optimal solution': safety and physical feasibility take priority over optimization or

mission continuation.

No software model, AI classifier, optimizer or predictive system shall bypass the Safety Kernel, aircraft protection systems, interlocks, equipment limits or human emergency authority.

12. CONTROLLED RAPID SEPARATION SYSTEM

12.1 Separation philosophy

The rapid separation system is a selective, staged, controlled mechanism for reducing the mass, fire load and rotating/energetic

hardware that must remain associated with the occupied capsule during the final descent. It is not a blanket requirement to release every aircraft component in every emergency.

The system shall use state-dependent release logic. Components shall be designated as jettisonable only after structural, aerodynamic, dynamic, fire, control, trajectory and collision analysis demonstrates that release is acceptable within a defined envelope.

12.2 Candidate separable components

- Main engines and associated high-mass engine installation interfaces, where practical.
- Selected transmission/drive components where release is structurally and dynamically acceptable.
- Main rotor blades and/or hub components only if detailed dynamic and trajectory analysis demonstrates safe clearance; main rotor release is NOT universally locked.
- Tail rotor, tail-rotor gearbox and drive shafting where release is safe.
- Primary fuel tanks and major fuel lines that constitute a significant fire hazard, after safe fuel isolation.
- Selected external structural panels or high-mass attachments that do not form part of the capsule primary load path.
- Other components only through configuration-controlled hazard and trajectory analysis.

12.3 Mandatory release protections

- Positive mechanical retention during normal flight.
- Electrical/logic inhibits against inadvertent release.
- Independent command paths.
- Defined arm/fire sequence.
- Release-state sensing.
- Fuel and energy isolation before or coordinated with release.
- Asymmetric/partial-release detection.
- Post-release trajectory monitoring where practical.
- Capsule-clear verification before parachute authorization.
- Defined failed-release and rollback/fallback behavior.

13. PRELIMINARY SIX-SECOND SURVIVAL SEQUENCE

The following sequence is a development objective inherited and strengthened from the prior LSH rapid-jettison baseline. It is

intentionally aggressive and shall remain [OPEN] until mechanism tests and dynamic simulations demonstrate that timing, reliability and separation quality can be achieved.

Time

Action

Safety Purpose

0.0–0.4 s

Validate emergency state; arm authorized release path; isolate fuel/electrical/energy hazards

Prevent release during an invalid or unsafe state.

0.4–2.2 s

Stage primary high-mass/rotating-system release where authorized

Reduce major mass and energy/fire hazards.

2.2–3.8 s

Release tail-rotor/drive and primary fuel hazards where authorized

Remove remaining major hazards.

3.8–5.4 s

Release remaining designated airframe/capsule attachments

Free the capsule from the main airframe.

5.4–6.0 s

Verify capsule clearance and recovery envelope

Prevent premature parachute deployment.

After clearance

Authorize capsule recovery system

Transition to capsule-only or capsule-dominant survival state.

The sequence shall not be treated as a fixed certification requirement. If the detailed architecture cannot safely achieve ≤ 6 s, the

target shall be revised under configuration control rather than achieved by reducing verification rigor.

Partial and asymmetric separation are first-class emergency states. The system shall not assume that every release mechanism

functions perfectly. It must recognize which components remain attached and determine whether the resulting state is survivable,

whether another controlled action is permitted, or whether the capsule must proceed with degraded recovery.

14. MULTI-MODE RECOVERY ARCHITECTURE

The HSC Generation 1 recovery architecture is intentionally layered so that survival is not dependent on one device.

Recovery Mode

Use Case

Status

Controlled flight recovery

Recoverable control/propulsion disturbance

[REQ / STUDY]

Autorotation

Engine/power loss when altitude/rotor state permit

[REQ / STUDY]

Selective mass/hazard separation

Fire, structural or combined emergency requiring reduction of carried hazard/mass

[REQ / CONCEPT]

Capsule separation

Catastrophic state where independent occupied recovery is preferable

[REQ / CONCEPT]

Distributed capsule parachutes

Primary post-separation vertical recovery

[STUDY — 8 CANOPIES]

Eight energy-absorbing supports

Final ground impact attenuation

[REQ / TARGET]

Optional airframe recovery parachute

Residual-airframe recovery or unmanned asset protection

[OPTION / TRADE STUDY]

Post-landing survival

Locator, communications, lighting, emergency power and rescue interface

[REQ]

The capsule parachute system should be distributed rather than treated as a single-point canopy where practical. The final number, canopy size, deployment sequence, reefing, riser architecture, failure tolerance and inflation dynamics require parachute sizing and test.

An independent parachute for the residual main airframe is retained as an optional trade study, not a mandatory V4.0 requirement. It can be valuable for reducing ground hazard, protecting unmanned equipment or providing an additional recovery

mode, but it introduces additional mass, drag, deployment hazards and potential interaction with the capsule. Its value shall

therefore be established through system-level trade analysis.

15. EMERGENCY STATE MACHINE

HSC Generation 1 shall use an explicit emergency state machine rather than a single binary 'normal/emergency' flag.

1

NORMAL FLIGHT — all safety layers monitored; release hardware mechanically locked.

2

ANOMALY DETECTED — sensor/model detects a potential abnormal condition.

3

CONFIRMATION — independent evidence and validity checks determine whether the condition is real.

4

IMPACT ASSESSMENT — estimate control authority, altitude, airspeed, fire/structural risk, rotor/engine state and available recovery modes.

5

RECOVERY ATTEMPT — use conventional control, engine redundancy or autorotation where safe and appropriate.

6

SURVIVAL AUTHORIZATION — Safety Kernel evaluates whether selective separation/capsule recovery is permitted.

7

STAGED SEPARATION — execute only the designated release set for the specific emergency state.

8

CAPSULE CLEARANCE — verify physical separation and identify any attached components.

9

RECOVERY DEPLOYMENT — authorize parachute/recovery system within validated envelope.

10

DESCENT MANAGEMENT — monitor attitude, rates, canopy state and landing-support readiness.

11

LANDING ATTENUATION — deploy/condition energy absorbers as required.

12

POST-LANDING SURVIVAL — stabilize, locate, communicate, protect occupants and support rescue.

13

AUDIT — preserve event data, release states, sensor states and command history for engineering analysis.

Representative state-dependent behavior: an isolated engine failure should not automatically trigger capsule separation; a major

fire may prioritize fuel isolation and selective separation; loss of control may require a different separation envelope; structural

damage may require immediate transition; a combined catastrophic event may require the full survival chain.

16. INDEPENDENCE, FAILURE MODES AND COMMON-CAUSE CONTROL

The survival architecture introduces new hazards as well as new protections. The following failure classes shall be treated as

explicit design cases.

Failure / Hazard

Required Design Response

Unintended separation

Mechanical locks, electrical inhibits, command validation, monitoring and quantitative safety objective.

Partial separation

State sensing, asymmetric-load analysis and defined degraded recovery mode.

Asymmetric separation

Dynamic analysis, CG/inertia update and post-release control assessment.

Release mechanism failure

Independent path or defined safe fallback; no assumption of perfect release.

Sensor loss / bad data

Validity monitoring, redundant/diverse sensing and safe-state logic.

Automatic detection failure

Independent backup and manual crew initiation.

Power-bus failure

Independent survival power where required for critical functions.

Communication loss

Local deterministic safety logic; communication shall not be the sole authorization path.

AI/model failure

Deterministic safety logic remains authoritative.

Fire during separation

Fuel isolation, fire containment and release sequencing.

Released component collision

Trajectory analysis, clearance envelopes and controlled sequencing.

Parachute deployment outside envelope

Hard inhibits and validated deployment conditions.

Landing-support failure

Eight-support redundancy and asymmetric/failed-leg structural cases.

Common-cause EMI/lightning/fire/structural damage

Dedicated common-cause analysis and physical/electrical segregation.

Independence is not established merely because two boxes, sensors or switches exist. The verification program shall assess common power, common wiring routes, common structure, common software, common sensor physics, common fire zones and

common environmental vulnerabilities.

17. INTELLIGENT MONITORING, PREDICTION AND CONTROL BOUNDARY

HSC Generation 1 may incorporate advanced health monitoring, digital-twin estimation, predictive fault detection and AI-assisted decision

support. These functions shall remain bounded by deterministic safety authorization.

Recommended information/control chain:

State / Health Estimation → Emergency Prediction / Forecast → Risk State → Candidate Recovery Actions → Resilience-First Decision → Deterministic Safety Validation → Interlock / Precondition Verification → Controlled Actuation → Post-Action Monitoring → Rollback / Fallback → Immutable Event Record

●

AI may detect patterns, estimate degradation and rank candidate actions.

●

AI may not directly bypass interlocks or safety limits.

●

AI confidence shall not be treated as safety authorization.

●

Deterministic protection and safety logic remains authoritative.

●

Human emergency authority remains non-bypassable.

●

Model failure shall lead to a defined degraded mode.

●

Critical command paths shall have software/configuration integrity controls.

●

All emergency decisions shall generate an auditable event record.

18. PRINCIPAL SYSTEM INTERFACES

Interface

Definition

Control Requirement

CAP-AF

Capsule ↔ airframe structural attachment

Normal-flight load path + controlled emergency release + positive retention.

CAP-PAR

Capsule ↔ parachute system

Deployment only after validated capsule state and clearance.

CAP-LG

Capsule ↔ eight landing supports

Primary crash/landing load path with energy absorption.

JET-PWR

Independent release power

Segregated from common single-point power failure where required.

JET-CMD

Automatic/backup/manual commands

Independent paths and protected actuation.

JET-SNS

Release-state sensing

Positive confirmation of attached/released state.

FUEL-ISO

Fuel isolation ↔ separation

Isolation before or coordinated with release according to hazard analysis.

REC-LOC

Post-landing locator/communications

Independent emergency power and antenna strategy.

AV-CTRL

Avionics/control ↔ Safety Kernel

Deterministic authorization boundary.

All interfaces crossing survival boundaries shall be documented in Interface Control Documents and assessed for common-cause

vulnerability. Connector, harness, hydraulic, fuel and structural interfaces shall be designed so that emergency separation does

not create an uncontrolled hazard.

19. VERIFICATION, VALIDATION AND EVIDENCE PROGRAM

V4.0 deliberately separates conceptual definition from demonstrated performance. The following evidence gates are required

before any high-confidence safety or performance claim is made.

Gate

Evidence Objective

G0 Architecture Freeze

Confirm safety philosophy, system boundaries, interfaces and emergency states.

G1 Analytical Closure

Mass, CG, inertia, rotor sizing, power, fuel, structural load paths and separation kinematics.

G2 Subsystem Demonstration

Release mechanisms, locks/inhibits, energy absorbers, parachute components, sensors and independent power.

G3 Integrated Ground Demonstration

End-to-end sequence without flight exposure; verify timing, state sensing and capsule clearance.

G4 Dynamic / 6-DOF Simulation

Vehicle and capsule dynamics through representative emergency states, partial/asymmetric release and parachute inflation.

G5 Structural / Crash Testing

Capsule, attachment points, seats, landing supports, energy absorbers and occupant-protection evidence.

G6 Recovery System Testing

Canopy deployment, inflation loads, failure cases, stability and landing performance.

G7 Flight Development

Controlled flight tests within approved envelope; validate normal and emergency recovery behavior.

G8 Certification / Qualification

Evidence package against the selected certification basis and applicable standards.

Terms shall be used carefully: 'specified' means defined in the design; 'analyzed' means a documented analytical result; 'simulated' means supported by a model; 'tested' means demonstrated in a defined test; 'verified' means evidence shows compliance with a requirement; 'validated' means suitability has been established for the intended use; 'qualified' and 'certified'

require the applicable formal processes.

20. 6-DOF EMERGENCY DYNAMICS PROGRAM

A dedicated six-degree-of-freedom simulation shall be developed for the aircraft, separated capsule and relevant released components. The simulation shall include translation and rotation, component release impulses, aerodynamic forces, rotor/propulsor effects where relevant, parachute inflation and terrain interaction.

- Aircraft pre-release attitude, airspeed, altitude and angular-rate envelopes.

- Release impulse and mechanism timing.

- Component mass, CG and inertia before and after each release.

- Asymmetric and partial release configurations.

- Main rotor and tail rotor release cases only where under active study.

- Capsule aerodynamic coefficients across relevant attitudes.

- Parachute deployment and inflation transient loads.

- Canopy failure/degradation cases.

- Ground-contact kinematics with slope and uneven terrain.

- Landing-support deformation and energy absorption.

- Occupant acceleration/pulse proxies for early screening.

- Collision envelopes between released hardware, capsule and parachutes.

The 6-DOF model is a core verification tool, not a substitute for physical testing. Model uncertainty, sensitivity and correlation to test data shall be documented.

21. ENGINEERING / IP VALUE SURFACES

The following architecture elements are candidate IP extraction surfaces. Their legal novelty and patentability are NOT established by this document and require a professional prior-art search and claim analysis.

Candidate IP Element

Technical Content

IP-ELEMENT-0001

Occupied survival boundary integrated into a 23-ton-class rotorcraft architecture.

IP-ELEMENT-0002

State-dependent selective separation of high-mass and fire-hazard systems from an occupied survival capsule.

IP-ELEMENT-0003

Deterministic Safety Kernel authorizing separation/recovery based on physical preconditions.

IP-ELEMENT-0004

Six-layer survival architecture combining diverse initiation, physical separation, impact attenuation and post-event recovery.

IP-ELEMENT-0005

Eight-support capsule-integrated impact attenuation architecture.

IP-ELEMENT-0006

Coordinated multi-mode recovery chain: control recovery → autorotation → selective separation → capsule recovery → ground attenuation.

IP-ELEMENT-0007

State-aware post-separation management for partial/asymmetric release states.

IP-ELEMENT-0008

Optional coordinated residual-airframe recovery as a separate survival mode.

IP-ELEMENT-0009

Immutable emergency event record linking detection, authorization, release states and recovery status.

22. PROPOSED TOP-LEVEL REQUIREMENT SET

ID

Requirement / Target

Status

HSC-REQ-SYS-001

Aircraft shall provide 10-12 occupant provisions within the selected cabin/capsule configuration.

[REQ / TARGET]

HSC-REQ-SYS-002

Generation 1 shall use a single main rotor and tail rotor architecture.

[REQ]

HSC-REQ-SYS-003

Design mass shall be based on a 23,000 kg target configuration.

[TARGET]

HSC-REQ-ROT-001

Main rotor diameter target shall be 22.0 m.

[TARGET]

HSC-REQ-ROT-002

Tail rotor diameter target shall be 3.6 m.

[TARGET]

HSC-REQ-RNG-001

Design range target shall be 1,000 km subject to mission closure.

[TARGET]

HSC-REQ-CAP-001

Occupied survival capsule shall constitute the final landing boundary in capsule-recovery mode.

[REQ]

HSC-REQ-CAP-002

Capsule shall include structural protection, occupant restraint, impact attenuation and post-event survival provisions.

[REQ]

HSC-REQ-LG-001

Capsule shall use eight short fixed mechanical landing supports as the preliminary architecture.

[TARGET]

HSC-REQ-JET-001

Rapid separation shall be selective and state-dependent.

[REQ]

HSC-REQ-JET-002

Automatic initiation and independent manual initiation shall be provided.

[REQ]

HSC-REQ-JET-003

Unintended separation shall be treated as a catastrophic hazard.

[REQ]

HSC-REQ-JET-004

No component shall be universally jettisonable without structural, dynamic, fire, control and collision analysis.

[REQ]

HSC-REQ-JET-005

Partial/asymmetric separation shall be explicitly modeled and detected.

[REQ]

HSC-REQ-SAF-001

Deterministic safety authorization shall be independent of AI confidence.

[REQ]

HSC-REQ-SAF-002

Human emergency authority shall not be bypassable.

[REQ]

HSC-REQ-REC-001

Capsule recovery shall use a distributed multi-canopy architecture subject to sizing.

[REQ / STUDY]

HSC-TGT-JET-001

Validated command to verified capsule-clear state target ≤ 6 s.

[TARGET / OPEN]

23. CRITICAL OPEN ITEMS — V4.0

- 1
Close the 23,000 kg mass model using component-level estimates and uncertainty.
 - 2
Close the 10–12 occupant capsule geometry and bottom-up mass.
 - 3
Select/size main rotor blade geometry, RPM, solidity, control system and transmission.
 - 4
Close tail rotor sizing against torque and directional-control requirements.
 - 5
Select candidate engines and close total installed power and OEI performance.
 - 6
Develop 1,000 km mission fuel model including reserves.
 - 7
Develop full 6-DOF aircraft/capsule/released-component model.
 - 8
Define the exact set of jettisonable components for each emergency state.
 - 9
Prove safe separation trajectories and post-jettison control for each candidate component.
 - 10
Develop independent automatic and manual command architecture and common-cause analysis.
 - 11
Define Safety Kernel requirements and deterministic implementation boundary.
 - 12
Size the distributed parachute system and establish canopy failure tolerance.
 - 13
Evaluate optional residual-airframe parachute versus added mass, drag and deployment risk.
 - 14
Size the eight landing supports and energy absorbers, including asymmetric failures.
 - 15
Perform capsule structural, crash, fatigue and damage-tolerance analyses.
 - 16
Define occupant injury criteria and test instrumentation.
 - 17
Define emergency power and post-separation electrical architecture.
 - 18
Define fire, fuel isolation and thermal protection architecture.
 - 19
Define emergency egress, rescue, locator and communication provisions.
 - 20
Establish certification basis and verification matrix.
- These open items are not weaknesses to be hidden; they are the correct engineering gates that separate a strong conceptual IP baseline from an unsupported performance claim.

24. ENGINEERING BASIS AND EXTERNAL REFERENCE NOTES

The V4.0 baseline is derived primarily from the user's prior LSH Document 00 Rev3.2 and the higher-maturity rapid-jettison Generation 1 document. The previous baseline established the six-layer survival philosophy, independent automatic/manual

initiation, controlled separation, eight landing supports, capsule-as-final-landing-boundary concept, six-second development

objective and the need to treat partial/asymmetric separation as first-class states.

The current V4.0 update changes the Generation 1 planning point to 23,000 kg, 22 m main rotor, 3.6 m tail rotor and 1,000 km

range target. The numerical 23-ton mass accounting in this revision is a new preliminary study allocation and must be replaced by

a bottom-up mass model during engineering development.

Current EASA CS-29 material was reviewed as an external engineering reference. The EASA material emphasizes that jettisonable configurations require satisfactory separation characteristics, including clear trajectory, no damaging interaction, no

adverse/uncontrollable aircraft reaction, acceptable post-jettison stability/control and acceptable post-jettison performance; the

V4.0 verification program therefore treats these as core analysis/test concerns rather than assuming safe release.

External reference: EASA, Easy Access Rules for Large Rotorcraft (CS-29), Amendment 12, March 2026.

<https://www.easa.europa.eu/en/document-library/easy-access-rules/online-publications/easy-access-rules-large-rotorcraft-cs-29-12>

Source baseline files used: LSH_00_Lightweight_Safe_Helicopter_Gen1_Rev3_2.pdf and

USCC_Document_00_Lightweight_Jettison_Gen1_Rev1.3_HigherMaturity-2.pdf. The source documents explicitly state that their

numerical performance values are preliminary and that independence, jettison timing, parachute sizing, impact loads and mass

properties remain verification gates.

25. V4.0 DESIGN PHILOSOPHY — CONTROLLED SURVIVAL, NOT A

SINGLE DEVICE

The defining engineering proposition of HSC Generation 1 is the integration of multiple survival mechanisms into one state-aware

architecture. The aircraft is not intended to depend solely on a parachute, solely on autorotation, solely on a detachable cabin or

solely on automatic software.

The intended chain is:

PREVENT / MONITOR → DETECT → CONFIRM → ASSESS → RECOVER IF POSSIBLE → SAFETY AUTHORIZE →

SELECTIVELY SEPARATE → VERIFY CAPSULE CLEARANCE → DEPLOY RECOVERY → MANAGE DESCENT →

ABSORB IMPACT → SURVIVE / LOCATE / RESCUE → AUDIT

The architecture becomes especially valuable when several failure mechanisms occur together. A single-engine failure may be

handled by normal redundancy or autorotation; a fire may require fuel isolation and selective separation; a loss of control may

require a different survival state; a combined fire/control/structural event may require the full capsule recovery chain.

The V4.0 baseline therefore treats safety as a system architecture and verification problem. The strongest future evidence will

come from a closed mass model, rotor/propulsion analysis, 6-DOF simulation, deterministic safety logic, separation mechanism

tests, capsule structural tests, parachute tests and progressively integrated demonstrations.

Document disposition: V4.0 is suitable as the controlled conceptual/master engineering baseline for the next

engineering phase. It should not yet be presented as a certified aircraft specification or as proof of achieved 23-ton performance, 1,000 km range or survival probability.

END OF DOCUMENT 00 — HSC Generation 1 GENERATION 1

26. DETAILED AIRCRAFT MASS BREAKDOWN — HSC GENERATION 1

The following component-level allocation is a planning-level engineering decomposition of the 23,000 kg top-level accounting model. It is not a manufacturing BOM, weighed hardware result, or certification mass-properties report.

Main Airframe — 4,400 kg

- Fuselage primary load-bearing structure — 1,450 kg
- Frames, bulkheads and longerons — 650 kg
- Tail boom and tail structural assemblies — 520 kg
- Engine and transmission support structure — 380 kg
- Rotor mast/transmission support integration structure — 260 kg
- External skins, fairings and aerodynamic panels — 310 kg
- Doors, access panels and hinges — 190 kg
- Firewalls, barriers and structural fire protection — 170 kg
- Structural fittings, lugs, fasteners and local reinforcements — 260 kg
- Cabin/service floor structure outside capsule boundary — 210 kg

Main Rotor System — 1,800 kg

- Main rotor blades — 22.0 m system — 820 kg
- Rotor hub and blade retention/grips — 280 kg
- Mast and rotor-head structural components — 260 kg
- Swashplate and pitch-control hardware — 170 kg
- Pitch links, control rods and bearings — 110 kg
- Rotor vibration/dynamic-control hardware — 80 kg
- Rotor lubrication/inspection/access hardware — 40 kg
- Configuration allowance — 40 kg

Tail Rotor System — 400 kg

- Tail rotor blades — 3.6 m system — 120 kg
- Tail rotor hub and blade retention — 65 kg
- Tail rotor gearbox — 95 kg
- Drive shafting, couplings and bearings — 60 kg
- Tail rotor controls and pitch mechanism — 35 kg
- Tail structure/interface hardware — 25 kg

Engines and Main Transmission System — 2,700 kg

- Engine #1 complete installed — 700 kg
- Engine #2 complete installed — 700 kg
- Engine accessories and engine-control hardware — 180 kg
- Main gearbox / combining transmission — 650 kg
- Intermediate/reduction transmission elements — 180 kg
- Drive shafts and couplings — 100 kg
- Lubrication, oil cooling and filtration — 80 kg
- Engine/gearbox mounts and vibration isolation — 60 kg
- Exhaust and hot-section installation hardware — 50 kg

Fuel System + Full Usable Fuel — 2,900 kg

- Usable fuel mass — 2,100 kg
- Fuel tanks and crash/fire-resistant tank structure — 280 kg
- Fuel pumps and boost/transfer units — 90 kg
- Fuel lines, hoses, valves and fittings — 110 kg
- Fuel filters, sensors and quantity measurement — 55 kg
- Fuel isolation/emergency shutoff hardware — 75 kg
- Venting, surge and inerting/fire-protection provisions — 70 kg
- Unusable/residual fuel allocation — 120 kg

Rapid Selective Separation System — 900 kg

- Primary capsule release mechanisms and locks — 240 kg
- Independent backup release mechanisms — 150 kg
- Local structural reinforcement and release fittings — 160 kg
- Independent initiators/actuators — 90 kg
- Release-state sensors and monitoring — 65 kg
- Independent power/signalling and protected wiring — 70 kg
- Fuel/energy isolation interfaces — 55 kg
- Retention, inhibit and safety-interlock hardware — 50 kg
- Configuration growth allowance — 20 kg

Avionics / Electrical / Hydraulic / Thermal / Control — 1,500 kg

- Flight-control computers/control electronics — 180 kg
- Flight-control actuators/servo hardware — 210 kg
- Navigation/air-data/flight sensors — 100 kg
- Communications/mission avionics — 90 kg
- Electrical generation/distribution — 190 kg
- Batteries/emergency electrical interfaces — 90 kg
- Wiring/harnesses/connectors — 170 kg
- Hydraulic pumps/reservoirs/lines/actuators — 180 kg
- Thermal management/cooling — 100 kg
- Environmental control/ventilation — 70 kg
- Fire detection/warning/suppression interfaces — 55 kg
- Health monitoring/data recording — 45 kg
- Lighting/service/misc. — 20 kg

Operating Fluids & Consumables — 300 kg

- Engine/transmission oil and other operating fluids — 180 kg
- Hydraulic fluid — 35 kg
- Coolant/thermal working fluid — 30 kg
- Other trapped/operating consumables — 55 kg