

1. The user is trying to execute a select statement. Which of the following background processes will obtain data from a disk for the user?
 - DBWn
 - LGWR
 - SERVER
 - USER

2. In order to perform administrative tasks on the database using Oracle password authentication, the DBA should have the following two privileges granted to them:
 - sysdba or sysoper
 - CONNECT or RESOURCE
 - restricted session or create session

3. Which component of the SGA stores parsed SQL statements used for process sharing?
 - Buffer cache
 - Private SQL area
 - Redo log buffer
 - Library cache

4. Which of the following choices does not identify an aspect of shared server processing architecture?
 - Each user gets his or her own server process for data retrieval.
 - dispatcher process is involved.
 - listener process is involved.
 - The server process sits idle infrequently.

5. Which is the default password for the SYSTEM user?
 - change_on_install
 - NO_PASSWORD
 - manager
 - ORACLE
 - NULL

6. Power will disconnect on the machine running Oracle in two minutes, but user JASON has left for the day while still connected to Oracle. His

workstation is locked, so he cannot be logged out from his desktop. How should the DBA shut down the instance?

- shutdown normal
- shutdown immediate
- shutdown abort
- shutdown force

2

7. Which of the following administrative tools in OEM can be used to view the initialization parameter settings for Oracle?

- Schema Manager
- Instance Manager
- Security Manager
- Data Manager

8. To Execute a create controlfile statement

Database should be:

- Opened
- Mounted
- In no mount state
- Mounted or opened

9. If the database is OPEN and in RESTRICTED mode:

- Only the DBA can log into the system.
- All users can log into the system but the database is in READ ONLY mode.
- Only users with restricted privilege can log in and perform normal operations.
- All users can log into the system but only users with restricted privilege can perform DML operations.

10. The ALTER DATABASE command can be used to start the Oracle instance.

- TRUE
- FALSE

11. Which statement about an Oracle instance is true?

- The redo log buffer is NOT part of the shared memory area of an Oracle instance.
- Multiple instances can execute on the same computer, each accessing its own physical database.
- An Oracle instance is a combination of memory structures, background processes, and user processes.
- In a shared server environment, the memory structure component of an instance consists of a single SGA and a single PGA.

12. Which of these actions cause a log switch?

- A transaction completes.
- The instance is started.
- The instance is shut down
- The current online redo log group is filled

13. Which background process performs a checkpoint in the database by writing modified blocks from the database buffer cache in the SGA to the data files?

- LGWR
- SMON
- DBWn
- CKPT

14. When is the SGA created in an Oracle database environment?

- When the database is created
- When the instance is started
- When the database is mounted
- When a user process is started

15:

You issue the following queries to obtain information about the redo log files:

SQL> SELECT group#, type, member FROM v\$logfile;

/databases/DB01/ORADATA/u03/log1a.rdo	ONLINE	1
/databases/DB01/ORADATA/u03/log1b.rdo	ONLINE	1
/databases/DB01/ORADATA/u02/log2a.rdo	ONLINE	2
/databases/DB01/ORADATA/u03/log2b.rdo	ONLINE	2
/databases/DB01/ORADATA/u02/log3a.rdo	ONLINE	3
/databases/DB01/ORADATA/u03/log3b.rdo	ONLINE	3

SQL> SELECT group#, sequence#, status FROM v\$log;

GROUP#	SEQUENCE#	STATUS
-----	-----	-----
1	250	INACTIVE
2	251	CURRENT
3	249	INACTIVE

You immediately issue this command:

```
ALTER DATABASE DROP LOGFILE MEMBER
'/databases/DB01/ORADATA/u03/log2b.rdo';
```

Why does the command fail?

- Each online redo log file group must have two members.
- You cannot delete any members of online redo log file groups.
- You cannot delete any members of the current online redo log file group
- You must delete the online redo log file in the operating system before issuing the ALTER DATABASE command.