

Q1:

Where does Oracle store the database creation timestamp?

- Database file header
- Control file
- Parameter file
- Redo log files
- Rollback segment

Q2: 2

To Execute a create controlfile statement

Database should be:

- Opened
- Mounted
- In no mount state
- Mounted or opened

Q3:

To Expand the size of redolog file group

- We should drop the file group, then recreate it with larger members in size
- Modify the size of the file group members
- Add more files to the redolog group
- Is not possible

Q4:

using a database with binary parameter file (spfile)

If we want to multiplex the controlfile, we have to shutdown the database

- True
- False

Q5:

Adding new data file to the database, will increase the controlfile size

- True
- False

Q6:

If all the redolog files in a database are full, and the database is running in no archive log mod, then the database will hang.

- True
- False

Q7: 2

Having a database with two redo log groups each having two members GROUP 1 (m1.log,m2.log), Group 2 (m3.log,m4.log).

What is the result of the following statement:

ALTER DATABASE DROP REDOLOG GROUP 1;

- Error: because the database should have at least two redo redo log groups.
- GROUP 1 will be deleted.
- Error: because we can't delete the first redo groups.
- The second member of each group will be deleted.

Q8:

When starting a database in restricted mode:

- no users can access the DB.
- Only users with DBA privileges can access the DB.
- Db can be accessed in read only mode.
- Only users with restricted session privilege can access the DB.

Q9: 2

What is the purpose of the database buffer cache in the SGA?

- To store shared SQL and PL/SQL
- To store data dictionary information
- To store copies of data blocks that can be shared by all users
- To store transaction data before it is copied to the redo logs

Q10:

Your database has a log group with three members. Two of the three members have become corrupted. What would happen when the database tries to write to this log group?

- The database will hang.
- LGWR will write to the available member.
- The instance will crash.
- Oracle will reformat the corrupt members.

Q11:

When a user process fails, what background process cleans up after it?

- SMON
- PMON
- DBWn

- User-server processes

Q12:

Which tool can I use to create a new database in oracle 9i?

- OUI
- DBCA
- SQL plus
- All the answers are right.

Q13:

Power will disconnect on the machine running Oracle in two minutes, but user JASON has left for the day while still connected to Oracle. His workstation is locked, so he cannot be logged out from his desktop. How should the DBA shut down the instance?

- shutdown normal
- shutdown immediate
- shutdown abort
- shutdown force

Q14:

Which is the default password for the SYS user?

- change on install
- NO_PASSWORD
- manager
- ORACLE

Q15: 3

You intend to use only password authentication and have used the password file utility to create a password file as follows:

Orapwd file={ORACLE_HOME}/database/pwdDB1 password=orapass entries=5

The REMOTE_LOGIN_PASSWORDFILE initialization parameter is set to NONE. You created a user and granted only the SYSDBA privilege to that user as follows:

```
CREATE USER dba_user
IDENTIFIED BY dba_pass;
```

```
GRANT sysdba TO dba_user;
```

The user attempts to connect to the database as follows:

```
connect dba_user/dba_pass as sysdba;
```

Why does the connection fail?

- The DBA privilege was not granted to dba_user.
- REMOTE LOGIN PASSWORDFILE is not set to EXCLUSIVE.
- The password file has been created in the wrong directory.
- The user did not specify the password orapass to connect as SYSDBA.