

No. of questions: 18

1	2	3	4
5	6	7	8
9	10	11	12
13	14	15	16
17	18		

<< Hide summary

Assessment result

No. of questions in assessment:	18
No. of correct answers:	11
No. of wrong answers:	7
No. of questions attempted:	18
No. of questions not attempted:	0
No. of questions presented:	18
Maximum score:	25
Actual score:	15
Percentage:	60%
Threshold percentage to pass:	35%
Assessment outcome:	Pass
Grade:	Grade definition is not available

1 out of 18

You issue this statement:

ALTER DATABASE BACKUP CONTROLFILE TO TRACE;

What does the statement generate?

- ☐ A binary copy of the control file.
- ☐ A text copy of the control file.
- ☒ A file containing a SQL statement which will re-create the control file.
- ☐ A file containing a SQL statement which will re-create the database.

☐ Clear

Score: 4 out of 4




Proceed



Next

No. of questions: 18



[Show summary >>](#)

1 out of 18

You issue this statement:

`ALTER DATABASE BACKUP CONTROLFILE TO TRACE;`

What does the statement generate?


- ☐ A binary copy of the control file.
- ☐ A text copy of the control file.
- ☒ A file containing a SQL statement which will re-create the control file.
- ☐ A file containing a SQL statement which will re-create the database.

☐ Clear

Score: 1 out of 1



No. of questions: 18



2 out of 18

[Show summary >>](#)

In user-managed backup and recover procedures, how are data files backed up?

- ☐ Using Recover Manager commands.
- ☐ Using SQL*Plus commands.
- ☐ Using SQL commands.
- ☒ Using operating system commands.

☐ Clear


Score: 1 out of 1

Previous

Proceed

Goto next page (ALT + N)

No. of questions: 18



3 out of 18

[Show summary >>](#)

In a shared server configuration, which two describe the actions that the listener can take to service a client request? (Choose two)

- ☐ The application initiating the session spawns a dedicated server process for the connection request
- ☒ The listener hands the connection request directly to a dispatcher
- ☐ The client connects to a dedicated server directly using a protocol address provided by the listener
- ☐ A dedicated server inherits the connection request from the listener
- ☒ The listener issues a redirect message to the client, containing the protocol address of a dispatcher. The client then terminates the network session to the listener and establishes a network session to the dispatcher, using the network address provided in the redirect message

☐ Clear

Score 2 out of 2




Previous



Proceed

[Goto next page \(ALT + N\)](#)



4 out of 18

[Show summary >>](#)

Which statement is true regarding checkpoints and recovery?

- ☒ A checkpoint defines the highest system change number (SCN)
- ☐ Only the redo records containing SCNs higher then the checkpoint need to be applied during recovery
- ☐ The LOG_CHECKPOINT_INTERVAL initialization parameter specifies the amount of time between incremental checkpoints
- ☐ All redo entries higher or at the SCN are known to be written to the data files

☐ Clear

Score 0 out of 1

Previous

Proceed

Goto next page (ALT + N)

No. of questions: 18

1	2	3	4
5	6	7	8
9	10	11	12
13	14	15	16
17	18		

5 out of 18

[Show summary >>](#)

When performing recover of a database in NOARCHIVELOG mode with RMAN, the target database must be in the _____ state to restore the control file.

- ☒ OPEN
- ☐ IDLE
- ☐ NOMOUNT
- ☐ MOUNT

☐ Clear

Score 0 out of 1

 Previous

 Proceed

 Goto next page (ALT + N)



6 out of 18

Two data files have been deleted at the operating system level by accident. Your database is running in ARCHIVELOG mode and online backups are taken nightly. One of the data files that has been deleted belongs to the USERS tablespace and the other belongs to the SYSTEM tablespace.

How can you recover from this situation?


- ☐ Shut down the database, restore the two data files and then start up the database.
- ☐ Take the SYSTEM and USERS tablespaces offline, recover the two datafiles and then bring the SYSTEM and USERS tablespaces online
- ☐ Take the system and users tablespace offline, restore the two data files, recover the two datafiles, and then bring the SYSTEM and USERS tablespaces online
- ☒ Shut down the database, restore the two data files, start up the database in MOUNT mode, recover the two data files, and then alter the database open

☐ Clear

Score 1 out of 1



Goto next page (ALT + N)



7 out of 18

You have lost all members of your current redo log file group. You issue this query:

SQL> select * from v\$log;

GROUP#	SEQ#	BYTES	ARC	STATUS	FIRST_TIME
1	60	153600	NO	INACTIVE	01-03-09:19:34
2	61	153600	NO	CURRENT	01-03-09:19:50

You then perform an incomplete recover. You receive this message:

ORA-00279: change 309141...03/09/01 19:50:14 Needed for thread 1
 ORA-00289: suggestion : /disk1/archive/arch_61.rdo
 ORA-00280: change 309043 for thread 1 is in sequence #61 Specify log: (<RET>=suggested | filename | AUTO | CANCEL)

How should you respond to this message?

- ☐ Enter the keyword CANCEL



Previous



Proceed

[Goto next page \(ALT + N\)](#)

No. of questions: 18

1	2	3	4
5	6	7	8
9	10	11	12
13	14	15	16
17	18		

7 out of 18

[Show summary >>](#)

1	60	153600	NO	INACTIVE	01-03-09:19:34
2	61	153600	NO	CURRENT	01-03-09:19:50

You then perform an incomplete recover. You receive this message:

ORA-00279: change 309141...03/09/01 19:50:14 Needed for thread 1
 ORA-00289: suggestion : /disk1/archive/arch_61.rdo
 ORA-00280: change 309043 for thread 1 is in sequence #61 Specify log. {<RET>=suggested | filename | AUTO | CANCEL}

How should you respond to this message?

- ☐ Enter the keyword CANCEL
- ☒ Enter the keyword AUTO
- ☐ Press the Enter or Return key
- ☐ Enter the filename '/disk1/archive/log2a.rdo'
- ☐ Clear



Previous




Proceed



Next

No. of questions: 18



8 out of 18

[Show summary >>](#)

Why can setting too low a value for the FAST_START_MTTR_TARGET parameter reduce your overall database performance?

- ☒ Redo blocks have to be written more frequently by LGWR.
- ☐ You need to substantially increase the size of your database buffer cache to hold the additional checkpoint records
- ☐ You need to substantially increase the size of your redo buffer cache to hold the additional checkpoint records
- ☐ Data blocks have to be written more frequently by DBWR.


☐ Clear

Score 0 out of 1

Previous

Proceed

Goto next page (ALT + N)



9 out of 18

[Show summary >>](#)

Archive file format LOG_ARCHIVE_FORMAT is defined as arch_%.s.arc. A week ago, you just archived arch_4.arc to tape, then removed all archived files to save disk space. Yesterday you saw arch_10.arc and arch_11.arc on the disk. Today, you see arch_3.arc in the archive directory. Which two things could be happened? (Choose two)

- ☐ A file name is randomly chosen by the archive process, as long as it is unique, it does not have to be sequential.
- ☒ The database was opened with the RESETLOGS option and log numbers restarted.
- ☐ The file names are only used when they are copied to tape.
- ☒ Log names run in circular fashion; arch_3.arc is re-created by the ARCn process.
- ☐ Redo logs were restored from tape for recovery.

Score 1 out of 2




Previous



Proceed

[Goto next page \(ALT + N\)](#)

No. of questions: 18



[Show summary >>](#)

10 out of 18

When you are performing media recover, and an archived log is lost or corrupt, which type of recover must you perform?

- ☐ Until cancel
- ☒ Until SCN
- ☐ Until time
- ☐ Recover using backup control file.

☐ Clear

Score 0 out of 1



Previous



Proceed



Next



11 out of 18

You discover that a disk failure occurred on DISK3 where the data file belonging to the USER_DATA table space is stored. The database is currently open and you need to recover the data file. You will restore the data file to DISK2. What is the correct sequence RMAN commands to restore and recover the data file?

- ☐ -RUN (SET NEWNAME FOR '/DISK3/user_data01.dbf' TO '/DISK2/user_data01.dbf'; RESTORE TABLESPACE user_data; RECOVER TABLESPACE user_data; ALTER DATABASE OPEN;)
- ☒ -RUN(SET NEWNAME FOR '/DISK3/user_data01.dbf' TO '/DISK2/user_data01.dbf'; RESTORE TABLESPACE user_data; SWITCH DATAFILE '/DISK3/user_data01.dbf'; RECOVER TABLESPACE user_data; ALTER DATABASE OPEN;)
- ☐ -RUN (RESTORE TABLESPACE user_data; SET NEWNAME FOR '/DISK3/user_data01.dbf' TO '/DISK2/user_data01.dbf'; SWITCH DATAFILE '/DISK3/user_data01.dbf'; RECOVER TABLESPACE user_data; ALTER DATABASE OPEN;)
- ☐ -RUN (RESTORE TABLESPACE user_data; RECOVER TABLESPACE user_data; ALTER DATABASE OPEN;)

☐ Clear

Score 1 out of 1




Previous



Proceed

[Goto next page \(ALT + N\)](#)

No. of questions: 18



[Show summary >>](#)

12 out of 18

Examine this syntax which allocates channels during a parallel image copy:

```
RMAN> CONFIGURE DEVICE TYPE disk parallelism 4;
2> COPY
3> datafile 1 TO '/BACKUP/datafile1.dbf',
4> datafile 2 TO '/BACKUP/datafile2.dbf',
5> datafile 3 TO '/BACKUP/datafile3.dbf';
RMAN> COPY
2> datafile 4 TO '/BACKUP/datafile4.dbf';
```

How many channels are used?

- ☐ 4
- ☐ 0
- ☒ 3
- ☐ 1

☐ Clear

Score: 1 out of 1




Previous



Proceed

[Goto next page \(ALT + N\)](#)

No. of questions: 18



[Show summary >>](#)

13 out of 18

Which two requirements are critically important to implement for your database backup strategy if you require a 24 hours a day, 7 days a week production environment? (Choose two)

- ☐ Open database backups.
- ☒ ARCHIVELOG mode.
- ☒ Consistent whole backups.
- ☐ NOARCHIVELOG mode.

☐ Clear


Score 1 out of 2

 Previous

 Proceed

 Goto next page (ALT + N)

No. of questions: 18



[Show summary >>](#)

14 out of 18

Your database is set in NOARCHIVELOG mode and is backed up every night. There are 10 redo log groups on the database, each with three members, making a total of 30 redo log files. At lunchtime the server unexpectedly gets shut down. Upon restarting you notice that the data file belonging to the SYSTEM tablespace has become corrupted. You also notice that there have been 15 log switches during the day. Which solution should you use to recover as much committed data as possible?

- ☐ Mount the instance, take the SYSTEM tablespace offline, open the database, and then restore the data file, recover it, and bring the tablespace online
- ☐ Restore all redo logs from last night's backup, then restart the database
- ☒ Restore the data file for the SYSTEM tablespace then open the database
- ☐ Perform a complete restore of all files from last night's backup, Data entered into the database today must be reentered

☐ Clear

Score 0 out of 1



Previous



Proceed

[Goto next page \(ALT + N\)](#)


Which two statements regarding the control file and Recovery Manager are true? (Choose two)

-

Previous Proceed

Goto next page (ALT + N)

No. of questions: 18



[Show summary >>](#)

16 out of 18

Consider this RMAN command:

RMAN> CONFIGURE RETENTION POLICY CLEAR;

What is the effect of this command?

- ☐ Backups will never expire
- ☐ The DELETE OBSOLETE command will fail with an error
- ☐ It removes any retention policy
- ☒ It sets the retention policy to the default of REDUNDANCY 1

☐ Clear

Score 1 out of 1



Previous



Proceed

[Goto next page \(ALT + N\)](#)

No. of questions: 18

1	2	3	4
5	6	7	8
9	10	11	12
13	14	15	16
17	18		

[Show summary >>](#)

17 out of 18

Oracle Net is responsible for establishing and maintaining the connection between the client application and the server. On the client side, Oracle Net is responsible for which three connectivity issues? (Choose three)

- ☐ The Oracle user being connected
- ☐ Privileges and role information
- ☒ How to handle exceptions and interrupts
- ☒ The location of the server
- ☒ Protocol involved in the connection
- ☐ Clear


Score 3 out of 3

[Previous](#)

[Proceed](#)

[Goto next page \(ALT + N\)](#)

No. of questions: 18



[Show summary >>](#)

18 out of 18

When **CONFIGURE CONTROLFILE AUTOBACKUP** is set to **ON**, RMAN automatically performs a control file autobackup in which situations? (Choose two)

- ☐ After every BACKUP or COPY command within a RUN block that is followed by the CONFIGURE CONTROLFILE AUTOBACKUP FORMAT command
- ☐ At the end of every RUN block
- ☒ After every BACKUP or COPY command issued at the RMAN prompt
- ☐ After every SET CONTROLFILE AUTOBACKUP FORMAT command
- ☒ At the end of every RUN block if the last command in the block was either BACKUP or COPY

☐ Clear

Score 2 out of 2



Previous



Proceed