

Question	Good Answer	
IGRP EIGRP load balancing different metrics destination	true	0.00
	false	2.00
OSPF IS-IS are link-state routing algorithms	true	2.00
	false	0.00
In RIP maximum number of hops 17	true	0.00
	false	2.00
change conf in fly	true	0.00
	false	2.00
RIP routing-update timer 130 s	true	0.00
	false	2.00
Running the SPF algorithm is not a CPU-intensive activity.	true	0.00
	false	2.00
Route poisoning closes the potential for longer routing loops.	true	2.00
	false	0.00
Maximum hop count for OSPF is	20	0.00
	25	0.00
	30	0.00
	26	0.00
	none of the above	3.00
Distance vector protocols update their routing table faster than link state protocols, Because :	They use a smaller number of messages	0.00
	Routers need lower processing power	0.00
	They communicate only with adjacent routers	0.00
	All of the above	0.00
	The whole statement is wrong	3.00
A protocol which shares attributes of both distance vector and link-state routing :	RIP	0.00
	RIPv.2	0.00
	EIGRP	3.00
	OSPF	0.00
	IGRP	0.00
algorithms that do not allow a router to know the exact topology of an internetwork	Hybrid algorithms	0.00
	Link-State algorithms	0.00
	Distance vector algorithms	3.00
	Autonomous algorithms	0.00
	All of the above	0.00
The OSPF link-state database is built using	BGP	3.00
	SRP	0.00
	LSA	3.00
	SPF	0.00
	All of the above	0.00
only one gateway,configure routing	Dynamic routing	0.00
	Multiple Path routing	0.00

	Static route	3.00
	IGMP routing	0.00
	none of the above	0.00
Hello metric depends on	Delay	3.00
	Cost	0.00
	Bandwidth	0.00
	Hops	0.00
	None of the above	0.00
EIGRP updates	full updates only when the metric for a route changes	0.00
	partial updates only when the metric for a bandwidth changes.	0.00
	full updates only when the metric for a route changes.	0.00
	partial updates only when the metric for a route changes.	3.00
	None of the above	0.00
OSPF,RIPv2 protocols use :	Broadcast in sending the table only to preconfigured neighbor	0.00
	Multicast in sending the table only to preconfigured neighbor	3.00
	Unicast in sending the table only to preconfigured neighbor	0.00
	Anycast in sending the table only to preconfigured neighbor	0.00
	None of the above	0.00
Metric	process	0.00
	meter	0.00
	weight	0.00
	metric	2.00
	route	0.00
stability despite potentially rapid changes RIP	split horizon	2.00
	hold-down mechanisms	2.00
	hop count	0.00
	Routing loops	0.00
	Poison reverse	1.00
	Non of the above	0.00
Examples of IGP	RIP	2.00
	EIGRP	2.00

	PGB	0.00
	SPF	0.00
	IGRP	1.00
	All of the choices	0.00
Routing algorithms can be classified by type such as	Static & dynamic	2.00
	Power & Clever	0.00
	Single-path & multipath	2.00
	Link-state & distance vector	1.00
	Non of the choices	0.00
Routing Table Entries could be :	Directly connected	1.25
	Static routing	1.25
	Dynamic routing	1.25
	Default route	1.25
	Depending Routing	0.00
OSPF has primary characteristics which are :	derived from several research efforts	0.00
	the protocol is open, which means that its specification is in the public domain	2.50
	OSPF is based on Dijkstra algorithm	2.50
	Distance vector algorithm in calculating LSA	0.00
	None of the above	0.00
Cautions of Link-State Routing :	Significant demands for resources	2.00
	Fast convergence	0.00
	Requires very strict network design	2.00
	Problems with partitioning of areas	1.00
	None of the above	0.00
EIGRP key technologies	neighbor discovery/recovery	1.25
	reliable transport protocol (RTP)	1.25
	redundant STP	0.00
	DUAL finite-state machine	1.25
	protocol-dependent modules	1.25
The distance vector routing approach determines the following in order to reach network in the internetwork :	direction	2.50
	metrics	0.00
	loops	0.00
	distance	2.50
	links	0.00