

BI_IT420_S07_S1_Final_11-08-2007

No. of questions 40

1	2	3	4
5	6	7	8
9	10	11	12
13	14	15	16
17	18	19	20
21	22	23	24
25	26	27	28
29	30	31	32
33	34	35	36
37	38	39	40

<< Hide summary

Assessment result

No. of questions in assessment:	40
No. of correct answers:	29
No. of wrong answers:	11
No. of questions attempted:	40
No. of questions not attempted:	0
No. of questions presented:	40
Maximum score:	51
Actual score:	36.5
Percentage:	71.57%
Threshold percentage to pass:	35%
Assessment outcome:	Pass
Grade:	Grade definition is not available

1 out of 40

Because the hold-down rule says that when a route is removed, no new route will be accepted for the same destination for some period of time, the triggered update has time to propagate throughout the network.

☒ True ☐ False ☐ Clear

Score 1 out of 1

Answer(s) True



Proceed



Next

BI_IT420_S07_S1_Final_11-08-2007

No. of questions 40



[Show summary >>](#)

2 out of 40

Static Route Uses a route that would be entered into the router by :

- ☐ Network detection algorithms
- ☐ Switching Algorithms
- ☒ Maunally by Administrator
- ☐ Deduced from routing tables
- ☐ Routing Algorithms

☐ Clear

Score 1 out of 1

Answer(s) Maunally by Administrator



Previous



Proceed



Next

[Goto next page \(ALT + N\)](#)

Premium

No. of questions 40

1 2 3 4

[Show summary >>](#)

7 out of 40

EIGRP supports:

- ☐ Rapid convergence
- ☒ VLSM
- ☐ Reduced bandwidth usage
- ☒ Multiple network-layer protocols
- ☐ Non of the above

Score 1.5 out of 2

Answer(s) Rapid convergence, VLSM and Multiple network-layer protocols

 Previous



Proceed

Goto next page (ALT + N)

Internet

http://bit.svuonline.org - Assessment Management System - Microsoft Internet Explorer

Saras[®]

from Excel-Soft

Assessment Management System

Premium

BI_ITI420_S07_S1_Final_11-08-2007

No. of questions 40

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

8 out of 40

Show summary >>

We can use ACL to :

☒

filtering traffic into or out of a router interface

☒

selecting types of traffic to be analyzed, forwarded

☐

Content routing

☐

Priority and Custom Queuing

☐

Non of the above

☐

Clear

Score 1.5 out of 2

Answer(s) filtering traffic into or out of a router interface, selecting types of traffic to be analyzed, forwarded and Priority and Custom Queuing

Previous

Proceed

Next

http://bit.svuonline.org - Assessment Management System - Microsoft Internet Explorer

Saras[®]
from Excel-Soft

Assessment Management System
Premium

BI_ITI420_S07_S1_Final_11-08-2007

No. of questions 40

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

Show summary >>

9 out of 40

Benefits of Link State routing (All responses must be correct) :

☒

Fast convergence

☐

Significant demands for resources

☒

Robustness against routing loops

☐

partitioning of areas

☒

hierarchical network design so resources can be optimized

☐

Clear

Score 2 out of 2

Answer(s) Fast convergence, Robustness against routing loops and hierarchical network design so resources can be optimized

Previous

Proceed

Next

Internet

http://bit.svuonline.org - Assessment Management System - Microsoft Internet Explorer

Saras[®]
from Excel-Soft

Assessment Management System
Premium

BI_ITI420_S07_S1_Final_11-08-2007

No. of questions 40

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

Show summary >>

10 out of 40

OSPF area characteristics (All questions must be correct)

☒

Detailed LSA

☒

Localizes impact of topology change

☐

Minimize routing table entries

☒

Summary table

☒

Requires hierarchal design

☐

All of the above

☐

None of the above

☐

Clear

Score 0 out of 2

Answer(s) Detailed LSA, Localizes impact of topology change, Minimize routing table entries and Requires hierarchal design

Previous

Proceed

Next

Internet

BI_ITI420_S07_S1_Final_11-08-2007

No. of questions: 40



[Show summary >>](#)

11 out of 40

Exterior routing protocols are used to communicate between

- ☒ Atmosphere systems
- ☐ External domains
- ☐ Redundant routers
- ☐ Autonomous systems

☐ Clear

Score 0 out of 1

Answer(s) Autonomous systems



Assessment Management System

Premium

BI_ITI420_S07_S1_Final_11-08-2007

No. of questions 40

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

12 out of 40

Show summary >>

Link-state routers keep track of the following (all responses must be correct)

☒

 Their neighbours

☐

 Summary table

☐

 All routers within the same area

☒

 Best paths toward a destination

☐

 Convergence recall☐

Score 2 out of 2

Answer(s) Their neighbours and Best paths toward a destination

Previous

Proceed

Next

Internet

No. of questions 40

13 out of 40

- ☒ Transit area (backbone or area 0)
- ☐ External Routing Domain
- ☒ Regular areas (non-backbone areas)
- ☐ Atonomus System

Answer(s) Transit area (backbone or area 0) and Regular areas (non-backbone areas)



Proceed

 Next

No. of questions 40

15 out of 40

☐ True ☒ False

Score 1 out of 1

Answer(s) False

 Previous

Proceed

 Next

http://bit.svuonline.org - Assessment Management System - Microsoft Internet Explorer

Saras[®]
from Excel-Soft

Assessment Management System
Premium

BI_ITI420_S07_S1_Final_11-08-2007

No. of questions 40

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

Show summary >>

17 out of 40

While routing packets from router to another till packets reach the destination , the routers will prevent the following from being changed :

- ☐ Source Physical address & Destination Physical address.
- ☒ Source IP address & Destination IP address.
- ☐ b. Source MAC address & Destination IP address.
- ☐ d. Source IP address & Destination MAC address.

☐ Clear

Score 1 out of 1

Answer(s) Source IP address & Destination IP address.

Previous

Proceed

Next

Internet

http://bit.svuonline.org - Assessment Management System - Microsoft Internet Explorer

Saras[®]
from Excel-Soft

Assessment Management System
Premium

BI_ITI420_S07_S1_Final_11-08-2007

No. of questions: 40

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

Show summary >>

18 out of 40

EIGRP does not make periodic updates. Instead, it sends partial updates only when the metric for a route changes.

☒ True ☐ False ☐ Clear

Score 1 out of 1

Answer(s) True

Feedback Correct

Previous

Proceed

Next

Internet

Internet

http://bit.svuonline.org - Assessment Management System - Microsoft Internet Explorer

Saras[®]

from Excel-Soft

Assessment Management System *Premium*

BI_ITI420_S07_S1_Final_11-08-2007

No. of questions 40

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

19 out of 40

Show summary >>

If RIPv2 has two routes towards the same destination, route A has metric 3 and route B has metric 6, how does RIPv2 do to distribute the load between both routes ?

☐

Route A will receive double traffic as route B

☐

Route B will receive equal traffic as route A

☒

Load will be distributed randomly, with a slight priority to route A

☐

Non of the above

☐ Clear

Score 0 out of 1

Answer(s) Non of the above

Previous

Proceed

Next

Internet

http://bit.svuonline.org - Assessment Management System - Microsoft Internet Explorer

Saras[®]
from Excel-Soft

Assessment Management System
Premium

BI_ITI420_S07_S1_Final_11-08-2007

No. of questions 40

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

25 out of 40

Show summary >>

IGRP uses a two dimension metric that is calculated by factoring weighted mathematical values for internetwork delay and reliability

☒ True

☐ False

☐ Clear

Score 0 out of 1

Answer(s) False

Previous

Proceed

Goto next page [ALT + N]

No. of questions 40

[Show summary >>](#)

27 out of 40

Static routing is not usable for networks with frequent changes

☒ True ☐ False

Score 1 out of 1

Answer(s) True

Feedback Correct

 Previous

Proceed

Goto next page (ALT + N)

No. of questions 40

[Show summary >>](#)

28 out of 40

The IS-IS is an improved distance vector routing protocol which is similar to link-state routing

☐ True ☒ False

Score 1 out of 1

Answer(s) False

 Previous Proceed

 Next

No. of questions 40

[Show summary >>](#)

29 out of 40

A protocol which shares attributes of both distance vector and link-state routing :

- ☐ RIP
- ☐ RIPv.2
- ☒ EIGRP
- ☐ OSPF

Score 1 out of 1

Answer(s) EIGRP

 Previous Proceed

 Next

http://bit.svuonline.org - Assessment Management System - Microsoft Internet Explorer

Saras[®]

from Excel-Soft

Assessment Management System

Premium

BI_ITI420_S07_S1_Final_11-08-2007

No. of questions 40

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

30 out of 40

Show summary >>

RIP metric depends on

☐ Delay

☐ Error rate

☒ Bandwidth

☐ Lowest hop count

☐ Clear

Score 0 out of 1

Answer(s) Lowest hop count

Previous

Proceed

Next

Internet

Internet 

No. of questions 40

34 out of 40

- ☒ Defining Rules for traffic exchange between different Networks
- ☐ Help the router distinguish between different networks
- ☐ Restrict the allowed traffic to a certain Network destination
- ☐ 1 and 3
- ☐ 1,2 and 3

Score 0 out of 1
Answer(s) 1 and 3

 Proceed

Next

Internet

http://bit.svuonline.org - Assessment Management System - Microsoft Internet Explorer

Saras[®]

from Excel-Soft

Assessment Management System *Premium*

BI_ITI420_S07_S1_Final_11-08-2007

No. of questions 40

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

37 out of 40

Show summary >>

RIPv1, IGRP protocols use

☐

Broadcast in sending the table only to preconfigured neighbor

☒

Multicast in sending the table only to preconfigured neighbor

☐

Unicast in sending the table only to preconfigured neighbor

☐

Anycast in sending the table only to preconfigured neighbor

☐

Clear

Score

0 out of 1

Answer(s)

Broadcast in sending the table only to preconfigured neighbor

Previous

Proceed

Next

No. of questions 40

[Show summary >>](#)

38 out of 40

Ping is an implementation of the IP Message Control Protocol (ICMP).

☐ True ☒ False

Score 0 out of 1

Answer(s) True

Feedback Wrong

 Previous Proceed

Goto next page (ALT + N)

Internet

http://bit.svuonline.org - Assessment Management System - Microsoft Internet Explorer

Saras

from Excel-Soft

Assessment Management System

Premium

BI_ITI420_S07_S1_Final_11-08-2007

No. of questions 40

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

39 out of 40

Show summary >>

One important difference between Distance vector and Link-State algorithms is

☐

Distance vector are more reliable, because they converge faster

☐

Distance vector send less messages than link-state

☒

Link-State don't use hierarchical communication

☐

Link-State algorithms tend to have loops and need multiple safety rules☐ Clear

Score 0 out of 1

Answer(s) Distance vector send less messages than link-state

Previous

Proceed

Next

http://bit.svuonline.org - Assessment Management System - Microsoft Internet Explorer

Saras[®]

from Excel-Soft

Assessment Management System

Premium

BI_ITI420_S07_S1_Final_11-08-2007

No. of questions: 40

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

40 out of 40

Show summary >>

A static routing table is constructed manually by the system administrator using the setroute command.

☐ True

☒ False

☐ Clear

Score 1 out of 1

Answer(s) False

Feedback Wrong

Previous

Proceed

Internet