

A DOMPDF Wrapper for Laravel

MIT license

5.9k stars 912 forks Activity

Star

Watch

Code Issues 55 Pull requests 8 Actions Wiki Security Insights

master

...



barryvdh Convert phpunit (#952) ...

✓ on Feb 5 173

[View code](#)

DOMPDF Wrapper for Laravel

Laravel wrapper for [Dompdf HTML to PDF Converter](#)

Tests passing license MIT stable v2.0.1 downloads 33.37 M Powered By [Fruitcake](#)

Installation

Laravel

Require this package in your composer.json and update composer. This will download the package and the dompdf + fontlib libraries also.

```
composer require barryvdh/laravel-dompdf
```

Lumen

After updating composer add the following lines to register provider in bootstrap/app.php

```
$app->register(\Barryvdh\DomPDF\ServiceProvider::class);
```

To change the configuration, copy the config file to your config folder and enable it in bootstrap/app.php :

```
$app->configure('dompdf');
```

Using

You can create a new DOMPDF instance and load a HTML string, file or view name. You can save it to a file, or stream (show in browser) or download.

```
use Barryvdh\DomPDF\Facade\Pdf;

$pdf = Pdf::loadView('pdf.invoice', $data);
return $pdf->download('invoice.pdf');
```



or use the App container:

☰ readme.md

```
$pdf->loadHTML('<h1>Test</h1>');
return $pdf->stream();
```

Or use the facade:

You can chain the methods:

```
return Pdf::loadFile(public_path().'/myfile.html')->save('/path-to/my_stored_file.pdf')->s
```



You can change the orientation and paper size, and hide or show errors (by default, errors are shown when debug is on)

```
Pdf::loadHTML($html)->setPaper('a4', 'landscape')->setWarnings(false)->save('myfile.pdf')
```



If you need the output as a string, you can get the rendered PDF with the output() function, so you can save/output it yourself.

Use `php artisan vendor:publish` to create a config file located at `config/dompdf.php` which will allow you to define local configurations to change some settings (default paper etc). You can also use your ConfigProvider to set certain keys.

Configuration

The default configuration settings are set in `config/dompdf.php`. Copy this file to your own config directory to modify the values. You can publish the config using this command:

```
php artisan vendor:publish --provider="Barryvdh\DomPDF\ServiceProvider"
```

You can still alter the dompdf options in your code before generating the pdf using this command:

```
Pdf::setOption(['dpi' => 150, 'defaultFont' => 'sans-serif']);
```

Available options and their defaults:

- **rootDir**: "{app_directory}/vendor/dompdf/dompdf"
- **tempDir**: "/tmp" (*available in config/dompdf.php*)
- **fontDir**: "{app_directory}/storage/fonts" (*available in config/dompdf.php*)
- **fontCache**: "{app_directory}/storage/fonts" (*available in config/dompdf.php*)
- **chroot**: "{app_directory}" (*available in config/dompdf.php*)
- **logOutputFile**: "/tmp/log.htm"
- **defaultMediaType**: "screen" (*available in config/dompdf.php*)
- **defaultPaperSize**: "a4" (*available in config/dompdf.php*)
- **defaultFont**: "serif" (*available in config/dompdf.php*)
- **dpi**: 96 (*available in config/dompdf.php*)
- **fontHeightRatio**: 1.1 (*available in config/dompdf.php*)
- **isPhpEnabled**: false (*available in config/dompdf.php*)
- **isRemoteEnabled**: true (*available in config/dompdf.php*)
- **isJavascriptEnabled**: true (*available in config/dompdf.php*)
- **isHtml5ParserEnabled**: false (*available in config/dompdf.php*)
- **isFontSubsettingEnabled**: false (*available in config/dompdf.php*)
- **debugPng**: false
- **debugKeepTemp**: false
- **debugCss**: false
- **debugLayout**: false
- **debugLayoutLines**: true
- **debugLayoutBlocks**: true
- **debugLayoutInline**: true
- **debugLayoutPaddingBox**: true
- **pdfBackend**: "CPDF" (*available in config/dompdf.php*)
- **pdfLibLicense**: ""
- **adminUsername**: "user"

- `adminPassword: "password"`

Tip: UTF-8 support

In your templates, set the UTF-8 Metatag:

```
<meta http-equiv="Content-Type" content="text/html; charset=utf-8"/>
```

Tip: Page breaks

You can use the CSS `page-break-before` / `page-break-after` properties to create a new page.

```
<style>
.page-break {
  page-break-after: always;
}
</style>
<h1>Page 1</h1>
<div class="page-break"></div>
<h1>Page 2</h1>
```

License

This DOMPDF Wrapper for Laravel is open-sourced software licensed under the [MIT license](#)

Releases 21

 **Support Laravel 10** Latest
on Feb 1

[+ 20 releases](#)

Sponsor this project



barryvdh Barry vd. Heuvel



<https://fruitcake.nl>

[Learn more about GitHub Sponsors](#)

Packages

No packages published

Used by 68.1k



Contributors 42



+ 31 contributors

Languages

● PHP 100.0%