





# Digital IIR Filters: Analysis Examples





```
% Script File: IIR_Anal_Ex1.m
%
% Crude Lowpass filter
% -----
%      b0 (1 + z^-1)
% H(z) = -----
%      (1 - c1 z^-1)
% c1 = 0.8
% b0 = ((1-c1)/2) is a gain factor so that H(z=1, or w=0) = 1
%
c1=0.8;
b0=(1-c1)/2;
b=b0*[1 1];
a=[1 -c1];
% plot results
L=[ -1.2 -20 -0.5 -1];
U=[ 1.2 5 0.5 5];
[c d]= sys(b,a,L,U);
```



```

% Script File: IIR_Anal_Ex2.m
%
% Crude Highpass filter
% -----
%
%      b0 (1 - z^-1)
%  H(z) = -----
%      (1 - c1 z^-1)
%
% c1 = -0.8
% b0 = ((1+c1)/2) is a gain factor so that H(z=-1, or w=pi) = 1
%
c1=-0.8;
b0=(1+c1)/2;
b=b0*[1 -1];
a=[1 -c1];
% plot results
L=[-1.2 -20 -0.5 -1];
U=[1.2 5 0.5 5];
[c d]=sys(b,a,L,U);

```







```

% Script File: IIR_Anal_Ex3.m
%
% Crude Bandpass filter
% -----
%
%      b0 (1+z^-1) (1-z^-1)/
% H(z) = -----
%      (1-c1 z^-1) (1-c2 z^-1))
%
% c1,2 = 0.9 exp(±j*pi/4)
% b0 = 1 is assumed below
%
j=sqrt(-1);
b0=1;
b=b0* conv([1 1],[1 -1]);
%
c1=0.9*exp(j*pi/4);
c2=conj(c1);
a=conv([1 -c1],[1 -c2]);
%
% plot results
L=[ -1.2 -20 -0.5 -1];
U=[ 1.2  30  0.5 10];
[c d]= sys(b,a,L,U);

```

% unity gain factor assumed  
% conv performs poly multiplication

% conv performs poly multiplication







```

% Script File: IIR_Anal_Ex4.m
%
% Crude Notch (or bandstop) filter
% -----
%
%      b0 (1-d1 z^-1) (1-d2 z^-1)
%  H(z) = -----
%      (1-c1 z^-1) (1-c2 z^-1);
%
% d1 = exp(j*pi/4); c1 = 0.9 exp(j*pi/4)
% b0 = (1-c1)(1-c2)/(1-d1)(1-d2)

j=sqrt(-1);
c1=0.9*exp(j*pi/4); c2=conj(c1);
d1= exp(j*pi/4); d2=conj(d1);
b0=(1-c1)*(1-c2)/((1-d1)*(1-d2));
b=b0*conv([1 -d1],[1 -d2]);
a=conv([1 -c1],[1 -c2]);



% plot results
L=[ -1.2 -20 -0.5 -1];
U=[ 1.2  5 0.5 20];
[c d]= sys(b,a,L,U);

```





```
% Script File IIR_Anal_Ex5.m
%
% An Allpass Filter (from O&S)
% -----
%
%      (z^-1 - c1) (z^-1 - c2)   a2 + a1 z^-1 + z^-2
%  H(z) = ----- = -----
%      (1-c1 z^-1) (1-c2 z^-1)  1 + a1 z^-1 + a2 z^-2
%
j=sqrt(-1);
c=[ 0.9*exp(j*pi/4)  0.9*exp(-j*pi/4)];
a=real(poly(c));
%
b=a(length(a):-1:1);
L=[-1.2 -1 -1 -2];
U=[1.2 1 1 20];
[c,d]=sys(b,a,L,U);
```

% 'b' is 'a' written backwards







Note the  
pole-zero  
pattern



```

% A "good" lowpass filter (from O&S)
% -----
%
%      0.05643 (1+z^-1) (1- 1.0166 z^-1 + z^-2)
% H(z) = -----
%      (1 - 0.6830 z^-1) (1 - 1.4461 z^-1 + 0.7957 z^-2)
%
b0=0.05643;
b1=[1 1];
b2=[1 -1.0166 1];
b=conv(b1,b2);
b=b0*b;
% coefficients of the first poly in the numerator
% coeff of the second poly
% coeffs of the product poly
%
a1=[1 -0.6830];
a2=[1 -1.4461 0.7957];
a=conv(a1,a2);
% repeat for the denominator
%
L=[-1.2 -60 -1 0];
U=[1.2 20 1 10];
[c,d] = sys(b,a,L,U);

```



```

function [c,d]=sys(b,a,L,U)
%
% system plots the pole-zero diagram, the frequency response, and
% the group delay of discrete-time LTI systems; a and b are the
% denominator and numerator coefficients of H(z).
% L and U are arrays containing the lower and upper limits for
% axes in plotted figures (pole-zero, H_mag, H_ARG, and ng, respectively)

% poles and zeros (other than those at the origin)
% -----
d=roots(b);
c=[];
if(length(a) > 1) c=roots(a); end
%
clf
% pole-zero plot (could also use the function zplane)
% -----
subplot(2,2,2),
j=sqrt(-1);
z=exp(j*2*pi*[0:360]/260);
plot(real(z),imag(z),'-'), hold on
if(length(a) > 1) plot(real(c),imag(c),'x'), end
plot(real(d),imag(d),'o')
plot([0 0],[L(1) U(1)],'--r');
plot([L(1) U(1)],[0 0],'--r');
axis([L(1) U(1) L(1) U(1)]);
title('Pole/Zero Plot')
axis('square');
%
% Frequency Response and Group Delay
% -----
[H,w]=freqz(b,a,256,'whole');
H_mag=20*log10(abs(H));
H_ARG=angle(H);
ng=grpdelay(b,a,256,'whole');
%
tpi=2*pi;
subplot(2,2,1),plot(w/tpi,H_mag,'-r');
axis([0 1 L(2) U(2)]);
axis('normal');
xlabel('Frequency f = F(Hz)/Fs'), ylabel('|H(f)| (dB)')
%
subplot(2,2,3),plot(w/tpi,H_ARG/pi,'-r');
axis([0 1 L(3) U(3)]);
xlabel('Frequency f = F(Hz)/Fs'), ylabel('angle(H)/pi')
%
subplot(2,2,4),plot(w/tpi,ng,'-');
axis([0 1 L(4) U(4)]);
xlabel('Frequency f = F(Hz)/Fs(Hz)'), ylabel('ng (samples)')
axis; subplot

```

see also the Matlab function "zplot"

## Digital FIR Filters: Analysis Examples

```
% Script File FIR_Anal.m
```

```
%
```

```
% Type I: h(n) even, M even
```

```
% -----
```

```
% Crude Notch Filter
```

```
% h(n)=delta(n)-delta(n-1)+delta(n-2)
```

```
% H(z) = 1 - z^-1 + z^-2;
```

```
%
```

```
a=1; b=[1 -1 1];
```

```
L= [-1.2 -40 -1 0]; U=[1.2 20 1 4];
```

```
[c d]=sys(b,a,L,U)
```

```
pause
```

```
% 2- Type II: h(n) even, M odd
```

```
% -----
```

```
% Boxcar Filter
```

```
% h(n)=delta(n)+delta(n-1)+...+delta(n-5);
```

```
% H(z) = 1+z^-1+z^-2+z^-3+z^-4+z^-5;
```

```
% H(z) = (1-z^-6)/(1-z^-1)
```

```
%
```

```
a=1; b=[1 1 1 1 1 1];
```

```
L= [-1.2 -40 -1 0]; U=[1.2 20 1 4];
```

```
[c d]=sys(b,a,L,U)
```

```
pause
```

```
% 3- Type III: h(n) odd, M even
```

```
% -----
```

```
% Comb Filter
```

```
% h(n)=delta(n)-delta(n-6);
```

```
% H(z) = 1 - z^-6;
```

```
%
```

```
a=1; b=[1 0 0 0 0 0 -1];
```

```
L= [-1.2 -30 -1 0]; U=[1.2 10 1 4];
```

```
[c d]=sys(b,a,L,U)
```

```
pause
```

```
%
```

```
% 4- Type IV: h(n) odd, M odd
```

```
% -----
```

```
% Crude Differentiator (Crude Highpass Filter)
```

```
% h(n)=delta(n)-delta(n-1);
```

```
% H(z) = 1 - z^-1;
```

```
%
```

```
a=1; b=[1 -1];
```


```
L= [-1.2 -40 -1 0]; U=[1.2 20 1 4];
```

```
[c d]=sys(b,a,L,U)
```

$$h(n) = h(M-n)$$

$$H(z^{-1}) = z^M H(z)$$


$$M=2$$



$$h(n) = h(M-n)$$

$$H(z^{-1}) = z^M H(z)$$

$$M=5$$




zero @  $z = -1$

$$h(n) = -h(M-n)$$

$$H(z^{-1}) = -z^M H(z)$$

$$M=6$$




zeros @  $z = \pm 1$

$$h(n) = -h(M-n)$$





$$H(z^{-1}) = -z^M H(z)$$

$$M=1$$





zero @  $z = 1$









Type I  
Crude Notch Filter



zero at  $z = -1$  ( $\omega = \pi$ );  
always!







Type II  
Allpass Filter



zeros at  $z = \pm 1$   
( $\omega = 0, \pi$ ); always

Type III  
multi-notch comb filter



zero at  $z = 1$   
( $\omega = 0$ ); always

Type IV  
Crude Highpass Filter

