

Attention-based Deep Multiple Instance Learning

Maximilian Ilse, Jakub Tomczak, Max Welling


AMLAB, University of Amsterdam

ICML 2018

Motivation

Typical size of benchmark


natural images: **up to 256x256**



Motivation

Typical size of benchmark

natural images: **up to 256x256**



Typical size of medical images:


~10,000x10,000



Motivation

Typical size of benchmark

natural images: **up to 256x256**



Typical size of medical images:


~10,000x10,000

How to process it?



Motivation


Goal: Find (local) objects (abnormal changes in tissue) in an image.



Motivation

Goal: Find (local) objects (abnormal changes in tissue) in an image.

Data: billions of pixels, 10^1 - 10^2 scans, weak labels (for regions or a scan).





Motivation

Goal: Find (local) objects (abnormal changes in tissue) in an image.

Data: billions of pixels, 10^1 - 10^2 scans, weak labels (for regions or a scan).


Solution: Use local information in the image and look for Regions of Interest.



Supervised Learning vs. Multiple Instance Learning

One image - one label


$$\mathbf{x} \in \mathbb{R}^D, \quad y \in \{0, 1\}$$



Supervised Learning vs. Multiple Instance Learning

One image - one label


$$\mathbf{x} \in \mathbb{R}^D, \quad y \in \{0, 1\}$$



Many images - one label

$$X = \{\mathbf{x}_1, \dots, \mathbf{x}_K\},$$


$$Y \in \{0, 1\}$$



Supervised Learning vs. Multiple Instance Learning

One image - one label

$$\mathbf{x} \in \mathbb{R}^D, \quad y \in \{0, 1\}$$




Many images - one label

$$X = \{\mathbf{x}_1, \dots, \mathbf{x}_K\},$$

$$Y \in \{0, 1\}$$

Individual labels:


$\{y_1, \dots, y_K\}$ are **unknown**.



Supervised Learning vs. Multiple Instance Learning

One image - one label


$$\mathbf{x} \in \mathbb{R}^D, \quad y \in \{0, 1\}$$



Many images - one label

$$X = \{\mathbf{x}_1, \dots, \mathbf{x}_K\},$$

$$Y \in \{0, 1\}$$



Individual labels:

$\{y_1, \dots, y_K\}$ are **unknown**.


Assumptions about the label Y :

$$Y = \begin{cases} 0, & \text{iff } \sum_k y_k = 0, \\ 1, & \text{otherwise.} \end{cases}$$

Supervised Learning vs. Multiple Instance Learning

One image - one label


$$\mathbf{x} \in \mathbb{R}^D, \quad y \in \{0, 1\}$$



Many images - one label

$$X = \{\mathbf{x}_1, \dots, \mathbf{x}_K\},$$

$$Y \in \{0, 1\}$$



Individual labels:

$\{y_1, \dots, y_K\}$ are **unknown**.

Instances with $(y_k = 1)$ = **key instances**

Assumptions about the label Y :

$$Y = \begin{cases} 0, & \text{iff } \sum_k y_k = 0, \\ 1, & \text{otherwise.} \end{cases}$$

Multiple Instance Learning

A MIL classifier as a probabilistic model:

$$p(Y|X) = \theta(X)^Y (1 - \theta(X))^{1-Y}$$

Multiple Instance Learning

A MIL classifier as a probabilistic model:

$$p(Y|X) = \theta(X)^Y (1 - \theta(X))^{1-Y}$$



Must be **permutation-invariant!**

Multiple Instance Learning

A MIL classifier as a probabilistic model:

$$p(Y|X) = \theta(X)^Y (1 - \theta(X))^{1-Y}$$



Must be **permutation-invariant!**

How?

Multiple Instance Learning

A MIL classifier as a probabilistic model:

$$p(Y|X) = \theta(X)^Y (1 - \theta(X))^{1-Y}$$

Theorem (Zaheer et al., 2017)

A scoring function for a set of instances X , $S(X) \in \mathbb{R}$, is a symmetric function (i.e., permutation invariant to the elements in X), if and only if it can be decomposed in the following form:

$$S(X) = g(\sum_{x \in X} f(x))$$

where f and g are suitable transformations.

Multiple Instance Learning

A MIL classifier as a probabilistic model:

$$p(Y|X) = \theta(X)^Y (1 - \theta(X))^{1-Y}$$

Theorem (Qi et al., 2017)

For any $\epsilon > 0$, a Hausdorff continuous symmetric function $S(X) \in \mathbb{R}$ can be arbitrarily approximated by a function in the form $g(\max_{x \in X} f(x))$, where \max is the element-wise vector maximum operator and f and g are continuous functions, that is:

$$|S(X) - g(\max_{x \in X} f(x))| < \epsilon.$$

Multiple Instance Learning

A MIL classifier as a probabilistic model:

$$p(Y|X) = \theta(X)^Y (1 - \theta(X))^{1-Y}$$

The theorems say that we can model a **permutation-invariant** $\theta(X)$ by composing:

- a transformation f of individual instances,
- a permutation-invariant function σ , e.g., sum, mean or max (**MIL pooling**),
- a transformation of combined instances using a function g :

$$\theta(X) = g(\sigma(f(x_1), \dots, f(x_K)))$$

Multiple Instance Learning: Components



We model both transformations f and g using **neural networks**.

Multiple Instance Learning: Components

We model both transformations f and g using **neural networks**.

Two approaches:

- **embedded-based**
- **instance-based**




Multiple Instance Learning: Components

We model both transformations f and g using **neural networks**.


Two approaches:

- **embedded-based**
- **instance-based**



MIL pooling:



- mean,
- max,
- other (e.g., Noisy-Or).



Multiple Instance Learning: Components

Issues:

- Embedded-based approach **lacks interpretability.**
- Instance-based approach **propagates error.**
- max and mean are **non-learnable.**




Multiple Instance Learning: Attention-based approach

We propose to use the attention mechanism as **MIL pooling**:

$$\mathbf{z} = \sum_{k=1}^K a_k \mathbf{h}_k,$$

where:

$$a_k = \frac{\exp\{\mathbf{w}_k^\top \tanh(\mathbf{V}\mathbf{h}_k^\top)\}}{\sum_{j=1}^K \exp\{\mathbf{w}_j^\top \tanh(\mathbf{V}\mathbf{h}_j^\top)\}},$$



Multiple Instance Learning: Attention-based approach


We propose to use the attention mechanism as **MIL pooling**:

$$\mathbf{z} = \sum_{k=1}^K a_k \mathbf{h}_k,$$

where:

$$a_k = \frac{\exp\{\mathbf{w}_k^\top (\tanh(\mathbf{V}\mathbf{h}_k^\top) \odot \text{sigm}(\mathbf{U}\mathbf{h}_k^\top))\}}{\sum_{j=1}^K \exp\{\mathbf{w}_j^\top (\tanh(\mathbf{V}\mathbf{h}_j^\top) \odot \text{sigm}(\mathbf{U}\mathbf{h}_j^\top))\}},$$

attention with **gating mechanism**




Multiple Instance Learning: Attention-based approach

The attention mechanism as **MIL pooling**:

- MIL operator is **trainable**;
- attention weights could be **interpreted (key instances)**.

Embedded-based approach

is **interpretable** and fully **trainable**.



Experiments: MNIST-based problem



$$Y = 0$$



$$Y = 1$$

Experiments: MNIST-based problem




$a_1=0.08884$ $a_2=0.09065$ $a_3=0.11254$ $a_4=0.07189$ $a_5=0.05136$ $a_6=0.03091$ $a_7=0.07404$




$a_8=0.07412$ $a_9=0.16541$ $a_{10}=0.02777$ $a_{11}=0.11683$ $a_{12}=0.04244$ $a_{13}=0.0532$

Experiments: MNIST-based problem



Experiments: MNIST-based problem



Experiments: Breast Cancer

METHOD	ACCURACY	PRECISION	RECALL	F-SCORE	AUC
Instance+max	0.614 \pm 0.020	0.585 \pm 0.03	0.477 \pm 0.087	0.506 \pm 0.054	0.612 \pm 0.026
Instance+mean	0.672 \pm 0.026	0.672 \pm 0.034	0.515 \pm 0.056	0.577 \pm 0.049	0.719 \pm 0.019
Embedding+max	0.607 \pm 0.015	0.558 \pm 0.013	0.546 \pm 0.070	0.543 \pm 0.042	0.650 \pm 0.013
Embedding+mean	0.741 \pm 0.023	0.741 \pm 0.023	0.654 \pm 0.054	0.689 \pm 0.034	0.796 \pm 0.012
Attention	0.745 \pm 0.018	0.718 \pm 0.021	0.715 \pm 0.046	0.712 \pm 0.025	0.775 \pm 0.016
Gated-Attention	0.755 \pm 0.016	0.728 \pm 0.016	0.731 \pm 0.042	0.725 \pm 0.023	0.799 \pm 0.020

Experiments: Colon Cancer

METHOD	ACCURACY	PRECISION	RECALL	F-SCORE	AUC
Instance+max	0.842 ± 0.021	0.866 ± 0.017	0.816 ± 0.031	0.839 ± 0.023	0.914 ± 0.010
Instance+mean	0.772 ± 0.012	0.821 ± 0.011	0.710 ± 0.031	0.759 ± 0.017	0.866 ± 0.008
Embedding+max	0.824 ± 0.015	0.884 ± 0.014	0.753 ± 0.020	0.813 ± 0.017	0.918 ± 0.010
Embedding+mean	0.860 ± 0.014	0.911 ± 0.011	0.804 ± 0.027	0.853 ± 0.016	0.940 ± 0.010
Attention	0.904 ± 0.011	0.953 ± 0.014	0.855 ± 0.017	0.901 ± 0.011	0.968 ± 0.009
Gated-Attention	0.898 ± 0.020	0.944 ± 0.016	0.851 ± 0.035	0.893 ± 0.022	0.968 ± 0.010

Experiments: Colon Cancer




Figure 10. Colon cancer example 1: (a) H&E stained histopathology image. (b) 27×27 patches centered around all marked nuclei. (c) Ground truth: Patches that belong to the class epithelial. (d) Attention heatmap: Every patch from (b) multiplied by its attention weight. (e) Instance+max heatmap: Every patch from (b) multiplied by its score from the Instance+max model. We rescaled the attention weights and instance scores using $a'_k = a_k - \min(\mathbf{a}) / (\max(\mathbf{a}) - \min(\mathbf{a}))$.

Experiments: Colon Cancer




Figure 11. Colon cancer example 2: (a) H&E stained histopathology image. (b) 27×27 patches centered around all marked nuclei. (c) Ground truth: Patches that belong to the class epithelial. (d) Attention heatmap: Every patch from (b) multiplied by its attention weight. (e) Instance+max heatmap: Every patch from (b) multiplied by its score from the Instance+max model. We rescaled the attention weights and instance scores using $a'_k = a_k - \min(\mathbf{a}) / (\max(\mathbf{a}) - \min(\mathbf{a}))$.

Experiments: Colon Cancer




Figure 12. Colon cancer example 3: (a) H&E stained histopathology image. (b) 27×27 patches centered around all marked nuclei. (c) Ground truth: Patches that belong to the class epithelial. (d) Attention heatmap: Every patch from (b) multiplied by its attention weight. (e) Instance+max heatmap: Every patch from (b) multiplied by its score from the Instance+max model. We rescaled the attention weights and instance scores using $a'_k = a_k - \min(\mathbf{a}) / (\max(\mathbf{a}) - \min(\mathbf{a}))$.

Conclusion




Deep MIL: a flexible approach to cope with large images.

Attention mechanism: interpretable and learnable MIL pooling.

Next step: Application to **whole-slide classification**.

Next step: **taking into account spatial dependencies** (non i.i.d. instances).

Conclusion



Deep MIL: a flexible approach to cope with large images.




Attention mechanism: interpretable and learnable MIL pooling.

Next step: Application to whole-slide classification.

Next step: taking into account spatial dependencies (non i.i.d. instances).



Conclusion




Deep MIL: a flexible approach to cope with large images.

Attention mechanism: **interpretable** and **learnable** MIL pooling.


Next step: Application to **whole-slide classification**.

Next step: **taking into account spatial dependencies** (non i.i.d. instances).

Conclusion



Deep MIL: a flexible approach to cope with large images.



Attention mechanism: **interpretable** and **learnable** MIL pooling.

Next step: Application to **whole-slide classification**.

Next step: **taking into account spatial dependencies (non i.i.d. instances)**.



Conclusion

Deep MIL: a flexible approach to cope with large images.

Attention mechanism: **interpretable** and **learnable** MIL pooling.

Next step: Application to **whole-slide classification**.

Next step: **taking into account spatial dependencies (non i.i.d. instances)**.

Code on github:

<https://github.com/AMLab-Amsterdam/AttentionDeepMIL>

Contact:

ilse.maximilian@gmail.com

jakubmkt@gmail.com



The research conducted by Maximilian Ilse was funded by the Nederlandse Organisatie voor Wetenschappelijk Onderzoek (Grant DLMedia: Deep Learning for Medical Image Analysis).



The research conducted by Jakub M. Tomczak was funded by the European Commission within the Marie Skłodowska-Curie Individual Fellowship (Grant No. 702666, "Deep learning and Bayesian inference for medical imaging").