


Generative Modeling by Estimating Gradients of the Data Distribution

Yang Song, Stefano Ermon

David Zimmerer
Medical Image Analysis (#MIA-san-mia)
DKFZ



dkfz.


GERMAN
CANCER RESEARCH CENTER
IN THE HELMHOLTZ ASSOCIATION



Research for a Life without Cancer


Generative modeling

Generative modeling




GANs

Generative modeling




GANs




VAEs


Generative modeling



GANs




VAEs




Flows


Generative modeling



GANs




VAEs




Flows

...


Generative modeling



GANs



VAEs




Flows

...


implicit

explicit


Generative modeling



GANs



VAEs



Flows

...

implicitly


explicitly

"learn" $p(x)$

“New” Idea:


Generative Modeling by Estimating Gradients of the Data Distribution

“New” Idea:
Generative Modeling by Estimating Gradients of the Data Distribution





Instead of learning the data distribution directly...

“New” Idea:
Generative Modeling by Estimating Gradients of the Data Distribution



...we learn the gradients of the data distribution

“New” Idea: Generative Modeling by Estimating Gradients of the Data Distribution



Score matching

- [1] A. Hyvärinen. Estimation of non-normalized statistical models by score matching. Journal of Machine Learning Research, 6(Apr):695–709, 2005.

Score matching

→ $\nabla_{\mathbf{x}} \log p(\mathbf{x})$ i.e. the Gradient of the Data Distribution a.k.a score

- [1] A. Hyvärinen. Estimation of non-normalized statistical models by score matching. Journal of Machine Learning Research, 6(Apr):695–709, 2005.

Score matching

→ $\nabla_{\mathbf{x}} \log p(\mathbf{x})$ i.e. the Gradient of the Data Distribution a.k.a score

Score matching^[1]:

$$\frac{1}{2} \mathbb{E}_{p_{\text{data}}} [\|\mathbf{s}_{\boldsymbol{\theta}}(\mathbf{x}) - \nabla_{\mathbf{x}} \log p_{\text{data}}(\mathbf{x})\|_2^2]$$

[1] A. Hyvärinen. Estimation of non-normalized statistical models by score matching. Journal of Machine Learning Research, 6(Apr):695–709, 2005.

Score matching

→ $\nabla_{\mathbf{x}} \log p(\mathbf{x})$ i.e. the Gradient of the Data Distribution a.k.a score

Score matching^[1]:

$$\frac{1}{2} \mathbb{E}_{p_{\text{data}}} [\|\mathbf{s}_{\boldsymbol{\theta}}(\mathbf{x}) - \nabla_{\mathbf{x}} \log p_{\text{data}}(\mathbf{x})\|_2^2]$$

equivalent up to a constant to:

$$\mathbb{E}_{p_{\text{data}}(\mathbf{x})} \left[\text{tr}(\nabla_{\mathbf{x}} \mathbf{s}_{\boldsymbol{\theta}}(\mathbf{x})) + \frac{1}{2} \|\mathbf{s}_{\boldsymbol{\theta}}(\mathbf{x})\|_2^2 \right]$$

[1] A. Hyvärinen. Estimation of non-normalized statistical models by score matching. Journal of Machine Learning Research, 6(Apr):695–709, 2005.

Score matching

→ $\nabla_{\mathbf{x}} \log p(\mathbf{x})$ i.e. the Gradient of the Data Distribution a.k.a score

Score matching^[1]:

$$\frac{1}{2} \mathbb{E}_{p_{\text{data}}} [\|\mathbf{s}_{\boldsymbol{\theta}}(\mathbf{x}) - \nabla_{\mathbf{x}} \log p_{\text{data}}(\mathbf{x})\|_2^2]$$

equivalent up to a constant to:

$$\mathbb{E}_{p_{\text{data}}(\mathbf{x})} \left[\text{tr}(\nabla_{\mathbf{x}} \mathbf{s}_{\boldsymbol{\theta}}(\mathbf{x})) + \frac{1}{2} \|\mathbf{s}_{\boldsymbol{\theta}}(\mathbf{x})\|_2^2 \right]$$


→ So what's new ?




[1] A. Hyvärinen. Estimation of non-normalized statistical models by score matching. Journal of Machine Learning Research, 6(Apr):695–709, 2005.

Trivial Implementation (on MNIST)

Trivial Implementation (on MNIST)




Trivial Implementation (on MNIST)





Spoiler: Improved Results




Spoiler: Improved Results



Spoiler: Improved Results



Spoiler: Improved Results



What are the problems ?

What are the problems ?

1. No Support (everywhere)

What are the problems ?

1. No Support (everywhere)
i.e. $p(x)$ not defined and thus gradient not defined

What are the problems ?


1. No Support (everywhere)
i.e. $p(x)$ not defined and thus gradient not defined
→ Solution: Add Gaussian Noise

What are the problems ?

1. No Support (everywhere)
i.e. $p(x)$ not defined and thus gradient not defined
→ Solution: Add Gaussian Noise
2. Inaccurate score estimation in low density regions

What are the problems ?

1. No Support (everywhere)
i.e. $p(x)$ not defined and thus gradient not defined
→ Solution: Add Gaussian Noise
2. Inaccurate score estimation in low density regions




What are the problems ?

1. No Support (everywhere)
i.e. $p(x)$ not defined and thus gradient not defined

→ Solution: Add Gaussian Noise

2. Inaccurate score estimation in low density regions




→ Solution add noise at different magnitudes

(large noise: filling low density regions, small noise: fine-adjustments in high density regions)

How to sample:


How to sample:



Scores


$$s_{\theta}(\mathbf{x})$$

How to sample:



Scores


$$s_{\theta}(\mathbf{x})$$



Follow the scores


$$\tilde{\mathbf{x}}_{t+1} \leftarrow \tilde{\mathbf{x}}_t + \frac{\epsilon}{2} s_{\theta}(\tilde{\mathbf{x}}_t)$$

How to sample:



Scores

$$s_\theta(\mathbf{x})$$




Follow the scores

$$\tilde{\mathbf{x}}_{t+1} \leftarrow \tilde{\mathbf{x}}_t + \frac{\epsilon}{2} s_\theta(\tilde{\mathbf{x}}_t)$$




How to sample:




Scores

$$s_{\theta}(\mathbf{x})$$



Follow the scores


$$\tilde{\mathbf{x}}_{t+1} \leftarrow \tilde{\mathbf{x}}_t + \frac{\epsilon}{2} s_{\theta}(\tilde{\mathbf{x}}_t)$$



Follow noisy scores:
Langevin dynamics


$$\mathbf{z}_t \sim \mathcal{N}(0, I)$$
$$\tilde{\mathbf{x}}_{t+1} \leftarrow \tilde{\mathbf{x}}_t + \frac{\epsilon}{2} s_{\theta}(\tilde{\mathbf{x}}_t) + \sqrt{\epsilon} \mathbf{z}_t$$

How to sample:




Scores

$$s_{\theta}(\mathbf{x})$$



Follow the scores

$$\tilde{\mathbf{x}}_{t+1} \leftarrow \tilde{\mathbf{x}}_t + \frac{\epsilon}{2} s_{\theta}(\tilde{\mathbf{x}}_t)$$




Follow noisy scores:
Langevin dynamics

$$\mathbf{z}_t \sim \mathcal{N}(0, I)$$
$$\tilde{\mathbf{x}}_{t+1} \leftarrow \tilde{\mathbf{x}}_t + \frac{\epsilon}{2} s_{\theta}(\tilde{\mathbf{x}}_t) + \sqrt{\epsilon} \mathbf{z}_t$$



Approach

Approach



Results



Results: Qualitative



Results: Qualitative



Results: Quantitative

Model	Inception 	FID 
CIFAR-10 Unconditional		
PixelCNN [59]	4.60	65.93
PixelIQN [42]	5.29	49.46
EBM [12]	6.02	40.58
WGAN-GP [18]	$7.86 \pm .07$	36.4
MoLM [45]	$7.90 \pm .10$	18.9
SNGAN [36]	$8.22 \pm .05$	21.7
ProgressiveGAN [25]	$8.80 \pm .05$	-
NCSN (Ours)	$8.87 \pm .12$	25.32
CIFAR-10 Conditional		
EBM [12]	8.30	37.9
SNGAN [36]	$8.60 \pm .08$	25.5
BigGAN [6]	9.22	14.73

Results: Reproducible

→ NeurIPS 2019 - Reproducibility Challenge^[2]

[2] A. Matosevic. Reproducibility Challenge – Generative Modeling by Estimating Gradients of the Data Distribution, NeurIPS 2019 Reproducibility Challenge Blind Report, <https://openreview.net/forum?id=SkxCSTqG6H>

Results: Reproducible

→ NeurIPS 2019 - Reproducibility Challenge^[2]

Reproducible ?

[2] A. Matosevic. Reproducibility Challenge – Generative Modeling by Estimating Gradients of the Data Distribution, NeurIPS 2019 Reproducibility Challenge Blind Report, <https://openreview.net/forum?id=SkxCSTqG6H>

Results: Reproducible

→ NeurIPS 2019 - Reproducibility Challenge^[2]

Reproducible ?



[2] A. Matosevic. Reproducibility Challenge – Generative Modeling by Estimating Gradients of the Data Distribution, NeurIPS 2019 Reproducibility Challenge Blind Report, <https://openreview.net/forum?id=SkxCSTqG6H>

Results: Reproducible

→ NeurIPS 2019 - Reproducibility Challenge^[2]

Reproducible ?



Hyper-parameter insensitive ?

[2] A. Matosevic. Reproducibility Challenge – Generative Modeling by Estimating Gradients of the Data Distribution, NeurIPS 2019 Reproducibility Challenge Blind Report, <https://openreview.net/forum?id=SkxCSTqG6H>

Results: Reproducible

→ NeurIPS 2019 - Reproducibility Challenge^[2]

Reproducible ?



Hyper-parameter insensitive ?



[2] A. Matosevic. Reproducibility Challenge – Generative Modeling by Estimating Gradients of the Data Distribution, NeurIPS 2019 Reproducibility Challenge Blind Report, <https://openreview.net/forum?id=SkxCSTqG6H>

The End

