PetStore

23 October 2026

Implementation report

Four applications are deployed on App Service. Each one pulls its image from Azure Container Registry. Traffic Manager reports every endpoint Online, and the storefront is live on the UI hostname.

Document control

Product	PetStore – catalog, orders, and administration
Date	23 October 2026
Resource group	Petstore-Resource-Group
Subscription	Petstore subscription
App Service plan	ASP-PetstoreResourceGroup-9881 · Basic B3 · Central India
Registry	petstoreazurecontainerregistry.azurecr.io
Evidence	Running shop and Azure portal screenshots. Secret values are not printed.

Contents

01 What this project covers
02 How the pieces fit
03 Storefront
04 Customer orders
05 Administration
06 Azure Database for PostgreSQL
07 Azure Blob Storage
08 Azure Key Vault
09 Azure Container Registry
10 Azure App Service
11 Azure Traffic Manager

Deployed applications

Web app	Image pulled from the registry	State
product-service-web-app	product-service-image · port 8081	Running, endpoint Online
order-service-wep-app	order-service-image · port 8083	Running, endpoint Online
pet-service-web-app	pet-service-image · port 8082	Running, endpoint Online
petstoreui-web-app	petstore-ui-image · port 80	Running, shop live, endpoint Online

1. What this project covers

PetStore is a small shop in which every pet is a product for sale. A visitor can browse, filter, and open a pet without signing in. Buying, order history, and administration are signed-in flows. The browser talks to two APIs. A third service shares the same database and the same secret source.

Area	What is in place	Shown by
Storefront	Catalog, category chips, details, cart drawer, checkout	Figure 1, Figure 2
Customer account	Separate shop session, order history, logout	Figure 3

Area	What is in place	Shown by
Administration	Categories, pets with a required photo, all orders, delete	Figure 4, Figure 5, Figure 6
Database	Azure Database for PostgreSQL Flexible Server, database `petstore`	Figure 7, Figure 8
Images	Azure Blob Storage account `petstore`, container `pet-container`	Figure 9, Figure 10
Secrets	Key Vault `db-credentials-petstore`. No database password, connection string, or account key in application YAML	Figure 11, Figure 12
Container images	Azure Container Registry `petstoreazurecontainerregistry`. GitHub Actions pushes four images on every push to `main`	Figure 13, Figure 14, Figure 15, Figure 16
Hosting	Four Linux web apps deployed on plan `ASP-PetstoreResourceGroup-9881`, Basic B3, Central India. Each app pulls its image from the container registry. The live shop is Figure 22	Figure 17 through Figure 23
Routing	Four Traffic Manager profiles, routing method Priority. Online means that deployed app answered the health probe	Figure 24 through Figure 28

product-service

Port 8081. Pets for sale, categories, and image upload. Reads the database username and password, plus the blob connection string and account key, from Key Vault.

order-service

Port 8083. Register, login, checkout, and orders. Issues the JWT. Makes sure the admin account exists. Reads the database username and password from Key Vault.

pet-service

Port 8082. Pet API on the same database. Reads the database username and password from the same vault. The shop UI sells through the product service.

The React application runs on port 3000. Swagger is available at `http://localhost:8081/swagger-ui.html` and `http://localhost:8083/swagger-ui.html`.

2. How the pieces fit

The browser keeps the cart in local storage. Login is issued by the order service. The product service trusts the same JWT. Shop and admin sessions are stored separately, so signing in as a customer does not sign the administrator out.

Caller	Calls	For
Storefront and admin UI	product-service `:8081`	Categories, pets, photos
Storefront and admin UI	order-service `:8083`	Register, login, checkout, orders
All three services	Key Vault `db-credentials-petstore`	Database username and password
product-service	Blob container `pet-container`	Upload, replace, and delete pet photos
All three services	PostgreSQL `petstore-server-name`	Database `petstore`
GitHub Actions on `main`	Container Registry `petstoreazurecontainerregistry`	Build and store the four application images
App Service	Those four images	Public HTTPS sites for the shop and the three APIs
Traffic Manager	The App Service hostnames	DNS answer for an endpoint whose health probe is passing

Application accounts

These are shop accounts stored in the database. They are not the Azure or database secrets.

Username	Password	Role
demo	demo123	USER
admin	admin123	ADMIN

> On startup, Hibernate creates any missing tables (`ddl-auto: update`). The order service creates the admin account when that username is missing. It does not reset an existing admin password.

Sections 10 and 11 are the hosted form of this same layout. App Service runs the four images. Traffic Manager watches those hostnames and answers DNS with an endpoint that is Online.

3. Storefront

The public shop is the home page. There is no login wall. Category chips are built from the pets already loaded, so a guest can filter by All, Cat, Dog, or Parrot. Each card shows the photo, category, name, description, and price, with Details and Add to cart. A new pet cannot be saved without an image, which is why every card in the catalog has a photograph.

Add to cart asks a guest to sign in. For a signed-in shopper it opens the cart drawer on the same page. Checkout needs a shop login, then clears the cart and opens that customer's orders.




Figure 1. Storefront at `localhost:3000`. Twenty pets, category filters, and a signed-in shopper named amir. The header shows Cart and My account. There is no admin button on the shop.




Figure 2. Cart drawer after adding Dog7. Parrot 1 and Dog7 are listed with quantity controls. The total is $759.00 and Checkout stays on this page until the order is placed.

4. Customer orders

A signed-in customer opens My account and sees only their own orders. The page is a data grid with search, column controls, and paging. Columns are Order, Items, Total, Status, and Placed. Customers cannot delete an order from this page. Delete stays on the admin orders screen.




Figure 3. Account page for amir. Order #6 is two cats for $603.00. Order #2 is three pets for $1,199.00. Both are PLACED. Log out is in the account menu, not in the shop header.

5. Administration

Administration lives at `/admin` and uses its own session. The navigation is Categories, Pets, and Orders. The signed-in administrator in these screenshots is `admin`. View store returns to the public shop without clearing the admin session.

Categories

Categories are created here before they can be chosen on a pet. The screenshot shows Cat, Dog, and Parrot, which are the same chips on the storefront. Each row can be deleted. The grid has search, filters, density, and export.




Figure 4. Admin categories. Three categories are in use. The add form is on the same page.

Pets

The pet list is the catalog the shop sells. Columns are Photo, Name, Category, Description, Price, and Actions. Edit and Delete are on each row. A new pet requires a photo. Uploads go to `pet-container`. Replacing a photo deletes the previous blob. Deleting a pet deletes its blob as well.




Figure 5. Admin pets. Parrots and cats are listed with the photograph stored in Blob Storage, a category, a price, and Edit / Delete.

Orders

Administrators see every order, including the customer id. The same orders that appear on a customer's account page appear here, with an extra Customer column and a Delete action. Delete is allowed only for the

ADMIN role.




Figure 6. Admin orders. Orders #6 and #2 belong to customer 3. Order #1 belongs to customer 2. Each row can be deleted.

6. Azure Database for PostgreSQL

All three services use one database, `petstore`, on an Azure Database for PostgreSQL flexible server. The server is in the Petstore resource group and is Ready.

Setting	Value
Server	petstore-server-name
Endpoint	petstore-server-name.postgres.database.azure.com
Subscription	Petstore subscription · b5c67bf9-6f36-431b-82ea-a27d96f61190
Resource group	Petstore-Resource-Group
Location	Central India
PostgreSQL	16
Compute	Burstable B2s · 2 vCores · 4 GiB RAM · 32 GiB storage
Administrator login	amirrahi29
High availability	Not enabled. This tier is aimed at development and test.




Figure 7. Flexible server overview. Status is Ready. The JDBC URL in each service points at this endpoint and the `petstore` database.

pgAdmin is connected to that server as `amirrahi29`. The `public` schema holds the application tables: `categories`, `order_items`, `orders`, `pets`, `products`, `roles`, and `users`. The products query in the screenshot returns the same catalog the storefront shows, twenty rows, with category and description filled in.




Figure 8. Database `petstore` on server pet-postgres. `SELECT * FROM public.products ORDER BY id` returns the pets for sale.

> The database username and password are not written in the service YAML files. Each service reads the Key Vault secrets named `username` and `password` when it starts, then uses them as `spring.datasource.username` and `spring.datasource.password`.

7. Azure Blob Storage

Pet photographs are files in the storage account `petstore`. The application container is `pet-container`. A second container, `$logs`, is the storage log container and is not used by the shop.




Figure 9. Containers on storage account petstore. `pet-container` is the container named in the product service. Its anonymous access level in the portal is Blob.

Each upload is stored under a generated file name. The database keeps the blob URL. When the API returns a pet, it adds a short-lived shared access signature so the page can show the image. The expiry configured for that link is 60 minutes. The storage connection string and account key come from the Key Vault secrets `connection-string` and `account-key`. The account name, blob endpoint, container name, and SAS lifetime stay in configuration because they are not secret values.




Figure 10. `pet-container` holding the pet images. Twenty blobs are listed, created when pets were saved from the admin form.

8. Azure Key Vault

One vault holds the values the services used to keep in YAML. It is `db-credentials-petstore`, in Petstore-Resource-Group, location India South Central, on the Petstore subscription.




Figure 11. The vault in the subscription. One vault is in use for this project.

Four secrets are enabled. None of the secret values are stored in the repository.

Secret	Used as	Services
`username`	Database username	product, order, pet

Secret	Used as	Services
`password`	Database password	product, order, pet
`connection-string`	Blob Storage connection string	product
`account-key`	Blob Storage account key	product




Figure 12. Secrets on `db-credentials-petstore`. All four are Enabled. The portal confirms `account-key` was created.

How a service reads them

The vault URL is the only Key Vault setting in configuration: `https://db-credentials-petstore.vault.azure.net/`. At startup each service signs in with `DefaultAzureCredential` and copies the secret values into the Spring environment before the database connection is opened. On a developer machine that credential is an Azure CLI login for an account that has Get permission on secrets. No client secret is written into the YAML.

> A service that starts without an Azure login stops with a clear error: it could not read the secrets from this vault. It does not fall back to a password in a file. Sign in with `az login` as a principal that can get secrets, then start the jars again.

9. Azure Container Registry

Each application already has a Dockerfile. A push to the `main` branch of `amirrahi29/Petstore-Microservice-App-SpringBoot-React` builds all four images and stores them in Azure Container Registry. The registry login server is `petstoreazurecontainerregistry.azurecr.io`.

Setting	Value
Registry	petstoreazurecontainerregistry
Login server	petstoreazurecontainerregistry.azurecr.io
Resource group	Petstore-Resource-Group
Subscription	Petstore subscription · b5c67bf9-6f36-431b-82ea-a27d96f61190
Location	India South Central

Setting	Value
SKU	Basic. Provisioning succeeded on 22 October 2026.
Sign-in from GitHub	OpenID Connect. The workflow does not store a registry password.




Figure 13. Registry overview. One registry is in the Petstore resource group, on the Basic plan, in India South Central.

The repository name is the service name with `-image` on the end. Each repository has two tags: `latest`, and the git commit that built it.

Application	Image	Port inside the image
product-service	product-service-image	8081
order-service	order-service-image	8083
pet-service	pet-service-image	8082
petstore-ui	petstore-ui-image	80




Figure 14. Repositories in the registry: `order-service-image`, `pet-service-image`, `petstore-ui-image`, and `product-service-image`.




Figure 15. `pet-service-image` has two tags, `latest` and the commit `39c7d5d`. The same pair is published for the other three images.




Figure 16. Manifest for `petstoreazurecontainerregistry.azurecr.io/pet-service-image:39c7d5d9d16c5881d0ec3490cc54a14afa1dce4e`. The image is a Linux amd64 OCI index.

> The four workflow files live in `.github/workflows`. A push to `main` starts all of them. While a build is running, GitHub shows a yellow status on the commit. It turns green when that image is in the registry. Section 10 is the next step: each web app pulls its image from this registry and runs it.

10. Azure App Service

The four applications are deployed. App Service runs them as Linux web apps in `Petstore-Resource-Group`, on one plan, `ASP-PetstoreResourceGroup-9881`, in Central India. The plan is Basic, size B3, with one instance. Nothing is copied up as a jar or a zip. The publishing model is Container, so each app pulls its image from `petstoreazurecontainerregistry.azurecr.io`, the registry in section 9.

Deployed, in this report, means three things that the screenshots show together. The app list says Running. Each overview says runtime status Healthy, with the container image coming from that registry. A browser opened on the public hostname renders the shop. Figure 22 is that last check for the UI: the catalog, with photos and prices, is the deployed `petstore-ui-image`, not a local dev server.

Web app	What it serves	Port	Default hostname
product-service-web-app	Catalog, categories, pet photos	8081	product-service-web-app-g7bhexgnaje3brbw.centralindia-01.azurewebsites.net
order-service-wep-app	Register, login, checkout, orders	8083	order-service-wep-app-huhhatejg5adc0cr.centralindia-01.azurewebsites.net
pet-service-web-app	Pet API on the same database	8082	pet-service-web-app-adgkgbhmfchtfge0.centralindia-01.azurewebsites.net
petstoreui-web-app	Storefront and the admin UI	80	petstoreui-web-app-e3cahqc4bad5dthh.centralindia-01.azurewebsites.net

The order app keeps the name `order-service-wep-app` that was used when it was created. That spelling is the resource name and the start of its hostname. Each public URL is HTTPS on the default domain above.




Figure 17. The deployment list. All four web apps are Running in Central India, on plan `ASP-PetstoreResourceGroup-9881`, pricing tier Basic, subscription Petstore subscription. Running is the platform state after App Service has pulled the image and started the container.




Figure 18. `order-service-wep-app` is deployed. Publishing model Container, operating system Linux, runtime status Healthy. The container image line is the order image App Service pulled from the registry. The default domain is the public hostname in the table.




Figure 19. `pet-service-web-app` is deployed on the same plan and in the same region. Runtime status Healthy. Its container image is pulled from `petstoreazurecontainerregistry`, the same way as the order app.




Figure 20. `petstoreui-web-app` is deployed. Runtime status Healthy, Linux, publishing model Container. This is the app whose hostname serves Figure 22 and Figure 23. App Service pulled `petstore-ui-image` from the registry to run it.

Deployment Center is where the pull is recorded. On `product-service-web-app` the main container is named `product-service`. Source is Azure Container Registry, image `product-service-image`, tag `5a99f3e102c5612cccff9ac7330e5eb319ffe8db`, port 8081. Continuous deployment for that main container is turned on, so App Service pulls this image from the registry when the app runs. The order, pet, and UI apps are wired the same way: one main container, image from this registry, port 8083, 8082, or 80.




Figure 21. The ACR pull for the deployed product app. Source Azure Container Registry, image `product-service-image`, tag `5a99f3e102c5612cccff9ac7330e5eb319ffe8db`, port 8081. Continuous deployment for the main container is on.

Figure 22 is the deployed shop, opened in a browser. The address bar is the App Service hostname, so this page is `petstoreui-web-app` after it pulled `petstore-ui-image`. The catalog matches section 3: no login wall, category chips, prices, photos, Details, and Add to cart, with 20 pets. Figure 23 is the same deployment at `/admin/products`. The signed-in administrator is `admin`, and the grid has photo, category, price, edit, and delete. Together these two figures show that the container App Service pulled is the application, and that it is serving traffic.




Figure 22. The deployed UI, live. `https://petstoreui-web-app-e3cahqc4bad5dthh.centralindia-01.azurewebsites.net` serves the catalog from the image App Service pulled from ACR. Twenty pets, filters for All, Cat, Dog, and Parrot.




Figure 23. The same deployed app, path `/admin/products`, signed in as `admin`. Administration is running on App Service, on the image pulled from the registry.

The UI image is built with the product and order hostnames in the table, so the browser on this shop calls those App Service URLs. The three Java apps still read `db-credentials-petstore` before they open PostgreSQL. On App Service that read uses the app's managed identity. A Healthy runtime status means the container finished that startup and is serving its port.

> The App Service Health Check setting on these overview blades is Not Configured. That setting is separate from runtime status. Endpoint health for DNS routing is the Traffic Manager probe in the next section.

11. Azure Traffic Manager

Traffic Manager answers DNS for a profile name such as `ui-traffic-manager.trafficmanager.net`. The client then connects to the address it was given. The profile chooses an endpoint whose health probe is passing. These four profiles use Priority routing. Each profile holds one External endpoint, aimed at one of the deployed web apps in section 10.

Monitor status Online means that deployed app answered. The probe calls the App Service hostname over HTTPS, and Online is the result when the container App Service pulled from ACR is up. It is the same fact as Figure 22, read from the routing side: the UI endpoint is Online because `petstoreui-web-app` is deployed and serving. The product, order, and pet endpoints are Online for the same reason on their own apps.

Profile	DNS name	Endpoint	Web app
ui-traffic-manager	ui-traffic-manager.trafficmanager.net	ui-service	petstoreui-web-app
product-traffic-manager	product-traffic-manager.trafficmanager.net	product-service	product-service-web-app
petstore-traffic-manager	petstore-traffic-manager.trafficmanager.net	order-service	order-service-wep-app
pet-traffic-manager	pet-traffic-manager.trafficmanager.net	pet-service	pet-service-web-app

All four profiles sit in `Petstore-Resource-Group`, on the Petstore subscription, with status Enabled and routing method Priority. The endpoint type is External. Each one targets the default hostname of the deployed app, the hostname App Service published after the ACR pull. Each endpoint is Enabled, and Monitor status is Online. The probe is HTTPS on port 443, path `/`. A success response from that deployed app is what the portal marks Online. A failed probe stops that endpoint from being offered.




Figure 24. Four profiles in front of the four deployed apps. Status Enabled, routing method Priority, resource group Petstore-Resource-Group. Each profile's endpoint is one App Service hostname.




Figure 25. `pet-traffic-manager`. Endpoint `pet-service` is Enabled and Online. Online means the deployed `pet-service-web-app`, the container pulled from ACR, answered the health probe.




Figure 26. `petstore-traffic-manager`. Endpoint `order-service` is Enabled and Online. The probe reached the deployed `order-service-wep-app`.




Figure 27. `product-traffic-manager`. Endpoint `product-service` is Enabled and Online. The probe reached the deployed `product-service-web-app`, the app whose ACR image and tag are in Figure 21.




Figure 28. `ui-traffic-manager`. Endpoint `ui-service` is Enabled and Online. Online here is the deployed storefront: the same `petstoreui-web-app` that serves Figure 22.

Priority with a single Online endpoint sends every DNS answer for that profile to that app. A second endpoint, at a worse priority, would be used only after this one stopped passing the probe. These profiles do not have a second endpoint, and every app is in Central India, so the screenshots show a healthy route rather than a failover between regions.

The shop in Figure 22 and Figure 23 is opened on the App Service hostname. From there the page calls the product and order hostnames in section 10. Traffic Manager's record of this setup is the health of each endpoint, and DNS lookups of the `trafficmanager.net` names. The apps themselves answer on the default domains listed above. Those domains are what the probes check.