

AutoML Agent Interface

Select the dataset type

image



Choose a dataset

MNIST



Select a GROQ LLM Model

gemini-2.0-flash



Run AutoML Agent

Instructor Response

Configuration Plan

To effectively train models on the MNIST dataset, consider these configurations:

1. Data Preprocessing:
 - Input Format: For CNNs, reshape input to (N, 1, 28, 28) for PyTorch or (N, 28, 28, 1) for TensorFlow. For dense layers, flatten the input to (N, 784).
 - Normalization: Scale pixel values to the range [0, 1] by dividing by 255.0.
2. Model Architecture:
 - CNN: A simple CNN with convolutional layers, ReLU activations, max pooling, and fully connected layers is a good starting point. The provided VGGNet configuration can serve as inspiration.
 - Dense Network: A multi-layer perceptron with ReLU activations can also be used, especially for baseline performance.
3. Training Parameters:
 - Batch Size: 128 is a commonly used batch size.
 - Epochs: Train for at least 10 epochs, but monitor validation loss to prevent overfitting.
 - Optimizer: Adam or SGD with momentum are suitable optimizers.
 - Learning Rate: Start with 0.001 and adjust as needed.

4. Regularization:

- Dropout: Add dropout layers (e.g., rate of 0.5) to prevent overfitting.
- Batch Normalization: Use batch normalization after convolutional layers.

5. SMAC Configuration:

- Facade Type: MultiFidelityFacade is appropriate if considering varying training epochs or subsets of the data.
- Budget Settings: Set min_budget to a small number of epochs (e.g., 5) and max_budget to the desired maximum number of epochs (e.g., 50).
- Number of Workers: Set n_workers based on available CPU/GPU resources. Start with 4 and increase if possible.

6. SMAC Scenario Parameters:

- walltime_limit: Set a reasonable time limit (e.g., 3600 seconds).
- n_trials: Set the number of trials based on the budget and time constraints (e.g., 200).

Best parameters to set in the Configuration Space:

- Learning Rate: UniformFloat(lower=1e-4, upper=1e-1, log=True, default_value=1e-3)
- Batch Size: Categorical([32, 64, 128, 256], default_value=128)
- Optimizer: Categorical(["Adam", "SGD"], default_value="Adam")
- Number of Convolutional Layers: Integer(lower=2, upper=5, default_value=3)
- Dropout Rate: UniformFloat(lower=0.0, upper=0.5, default_value=0.2)
- Number of Epochs: Integer(lower=10, upper=50, default_value=20)

Scenario Plan

1. Data Preprocessing:

- Reshape input data to the appropriate format (N, 1, 28, 28) for CNNs or flatten to (N, 784) for dense layers.
- Normalize pixel values by dividing by 255.0.

2. Model Definition:

- Define a CNN or dense network using a configuration space. Allow SMAC to tune hyperparameters like the number of layers, filter sizes, and dropout rates.

3. SMAC Scenario Configuration:

- Use MultiFidelityFacade for multi-fidelity optimization to potentially reduce optimization time.
- Set min_budget and max_budget for the number of epochs.

- Set `n_workers` based on available resources.
 - Set `walltime_limit` and `n_trials` to control the optimization process.
4. Special Considerations:
- MNIST is a relatively simple dataset, so more complex models may not be necessary.
 - Ensure proper data loading and batching to avoid memory issues.
 - Monitor training and validation loss to prevent overfitting.

Train Function Plan

1. Define the Model:
 - The train function should take a configuration (hyperparameter settings) as input.
 - Based on the configuration, create the neural network model (CNN or dense network).
2. Data Loading and Preprocessing:
 - Load the MNIST dataset.
 - Apply the necessary preprocessing steps (reshaping, normalization).
 - Create data loaders for training and validation.
3. Training Loop:
 - Set up the optimizer (e.g., Adam, SGD) with the learning rate from the configuration.
 - Iterate over the training data for a specified number of epochs (potentially controlled by the budget in multi-fidelity optimization).
 - Calculate the loss and update the model parameters.
4. Validation:
 - After each epoch (or at the end of training), evaluate the model on the validation set.
 - Calculate the validation accuracy or loss.
5. Return Value:
 - Return the validation loss (or 1 - validation accuracy) as the performance metric for SMAC to minimize.

Generated Configuration Space Code

```
from ConfigSpace import ConfigurationSpace, UniformFloatHyperparameter, UniformInt

def get_configspace() -> ConfigurationSpace:
    """
    Defines the configuration space for hyperparameter optimization of a CNN model
```

Returns:

ConfigurationSpace: The configuration space object.

"""

```
cs = ConfigurationSpace()
```

Learning Rate

```
learning_rate = UniformFloatHyperparameter(  
    "learning_rate",  
    lower=1e-4,  
    upper=1e-1,  
    default_value=1e-3,  
    log=True  
)  
cs.add_hyperparameter(learning_rate)
```

Batch Size

```
batch_size = CategoricalHyperparameter(  
    "batch_size",  
    choices=[32, 64, 128, 256],  
    default_value=128  
)  
cs.add_hyperparameter(batch_size)
```

Optimizer

```
optimizer = CategoricalHyperparameter(  
    "optimizer",  
    choices=["Adam", "SGD"],  
    default_value="Adam"  
)  
cs.add_hyperparameter(optimizer)
```

Number of Convolutional Layers

```
num_conv_layers = UniformIntegerHyperparameter(  
    "num_conv_layers",  
    lower=2,  
    upper=5,  
    default_value=3  
)  
cs.add_hyperparameter(num_conv_layers)
```

Dropout Rate

```
dropout_rate = UniformFloatHyperparameter(  
    "dropout_rate",  
    lower=0.0,  
    upper=0.5,
```

```

        default_value=0.2
    )
    cs.add_hyperparameter(dropout_rate)

    # Number of Epochs
    num_epochs = UniformIntegerHyperparameter(
        "num_epochs",
        lower=10,
        upper=50,
        default_value=20
    )
    cs.add_hyperparameter(num_epochs)

    # Number of Filters for the first Conv Layer
    num_filters_first_layer = CategoricalHyperparameter(
        "num_filters_first_layer",
        choices=[16, 32, 64],
        default_value=32
    )
    cs.add_hyperparameter(num_filters_first_layer)

    use_batch_norm = CategoricalHyperparameter(
        "use_batch_norm",
        choices=[True, False],
        default_value=True
    )
    cs.add_hyperparameter(use_batch_norm)

    return cs

```

Generated Scenario Code

```

from smac import Scenario
from ConfigSpace import ConfigurationSpace

def generate_scenario(cs: ConfigurationSpace) -> Scenario:
    """
    Generates a SMAC scenario configuration for hyperparameter optimization of an

    Args:
        cs (ConfigurationSpace): The configuration space from which to sample conf

    Returns:
        Scenario: A SMAC Scenario object configured for the image dataset.

```

```
"""

scenario = Scenario(
    configspace=cs,
    name="HyperparameterOptimization",
    output_directory="./logs/gemini-2.0-flash_MNIST_20250617_182223",
    deterministic=False,
    n_trials=10,
    min_budget=1,
    max_budget=10,
    n_workers=1
)
return scenario
```

Generated Training Function Code

```
import torch
import torch.nn as nn
import torch.nn.functional as F
import torch.optim as optim
from ConfigSpace import Configuration
from typing import Any
import numpy as np
from math import sqrt
import pandas as pd

def train(cfg: Configuration, dataset: Any, seed: int) -> float:
    """
    Trains a CNN model on an image dataset using PyTorch.

    Args:
        cfg (Configuration): Hyperparameter configuration.
        dataset (Any): Dictionary containing 'X' (features) and 'y' (labels).
        seed (int): Random seed for reproducibility.

    Returns:
        float: Negative validation accuracy.
    """
    torch.manual_seed(seed)

    # Extract hyperparameters
    lr = cfg.get('learning_rate')
    batch_size = cfg.get('batch_size')
    optimizer_name = cfg.get('optimizer')
```

```
num_conv_layers = cfg.get('num_conv_layers')
dropout_rate = cfg.get('dropout_rate')
num_epochs = cfg.get('num_epochs')
num_filters_first_layer = cfg.get('num_filters_first_layer')
use_batch_norm = cfg.get('use_batch_norm')

# Device configuration
device = torch.device("cuda" if torch.cuda.is_available() else "cpu")

# Data preparation
X, y = dataset['X'], dataset['y']

# Reshape and normalize data
if isinstance(X, pd.DataFrame):
    X = X.values
if isinstance(y, pd.Series):
    y = y.values

batch_size = int(batch_size)
if not isinstance(batch_size, int) or batch_size <= 0:
    raise ValueError(f"batch_size should be a positive integer value, but got

if len(X.shape) == 2:
    n_features = X.shape[1]
    height = width = int(sqrt(n_features))
    if height * height != n_features:
        raise ValueError("Input is not a square image")
    X = X.reshape(-1, 1, height, width)
elif len(X.shape) == 3:
    X = X.reshape(-1, 1, X.shape[1], X.shape[2])
elif len(X.shape) == 4:
    pass # Assuming (N, C, H, W) or (N, H, W, C)
else:
    raise ValueError("Invalid input shape")

X = X.astype(np.float32) / 255.0
y = y.astype(np.int64)

X = torch.tensor(X, device=device)
y = torch.tensor(y, device=device)

# Split into training and validation (80/20 split)
train_size = int(0.8 * len(X))
X_train, X_val = X[:train_size], X[train_size:]
y_train, y_val = y[:train_size], y[train_size:]
```

```

train_dataset = torch.utils.data.TensorDataset(X_train, y_train)
val_dataset = torch.utils.data.TensorDataset(X_val, y_val)

train_loader = torch.utils.data.DataLoader(train_dataset, batch_size=batch_size)
val_loader = torch.utils.data.DataLoader(val_dataset, batch_size=batch_size, s

# Model definition
class CNN(nn.Module):
    def __init__(self, num_classes, num_conv_layers, dropout_rate, num_filters
        super(CNN, self).__init__()
        self.conv_layers = nn.ModuleList()
        self.batch_norm_layers = nn.ModuleList() # Batch norm layers list

        in_channels = 1 # Assuming grayscale images
        num_filters = num_filters_first_layer

        for i in range(num_conv_layers):
            self.conv_layers.append(nn.Conv2d(in_channels, num_filters, kernel
            if use_batch_norm:
                self.batch_norm_layers.append(nn.BatchNorm2d(num_filters)) #
            in_channels = num_filters
            num_filters = min(num_filters * 2, 128) # Increase filters with e

        self.pool = nn.MaxPool2d(2, 2)
        self.dropout = nn.Dropout(dropout_rate)

        # Calculate the size of the flattened layer after convolutions
        self.flattened_size = self._calculate_flattened_size(1, X.shape[2], X.

        self.fc1 = nn.Linear(self.flattened_size, 128) # Reduced FC layer siz
        self.fc2 = nn.Linear(128, num_classes)

        self.use_batch_norm = use_batch_norm

    def _calculate_flattened_size(self, in_channels, height, width, use_batch_
        # Simulate the convolutional layers to determine the output size
        x = torch.randn(1, in_channels, height, width)
        with torch.no_grad():
            for i, conv in enumerate(self.conv_layers):
                x = F.relu(conv(x))
                if use_batch_norm and i < len(self.batch_norm_layers):
                    x = self.batch_norm_layers[i](x) # Apply batch norm if en
                x = self.pool(x)
        return x.view(1, -1).size(1)

```



```

def forward(self, x):
    for i, conv in enumerate(self.conv_layers):
        x = F.relu(conv(x))
        if self.use_batch_norm and i < len(self.batch_norm_layers):
            x = self.batch_norm_layers[i](x) # Apply batch norm if enable
        x = self.pool(x)
    x = torch.flatten(x, 1)
    x = self.dropout(x)
    x = F.relu(self.fc1(x))
    x = self.fc2(x)
    return x

model = CNN(len(torch.unique(y)), num_conv_layers, dropout_rate, num_filters_f

# Optimizer
if optimizer_name == "Adam":
    optimizer = optim.Adam(model.parameters(), lr=lr)
elif optimizer_name == "SGD":
    optimizer = optim.SGD(model.parameters(), lr=lr, momentum=0.9)
else:
    raise ValueError(f"Unknown optimizer: {optimizer_name}")

# Loss function
criterion = nn.CrossEntropyLoss()

# Training loop
for epoch in range(num_epochs):
    model.train()
    for batch_idx, (data, target) in enumerate(train_loader):
        optimizer.zero_grad()
        output = model(data)
        loss = criterion(output, target)
        loss.backward()
        optimizer.step()

# Validation
model.eval()
correct = 0
total = 0
with torch.no_grad():
    for data, target in val_loader:
        output = model(data)
        _, predicted = torch.max(output.data, 1)
        total += target.size(0)
        correct += (predicted == target).sum().item()

```

```
accuracy = correct / total  
print(f"Validation Accuracy: {accuracy:.4f}")  
  
return -accuracy
```

AutoML Agent setup complete!

Loss Value

-0.9873333333333333

Starting Optimization Process

Starting Optimization Process

Prompts Used

▼ {

"config" :

```
"""Generate a production-grade Python configuration space for machine learning
hyperparameter optimization with the following STRICT requirements:"""
```

```
---
```

```
### **Function signature** must be:
```

```
```python
from ConfigSpace import ConfigurationSpace, UniformFloatHyperparameter,
UniformIntegerHyperparameter, CategoricalHyperparameter
def get_configspace() -> ConfigurationSpace:
```
```

```
---
```

```
### **Configuration Space Requirements:**
```

```
* The configuration space must be appropriate for the dataset type and
characteristics:
```

```
    * Dataset Description: `This is an image dataset.`
```

```
Number of classes: 10
```

```
Class distribution:
```

```
1      6742
```

```
7      6265
```

```
3      6131
```

```
2      5958
```

```
9      5949
```

```
0      5923
```

```
6      5918
```

```
8      5851
```

```
4      5842
```

```
5      5421
```

```
Name: count, dtype: int64
```

```
Image Data Handling Requirements:
```

```
1. Input Format Requirements:
```

- For CNN models: Input must be in (batch, channels, height, width) format
- For dense/linear layers: Input should be flattened

```
2. Data Processing Steps:
```

```
    a) For flattened input (2D):
```

- Calculate dimensions: height = width = int(sqrt(n_features))
- Verify square dimensions: height * height == n_features
- Reshape to (N, 1, H, W) for CNNs

```
    b) For 3D input (N, H, W):
```

- Add channel dimension: reshape to (N, 1, H, W)

- c) For 4D input:
 - Verify channel order matches framework requirements

3. Framework-Specific Format:

- PyTorch: (N, C, H, W)
- TensorFlow: (N, H, W, C)
- Convert between formats if necessary

4. Normalization:

- Scale pixel values to [0, 1] by dividing by 255.0
- Or standardize to mean=0, std=1

* Recommended Configuration based on the planner:

* `To effectively train models on the MNIST dataset, consider these configurations:

1. Data Preprocessing:

- * Input Format: For CNNs, reshape input to (N, 1, 28, 28) for PyTorch or (N, 28, 28, 1) for TensorFlow. For dense layers, flatten the input to (N, 784).
- * Normalization: Scale pixel values to the range [0, 1] by dividing by 255.0.

2. Model Architecture:

- * CNN: A simple CNN with convolutional layers, ReLU activations, max pooling, and fully connected layers is a good starting point. The provided VGGNet configuration can serve as inspiration.
- * Dense Network: A multi-layer perceptron with ReLU activations can also be used, especially for baseline performance.

3. Training Parameters:

- * Batch Size: 128 is a commonly used batch size.
- * Epochs: Train for at least 10 epochs, but monitor validation loss to prevent overfitting.
- * Optimizer: Adam or SGD with momentum are suitable optimizers.
- * Learning Rate: Start with 0.001 and adjust as needed.

4. Regularization:

- * Dropout: Add dropout layers (e.g., rate of 0.5) to prevent overfitting.
- * Batch Normalization: Use batch normalization after convolutional layers.

5. SMAC Configuration:

- * Facade Type: MultiFidelityFacade is appropriate if considering varying training epochs or subsets of the data.
- * Budget Settings: Set min_budget to a small number of epochs (e.g., 5) and max_budget to the desired maximum number of epochs (e.g., 50).

- * **Number of Workers:** Set `n_workers` based on available CPU/GPU resources. Start with 4 and increase if possible.

6. SMAC Scenario Parameters:

- * `walltime_limit`: Set a reasonable time limit (e.g., 3600 seconds).
- * `n_trials`: Set the number of trials based on the budget and time constraints (e.g., 200).

Best parameters to set in the Configuration Space:

- * **Learning Rate:** `UniformFloat(lower=1e-4, upper=1e-1, log=True, default_value=1e-3)`
- * **Batch Size:** `Categorical([32, 64, 128, 256], default_value=128)`
- * **Optimizer:** `Categorical(["Adam", "SGD"], default_value="Adam")`
- * **Number of Convolutional Layers:** `Integer(lower=2, upper=5, default_value=3)`
- * **Dropout Rate:** `UniformFloat(lower=0.0, upper=0.5, default_value=0.2)`
- * **Number of Epochs:** `Integer(lower=10, upper=50, default_value=20)``

- * The configuration space **must** include:

- * Appropriate hyperparameter ranges based on the dataset characteristics
- * Reasonable default values
- * Proper hyperparameter types (continuous, discrete, categorical)
- * Conditional hyperparameters if needed
- * Proper bounds and constraints

- * **Best Practices:**

- * Use meaningful hyperparameter names
- * Include proper documentation for each hyperparameter
- * Consider dataset size and complexity when setting ranges
- * Ensure ranges are not too narrow or too wide
- * Add proper conditions between dependent hyperparameters

- * **Common Hyperparameters to Consider:**

- * Learning rate (if applicable)
- * Model-specific hyperparameters
- * Regularization parameters
- * Architecture parameters
- * Optimization parameters

Output Format:

- * Return **only** the ``get_configspace()`` function
- * Include necessary imports
- * No example usage or additional code
- * The function must be self-contained and executable

```
---

### **Error Prevention:**

* Ensure all hyperparameter names are valid Python identifiers
* Verify that all ranges and bounds are valid
* Check that conditional hyperparameters are properly defined
* Validate that default values are within the specified ranges

---

### **Example Structure:**

```python
def get_configspace() -> ConfigurationSpace:
 cs = ConfigurationSpace()

 # Add hyperparameters
 learning_rate = UniformFloatHyperparameter(
 "learning_rate", lower=1e-4, upper=1e-1, default_value=1e-2, log=True
)
 cs.add_hyperparameter(learning_rate)

 # Add more hyperparameters...

 return cs
```

---

**Reminder:** The output must be limited to:
* Valid `import` statements
* A single `get_configspace()` function that returns a properly configured `ConfigurationSpace` object
* No additional code or explanations"
```

"scenario" :

****Generate a production-grade Python scenario configuration for SMAC hyperparameter optimization with the following STRICT requirements:****

**Function signature must be:**

```
```python
from smac import Scenario
from ConfigSpace import ConfigurationSpace
def generate_scenario(cs: ConfigurationSpace) -> Scenario:
```
```

**Scenario Configuration Requirements:**

- * The scenario **must** be optimized for the dataset characteristics:
- * Dataset Description: `This is an image dataset.

Number of classes: 10

Class distribution:

| | |
|---|------|
| 1 | 6742 |
| 7 | 6265 |
| 3 | 6131 |
| 2 | 5958 |
| 9 | 5949 |
| 0 | 5923 |
| 6 | 5918 |
| 8 | 5851 |
| 4 | 5842 |
| 5 | 5421 |

Name: count, dtype: int64

Image Data Handling Requirements:

1. Input Format Requirements:

- For CNN models: Input must be in (batch, channels, height, width) format
- For dense/linear layers: Input should be flattened

2. Data Processing Steps:

a) For flattened input (2D):

- Calculate dimensions: height = width = int(sqrt(n_features))
- Verify square dimensions: height * height == n_features
- Reshape to (N, 1, H, W) for CNNs

b) For 3D input (N, H, W):

- Add channel dimension: reshape to (N, 1, H, W)

c) For 4D input:

- Verify channel order matches framework requirements

3. Framework-Specific Format:

- PyTorch: (N, C, H, W)
- TensorFlow: (N, H, W, C)
- Convert between formats if necessary

4. Normalization:

- Scale pixel values to [0, 1] by dividing by 255.0
- Or standardize to mean=0, std=1

* The scenario **must** include:

- * Appropriate budget settings (min_budget, max_budget)
- * Optimal number of workers for parallelization
- * Reasonable walltime and CPU time limits
- * Proper trial resource constraints
- * Appropriate number of trials

* **Best Practices:**

- * Set deterministic=False for better generalization
- * Use multi-fidelity optimization when appropriate
- * Configure proper output directory structure
- * Set appropriate trial resource limits
- * Enable parallel optimization when possible

* **Resource Management:**

- * Set appropriate memory limits for trials
- * Configure proper walltime limits
- * Enable parallel processing when beneficial
- * Consider dataset size for budget settings

Available Parameters:

configspace : ConfigurationSpace

The configuration space from which to sample the configurations.

name : str | None, defaults to None

The name of the run. If no name is passed, SMAC generates a hash from the meta data.

Specify this argument to identify your run easily.

output_directory : Path, defaults to Path("smac3_output")

The directory in which to save the output. The files are saved in ``./output_directory/name/seed``.

deterministic : bool, defaults to False

If deterministic is set to true, only one seed is passed to the target function.

Otherwise, multiple seeds (if `n_seeds` of the intensifier is greater than 1) are passed to the target function to ensure generalization.

`objectives` : str | list[str] | None, defaults to "cost"

The objective(s) to optimize. This argument is required for multi-objective optimization.

`crash_cost` : float | list[float], defaults to `np.inf`

Defines the cost for a failed trial. In case of multi-objective, each objective can be associated with a different cost.

`termination_cost_threshold` : float | list[float], defaults to `np.inf`

Defines a cost threshold when the optimization should stop. In case of multi-objective, each objective *must* be associated with a cost. The optimization stops when all objectives crossed the threshold.

`walltime_limit` : float, defaults to `np.inf`

The maximum time in seconds that SMAC is allowed to run.

`cputime_limit` : float, defaults to `np.inf`

The maximum CPU time in seconds that SMAC is allowed to run.

`trial_walltime_limit` : float | None, defaults to None

The maximum time in seconds that a trial is allowed to run. If not specified, no constraints are enforced. Otherwise, the process will be spawned by `pynisher`.

`trial_memory_limit` : int | None, defaults to None

The maximum memory in MB that a trial is allowed to use. If not specified, no constraints are enforced. Otherwise, the process will be spawned by `pynisher`.

`n_trials` : int, defaults to 100

The maximum number of trials (combination of configuration, seed, budget, and instance, depending on the task) to run.

`use_default_config`: bool, defaults to False.

If True, the configspace's default configuration is evaluated in the initial design.

For historic benchmark reasons, this is False by default.

Notice, that this will result in `n_configs + 1` for the initial design.

Respecting `n_trials`, this will result in one fewer evaluated configuration in the optimization.

`instances` : list[str] | None, defaults to None

Names of the instances to use. If None, no instances are used.

Instances could be dataset names, seeds, subsets, etc.

`instance_features` : dict[str, list[float]] | None, defaults to None

Instances can be associated with features. For example, meta data of the dataset (mean, var, ...) can be

```

    The surrogate (mean, var, ...) can be
    incorporated which are then further used to expand the training data of
    the surrogate model.
    min_budget : float | int | None, defaults to None
        The minimum budget (epochs, subset size, number of instances, ...) that
        is used for the optimization.
        Use this argument if you use multi-fidelity or instance optimization.
    max_budget : float | int | None, defaults to None
        The maximum budget (epochs, subset size, number of instances, ...) that
        is used for the optimization.
        Use this argument if you use multi-fidelity or instance optimization.
    seed : int, defaults to 0
        The seed is used to make results reproducible. If seed is -1, SMAC will
        generate a random seed.
    n_workers : int, defaults to 1
        The number of workers to use for parallelization. If `n_workers` is
        greather than 1, SMAC will use
        Dask to parallelize the optimization.

---

### **Output Format:**

* Return only the `generate_scenario(cs)` function
* Include necessary imports
* No example usage or additional code
* The function must be self-contained and executable

---

### **Error Prevention:**

* Ensure all parameters are within valid ranges
* Verify that resource limits are reasonable
* Check that budget settings are appropriate
* Validate that parallelization settings are correct
* Ensure the training function can be pickled for parallel processing

---

### **Example Structure:**

```python
def generate_scenario(cs: ConfigurationSpace) -> Scenario:
 scenario = Scenario(
 configspace=cs,
 name="HyperparameterOptimization",
 output_directory="/logs/gemini-2.0-flash-MNTST-20250617-182222" //this

```

```

 output_directory = './logs/gemini-2.0-flash_MNIST_20250617_182223' // this
is important and should not be changed
 deterministic=True,
 //other parameters based on the information
)
 return scenario
'''

Suggested Scenario Plan:

1. Data Preprocessing:
 * Reshape input data to the appropriate format (N, 1, 28, 28) for CNNs or
 flatten to (N, 784) for dense layers.
 * Normalize pixel values by dividing by 255.0.

2. Model Definition:
 * Define a CNN or dense network using a configuration space. Allow SMAC
 to tune hyperparameters like the number of layers, filter sizes, and dropout
 rates.

3. SMAC Scenario Configuration:
 * Use MultiFidelityFacade for multi-fidelity optimization to potentially
 reduce optimization time.
 * Set min_budget and max_budget for the number of epochs.
 * Set n_workers based on available resources.
 * Set walltime_limit and n_trials to control the optimization process.

4. Special Considerations:
 * MNIST is a relatively simple dataset, so more complex models may not be
 necessary.
 * Ensure proper data loading and batching to avoid memory issues.
 * Monitor training and validation loss to prevent overfitting.

Reminder: The output must be limited to:
* Valid `import` statements
* A single `generate_scenario(cs)` function that returns a properly configured
 `Scenario` object
* No additional code or explanations
* The output_directory should be "./logs/gemini-2.0-
 flash_MNIST_20250617_182223"
* Set the number of trials to 10 for sufficient exploration
* set the number of workers to 1
* do not set these parameters: walltime_limit, cputime_limit,
 trial_walltime_limit, trial_memory_limit"

```

```
crat_wattume_limit, crat_memory_limit=
```

```
"train_function" :
```

```
"""Generate a production-grade Python training function for machine learning
with the following STRICT requirements:"""
```

```

```

```
Function signature must be:
```

```
```python
from ConfigSpace import Configuration
from typing import Any
def train(cfg: Configuration, dataset: Any, seed: int) -> float:
```
```

```

```

```
Function Behavior Requirements:
```

```
* The function must handle the dataset properly:
 * Dataset Description: `This is an image dataset.
```

```
Number of classes: 10
```

```
Class distribution:
```

```
1 6742
7 6265
3 6131
2 5958
9 5949
0 5923
6 5918
8 5851
4 5842
5 5421
```

```
Name: count, dtype: int64
```

```
Image Data Handling Requirements:
```

```
1. Input Format Requirements:
```

- For CNN models: Input must be in (batch, channels, height, width) format
- For dense/linear layers: Input should be flattened

```
2. Data Processing Steps:
```

```
a) For flattened input (2D):
```

- Calculate dimensions: height = width = int(sqrt(n\_features))
- Verify square dimensions: height \* height == n\_features
- Reshape to (N, 1, H, W) for CNNs

```
b) For 3D input (N, H, W):
```

- Add channel dimension: reshape to (N, 1, H, W)

```
c) For 4D input:
```



- Verify channel order matches framework requirements

### 3. Framework-Specific Format:

- PyTorch: (N, C, H, W)
- TensorFlow: (N, H, W, C)
- Convert between formats if necessary

### 4. Normalization:

- Scale pixel values to [0, 1] by dividing by 255.0
- Or standardize to mean=0, std=1

```

* ConfigSpace Definition: `from ConfigSpace import ConfigurationSpace,
UniformFloatHyperparameter, UniformIntegerHyperparameter,
CategoricalHyperparameter, InCondition

def get_configspace() -> ConfigurationSpace:
 """
 Defines the configuration space for hyperparameter optimization of a CNN
 model.

 Returns:
 ConfigurationSpace: The configuration space object.
 """
 cs = ConfigurationSpace()

 # Learning Rate
 learning_rate = UniformFloatHyperparameter(
 "learning_rate",
 lower=1e-4,
 upper=1e-1,
 default_value=1e-3,
 log=True
)
 cs.add_hyperparameter(learning_rate)

 # Batch Size
 batch_size = CategoricalHyperparameter(
 "batch_size",
 choices=[32, 64, 128, 256],
 default_value=128
)
 cs.add_hyperparameter(batch_size)

 # Optimizer
 optimizer = CategoricalHyperparameter(
 "optimizer",
 choices=["Adam", "SGD"],

```

```
 default_value="Adam"
)
 cs.add_hyperparameter(optimizer)

 # Number of Convolutional Layers
 num_conv_layers = UniformIntegerHyperparameter(
 "num_conv_layers",
 lower=2,
 upper=5,
 default_value=3
)
 cs.add_hyperparameter(num_conv_layers)

 # Dropout Rate
 dropout_rate = UniformFloatHyperparameter(
 "dropout_rate",
 lower=0.0,
 upper=0.5,
 default_value=0.2
)
 cs.add_hyperparameter(dropout_rate)

 # Number of Epochs
 num_epochs = UniformIntegerHyperparameter(
 "num_epochs",
 lower=10,
 upper=50,
 default_value=20
)
 cs.add_hyperparameter(num_epochs)

 # Number of Filters for the first Conv Layer
 num_filters_first_layer = CategoricalHyperparameter(
 "num_filters_first_layer",
 choices=[16, 32, 64],
 default_value=32
)
 cs.add_hyperparameter(num_filters_first_layer)

 use_batch_norm = CategoricalHyperparameter(
 "use_batch_norm",
 choices=[True, False],
 default_value=True
)
 cs.add_hyperparameter(use_batch_norm)

 return cs
```

```

 * SMAC Scenario: `from smac import Scenario
from ConfigSpace import ConfigurationSpace

def generate_scenario(cs: ConfigurationSpace) -> Scenario:
 """
 Generates a SMAC scenario configuration for hyperparameter optimization of
 an image dataset.

 Args:
 cs (ConfigurationSpace): The configuration space from which to sample
 configurations.

 Returns:
 Scenario: A SMAC Scenario object configured for the image dataset.
 """

 scenario = Scenario(
 configspace=cs,
 name="HyperparameterOptimization",
 output_directory="./logs/gemini-2.0-flash_MNIST_20250617_182223",
 deterministic=False,
 n_trials=10,
 min_budget=1,
 max_budget=10,
 n_workers=1
)
 return scenario

```

- \* The function **must** accept a `dataset` dictionary with:
  - \* `dataset['X']`: feature matrix or input tensor
  - \* `dataset['y']`: label vector or label tensor
- \* The function **must** handle the configuration properly:
  - \* Access primitive values using `cfg.get('key')`
  - \* Handle all hyperparameters defined in the configuration space
  - \* Apply proper type conversion and validation
  - \* Handle conditional hyperparameters correctly
- \* **Model Requirements:**
  - \* Infer input and output dimensions dynamically
  - \* Follow data format requirements
  - \* Handle necessary data transformations
  - \* Implement proper model initialization
  - \* Use appropriate loss functions
  - \* Apply proper regularization

```
* Apply proper regularization
* Handle model-specific requirements

* **Training Requirements:**
* Implement proper training loop
* Handle batch processing
* Apply proper optimization
* Implement early stopping if needed
* Handle validation if required
* Return appropriate loss value

* **Performance Optimization Requirements:**
* Minimize memory usage and allocations
* Use vectorized operations where possible
* Avoid unnecessary data copying
* Optimize data loading and preprocessing
* Use efficient data structures
* Minimize CPU/GPU synchronization
* Implement efficient batch processing
* Use appropriate device placement (CPU/GPU)
* Optimize model forward/backward passes
* Minimize Python overhead

* **Code Optimization Requirements:**
* Keep code minimal and focused
* Avoid redundant computations
* Use efficient algorithms
* Minimize function calls
* Optimize loops and iterations
* Use appropriate data types
* Avoid unnecessary object creation
* Implement efficient error handling
* Use appropriate caching strategies
* The train function should be computational efficient

* **Best Practices:**
* Use proper error handling
* Implement proper logging
* Handle edge cases
* Ensure reproducibility
* Optimize performance
* Follow framework best practices

Frameworks:

Choose at least 2 of the following frameworks based on the dataset and
```

CHOOSE **one** of the following frameworks based on the dataset and requirements:

- \* **PyTorch**: For deep learning tasks
- \* **TensorFlow**: For deep learning tasks
- \* **scikit-learn**: For traditional ML tasks

---

### **Output Format:**

- \* Return **only** the `train()` function
- \* Include necessary imports
- \* No example usage or additional code
- \* The function must be self-contained and executable
- \* Code must be minimal and optimized for performance

---

### **Error Prevention:**

- \* Validate all inputs
- \* Handle missing or invalid hyperparameters
- \* Check data types and shapes
- \* Handle edge cases
- \* Implement proper error messages

---

### **Example Structure:**

```
```python
def train(cfg: Configuration, dataset: Any, seed: int) -> float:
    # Set random seed for reproducibility
    torch.manual_seed(seed)

    # Extract hyperparameters efficiently
    lr, bs = cfg.get('learning_rate'), cfg.get('batch_size')

    # Prepare data efficiently
    X, y = dataset['X'], dataset['y']

    # Initialize model with optimized parameters
    model = Model(X.shape[1], **cfg).to(device)

    # Optimized training loop
    for epoch in range(10):
        loss = train_epoch(model, X, y, lr, bs)
```

```
        return loss
    ...

---

**Reminder:** The output must be limited to:
* Valid `import` statements
* A single `train()` function that returns a float loss value
* No additional code or explanations
* Code must be optimized for performance and minimal in size
* Return negative loss/error since SMAC minimizes the objective
* For accuracy metrics, return negative accuracy (e.g. -accuracy)
* For error metrics, return the raw error value (e.g. mse, rmse)
* Ensure consistent sign convention across all metrics
* For tracking the progress add prints
    1. Define the Model:
        * The train function should take a configuration (hyperparameter
        settings) as input.
        * Based on the configuration, create the neural network model (CNN or
        dense network).

    2. Data Loading and Preprocessing:
        * Load the MNIST dataset.
        * Apply the necessary preprocessing steps (reshaping, normalization).
        * Create data loaders for training and validation.

    3. Training Loop:
        * Set up the optimizer (e.g., Adam, SGD) with the learning rate from the
        configuration.
        * Iterate over the training data for a specified number of epochs
        (potentially controlled by the budget in multi-fidelity optimization).
        * Calculate the loss and update the model parameters.

    4. Validation:
        * After each epoch (or at the end of training), evaluate the model on the
        validation set.
        * Calculate the validation accuracy or loss.

    5. Return Value:
        * Return the validation loss (or 1 - validation accuracy) as the
        performance metric for SMAC to minimize.
    "
}
```

[Download Generated Code and Prompts](#)

