

```

        square += odd;
    }

    return 0;
}

```

The `for` statement in this program initializes one variable (`square`), tests another (`i`), and increments a third (`odd`). `i` is the number to be squared, `square` is the square of `i`, and `odd` is the odd number that must be added to the current `square` to get the next square (allowing the program to compute consecutive squares without performing any multiplications).

linked lists ► 17.5

The tremendous flexibility of the `for` statement can sometimes be useful; we'll find it to be a great help when working with linked lists. The `for` statement can easily be misused, though, so don't go overboard. The `for` loop in `square3.c` would be a lot clearer if we rearranged its pieces so that the loop is clearly controlled by `i`.

## 6.4 Exiting from a Loop

We've seen how to write loops that have an exit point before the loop body (using `while` and `for` statements) or after it (using `do` statements). Occasionally, however, we'll need a loop with an exit point in the middle. We may even want a loop to have more than one exit point. The `break` statement makes it possible to write either kind of loop.

After we've examined the `break` statement, we'll look at a couple of related statements: `continue` and `goto`. The `continue` statement makes it possible to skip part of a loop iteration without jumping out of the loop. The `goto` statement allows a program to jump from one statement to another. Thanks to the availability of statements such as `break` and `continue`, the `goto` statement is rarely used.

### The `break` Statement

We've already discussed how a `break` statement can transfer control out of a `switch` statement. The `break` statement can also be used to jump out of a `while`, `do`, or `for` loop.

Suppose that we're writing a program that checks whether a number `n` is prime. Our plan is to write a `for` statement that divides `n` by the numbers between 2 and `n - 1`. We should break out of the loop as soon as any divisor is found; there's no need to try the remaining possibilities. After the loop has terminated, we can use an `if` statement to determine whether termination was premature (hence `n` isn't prime) or normal (`n` is prime):

```

for (d = 2; d < n; d++)
    if (n % d == 0)
        break;

```