

## 2.2 The General Form of a Simple Program

Let's take a closer look at `pun.c` and see how we can generalize it a bit. Simple C programs have the form

*directives*

```
int main(void)
{
    statements
}
```

In this template, and in similar templates elsewhere in this book, items printed in Courier would appear in a C program exactly as shown; items in *italics* represent text to be supplied by the programmer.

Notice how the braces show where `main` begins and ends. C uses `{` and `}` in much the same way that some other languages use words like `begin` and `end`. This illustrates a general point about C: it relies heavily on abbreviations and special symbols, one reason that C programs are concise (or—less charitably—cryptic).

### Q&A

Even the simplest C programs rely on three key language features: directives (editing commands that modify the program prior to compilation), functions (named blocks of executable code, of which `main` is an example), and statements (commands to be performed when the program is run). We'll take a closer look at these features now.

### Directives

Before a C program is compiled, it is first edited by a preprocessor. Commands intended for the preprocessor are called directives. Chapters 14 and 15 discuss directives in detail. For now, we're interested only in the `#include` directive.

The `pun.c` program begins with the line

```
#include <stdio.h>
```

headers ► 15.2

This directive states that the information in `<stdio.h>` is to be “included” into the program before it is compiled. `<stdio.h>` contains information about C's standard I/O library. C has a number of *headers* like `<stdio.h>`; each contains information about some part of the standard library. The reason we're including `<stdio.h>` is that C, unlike some programming languages, has no built-in “read” and “write” commands. The ability to perform input and output is provided instead by functions in the standard library.

Directives always begin with a `#` character, which distinguishes them from other items in a C program. By default, directives are one line long; there's no semicolon or other special marker at the end of a directive.