

Invertible Conditional GANs for image editing

published: 2016-11 NIPS 2016

authors: Computer Vision Center Barcelona, Spain

cGANs, where the introduction of external information allows to determine specific representations of the generated images. In this work, we evaluate encoders to inverse the mapping of a cGAN, ie., mapping a real image into a latent space and a conditional representation.

Contributions

1. Proposing lcGANs, composed of two crucial parts: an encoder and a cGAN.
2. Introducing an encoder in the conditional GAN frame work to compress a real image x into a latent representation z and conditional vector y .

This inversion would allow us to have a latent representation z from a real image x and, then, we would be able to explore the latent space by interpolating or adding variations on it, which would result in variations on the generated image x .

Generator:

$$x = G(z, y)$$

Inverted mapping:


$$(z, y) = E(x)$$

Our approach consists of training an encoder E once the cGAN has been trained. The encoder E is composed of two sub-encoders: E_z , which encodes an image to z, and E_y , which encodes an image to y.

Encoder:

$$L_{ez} = E_{z \sim p_z, y \sim p_y} \|z - E_z(G(z, y))\|_2^2$$

$$L_{ey} = E_{x, y \sim p_{data}} \|y - E_y(x)\|_2^2$$




Conditional position

The conditional information vector y are always concatenated in the filter dimension at the input level in generator. As for the discriminator, different authors insert y in different parts of the model. **We expect that the earlier y is positioned in the model the better since the model is allowed to have more learning interactions with y .**

Conditional sampling

There are two types of conditional information, y and y' . The first one is trivially sampled from $(x, y) \sim p_{data}$ and is used for training the discriminator $D(x, y)$ with a real image x and its associated label y . The second one is sampled from $y' \sim p_y$ and serves as input to the generator $G(z, y')$ along with a latent vector $z \sim p_z$ to generate an image x' . We will directly sample y from p_{data} .

Model architecture



Real image



aurora

Reconstructed images



Blonde



Bangs



Smile



Male

