



Sharif University of Technology
Department of Computer Engineering

Embedded System Design

StateCharts (Cont.) (8)

A. Ejlali

Moore and Mealy Automata


- **Moore:**
 - Output reactions are assigned to the nodes of an automaton
- **Mealy:**
 - Output reactions are assigned to the arcs of an automaton
 - Mixed Moore-Mealy automata are also possible.

Example: Moore

State PS=S1,NS;

Event e;

```
while(1){
  case(PS){
    S1:
      Turn_off(Heater);
      Turn_off(Cooler);
      e=Wait_for_event();
      if(e=='T<15') NS=S3;
      else if(e=='T>35') NS=S2; end if;
    S2:
      Turn_off(Heater);
      Turn_on(Cooler);
      e=Wait_for_event();
      if(e=='T<25') NS=S1; end if;
    S3:
      Turn_on(Heater);
      Turn_off(Cooler);
      e=Wait_for_event();
      if(e=='T>30') NS=S1; end if;
  }
  PS=NS;
}
```




Example: Mealy


State PS=S1,NS;

Event e;

```
while(1){  
  case(PS){  
    S1:  
      e=Wait_for_event();  
      if(e=='T<15')  
        NS=S3;  
        Turn_on(Heater);  
        Turn_off(Cooler);  
      else if(e=='T>35')  
        NS=S2;  
        Turn_off(Heater);  
        Turn_on(Cooler);  
      end if;  
    S2:  
      ...  
    S3:  
      ...  
  }  
  PS=NS;  
}
```




Mutually Dependent Assignments




Hysteresis

- Hysteresis is used to prevent **chattering** where the system would have rapid state transitions when the sensor input is close to the setpoint.



State Inertia

- Alternative solution is state inertia: a single threshold + state holding for at least T_{min} .
- Problem:
 - It does not have **time-scale invariance**
 - Time-Scale Invariance: time scaling at the input results in the same time scaling at the output.






Sharif University of Technology
Department of Computer Engineering

Embedded System Design

The MoC of Differential Equations (9)

A. Ejlali

Actor Models



- **Actor:** A box like that above, where the inputs are functions and the outputs are functions, is called an actor.

Actors

- Closely related to the concept of **functional** in mathematics.
- Can be used to model sensors, actuators, computation, and plant.

Example 1


- **Actor model of the plant in the air conditioning system.**

$$dE = mc dT$$

$$dT = \frac{1}{mc} dE$$

$$T = \frac{1}{mc} \int_{E_0}^{E_1} dE + T_0$$

$$T = \frac{1}{mc} \int_{t_0}^{t_1} P(t) dt + T_0$$



Example 2


- **Actor model of the plant in one dimensional velocity control.**

$$F = ma$$

$$F = m \frac{dv}{dt}$$

$$dv = \frac{1}{m} F dt$$

$$v = \frac{1}{m} \int_{t_0}^{t_1} F(t) dt + v_0$$



Key Point in Modeling a Plant

- The most important point in modelling a plant as an actor is to correctly determine the input(s) and output(s).
 - **Output** is what you desire to control.
 - **Input** is what you really give (apply) to the system from the viewpoint of the controller.