

SIMPLIFIED GUIDE

Farmer Marketplace Quick Start

A visual guide to the demo data, local startup, and the buyer, farmer, and admin journeys.

Current database status

Not reachable on this machine. PostgreSQL port 5432 refused the connection, and the local Docker daemon requires administrator access. The schema and deployment configuration are ready, but rows could not be inserted during this check.

Repository: /home/amisiespoir-07/Dev/singapore
Branch: main | Git remote: not configured

1. What is ready

Application

The FastAPI and Next.js code compiles. The PostGIS migration, Compose configuration, and four database integration tests are present.

Database today

Not running on this computer. Start Docker with administrator access, apply the migration, and load the seed before expecting the app to show records.

Harvest Hub

Phase 2 supply matching for farmers and buyers

Choose a demo role

Buyer demo

Open a request and match nearby supply

[Open interface](#)**Farmer demo**

Review and accept assigned orders

[Open interface](#)**Admin demo**

Moderate users, listings, and orders

[Open interface](#)

Illustrated from the current Next.js interface

These are illustrated screens based on the current UI and seed values. They are not evidence of a live database connection.

2. Dummy data included

Running the seed command resets marketplace tables and inserts the following demo records.

Users

Email	Role	Purpose
buyer@example.com	Buyer	Creates requests and orders
farmer.one@example.com	Farmer	Green Valley Farm
farmer.two@example.com	Farmer	Sunrise Fields
admin@example.com	Admin	Moderates users and listings

Farms and available produce

Farm	Location	Product	Available after sample orders	Price/kg
Green Valley	1.2921, 36.8219	Tomatoes	60 kg	0.70
Sunrise Fields	1.3102, 36.8127	Tomatoes	50 kg	0.75
Green Valley	1.2921, 36.8219	Onions	150 kg	0.45
Sunrise Fields	1.3102, 36.8127	Cabbage	60 kg	0.55

Expected match

The 100 kg tomato request is filled by 60 kg from Green Valley plus 40 kg from Sunrise Fields. Inventory is rechecked when the grouped order is created.

3. Start the application locally

Run these commands from the repository root.

```
sudo docker compose up -d database
.venv/bin/alembic upgrade head
.venv/bin/python -m api.scripts.seed_demo --yes-reset
```

Start the backend in terminal 1:

```
.venv/bin/uvicorn app.main:app --app-dir api --reload
```

Start the frontend in terminal 2:

```
cd apps/web
npm install
npm run dev
```

Open the application:

- Frontend: <http://localhost:3000>
- API documentation: <http://127.0.0.1:8000/docs>
- Database health: <http://127.0.0.1:8000/health>

Healthy result

The health endpoint should return: {"status":"ok","database":"connected"}

4. Buyer journey

Buyer request and grouped match

Open buyer request

Product

Tomatoes

Quantity

100 kg

Maximum price

0.80 / kg

Search radius

50 km

Pickup

1.3000, 36.8200

Find nearby supply

Complete match

100 of 100 kg allocated

60 kg from lot_demo_tomatoes

0.90 km | 0.70/kg | score 0.352

40 kg from lot_demo_tomatoes_sunrise

1.39 km | 0.75/kg | score 0.395

Create grouped order

Steps

- Choose Buyer demo.
- Confirm Tomatoes, 100 kg, maximum 0.80/kg, 50 km radius, and pickup coordinates.
- Select Find nearby supply. Review distance, price, score, and quantities.
- Select Create grouped order. The backend locks inventory, creates linked farmer orders, and marks the request ORDERED.

Do not reuse the request

A completed request cannot create a second grouped order. The API returns conflict status 409.

Generated from the repository on 2 October 2026

Page 5

5. Farmer and admin journeys

Farmer and administrator views

Farmer order queue

ord_demo_pending

PENDING

10 kg tomatoes

ord_demo_1

ACCEPTED

20 kg tomatoes

Accept order

Admin moderation

buyer@example.com

buyer | active

Change

farmer.one@example.com

farmer | active

Change

Tomatoes - lot_demo_tomatoes

60 kg | active

Change

Farmer

- Choose Farmer demo to see orders assigned to that farmer's lots.
- Accept a PENDING order. Only the owning farmer can accept it.
- Use the map panel to confirm the farm location.

Administrator

- Choose Admin demo to view all users, listings, and orders.
- Disable or enable buyer/farmer accounts.
- Deactivate or reactivate listings. Admin accounts cannot be disabled here.

6. Verify dummy data

```
curl http://127.0.0.1:8000/health  
.venv/bin/pytest api/tests
```

Optional SQL checks

```
SELECT count(*) FROM users; -- expected 4  
SELECT count(*) FROM farms; -- expected 2  
SELECT count(*) FROM lots; -- expected 4  
SELECT count(*) FROM buyer_requests; -- expected 1  
SELECT count(*) FROM orders; -- expected 2 before new UI actions  
SELECT PostGIS_Full_Version();
```

If it does not work

Symptom	Action
Connection refused on 5432	Start Docker/PostGIS and wait for its health check.
Docker permission denied	Use sudo or add your user to the Docker group, then sign out and back in.
Missing tables	Run .venv/bin/alembic upgrade head.
No products	Run the controlled seed command once.
Browser CORS error	Confirm the frontend URL is present in CORS_ORIGINS.

7. Safety notes

**Seed command
deletes data**

The --yes-reset option clears existing marketplace rows. Use it only for a demo or an empty development database.

- Set `ENABLE_DEMO_SEED=0` for online deployments.
- Never commit `DATABASE_URL`, passwords, or Vercel tokens.
- Use a separate preview database or branch for preview deployments.
- Run migrations before sending production traffic to a new backend version.
- Back up production data before destructive migrations.

You are ready when the health endpoint reports a connected database, the four integration tests pass, and all three demo roles load without errors.