

# Data624 - Homework7

Amit Kapoor

3/28/2021

## Contents

<b>Exercise 6.2</b>	<b>1</b>
(a) . . . . .	1
(b) . . . . .	2
(c) . . . . .	3
(d) . . . . .	5
(e) . . . . .	6
(f) . . . . .	14
<b>Exercise 6.3</b>	<b>14</b>
(a) . . . . .	15
(b) . . . . .	16
(c) . . . . .	17
(d) . . . . .	20
(e) . . . . .	20
(f) . . . . .	22

```
library(AppliedPredictiveModeling)
library(tidyverse)
library(caret)
library(naniar)
library(corrplot)
```

## Exercise 6.2

Developing a model to predict permeability (see Sect. 1.4) could save significant resources for a pharmaceutical company, while at the same time more rapidly identifying molecules that have a sufficient permeability to become a drug:

### (a)

Start R and use these commands to load the data.

The matrix fingerprints contains the 1,107 binary molecular predictors for the 165 compounds, while permeability contains permeability response.

```
data(permeability)
```

```
glimpse(permeability)
```

```
## num [1:165, 1] 12.52 1.12 19.41 1.73 1.68 ...
## - attr(*, "dimnames")=List of 2
```

```
## ..$ : chr [1:165] "1" "2" "3" "4" ...
## ..$ : chr "permeability"
nrow(permeability)

## [1] 165
glimpse(fingerprints)

## num [1:165, 1:1107] 0 0 0 0 0 0 0 0 0 0 ...
## - attr(*, "dimnames")=List of 2
## ..$ : chr [1:165] "1" "2" "3" "4" ...
## ..$ : chr [1:1107] "X1" "X2" "X3" "X4" ...
ncol(fingerprints)

## [1] 1107
nrow(fingerprints)

## [1] 165
```

In this data there were 165 unique compounds; 1107 molecular fingerprints were determined for each. A molecular fingerprint is a binary sequence of numbers that represents the presence or absence of a specific molecular sub-structure. The response is highly skewed, the predictors are sparse (15.5 percent are present), and many predictors are strongly associated

## (b)


The fingerprint predictors indicate the presence or absence of substructures of a molecule and are often sparse meaning that relatively few of the molecules contain each substructure. Filter out the predictors that have low frequencies using the `nearZeroVar` function from the `caret` package. How many predictors are left for modeling?

```
remove.features <- nearZeroVar(fingerprints)
X <- fingerprints[,-remove.features]
length(remove.features) %>% paste('columns are removed. ', dim(X)[2], ' predictors are left for modeling')

## [1] "719 columns are removed. 388 predictors are left for modeling."
```

We will now look into pairwise correlation above 0.90. We will then remove the predictors having correlation with cutoff 0.90.

```
plot(cor(X))
```



```
corr.90 <- findCorrelation(cor(X), cutoff=0.90)
X <- X[,-corr.90]
length(corr.90) %>% paste('columns having correlation 0.90 or more are removed. ', dim(X)[2], ' predictors are left for modeling')

## [1] "278 columns having correlation 0.90 or more are removed. 110 predictors are left for modeling"
```

(c)

Split the data into a training and a test set, pre-process the data, and tune a PLS model. How many latent variables are optimal and what is the corresponding resampled estimate of  $R^2$ ?

```
set.seed(786)
partition <- createDataPartition(permeability, p=0.70, list = FALSE)

# predictor
X.train <- X[partition,]
X.test <- X[-partition,]

# response
y.train <- permeability[partition,]
y.test <- permeability[-partition,]

# tune pls model
pls.fit <- train(x=X.train,
                 y=y.train,
                 method="pls",
                 metric="Rsquared",
                 tuneLength=10,
                 trControl=trainControl(method = "cv", verboseIter = TRUE),
                 preProcess=c("center", "scale")
                 )


## + Fold01: ncomp=10
## - Fold01: ncomp=10
```

```

## + Fold02: ncomp=10
## - Fold02: ncomp=10
## + Fold03: ncomp=10
## - Fold03: ncomp=10
## + Fold04: ncomp=10
## - Fold04: ncomp=10
## + Fold05: ncomp=10
## - Fold05: ncomp=10
## + Fold06: ncomp=10
## - Fold06: ncomp=10
## + Fold07: ncomp=10
## - Fold07: ncomp=10
## + Fold08: ncomp=10
## - Fold08: ncomp=10
## + Fold09: ncomp=10
## - Fold09: ncomp=10
## + Fold10: ncomp=10
## - Fold10: ncomp=10
## Aggregating results
## Selecting tuning parameters
## Fitting ncomp = 2 on full training set
pls.fit

## Partial Least Squares
##
## 117 samples
## 110 predictors
##
## Pre-processing: centered (110), scaled (110)
## Resampling: Cross-Validated (10 fold)
## Summary of sample sizes: 107, 105, 105, 106, 105, 105, ...
## Resampling results across tuning parameters:
##
##   ncomp  RMSE      Rsquared   MAE
##   1      11.63701  0.4469410   8.212073
##   2      11.19413  0.4761420   8.071552
##   3      11.33762  0.4704264   8.606355
##   4      11.37860  0.4705414   8.654649
##   5      11.49895  0.4629129   8.619412
##   6      11.77805  0.4598600   8.916459
##   7      12.31715  0.4351858   9.354903
##   8      13.33637  0.3873041   9.915650
##   9      13.96776  0.3398617  10.369458
##  10      14.81892  0.2927483  10.927883
##
## Rsquared was used to select the optimal model using the largest value.
## The final value used for the model was ncomp = 2.
# plot R-squared vs components
plot(pls.fit)

```



```
pls.fit$results %>%
  filter(ncomp == pls.fit$bestTune$ncomp) %>%
  select(ncomp, RMSE, Rsquared)
```

```
##   ncomp    RMSE Rsquared
## 1     2 11.19413 0.476142
```

After applying partial least square model, we see now that number of components 2 produces minimum RMSE (11.19413) and max  $R^2$  (0.476142).

(d)


Predict the response for the test set. What is the test set estimate of  $R^2$ ?

```
# Prediction from pls model
pls.prediction <- predict(pls.fit, X.test)
postResample(pred=pls.prediction, obs=y.test)
```

```
##      RMSE   Rsquared    MAE
## 12.4644848 0.4761679 9.4899066
```

```
# plot
plot(pls.prediction, y.test,
     main="Observed vs Predicted Permeability from PLS model (n=2)",
     xlab="Predicted Permeability",
     ylab="Observed Permeability")
abline(0,1,col="red")
```

## Observed vs Predicted Permeability from PLS model (n=2)



The plot shows the predicted vs observed permeability. The performance shows that the model fits the test data with RMSE as 12.464 and handles 48% of variability of data.

(e)

Try building other models discussed in this chapter. Do any have better predictive performance?

We will try to fit below 3 penalized models and compare the performance against the PLS model:

- Ridge regression: param tuned would be  $\lambda$  (0 to 1 by 0.1)
- Lasso regression: param tuned would be fraction (0 to 0.5 by 0.05)
- Elastic net: param tuned would be fraction and  $\lambda$  (0 to 1 by 0.1)

We will set the same seed for all the model.  $R^2$  matrix will be used for all the models evaluation.

```
set.seed(786)
# tune ridge model
ridge.fit <- train(x=X.train,
                  y=y.train,
                  method="ridge",
                  metric="Rsquared",
                  tuneGrid = data.frame(lambda=seq(0,1,by=0.1)),
                  trControl=trainControl(method = "cv",number=10),
                  preProcess=c("center", "scale")
                  )
```

```
ridge.fit
```


```
## Ridge Regression
##
## 117 samples
## 110 predictors
```

```
##
## Pre-processing: centered (110), scaled (110)
## Resampling: Cross-Validated (10 fold)
## Summary of sample sizes: 106, 105, 105, 105, 106, 106, ...
## Resampling results across tuning parameters:
##
##   lambda  RMSE          Rsquared    MAE
##   0.0     1.357937e+15  0.1142670  3.920028e+14
##   0.1     1.307559e+01  0.4010144  9.842309e+00
##   0.2     1.252247e+01  0.4426120  9.395175e+00
##   0.3     1.242482e+01  0.4613298  9.289079e+00
##   0.4     1.250699e+01  0.4711338  9.342353e+00
##   0.5     1.269048e+01  0.4765397  9.538792e+00
##   0.6     1.294065e+01  0.4795180  9.798881e+00
##   0.7     1.323834e+01  0.4810652  1.009804e+01
##   0.8     1.357141e+01  0.4817329  1.041612e+01
##   0.9     1.393148e+01  0.4818460  1.074867e+01
##   1.0     1.431243e+01  0.4816042  1.107811e+01
##
## Rsquared was used to select the optimal model using the largest value.
## The final value used for the model was lambda = 0.9.
```

```
ridge.fit$bestTune
```

```
##   lambda
## 10    0.9
```

```
plot(ridge.fit)
```



```
set.seed(786)
# tune lasso model
```

```
lasso.fit <- train(x=X.train,
                  y=y.train,
                  method="lasso",
                  metric="Rsquared",
                  tuneGrid = data.frame(fraction=seq(0,0.5,by=0.05)),
                  trControl=trainControl(method = "cv",number=10),
                  preProcess=c("center", "scale")
                )
```

```
lasso.fit
```


```
## The lasso
##
## 117 samples
## 110 predictors
##
## Pre-processing: centered (110), scaled (110)
## Resampling: Cross-Validated (10 fold)
## Summary of sample sizes: 106, 105, 105, 105, 106, 106, ...
## Resampling results across tuning parameters:
##
## fraction RMSE      Rsquared MAE
## 0.00      1.461272e+01      NaN  1.162243e+01
## 0.05      6.790543e+13  0.1342870  1.960261e+13
## 0.10      1.358019e+14  0.1181636  3.920262e+13
## 0.15      2.036983e+14  0.1158398  5.880263e+13
## 0.20      2.715947e+14  0.1210925  7.840264e+13
## 0.25      3.394911e+14  0.1281866  9.800265e+13
## 0.30      4.073875e+14  0.1372525  1.176027e+14
## 0.35      4.752840e+14  0.1420937  1.372027e+14
## 0.40      5.431804e+14  0.1485860  1.568027e+14
## 0.45      6.110768e+14  0.1515643  1.764027e+14
## 0.50      6.789732e+14  0.1534889  1.960027e+14
##
## Rsquared was used to select the optimal model using the largest value.
## The final value used for the model was fraction = 0.5.
```

```
lasso.fit$bestTune
```

```
## fraction
## 11      0.5
```

```
plot(lasso.fit)
```





```
set.seed(786)
# tune enet model
enet.fit <- train(x=X.train,
  y=y.train,
  method="enet",
  metric="Rsquared",
  tuneGrid = expand.grid(fraction=seq(0,1,by=0.1), lambda=seq(0,1,by=0.1)),
  trControl=trainControl(method = "cv",number=10),
  preProcess=c("center", "scale")
)

enet.fit
```

```
## Elasticnet
##
## 117 samples
## 110 predictors
##
## Pre-processing: centered (110), scaled (110)
## Resampling: Cross-Validated (10 fold)
## Summary of sample sizes: 106, 105, 105, 105, 106, 106, ...
## Resampling results across tuning parameters:
##
##   lambda  fraction  RMSE          Rsquared  MAE
##   0.0     0.0       1.461272e+01      NaN      1.162243e+01
##   0.0     0.1       1.358019e+14  0.1181636  3.920262e+13
##   0.0     0.2       2.715947e+14  0.1210925  7.840264e+13
##   0.0     0.3       4.073875e+14  0.1372525  1.176027e+14
##   0.0     0.4       5.431804e+14  0.1485860  1.568027e+14
##   0.0     0.5       6.789732e+14  0.1534889  1.960027e+14
```

##	0.0	0.6	8.147661e+14	0.1221618	2.352027e+14
##	0.0	0.7	9.505589e+14	0.1165096	2.744027e+14
##	0.0	0.8	1.086352e+15	0.1152884	3.136027e+14
##	0.0	0.9	1.222145e+15	0.1147560	3.528028e+14
##	0.0	1.0	1.357937e+15	0.1142670	3.920028e+14
##	0.1	0.0	1.461272e+01	NaN	1.162243e+01
##	0.1	0.1	1.174780e+01	0.4560660	8.547924e+00
##	0.1	0.2	1.128228e+01	0.4567847	7.903859e+00
##	0.1	0.3	1.112004e+01	0.4817382	7.952052e+00
##	0.1	0.4	1.116090e+01	0.4862802	8.144424e+00
##	0.1	0.5	1.134600e+01	0.4828980	8.356659e+00
##	0.1	0.6	1.177955e+01	0.4598641	8.755711e+00
##	0.1	0.7	1.215731e+01	0.4407769	9.117553e+00
##	0.1	0.8	1.248846e+01	0.4253997	9.380539e+00
##	0.1	0.9	1.278433e+01	0.4129785	9.609654e+00
##	0.1	1.0	1.307559e+01	0.4010144	9.842309e+00
##	0.2	0.0	1.461272e+01	NaN	1.162243e+01
##	0.2	0.1	1.199338e+01	0.4483824	8.885793e+00
##	0.2	0.2	1.122765e+01	0.4668804	7.867286e+00
##	0.2	0.3	1.118931e+01	0.4769086	7.966145e+00
##	0.2	0.4	1.115283e+01	0.4898601	8.109737e+00
##	0.2	0.5	1.121380e+01	0.4947837	8.266779e+00
##	0.2	0.6	1.139984e+01	0.4908794	8.403479e+00
##	0.2	0.7	1.171936e+01	0.4762297	8.700399e+00
##	0.2	0.8	1.201796e+01	0.4627385	8.984932e+00
##	0.2	0.9	1.228207e+01	0.4519167	9.204006e+00
##	0.2	1.0	1.252247e+01	0.4426120	9.395175e+00
##	0.3	0.0	1.461272e+01	NaN	1.162243e+01
##	0.3	0.1	1.205633e+01	0.4476169	9.023007e+00
##	0.3	0.2	1.119102e+01	0.4744092	7.890374e+00
##	0.3	0.3	1.124332e+01	0.4757735	7.952545e+00
##	0.3	0.4	1.120933e+01	0.4907321	8.130941e+00
##	0.3	0.5	1.126181e+01	0.4968430	8.297258e+00
##	0.3	0.6	1.136627e+01	0.5003137	8.413138e+00
##	0.3	0.7	1.161553e+01	0.4936135	8.587954e+00
##	0.3	0.8	1.192758e+01	0.4795287	8.851330e+00
##	0.3	0.9	1.219473e+01	0.4692966	9.094764e+00
##	0.3	1.0	1.242482e+01	0.4613298	9.289079e+00
##	0.4	0.0	1.461272e+01	NaN	1.162243e+01
##	0.4	0.1	1.208297e+01	0.4466454	9.083181e+00
##	0.4	0.2	1.119476e+01	0.4774469	7.892279e+00
##	0.4	0.3	1.126480e+01	0.4780977	7.928803e+00
##	0.4	0.4	1.129394e+01	0.4904605	8.172674e+00
##	0.4	0.5	1.137279e+01	0.4966126	8.369748e+00
##	0.4	0.6	1.147057e+01	0.5025237	8.493729e+00
##	0.4	0.7	1.168565e+01	0.5004571	8.645898e+00
##	0.4	0.8	1.198753e+01	0.4890132	8.867928e+00
##	0.4	0.9	1.226493e+01	0.4791725	9.117997e+00
##	0.4	1.0	1.250699e+01	0.4711338	9.342353e+00
##	0.5	0.0	1.461272e+01	NaN	1.162243e+01
##	0.5	0.1	1.209136e+01	0.4462680	9.103379e+00
##	0.5	0.2	1.118549e+01	0.4806604	7.867273e+00
##	0.5	0.3	1.129283e+01	0.4792371	7.917353e+00
##	0.5	0.4	1.139194e+01	0.4898455	8.240788e+00

##	0.5	0.5	1.151586e+01	0.4955996	8.480695e+00
##	0.5	0.6	1.162994e+01	0.5020806	8.615972e+00
##	0.5	0.7	1.184713e+01	0.5024430	8.783202e+00
##	0.5	0.8	1.214099e+01	0.4938037	9.002360e+00
##	0.5	0.9	1.243341e+01	0.4842337	9.278943e+00
##	0.5	1.0	1.269048e+01	0.4765397	9.538792e+00
##	0.6	0.0	1.461272e+01	NaN	1.162243e+01
##	0.6	0.1	1.208972e+01	0.4465556	9.099953e+00
##	0.6	0.2	1.117610e+01	0.4832594	7.837067e+00
##	0.6	0.3	1.132099e+01	0.4803361	7.909903e+00
##	0.6	0.4	1.150076e+01	0.4893696	8.306793e+00
##	0.6	0.5	1.167750e+01	0.4943419	8.599148e+00
##	0.6	0.6	1.182466e+01	0.5003983	8.756518e+00
##	0.6	0.7	1.205862e+01	0.5022022	8.956576e+00
##	0.6	0.8	1.236015e+01	0.4955709	9.217107e+00
##	0.6	0.9	1.266470e+01	0.4867716	9.515938e+00
##	0.6	1.0	1.294065e+01	0.4795180	9.798881e+00
##	0.7	0.0	1.461272e+01	NaN	1.162243e+01
##	0.7	0.1	1.208224e+01	0.4469407	9.086645e+00
##	0.7	0.2	1.116929e+01	0.4852350	7.804197e+00
##	0.7	0.3	1.135107e+01	0.4816836	7.908633e+00
##	0.7	0.4	1.162213e+01	0.4889297	8.384935e+00
##	0.7	0.5	1.185328e+01	0.4930018	8.721644e+00
##	0.7	0.6	1.204433e+01	0.4985102	8.912435e+00
##	0.7	0.7	1.230412e+01	0.5009427	9.182065e+00
##	0.7	0.8	1.261815e+01	0.4959287	9.488062e+00
##	0.7	0.9	1.293996e+01	0.4878788	9.795584e+00
##	0.7	1.0	1.323834e+01	0.4810652	1.009804e+01
##	0.8	0.0	1.461272e+01	NaN	1.162243e+01
##	0.8	0.1	1.206811e+01	0.4476790	9.063588e+00
##	0.8	0.2	1.116463e+01	0.4868431	7.768901e+00
##	0.8	0.3	1.138407e+01	0.4831699	7.912801e+00
##	0.8	0.4	1.174533e+01	0.4888881	8.465786e+00
##	0.8	0.5	1.204078e+01	0.4916686	8.854128e+00
##	0.8	0.6	1.227822e+01	0.4967980	9.113438e+00
##	0.8	0.7	1.257221e+01	0.4992868	9.435123e+00
##	0.8	0.8	1.290686e+01	0.4954399	9.766742e+00
##	0.8	0.9	1.325148e+01	0.4880354	1.009341e+01
##	0.8	1.0	1.357141e+01	0.4817329	1.041612e+01
##	0.9	0.0	1.461272e+01	NaN	1.162243e+01
##	0.9	0.1	1.204940e+01	0.4483771	9.035093e+00
##	0.9	0.2	1.116177e+01	0.4880689	7.731852e+00
##	0.9	0.3	1.142396e+01	0.4843389	7.918399e+00
##	0.9	0.4	1.186864e+01	0.4892936	8.542601e+00
##	0.9	0.5	1.223885e+01	0.4903595	8.995320e+00
##	0.9	0.6	1.252730e+01	0.4950438	9.333403e+00
##	0.9	0.7	1.285825e+01	0.4973112	9.693645e+00
##	0.9	0.8	1.322112e+01	0.4944646	1.005931e+01
##	0.9	0.9	1.359040e+01	0.4877176	1.040854e+01
##	0.9	1.0	1.393148e+01	0.4818460	1.074867e+01
##	1.0	0.0	1.461272e+01	NaN	1.162243e+01
##	1.0	0.1	1.202690e+01	0.4493657	9.004348e+00
##	1.0	0.2	1.116484e+01	0.4887120	7.708108e+00
##	1.0	0.3	1.147188e+01	0.4852200	7.927144e+00


```
## 1.0 0.4 1.199165e+01 0.4898434 8.619211e+00
## 1.0 0.5 1.244455e+01 0.4892267 9.161889e+00
## 1.0 0.6 1.278751e+01 0.4931700 9.565456e+00
## 1.0 0.7 1.315725e+01 0.4953460 9.964516e+00
## 1.0 0.8 1.355341e+01 0.4931895 1.035892e+01
## 1.0 0.9 1.394499e+01 0.4873878 1.072357e+01
## 1.0 1.0 1.431243e+01 0.4816042 1.107811e+01
##
```

```
## Rsquared was used to select the optimal model using the largest value.
## The final values used for the model were fraction = 0.6 and lambda = 0.4.
```

```
enet.fit$bestTune
```

```
## fraction lambda
## 51 0.6 0.4
```

```
plot(enet.fit)
```



```
set.seed(786)
summary(resamples(list(PLS=pls.fit, Ridge=ridge.fit, Lasso=lasso.fit, Elasticnet=enet.fit)))
```

```
##
## Call:
## summary.resamples(object = resamples(list(PLS = pls.fit, Ridge =
## ridge.fit, Lasso = lasso.fit, Elasticnet = enet.fit)))
##
## Models: PLS, Ridge, Lasso, Elasticnet
## Number of resamples: 10
##
## MAE
```

```
##           Min.    1st Qu.      Median      Mean      3rd Qu.
## PLS          4.394289  6.610297    8.479611 8.071552e+00  9.875764
## Ridge        6.210415  8.356001    9.765291 1.074867e+01 11.134924
## Lasso       25.491473 90.877616 2249.801725 1.960027e+14 77661.980610
## Elasticnet   5.054485  6.645612    8.115724 8.493729e+00  8.869695
##           Max. NA's
## PLS          1.075878e+01    0
## Ridge        1.920052e+01    0
## Lasso        1.960027e+15    0
## Elasticnet   1.586292e+01    0
##
## RMSE
##           Min.    1st Qu.      Median      Mean      3rd Qu.
## PLS          6.290607  8.377139    12.19528 1.119413e+01 13.43221
## Ridge        8.337455 10.191079    13.74461 1.393148e+01 16.99641
## Lasso       44.734039 170.204105 4149.21338 6.789732e+14 171049.39095
## Elasticnet   7.363015  9.416748    11.54396 1.147057e+01 11.90036
##           Max. NA's
## PLS          1.594366e+01    0
## Ridge        2.185108e+01    0
## Lasso        6.789732e+15    0
## Elasticnet   1.842877e+01    0
##
## Rsquared
##           Min.    1st Qu.      Median      Mean      3rd Qu.      Max. NA's
## PLS          0.16129728 0.25233183 0.56351166 0.4761420 0.6036028 0.8025506    0
## Ridge        0.08380318 0.28691652 0.51368868 0.4818460 0.6857065 0.8412046    0
## Lasso        0.03511831 0.04684349 0.08472472 0.1534889 0.2044714 0.5015686    0
## Elasticnet   0.09920794 0.33110233 0.54300031 0.5025237 0.6672628 0.7914440    0
```

```
accuracy <- function(models, predictor, response) {
  ac <- list()
  i <- 1
  for (m in models) {
    prediction <- predict(m, newdata = predictor)
    ac[[i]] <- postResample(pred=prediction, obs = response)
    i <- i+1
  }
  names(ac) <- c("pls","ridge","lasso","enet")
  return(ac)
}
```

```
models <- list(pls.fit, ridge.fit, lasso.fit, enet.fit)
accuracy(models, X.test, y.test)
```

```
## $pls
##      RMSE   Rsquared      MAE
## 12.4644848 0.4761679 9.4899066
##
## $ridge
##      RMSE   Rsquared      MAE
## 13.1757984 0.5906079 9.7296879
##
## $lasso
##      RMSE   Rsquared      MAE
```

```
## 3.919983e+03 4.075392e-02 1.181761e+03
##
## $enet
##      RMSE    Rsquared      MAE
## 11.6267322 0.5639022 8.7051313
```


The test set evaluation seems to show Ridge model is best with  $R^2=0.59$  but the cross validation earlier showed the best model as elastic net. I would prefer to go with cross validation as it is closer to true distribution. With this explanation, we can conclude that elastic net predicted the test set with best accuracy having  $RMSE = 11.62$  and  $R^2 = 0.56$

(f)

Would you recommend any of your models to replace the permeability laboratory experiment?

I would not recommend any of the models described above to replace the permeability laboratory experiment. The MAE of all the models are roughly between 8 and 10 that means model predictions of on avg 8 to 10 off. If we look at the permeability histogram most of the values are under 10 so models accuracies are not good enough to replace lab test.

```
hist(permeability)
```



## Exercise 6.3

A chemical manufacturing process for a pharmaceutical product was discussed in Sect. 1.4. In this problem, the objective is to understand the relationship between biological measurements of the raw materials (predictors), measurements of the manufacturing process (predictors), and the response of product yield. Biological predictors cannot be changed but can be used to assess the quality of the raw material before processing. On the other hand, the manufacturing process predictors can be changed in the manufacturing process. Improving product yield by 1% will boost revenue by approximately one hundred thousand dollars per batch:

(a)

Start R and use these commands to load the data:

```
data(ChemicalManufacturingProcess)
```

```
glimpse(ChemicalManufacturingProcess)
```

```
## Rows: 176
## Columns: 58
## $ Yield <dbl> 38.00, 42.44, 42.03, 41.42, 42.49, 43.57, 43.12~
## $ BiologicalMaterial01 <dbl> 6.25, 8.01, 8.01, 8.01, 7.47, 6.12, 7.48, 6.94,~
## $ BiologicalMaterial02 <dbl> 49.58, 60.97, 60.97, 60.97, 63.33, 58.36, 64.47~
## $ BiologicalMaterial03 <dbl> 56.97, 67.48, 67.48, 67.48, 72.25, 65.31, 72.41~
## $ BiologicalMaterial04 <dbl> 12.74, 14.65, 14.65, 14.65, 14.02, 15.17, 13.82~
## $ BiologicalMaterial05 <dbl> 19.51, 19.36, 19.36, 19.36, 17.91, 21.79, 17.71~
## $ BiologicalMaterial06 <dbl> 43.73, 53.14, 53.14, 53.14, 54.66, 51.23, 54.45~
## $ BiologicalMaterial07 <dbl> 100, 100, 100, 100, 100, 100, 100, 100, 100, 10~
## $ BiologicalMaterial08 <dbl> 16.66, 19.04, 19.04, 19.04, 18.22, 18.30, 18.72~
## $ BiologicalMaterial09 <dbl> 11.44, 12.55, 12.55, 12.55, 12.80, 12.13, 12.95~
## $ BiologicalMaterial10 <dbl> 3.46, 3.46, 3.46, 3.46, 3.05, 3.78, 3.04, 3.85,~
## $ BiologicalMaterial11 <dbl> 138.09, 153.67, 153.67, 153.67, 147.61, 151.88,~
## $ BiologicalMaterial12 <dbl> 18.83, 21.05, 21.05, 21.05, 21.05, 20.76, 20.75~
## $ ManufacturingProcess01 <dbl> NA, 0.0, 0.0, 0.0, 10.7, 12.0, 11.5, 12.0, 12.0~
## $ ManufacturingProcess02 <dbl> NA, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0~
## $ ManufacturingProcess03 <dbl> NA, NA, NA, NA, NA, NA, 1.56, 1.55, 1.56, 1.55,~
## $ ManufacturingProcess04 <dbl> NA, 917, 912, 911, 918, 924, 933, 929, 928, 938~
## $ ManufacturingProcess05 <dbl> NA, 1032.2, 1003.6, 1014.6, 1027.5, 1016.8, 988~
## $ ManufacturingProcess06 <dbl> NA, 210.0, 207.1, 213.3, 205.7, 208.9, 210.0, 2~
## $ ManufacturingProcess07 <dbl> NA, 177, 178, 177, 178, 178, 177, 178, 177, 177~
## $ ManufacturingProcess08 <dbl> NA, 178, 178, 177, 178, 178, 178, 178, 177, 177~
## $ ManufacturingProcess09 <dbl> 43.00, 46.57, 45.07, 44.92, 44.96, 45.32, 49.36~
## $ ManufacturingProcess10 <dbl> NA, NA, NA, NA, NA, NA, 11.6, 10.2, 9.7, 10.1, ~
## $ ManufacturingProcess11 <dbl> NA, NA, NA, NA, NA, NA, 11.5, 11.3, 11.1, 10.2,~
## $ ManufacturingProcess12 <dbl> NA, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0~
## $ ManufacturingProcess13 <dbl> 35.5, 34.0, 34.8, 34.8, 34.6, 34.0, 32.4, 33.6,~
## $ ManufacturingProcess14 <dbl> 4898, 4869, 4878, 4897, 4992, 4985, 4745, 4854,~
## $ ManufacturingProcess15 <dbl> 6108, 6095, 6087, 6102, 6233, 6222, 5999, 6105,~
## $ ManufacturingProcess16 <dbl> 4682, 4617, 4617, 4635, 4733, 4786, 4486, 4626,~
## $ ManufacturingProcess17 <dbl> 35.5, 34.0, 34.8, 34.8, 33.9, 33.4, 33.8, 33.6,~
## $ ManufacturingProcess18 <dbl> 4865, 4867, 4877, 4872, 4886, 4862, 4758, 4766,~
## $ ManufacturingProcess19 <dbl> 6049, 6097, 6078, 6073, 6102, 6115, 6013, 6022,~
## $ ManufacturingProcess20 <dbl> 4665, 4621, 4621, 4611, 4659, 4696, 4522, 4552,~
## $ ManufacturingProcess21 <dbl> 0.0, 0.0, 0.0, 0.0, -0.7, -0.6, 1.4, 0.0, 0.0, ~
## $ ManufacturingProcess22 <dbl> NA, 3, 4, 5, 8, 9, 1, 2, 3, 4, 6, 7, 8, 10, 11,~
## $ ManufacturingProcess23 <dbl> NA, 0, 1, 2, 4, 1, 1, 2, 3, 1, 3, 4, 1, 2, 3, 4~
## $ ManufacturingProcess24 <dbl> NA, 3, 4, 5, 18, 1, 1, 2, 3, 4, 6, 7, 8, 2, 15,~
## $ ManufacturingProcess25 <dbl> 4873, 4869, 4897, 4892, 4930, 4871, 4795, 4806,~
## $ ManufacturingProcess26 <dbl> 6074, 6107, 6116, 6111, 6151, 6128, 6057, 6059,~
## $ ManufacturingProcess27 <dbl> 4685, 4630, 4637, 4630, 4684, 4687, 4572, 4586,~
## $ ManufacturingProcess28 <dbl> 10.7, 11.2, 11.1, 11.1, 11.3, 11.4, 11.2, 11.1,~
## $ ManufacturingProcess29 <dbl> 21.0, 21.4, 21.3, 21.3, 21.6, 21.7, 21.2, 21.2,~
## $ ManufacturingProcess30 <dbl> 9.9, 9.9, 9.4, 9.4, 9.0, 10.1, 11.2, 10.9, 10.5~
## $ ManufacturingProcess31 <dbl> 69.1, 68.7, 69.3, 69.3, 69.4, 68.2, 67.6, 67.9,~
## $ ManufacturingProcess32 <dbl> 156, 169, 173, 171, 171, 173, 159, 161, 160, 16~
```

```
## $ ManufacturingProcess33 <dbl> 66, 66, 66, 68, 70, 70, 65, 65, 65, 66, 67, 67,~
## $ ManufacturingProcess34 <dbl> 2.4, 2.6, 2.6, 2.5, 2.5, 2.5, 2.5, 2.5, 2.5, 2.~
## $ ManufacturingProcess35 <dbl> 486, 508, 509, 496, 468, 490, 475, 478, 491, 48~
## $ ManufacturingProcess36 <dbl> 0.019, 0.019, 0.018, 0.018, 0.017, 0.018, 0.019~
## $ ManufacturingProcess37 <dbl> 0.5, 2.0, 0.7, 1.2, 0.2, 0.4, 0.8, 1.0, 1.2, 1.~
## $ ManufacturingProcess38 <dbl> 3, 2, 2, 2, 2, 2, 2, 2, 3, 3, 2, 3, 3, 3, 3,~
## $ ManufacturingProcess39 <dbl> 7.2, 7.2, 7.2, 7.2, 7.3, 7.2, 7.3, 7.3, 7.4, 7.~
## $ ManufacturingProcess40 <dbl> NA, 0.1, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0~
## $ ManufacturingProcess41 <dbl> NA, 0.15, 0.00, 0.00, 0.00, 0.00, 0.00, 0.00, 0~
## $ ManufacturingProcess42 <dbl> 11.6, 11.1, 12.0, 10.6, 11.0, 11.5, 11.7, 11.4,~
## $ ManufacturingProcess43 <dbl> 3.0, 0.9, 1.0, 1.1, 1.1, 2.2, 0.7, 0.8, 0.9, 0.~
## $ ManufacturingProcess44 <dbl> 1.8, 1.9, 1.8, 1.8, 1.7, 1.8, 2.0, 2.0, 1.9, 1.~
## $ ManufacturingProcess45 <dbl> 2.4, 2.2, 2.3, 2.1, 2.1, 2.0, 2.2, 2.2, 2.1, 2.~
```

The matrix `processPredictors` contains the 57 predictors (12 describing the input biological material and 45 describing the process predictors) for the 176 manufacturing runs. `yield` contains the percent yield for each run.

## (b)

A small percentage of cells in the predictor set contain missing values. Use an imputation function to fill in these missing values (e.g., see Sect. 3.8).


```
# columns having missing values
colnames(CheicalManufacturingProcess)[!complete.cases(t(CheicalManufacturingProcess))]
```

```
## [1] "ManufacturingProcess01" "ManufacturingProcess02" "ManufacturingProcess03"
## [4] "ManufacturingProcess04" "ManufacturingProcess05" "ManufacturingProcess06"
## [7] "ManufacturingProcess07" "ManufacturingProcess08" "ManufacturingProcess10"
## [10] "ManufacturingProcess11" "ManufacturingProcess12" "ManufacturingProcess14"
## [13] "ManufacturingProcess22" "ManufacturingProcess23" "ManufacturingProcess24"
## [16] "ManufacturingProcess25" "ManufacturingProcess26" "ManufacturingProcess27"
## [19] "ManufacturingProcess28" "ManufacturingProcess29" "ManufacturingProcess30"
## [22] "ManufacturingProcess31" "ManufacturingProcess33" "ManufacturingProcess34"
## [25] "ManufacturingProcess35" "ManufacturingProcess36" "ManufacturingProcess40"
## [28] "ManufacturingProcess41"
```

So there are 28 columns having missing values.

```
gg_miss_var(CheicalManufacturingProcess[,-c(1)]) + labs(y = "Sorted by Missing values")
```





We will next use `preProcess()` method to impute the missing values using `knnImpute` (K nearest neighbor).

```
pre.proc <- preProcess(ChemicalManufacturingProcess[,c(-1)], method = "knnImpute")
chem_df <- predict(pre.proc, ChemicalManufacturingProcess[,c(-1)])
```

```
# columns having missing values
colnames(chem_df)[!complete.cases(t(chem_df))]
```

```
## character(0)
```

(c)

Split the data into a training and a test set, pre-process the data, and tune a model of your choice from this chapter. What is the optimal value of the performance metric?

We will first look into pairwise correlation above 0.90 and remove the predictors having correlation with

cutoff 0.90.

```
chem.remove.pred <- nearZeroVar(chem_df)
chem_df <- chem_df[,-chem.remove.pred]
length(chem.remove.pred) %>% paste('columns are removed. ', dim(chem_df)[2], ' predictors are left for modeling.')

## [1] "1 columns are removed. 56 predictors are left for modeling."

chem.corr.90 <- findCorrelation(cor(chem_df), cutoff=0.90)
chem_df <- chem_df[,-chem.corr.90]
length(chem.corr.90) %>% paste('columns having correlation 0.90 or more are removed. ', dim(chem_df)[2])

## [1] "10 columns having correlation 0.90 or more are removed. 46 predictors are left for modeling."

set.seed(786)

pre.proc <- preProcess(chem_df, method = c("center", "scale"))
chem_df <- predict(pre.proc, chem_df)

# partition
chem.part <- createDataPartition(CheicalManufacturingProcess$Yield, p=0.70, list = FALSE)

# predictor
X.train <- chem_df[chem.part,]
X.test <- chem_df[-chem.part,]

# response
y.train <- ChemicalManufacturingProcess$Yield[chem.part]
y.test <- ChemicalManufacturingProcess$Yield[-chem.part]

# tune elastic net model
chem.enet.fit <- train(x=X.train,
                      y=y.train,
                      method="glmnet",
                      metric="Rsquared",
                      trControl=trainControl(method = "cv", number=5),
                      tuneLength = 5
                      )

chem.enet.fit
```


```
## glmnet
##
## 124 samples
## 46 predictor
##
## No pre-processing
## Resampling: Cross-Validated (5 fold)
## Summary of sample sizes: 100, 100, 97, 99, 100
## Resampling results across tuning parameters:
##
##  alpha  lambda      RMSE      Rsquared  MAE
##  0.100  0.001024807  2.437142  0.4167444  1.3738911
##  0.100  0.004756735  2.171840  0.4354025  1.2798122
##  0.100  0.022078808  1.773079  0.4862779  1.0951859
```

```

## 0.100 0.102480755 1.741586 0.5153721 1.0496783
## 0.100 0.475673550 1.420592 0.5498365 0.9911166
## 0.325 0.001024807 2.399571 0.4187277 1.3616936
## 0.325 0.004756735 1.858980 0.4577205 1.1801050
## 0.325 0.022078808 1.677929 0.5091625 1.0428443
## 0.325 0.102480755 1.489842 0.5443141 0.9903039
## 0.325 0.475673550 1.153410 0.6330924 0.9428937
## 0.550 0.001024807 2.282323 0.4230863 1.3256726
## 0.550 0.004756735 1.719922 0.4771800 1.1236580
## 0.550 0.022078808 1.681135 0.5142778 1.0333020
## 0.550 0.102480755 1.251745 0.5891387 0.9420367
## 0.550 0.475673550 1.201174 0.6140061 0.9885106
## 0.775 0.001024807 2.177305 0.4273587 1.2923780
## 0.775 0.004756735 1.653702 0.4903066 1.0886707
## 0.775 0.022078808 1.724256 0.5119351 1.0405219
## 0.775 0.102480755 1.144145 0.6324621 0.9140864
## 0.775 0.475673550 1.253042 0.5995470 1.0359208
## 1.000 0.001024807 2.054639 0.4329975 1.2528551
## 1.000 0.004756735 1.573404 0.5062840 1.0459723
## 1.000 0.022078808 1.720022 0.5111281 1.0423849
## 1.000 0.102480755 1.152242 0.6269674 0.9229554
## 1.000 0.475673550 1.313817 0.5876851 1.0908059
##
## Rsquared was used to select the optimal model using the largest value.
## The final values used for the model were alpha = 0.325 and lambda = 0.4756735.
chem.enet.fit$bestTune

##      alpha      lambda
## 10 0.325 0.4756735
plot(chem.enet.fit)

```



```
set.seed(786)
data.frame(RSquared=chem.enet.fit[["results"]][["Rsquared"]][as.numeric(rownames(chem.enet.fit$bestTune))],
           RMSE=chem.enet.fit[["results"]][["RMSE"]][as.numeric(rownames(chem.enet.fit$bestTune))])
```

```
##      RSquared      RMSE
## 1 0.6330924 1.15341
```

(d)

Predict the response for the test set. What is the value of the performance metric and how does this compare with the resampled performance metric on the training set?

```
enet.pred <- predict(chem.enet.fit, newdata = X.test)
(pred.result <- postResample(pred = enet.pred, obs=y.test))
```

```
##      RMSE  Rsquared      MAE
## 1.3301919 0.5123376 1.0823407
```

(e)

Which predictors are most important in the model you have trained? Do either the biological or process predictors dominate the list?


**caret::varImp** calculation of variable importance for regression and classification models, is generic method for calculating variable importance for objects produced by train and method specific methods. The number returned is a relative measure of variable importance.

We can see here that the most contribution predictor is ManufacturingProcess32 and we can conclude that Manufacturing process predictors dominate the list.

```
varImp(chem.enet.fit)
```

```
## glmnet variable importance
##
##    only 20 most important variables shown (out of 46)
##
##              Overall
## ManufacturingProcess32 100.00
## ManufacturingProcess09 66.22
## ManufacturingProcess13 48.62
## BiologicalMaterial06   32.50
## ManufacturingProcess36 26.92
## ManufacturingProcess17 25.93
## ManufacturingProcess06 21.52
## BiologicalMaterial03   18.76
## ManufacturingProcess34 15.12
## ManufacturingProcess15 11.36
## ManufacturingProcess37 10.74
## ManufacturingProcess10  0.00
## ManufacturingProcess07  0.00
## ManufacturingProcess33  0.00
## ManufacturingProcess02  0.00
## ManufacturingProcess16  0.00
## ManufacturingProcess05  0.00
## BiologicalMaterial05    0.00
## ManufacturingProcess30  0.00
## ManufacturingProcess08  0.00
```

```
plot(varImp(chem.enet.fit), top=20)
```



(f)

Explore the relationships between each of the top predictors and the response. How could this information be helpful in improving yield in future runs of the manufacturing process?

```
coeffs = coef(chem.enet.fit$finalModel, chem.enet.fit$bestTune$lambda)
(coeffs.df = data.frame(cbind(variables = coeffs@Dimnames[[1]][coeffs@i+1], coef = coeffs@x)))
```

```
##           variables           coef
## 1      (Intercept)  40.1826173671972
## 2  BiologicalMaterial03  0.096166348616399
## 3  BiologicalMaterial06  0.166570232040782
## 4  ManufacturingProcess06  0.110297740389495
## 5  ManufacturingProcess09  0.339419229880968
## 6  ManufacturingProcess13 -0.249207854549869
## 7  ManufacturingProcess15  0.0582484042571225
## 8  ManufacturingProcess17 -0.132925194155295
## 9  ManufacturingProcess32  0.512533203246302
## 10 ManufacturingProcess34  0.0774694027998954
## 11 ManufacturingProcess36 -0.137952195417695
## 12 ManufacturingProcess37 -0.0550415346074052
```

```
coeffs.df[coeffs.df$coef>0,]
```

```
##           variables           coef
## 1      (Intercept)  40.1826173671972
## 2  BiologicalMaterial03  0.096166348616399
## 3  BiologicalMaterial06  0.166570232040782
## 4  ManufacturingProcess06  0.110297740389495
## 5  ManufacturingProcess09  0.339419229880968
## 7  ManufacturingProcess15  0.0582484042571225
## 9  ManufacturingProcess32  0.512533203246302
## 10 ManufacturingProcess34  0.0774694027998954
```

```
coeffs.df[coeffs.df$coef<0,]
```

```
##           variables           coef
## 6  ManufacturingProcess13 -0.249207854549869
## 8  ManufacturingProcess17 -0.132925194155295
## 11 ManufacturingProcess36 -0.137952195417695
## 12 ManufacturingProcess37 -0.0550415346074052
```

```
cor(ChemicalManufacturingProcess$Yield, ChemicalManufacturingProcess$ManufacturingProcess32)
```

```
## [1] 0.6083321
```

```
cor(ChemicalManufacturingProcess$Yield, ChemicalManufacturingProcess$ManufacturingProcess13)
```

```
## [1] -0.5036797
```