

Attacking Web Applications with Ffuf:

Link to challenge: <https://academy.hackthebox.com/module/54>

(log in required)

Class: Tier 0 | Easy | Offensive

**Before we begin:** in the pwnbox, the wordlists we will use are in default located in the directory '/usr/share/seclists/Discovery/Web-Content'. it will be true throughout the module, unless specified otherwise.

## Basic Fuzzing

### Directory Fuzzing:

**Question:** In addition to the directory we found above, there is another directory that can be found. What is it?

**Answer:** forum

**Method:** we will use the wordlist 'directory-list-2.3-small.txt' and the ffuf command:

```
ffuf -w /usr/share/seclists/Discovery/Web-Content/directory-list-2.3-small.txt:FUZZ -u http://<target-IP>:<target-port>/FUZZ -s
```

using the '-s' flag to silence unnecessary output:

```
[eu-academy-2]-[10.10.15.17]-[htb-ac-1099135@htb-uxqwx/ujcn]-[~]  
[*]$ ffuf -w /usr/share/seclists/Discovery/Web-Content/directory-list-2.3-small.txt:FUZZ -u http://83.136.253.163:38674/FUZZ -s  
#  
#  
# This work is licensed under the Creative Commons  
# Attribution-Share Alike 3.0 License. To view a copy of this  
# Copyright 2007 James Fisher  
# or send a letter to Creative Commons, 171 Second Street,  
# license, visit http://creativecommons.org/licenses/by-sa/3.0/  
# directory-list-2.3-small.txt  
forum  
#  
# Suite 300, San Francisco, California, 94105, USA.  
# on at least 3 different hosts  
# Priority-ordered case-sensitive list, where entries were found  
#  
blog
```

We got the value 'forum'.

## Page Fuzzing:

**Question:** Try to use what you learned in this section to fuzz the '/blog' directory and find all pages. One of them should contain a flag. What is the flag?

**Answer:** HTB{bru73\_f0r\_c0mm0n\_p455w0rd5}

**Method: Method 1:** we will use the wordlist 'web-extensions.txt' which contains extensions for webpages, on the parameter 'index' to see what extensions are out there:

```
ffuf -w /usr/share/seclists/Discovery/Web-Content/web-extensions.txt:FUZZ -u http://<target-IP>:<target-port>/indexFUZZ
```

\*we assume here the path-name is 'index'. \*

```
[eu-academy-2]-[10.10.15.17]-[htb-ac-1099135@htb-uxqwx7ujcn]-[~]
[*]$ ffuf -w /usr/share/seclists/Discovery/Web-Content/web-extensions.txt:FUZZ -u http://83.136.253.163:38674/indexFUZZ
```

\*

\*

```
.. Matched: 1 Response Status: 200,299,301,302,307,401,403,405,500

.php [Status: 200, Size: 986, Words: 423, Lines: 56, Duration: 1391ms]
.php [Status: 403, Size: 282, Words: 20, Lines: 10, Duration: 4420ms]
:: Progress: [41/41] :: Job [1/1] :: 9 req/sec :: Duration: [0:00:04] :: Errors: 0 ::
```

The extension 'php' returned status code 200 (success), lets make another scan for php pages in '/blog':

```
ffuf -w /usr/share/seclists/Discovery/Web-Content/directory-list-2.3-small.txt:FUZZ -u http://<target-IP>:<target-port>/blog/FUZZ.php -s
```

```
[eu-academy-2]-[10.10.15.17]-[htb-ac-1099135@htb-uxqwx7ujcn]-[~]
[*]$ ffuf -w /usr/share/seclists/Discovery/Web-Content/directory-list-2.3-small.txt:FUZZ -u http://83.136.253.163:38674/blog/FUZZ.php -s
#
#
# directory-list-2.3-small.txt
# Copyright 2007 James Fisher
# Suite 300, San Francisco, California, 94105, USA.
index
#
#
# Priority-ordered case-sensitive list, where entries were found
# This work is licensed under the Creative Commons
# Attribution-Share Alike 3.0 License. To view a copy of this
# or send a letter to Creative Commons, 171 Second Street,
# license, visit http://creativecommons.org/licenses/by-sa/3.0/
#
# on at least 3 different hosts
home
```

Going for the discovered URL on browser:

```
http://<target-IP>:<target-port>/blog/home.php
```



**Method 2:** we can also combine the 2 commands above to a single command, bruteforcing both the path-name and the extension simultaneously, negating the need to assume the path-name '/index' in the original technique. However, due to the nature of 2 word-lists, the bruteforcing of this method is a far more lengthy process, taking approximately 10 minutes:

```
ffuf -w /usr/share/seclists/Discovery/Web-Content/directory-list-2.3-small.txt:FUZZ1 -w /usr/share/seclists/Discovery/Web-Content/web-extensions.txt:FUZZ2 -u http://<target-IP>:<target-port>/blog/FUZZ1FUZZ2 -mc 200 -fs 0
```

```
[eu-academy-2]~[10.10.15.17]~[htb-ac-1099135@htb-uxqwx7ujcn]~[~]  
[*]$ ffuf -w /usr/share/seclists/Discovery/Web-Content/directory-list-2.3-small.txt:FUZZ1 -w /usr/share/seclists/Discovery/Web-Content/web-extensions.txt:FUZZ2 -u http://83.136.253.163:38674/blog/FUZZ1FUZZ2 -mc 200 -fs 0
```

\*

\*

```
:: Matched: : Response status: 200  
:: Filter : Response size: 0  
  
[Status: 200, Size: 1046, Words: 438, Lines: 58, Duration: 77ms]  
* FUZZ1: home  
* FUZZ2: .php  
  
:: Progress: [3594224/3594224] :: Job [1/1] :: 33333 req/sec :: Duration: [0:10:06] :: Errors: 0 ::
```

## Recursive Fuzzing:

**Question:** Try to repeat what you learned so far to find more files/directories. One of them should give you a flag. What is the content of the flag?

**Answer:** HTB{fuzz1n6\_7h3\_w3b!}

**Method:** lets run recursive search for php files using the command:

```
ffuf -w /usr/share/seclists/Discovery/Web-Content/directory-list-2.3-small.txt:FUZZ -u http://<target-IP>:<target-port>/FUZZ -recursion -recursion-depth 1 -e .php -v -mc 200 -fs 0
```

using death-1

```
[eu-academy-2]-[10.10.15.17]-[htb-ac-1099135@htb-uxqwx7ujcn]-[~]  
[*]$ ffuf -w /usr/share/seclists/Discovery/Web-Content/directory-list-2.3-small.txt:FUZZ -u http://94.237.53.113:37010/FUZZ -recursion -recursion-depth 1 -e .php -v -mc 200 -fs 0
```

\*

\*

```
FUZZ: home.php  
  
[INFO] Starting queued job on target: http://94.237.53.113:37010/forum/FUZZ  
  
[Status: 200, Size: 21, Words: 1, Lines: 1, Duration: 0ms]  
| URL | http://94.237.53.113:37010/forum/flag.php  
* FUZZ: flag.php  
  
:: Progress: [175328/175328] :: Job [3/3] :: 1941 req/sec :: Duration: [0:00:28] :: Errors: 0 ::
```

then, we enter the website:

```
http://<target-IP>:<target-port>/forum/flag.php
```

```
← → ↻ 🏠 🔒 http://94.237.53.113:37010/forum/flag.php  
📦 HTB Labs 📦 HTB Certifications 📦 HTB Academy 📦 CTF Platform 📦 Help Center  
HTB{fuzz1n6_7h3_w3b!}
```

## Domain Fuzzing

## Sub-domain Fuzzing:

**Question:** Try running a sub-domain fuzzing test on 'inlanefreight.com' to find a customer sub-domain portal. What is the full domain of it?

**Answer:** [customer.inlanefreight.com](http://customer.inlanefreight.com)

**Method:** we will use the wordlist '[subdomains-top1million-5000.txt](#)' which in the pwnbox is located at '/usr/share/seclists/Discovery/DNS/subdomains-top1million-5000.txt'. we will use the command:

```
ffuf -w /usr/share/seclists/Discovery/DNS/subdomains-top1million-5000.txt:FUZZ -u https://FUZZ.inlanefreight.com/
```

```
[eu-academy-2]-[10.10.15.17]-[htb-ac-1099135@htb-uxqwx7ujcn]-[~]
[*]$ ffuf -w /usr/share/seclists/Discovery/DNS/subdomains-top1million-5000.txt:FUZZ -u https://FUZZ.inlanefreight.com/

      /\_/\   /\_/\   /\_/\
     /\ \_/\  /\ \_/\  /\ \_/\
    /\ \_\/\  /\ \_\/\  /\ \_\/\
    /\ \_\/\  /\ \_\/\  /\ \_\/\
    /\ \_\/\  /\ \_\/\  /\ \_\/\
    /\ \_\/\  /\ \_\/\  /\ \_\/\

v2.1.0-dev
```

---

```
:: Method       : GET
:: URL          : https://FUZZ.inlanefreight.com/
:: Wordlist      : FUZZ: /usr/share/seclists/Discovery/DNS/subdomains-top1million-5000.txt
:: Full request :
```

\*

\*

```
ns3 [Status: 301, Size: 0, Words: 1, Lines: 1, Duration: 253ms]
blog [Status: 301, Size: 0, Words: 1, Lines: 1, Duration: 269ms]
support [Status: 301, Size: 0, Words: 1, Lines: 1, Duration: 279ms]
my [Status: 301, Size: 0, Words: 1, Lines: 1, Duration: 260ms]
www [Status: 200, Size: 22266, Words: 2903, Lines: 316, Duration: 337ms]
customer [Status: 301, Size: 0, Words: 1, Lines: 1, Duration: 77ms]
```

The only result which appears on the scan results and not in the section's guide is 'customer', so that is the subdomain we seek.

## Filtering Results:

**Question:** Try running a VHost fuzzing scan on 'academy.htb', and see what other VHosts you get. What other VHosts did you get?

**Answer:** test.academy.htb

**Method:** first, we will have to link the Vhost to the target IP in the file '/etc/hosts' in the pwnbox:

```
sudo nano /etc/hosts
```

and in it

```
<target-IP> academy.htb
```

```
GNU nano 7.2 /etc/hosts
1 127.0.0.1 localhost
2 127.0.1.1 debian12-parrot
3
4 # The following lines are desirable for IPv6 capable hosts
5 ::1 localhost ip6-localhost ip6-loopback
6 ff02::1 ip6-allnodes
7 ff02::2 ip6-allrouters
8 127.0.0.1 localhost
9 127.0.1.1 htb-uxqwx7ujcn htb-uxqwx7ujcn.htb-cloud.com
10
11 94.237.53.113 academy.htb ←
```

Now, we would like to use the command

```
ffuf -w /usr/share/seclists/Discovery/DNS/subdomains-top1million-5000.txt:FUZZ -u http://academy.htb:<target-port>/ -H 'Host: FUZZ.academy.htb'
```

without filtering for a size (using the 'subdomains-top1million-5000.txt' wordlist) – however that will result in flooding of 'dummy' results:



The result which does not appears in the section's guide is 'test'. So that is our result.

## Parameter Fuzzing

## Parameter Fuzzing - GET:

**Question:** Using what you learned in this section, run a parameter fuzzing scan on this page. what is the parameter accepted by this webpage?

**Answer:** user

**Method:** for this question we are provided with the URL:

```
'http://admin.academy.htb:<target-port>/admin/admin.php'
```

(don't forget to link the vhost subdomain in '/etc/hosts')

```
11 94.237.53.113 academy.htb
12 94.237.53.113 admin.academy.htb ←
```

)

And we need to find acceptable parameter property. For that we will use the wordlist '[burp-parameter-names.txt](#)' and the command:

```
ffuf -w /usr/share/seclists/Discovery/Web-Content/burp-  
parameter-names.txt:FUZZ -u  
http://admin.academy.htb:<target-  
port>/admin/admin.php?FUZZ=key -fs 798
```

\*We will add '-fs 798' upfront to skip the lengthy process of finding the size to filter as we shown in the previous section. \*

```
[eu-academy-2]-[10.10.15.17]-[htb-ac-1099135@htb-uxqwx7ujcn]-[~]
[*]$ ffuf -w /usr/share/seclists/Discovery/Web-Content/burp-parameter-names.txt:FUZZ -u http://admin.academy.htb:37010/ad
min/admin.php?FUZZ=key -fs 798

      /'_-\ /'_-\ /'_-\
     /\ \_/\ /\ \_/\  _ _  /\ \_/\
    /\ \_/\ /\ \_/\ /\ \_/\ /\ \_/\
    /\ \_/\ /\ \_/\ /\ \_/\ /\ \_/\
    /\ \_/\ /\ \_/\ /\ \_/\ /\ \_/\
    /\ \_/\ /\ \_/\ /\ \_/\ /\ \_/\

v2.1.0-dev

:: Method      : GET
:: URL         : http://admin.academy.htb:37010/admin/admin.php?FUZZ=key
:: Wordlist    : FUZZ: /usr/share/seclists/Discovery/Web-Content/burp-parameter-names.txt
```

\*

\*

```
user [Status: 200, Size: 783, Words: 221, Lines: 54, Duration: 0ms]
:: Progress: [6453/6453] :: Job [1/1] :: 78 req/sec :: Duration: [0:00:04] :: Errors: 0 ::
```



## Value Fuzzing:

**Question:** Try to create the 'ids.txt' wordlist, identify the accepted value with a fuzzing scan, and then use it in a 'POST' request with 'curl' to collect the flag. What is the content of the flag?

**Answer:** HTB{p4r4m373r\_fuzz1n6\_15\_k3y!}

**Method:** we will use the following bash command to create a file 'ids.txt', containing all the numbers from 1 to 1000

```
for i in $(seq 1 1000); do echo $i >> ids.txt; done
```

```
[eu-academy-2]-[10.10.15.17]-[htb-ac-1099135@htb-uxqwx7ujcn]-[~]  
[*]$ for i in $(seq 1 1000); do echo $i >> ids.txt; done
```

when the file is ready, we will use it as wordlist for the POST request parameter bruteforce:

```
ffuf -w ids.txt:FUZZ -u http://admin.academy.htb:<target-port>/admin/admin.php -X POST -d 'id=FUZZ' -H 'Content-Type: application/x-www-form-urlencoded' -fs 768
```

\* do remember to keep the vhost subdomain linked to the IP in '/etc/hosts'.

And also we set the '-fs' to 768 upfront.\*

```
[eu-academy-2]-[10.10.15.17]-[htb-ac-1099135@htb-uxqwx7ujcn]-[~]  
[*]$ ffuf -w ids.txt:FUZZ -u http://admin.academy.htb:37010/admin/admin.php -X POST -d 'id=FUZZ' -H 'Content-Type: application/x-www-form-urlencoded' -fs 768
```

\*

\*

```
73 [Status: 200, Size: 787, Words: 218, Lines: 54, Duration: 2ms]  
:: Progress: [1000/1000] :: Job [1/1] :: 149 req/sec :: Duration: [0:00:01] :: Errors: 0 ::
```

The correct value id 73. Accessing it via the browser wont work (as it will send a GET request, the web-server page is accepting POST requests. So we will use curl instead:

```
curl http://admin.academy.htb:<target-IP>/admin/admin.php -X POST -d 'id=73' -H 'Content-Type: application/x-www-form-urlencoded'
```

```
[eu-academy-2]-[10.10.15.17]-[htb-ac-1099135@htb-kxobmggrk8]-[~]  
[*]$ curl http://admin.academy.htb:34473/admin/admin.php -X POST -d 'id=73'  
-H 'Content-Type: application/x-www-form-urlencoded'  
<div class='center'><p>HTB{p4r4m373r_fuzz1n6_15_k3y!}</p></div>  
<html>
```

# Skills Assessment

## Skills Assessment - Web Fuzzing:

**Question:** Run a sub-domain/vhost fuzzing scan on '\*.academy.htb' for the IP shown above. What are all the sub-domains you can identify? (Only write the sub-domain name)

**Answer:** test,archive,faculty

**Method:** first lets link the vhost 'academy.htb' to the target IP in the /etc/hosts':

```
sudo nano /etc/hosts
```

→

```
<target-IP> academy.htb
```

```
GNU nano 7.2 /etc/hosts *
1 94.237.55.106 academy.htb
```

Now when that's link – lets run vhost subdomain bruteforce, using the usual 'subdomains-top1million-5000.txt' wordlist:

```
ffuf -w /usr/share/seclists/Discovery/DNS/subdomains-top1million-5000.txt:FUZZ -u http://academy.htb:<target-port>/ -H 'Host: FUZZ.academy.htb' -fs 985
```

```
[eu-academy-2]~[10.10.15.17]~[htb-ac-1099135@htb-vxaljeaerg]~[~]
[+]$ ffuf -w /usr/share/seclists/Discovery/DNS/subdomains-top1million-5000.txt:FUZZ -u http://academy.htb:34355/ -H 'Host: FUZZ.academy.htb' -fs 985
```

\*

\*

```
.. matches: 1 Response status: 200 233/361/362/367/401/403/405/500
:: Filter : Response size: 985

archive [Status: 200, Size: 0, Words: 1, Lines: 1, Duration: 0ms]
faculty [Status: 200, Size: 0, Words: 1, Lines: 1, Duration: 0ms]
test [Status: 200, Size: 0, Words: 1, Lines: 1, Duration: 994ms]
:: Progress: [4989/4989] :: Job [1/1] :: 62 req/sec :: Duration: [0:00:05] :: Errors: 0 ::
```

**Question:** Before you run your page fuzzing scan, you should first run an extension fuzzing scan. What are the different extensions accepted by the domains?

**Answer:** php,phps,php7

**Method:** first, we will have to link the VHost found subdomains to the target IP in '/etc/hosts/' as well:

```
sudo nano /etc/hosts
```

→

```
<target-IP> test.academy.htb
<target-IP> faculty.academy.htb
<target-IP> archive.academy.htb
```

```
GNU nano 7.2 /etc/hosts
1 94.237.55.106 academy.htb
2 94.237.55.106 test.academy.htb
3 94.237.55.106 faculty.academy.htb
4 94.237.55.106 archive.academy.htb
5
```

Now lets put the found subdomain in a file called 'found\_subs.txt', along with the main 'academy' domain:

```
echo 'academy
test
faculty
archive' > found_subs.txt
```

```
[eu-academy-2]-[10.10.15.17]-
[★]$ echo 'academy
test
faculty
archive' > found_subs.txt
[eu-academy-2]-[10.10.15.17]-
[★]$ cat found_subs.txt
academy
test
faculty
archive
```

Now we are ready to run the ffuf:

```
ffuf -w found_subs.txt:SUB -w
/usr/share/seclists/Discovery/Web-Content/web-
extensions.txt:EXT -u http://SUB.academy.htb:<target-
port>/indexEXT
```

\*yes, we can use variables 'SUB' and 'EXT' instead of 'FUZZ'. \*:

```
[eu-academy-2]-[10.10.15.17]-[htb-ac-1099135@htb-vxal]eaerg-[~]  
[*]$ ffuf -w found_subs.txt:SUB -w /usr/share/seclists/Discovery/Web-Content/web-extensions.txt:EXT -u http://SUB.academy.htb:34355/indexEXT  
  
      /\_/\   /\_/\       /\_/  
    /\_\/  /\_\/  _ _  /\_/  
   \/ _\ \/ _\  /\_/\_/\_/\_/\_/  
   /\_\/  /\_\/  /\_/\_/\_/\_/\_/  
   /\_/\   /\_/\   /\_/\   /\_/  
   /\_/\   /\_/\   /\_/\   /\_/  
  
v2.1.0-dev
```

---

```
:: Method          : GET  
:: URL             : http://SUB.academy.htb:34355/indexEXT  
:: Wordlist         : SUB: /home/htb-ac-1099135/found_subs.txt  
:: Wordlist         : EXT: /usr/share/seclists/Discovery/Web-Content/web-extensions.txt  
:: Follow_redirects : false
```

\*

\*

```
[Status: 200, Size: 0, Words: 1, Lines: 1, Duration: 1ms]
  * EXT: .php
  * SUB: faculty

[Status: 200, Size: 0, Words: 1, Lines: 1, Duration: 3ms]
  * EXT: .php
  * SUB: test

[Status: 403, Size: 287, Words: 20, Lines: 10, Duration: 0ms]
  * EXT: .phps
  * SUB: faculty

[Status: 403, Size: 287, Words: 20, Lines: 10, Duration: 0ms]
  * EXT: .phps
  * SUB: archive
```

```
[Status: 403, Size: 284, Words: 20, Lines: 10, Duration: 0ms]
* EXT: .phps
* SUB: test

[Status: 200, Size: 0, Words: 1, Lines: 1, Duration: 1ms]
* EXT: .php7
* SUB: faculty

[Status: 200, Size: 0, Words: 1, Lines: 1, Duration: 5006ms]
* EXT: .php
* SUB: archive

:: Progress: [123/123] :: Job [1/1] :: 24 req/sec :: Duration: [0:00:05] :: Errors: 0 ::
```

There are 3 extensions overall: php,phps,php7

**Question:** One of the pages you will identify should say 'You don't have access!'. What is the full page URL?

**Answer:** `http://faculty.academy.htb:PORT/courses/linux-security.php7`

**Method:** first we will use recursive enumeration to find paths and sub-paths.  
Depth 2 will suffice:

```
ffuf -w found_subs.txt:SUB -w
/usr/share/seclists/Discovery/Web-Content/directory-list-
2.3-small.txt:FUZZ -u http://SUB.academy.htb:<target-
port>/FUZZ -recursion -recursion-depth 2 -fs 0
```

```
[eu-academy-2]-[10.10.15.17]-[htb-ac-1099135@htb-vxaljeaerg]-[~]
[*]$ ffuf -w found_subs.txt:SUB -w /usr/share/seclists/Discovery/Web-Content/directory-list-2.3-small.txt:FUZZ -u http://SUB.academy.htb:34355/FUZZ -recursion -recursion-depth 2 -fs 0
```

```
'_\' '_\      '\_\n/\__ /\__ _ _ /\__\n\\ ,\_ \\ \_,V\ \/_ \| \_\_\n\\ __ \| \_\_\ \| \_\_\ \| \_\_\n'_ \| \_\_\ \| \_\_\ \| \_\_\ \| \_\_\n'\_\'   '\_\'   '\_\'
```

v2.1.0-dev

---

```
:: Method       : GET\n:: URL          : http://SUB.academy.htb:34355/FUZZ\n:: Wordlist     : SUB: /home/htb-ac-1099135/found_subs.txt\n:: Wordlist     : FUZZ: /usr/share/seclists/Discovery/Web-Content/directory-list-2.3-small.txt\n:: Follow_redirects : false
```

\*

\*

```
[Status: 301, Size: 337, Words: 20, Lines: 10, Duration: 0ms]
* FUZZ: courses
* SUB: archive

[INFO] Adding a new job to the queue: http://archive.academy.htb:34355/courses/FUZZ

[Status: 301, Size: 337, Words: 20, Lines: 10, Duration: 0ms]
* FUZZ: courses
* SUB: faculty

[INFO] Adding a new job to the queue: http://faculty.academy.htb:34355/courses/FUZZ

[INFO] Starting queued job on target: http://archive.academy.htb:34355/courses/FUZZ

[INFO] Starting queued job on target: http://faculty.academy.htb:34355/courses/FUZZ

:: Progress: [87664/87664] :: Job [3/3] :: 961 req/sec :: Duration: [0:00:16] :: Errors: 87664 ::
```

The scan found the path 'courses', on the subdomains 'archive' and 'faculty'.



Now we will look for the file, somewhere within the found path.

We will put that path in a file called 'found\_paths.txt', along with the main path:

```
echo '/  
courses/' > found_paths.txt
```

```
[eu-academy-2]-[10.10.15.17]-  
[★]$ echo '/  
courses/' > found_paths.txt  
[eu-academy-2]-[10.10.15.17]-  
[★]$ cat found_paths.txt  
/  
courses/
```

Similarly, let's put the found extensions from the previous question to a file called 'found\_exts.txt':

```
echo 'php  
phps  
php7' > found_exts.txt
```

```
[eu-academy-2]-[10.10.15.17]  
[★]$ echo 'php  
phps  
php7' > found_exts.txt  
[eu-academy-2]-[10.10.15.17]  
[★]$ cat found_exts.txt  
php  
phps  
php7
```

Now we are ready to begin the scan for the file-name, throughout the subdomains, paths, and extensions – we will scour the 'directory-list-2.3-small.txt' wordlist to find the correct file-name:

```
ffuf -w found_subs.txt:SUB -w found_paths.txt:PATH -w  
/usr/share/seclists/Discovery/Web-Content/directory-list-  
2.3-small.txt:FUZZ -w found_exts.txt:EXT -u  
http://SUB.academy.htb:<target-port>/PATHFUZZ.EXT -mc 200 -  
fs 0
```



**Question:** In the page from the previous question, you should be able to find multiple parameters that are accepted by the page. What are they?

**Answer:** user,username

**Method:** we will bruteforce POST requests, using the 'burp-parameter-names.txt' wordlist:

```
ffuf -w /usr/share/seclists/Discovery/Web-Content/burp-parameter-names.txt:FUZZ -u http://faculty.academy.htb:<target-port>/courses/linux-security.php7 -X POST -d "FUZZ=key" -H 'Content-Type: application/x-www-form-urlencoded' -fs 774
```

```
[eu-academy-2]-[10.10.15.17]-[htb-ac-1099135@htb-lycmjofkp9]-[~]  
[*]$ ffuf -w /usr/share/seclists/Discovery/Web-Content/burp-parameter-names.txt:FUZZ -u http://faculty.academy.htb:31370/courses/linux-security.php7 -X POST -d "FUZZ=key" -H 'Content-Type: application/x-www-form-urlencoded' -fs 774
```



```
v2.1.0-dev
```

---

```
:: Method      : POST  
:: URL        : http://faculty.academy.htb:31370/courses/linux-security.php7  
:: Wordlist    : FUZZ: /usr/share/seclists/Discovery/Web-Content/burp-parameter-names.txt  
:: Header     : Content-Type: application/x-www-form-urlencoded  
:: Data       : FUZZ=key
```

\*

\*

```
:: Threads    : 40  
:: Matcher    : Response status: 200-299,301,302,307,401,403,405,500  
:: Filter     : Response size: 774
```

---

```
user          [Status: 200, Size: 780, Words: 223, Lines: 53, Duration: 5ms]  
username      [Status: 200, Size: 781, Words: 223, Lines: 53, Duration: 7ms]  
:: Progress: [6453/6453] :: Job [1/1] :: 150 req/sec :: Duration: [0:00:03] :: Errors: 0 ::
```

Finding the parameters names 'user' and 'username'.

**Question:** Try fuzzing the parameters you identified for working values. One of them should return a flag. What is the content of the flag?

**Answer:** HTB{w3b\_fuzz1n6\_m4573r}

**Method:** first lets put the 'user' and 'username' in 'found\_parameters.txt':

```
echo 'user  
username' > found_parameters.txt
```

```
[eu-academy-2]-[10.10.15.17]-[htb-1ycmjofkp9]-[~]  
[*]$ echo 'user  
username' > found_parameters.txt  
[eu-academy-2]-[10.10.15.17]-[htb-1ycmjofkp9]-[~]  
[*]$ cat found_parameters.txt  
user  
username
```

Now, we need to find proper wordlist for parameter's value bruteforcing. But in the built in 'seclists' – there are many possible wordlists.

Lets take a look in this 'Names' directory:

```
ls /usr/share/seclists/Usernames/Names
```

```
[eu-academy-2]-[10.10.15.17]-[htb-ac-1099135@htb-1ycmjofkp9]-[~]  
[*]$ ls /usr/share/seclists/Usernames/Names  
familynames-usa-top1000.txt  forenames-india-top1000.txt  names.txt  
femalenames-usa-top1000.txt  malenames-usa-top1000.txt
```

There are possible wordlists here, however checking them one by one might be tedious, so let's combine them to a single wordlist within the user's home directory:

```
cat /usr/share/seclists/Usernames/Names/*.txt > allnames.txt  
the combined list is to be called 'allnames.txt'
```

now its time to run out bruteforce script on that 'allnames.txt' and 'found\_parameters.txt'. we will upfront make sure to ignore the data related to sizes 780 and 781 (ignore those lines, and the 3 lines below them):

```
ffuf -w found_parameters.txt:PARAM -w allnames.txt:FUZZ -u
http://faculty.academy.htb:<target-port>/courses/linux-
security.php7 -X POST -d 'PARAM=FUZZ' -H 'Content-Type:
application/x-www-form-urlencoded' -mc 200 | sed -e '/Size:
780/,+3d' -e '/Size: 781/,+3d'
```

```
[eu-academy-2]-[10.10.15.17]-[htb-ac-1099135@htb-1ycmjofkp9]-[~]  
→ [*$] ffuf -w found_parameters.txt:PARAM -w allnames.txt:FUZZ -u http://faculty.academy.htb:46477/courses/linux-security.ph  
p7 -X POST -d 'PARAM=FUZZ' -H 'Content-Type: application/x-www-form-urlencoded' -mc 200 | sed -e '/Size: 780/,+3d' -e '/Size: 7  
81/,+3d'
```

v2.1.0-dev

```
:: Method : POST
:: URL : http://faculty.academy.htb:46477/courses/linux-security.php7
:: Wordlist : PARA: /home/htb-ac-1099135/found_parameters.txt
:: Wordlist : FUZZ: /home/htb-ac-1099135/allnames.txt
:: Header : Content-Type: application/x-www-form-urlencoded
:: Data : PARA=FUZZ
:: Follow redirects : false
:: Calibration : false
:: Timeout : 10
:: Threads : 40
:: Matcher : Response status: 200
```

```
[Status: 200, Size: 773, Words: 218, Lines: 53, Duration: 5ms]
* FUZZ: HARRY
* PARA: username
:: Progress: [6152/28354] :: Job [1/1] :: 2222 req/sec :: Duration: [0:00:03] :: Errors: 0 ::
[Status: 200, Size: 773, Words: 218, Lines: 53, Duration: 6ms]
* FUZZ: harry
* PARA: username
:: Progress: [28354/28354] :: Job [1/1] :: 2105 req/sec :: Duration: [0:00:13] :: Errors: 0 ::
```

We found the values 'harry' or 'HARRY' fit to the parameter 'username'.

All we have left to do, is to curl the flag using POST request, and all the obtained parameters and values:

```
curl http://faculty.academy.htb:<target-port>/courses/linux-security.php7 -X POST -d 'username=harry' -H 'Content-Type: application/x-www-form-urlencoded'
```

```
[eu-academy-2]-[10.10.15.17]-[htb-ac-1099135@htb-lycmjofkp9]-[~]  
➔ [*]$ curl http://faculty.academy.htb:43159/courses/linux-security.php7 -X POST -d 'username=harry' -H 'Content-Type: application/x-www-form-urlencoded'  
<div class='center'><p>HTB{w3b_fuzz1n6_m4573r}</p></div>  
<html>
```