Train In Data

Open-source Python packages for Feature Selection

Open-source for Feature engineering

scikit learn

MLXTEND

Feature-engine

Fit – transform functionality

- fit() ➔ finds important features
- transform() ➔ transforms data
  - Removes unwanted features

Pipeline



:

```
# we stack all the selection methods inside a pipeline

pipe = Pipeline([
    ('constant', DropConstantFeatures(tol=0.998)),
    ('duplicated', DropDuplicateFeatures()),
    ('correlation', SmartCorrelatedSelection(selection_method='variance')),
])

pipe.fit(X_train)
```

Pipeline




```
# train pipeline
price_pipe.fit(X_train, y_train)

# transform data
price_pipe.transform(X_train)
price_pipe.transform(X_test)
```

Prev Up Next

scikit-learn 0.24.0
Other versions

Please cite us if you use the software.

1.13. Feature selection
1.13.1. Removing features with low variance
1.13.2. Univariate feature selection
1.13.3. Recursive feature elimination
1.13.4. Feature selection using SelectFromModel
1.13.5. Sequential Feature Selection
1.13.6. Feature selection as part of a pipeline

1.13. Feature selection

The classes in the `sklearn.feature_selection` module can be used for feature selection/dimensionality reduction on sample sets, either to improve estimators' accuracy scores or to boost their performance on very high-dimensional datasets.

1.13.1. Removing features with low variance

`VarianceThreshold` is a simple baseline approach to feature selection. It removes all features whose variance doesn't meet some threshold. By default, it removes all zero-variance features, i.e. features that have the same value in all samples.

As an example, suppose that we have a dataset with boolean features, and we want to remove all features that are either one or zero (on or off) in more than 80% of the samples. Boolean features are Bernoulli random variables, and the variance of such variables is given by

$$\mathrm{Var}[X] = p(1-p)$$

so we can select using the threshold `.8 * (1 - .8)`:

```
>>> from sklearn.feature_selection import VarianceThreshold
>>> X = [[0, 0, 1], [0, 1, 0], [1, 0, 0], [0, 1, 1], [0, 1, 0], [0, 1, 1]]
>>> sel = VarianceThreshold(threshold=(.8 * (1 - .8)))
>>> sel.fit_transform(X)
array([[0, 1],
       [1, 0],
       [0, 0],
       [1, 1],
       [1, 0],
       [1, 1]])
```

As expected, `VarianceThreshold` has removed the first column, which has a probability $p = 5/6 > .8$ of containing a zero.

Welcome to mlxtend's documentation!

Mlxtend (machine learning extensions) is a Python library of useful tools for the day-to-day data science tasks.

Links

- Documentation: http://rasbt.github.io/mlxtend
- Source code repository: https://github.com/rasbt/mlxtend
- PyPI: https://pypi.python.org/pypi/mlxtend
- Questions? Check out the Google Groups mailing list

END

lxtend's documentation!

earning extensions) is a Python library of useful tools for the day-to-day data

8 | pypi package 0.18.0 | python 3.6 | python 3.7 | license BSD | discuss google group

Links

- Documentation: http://rasbt.github.io/mlxtend
- Source code repository: https://github.com/rasbt/mlxtend
- PyPI: https://pypi.python.org/pypi/mlxtend
- Questions? Check out the Google Groups mailing list

Feature-engine

- https://www.trainindata.com/feature-engine
- https://feature-engine.readthedocs.io/en/latest/
- https://github.com/solegalli/feature_engine

```
pip install feature-engine

conda install -c conda-forge feature_engine
```

Feature-engine: A Python library for Feature Engineering for Machine Learning

Feature-engine rocks!

Feature-engine is a Python library with multiple transformers to engineer features for use in machine learning models. Feature-engine preserves Scikit-learn functionality with methods `fit()` and `transform()` to learn parameters from and then transform the data.

Feature-engine includes transformers for:

- Missing data imputation
- Categorical variable encoding
- Discretisation
- Variable transformation

Feature Selection

Feature-engine's feature selection transformers are used to drop subsets of variables. Or in other words to select subsets of variables.

- DropFeatures
  - API Reference
  - Example
- DropConstantFeatures
  - API Reference
  - Example
- DropDuplicateFeatures
  - API Reference
  - Example
- DropCorrelatedFeatures
  - API Reference
  - Example
- SmartCorrelatedSelection
  - API Reference
  - Example
- SelectByShuffling

Train In Data

Thank you

www.traininindata.com