Javarevisited

Blog about Java, Programming, Spring, Hibernate, Interview Questions, Books and Online Course Recommendations from Udemy, Pluarlsight etc

Home core java spring hibernate collections multithreading design patterns interview questions coding data structure OOP java 8 books About Me

Java Certifications JDBC jsp-servlet JSON SQL Linux Courses online resources jvm-internals REST Eclipse jQuery Java IO Java XML

FRIDAY, MARCH 24, 2017

Difference between Wait and Sleep, Yield in Java

The difference between wait and sleep or the difference between sleep and yield in Java are one of the popular <u>core Java interview questions</u> and asked on <u>multi-threading interviews</u>. Out of three methods which can be used to pause a thread in Java, sleep() and yield() methods are defined in thread class while wait() is defined in the Object class, which is another interview question. The key difference between wait() and sleep() is that former is used for inter-thread communication while later is used to introduced to pause the current thread for a short duration. This difference is more obvious from the fact that, when a thread calls the wait() method, it releases the monitor or lock it was holding on that object, but when a thread calls the sleep() method, it never releases the monitor even if it is holding.

Coming back to yield(), it's little different than wait() and sleep(), it just releases the CPU hold by Thread to give another thread an opportunity to run though it's not guaranteed who will get the CPU. It totally depends upon thread scheduler and it's even possible that the thread which calls the yield() method gets the CPU again. Hence, it's not reliable to depend upon yield() method, it's just on best effort basis.

Wait vs Sleep vs Yield in Java

Interview Questions

 core java interview question (168)
 Coding Interview Question (72)
 data structure and algorithm (68)
interview questions (46)
SQL Interview Questions (30)
 design patterns (30)
object oriented programming (30)
thread interview questions (30)
 collections interview questions (25)
 spring interview questions (17)
 database interview questions (16)
 servlet interview questions (15)
 Programming interview question (6)
 hibernate interview questions (6)

Best of Javarevisited

How Spring MVC works internally?		
How to design a vending machine in Java?		
How HashMap works in Java?		
Why String is Immutable in Java?		
10 Articles Every Programmer Must Read		
How to convert lambda expression to method		
reference in Java 8?		
10 Tips to improve Programming Skill		

In this Java tutorial, we will learn *what is sleep in Java*, important points of sleep in java *and difference* between Wait and sleep in Java.

<u>Difference between Wait and Sleep in Java</u>



Main difference between wait and sleep is that wait() method release the acquired monitor when thread is waiting while Thread.sleep() method keeps the lock or monitor even if thread is waiting. Also, wait for method in Java should be called from synchronized method or block while there is no such requirement for sleep() method.


Another difference is **Thread.sleep()** method is a static method and **applies on current thread**, while <u>wait()</u> is an instance specific method and only got wake up if some other thread calls notify method on same object. also, in the case of sleep, sleeping thread immediately goes to Runnable state after waking up while in the case of wait, waiting for a thread first acquires the lock and then goes into Runnable state. So based upon your need, if you want to <u>pause a thread</u> for specified duration then use sleep() method and if you want to implement inter-thread communication use wait method.

Here is the list of difference between wait and sleep in Java:

- 1) wait is called from synchronized context only while sleep can be called without synchronized block. see Why to wait and notify needs to call from synchronized method for more detail.
- 2) waiting thread can be awake by calling notify and notifyAll while sleeping thread can not be awakened by calling notify method.
- 3) wait is normally done on condition, Thread wait until a condition is true while sleep is just to put your thread on sleep.
- 4) wait for release lock on an object while waiting while sleep doesn't release lock while waiting.

10 OOP design principles programmer should know		
How Synchronization works in Java?		
10 tips to work fast in Linux		
5 Books to improve Coding Skills		
Java Tutorials		
date and time tutorial (21)		
FIX protocol tutorial (15)		
Java Certification OCPJP SCJP (22)		
java collection tutorial (73)		
java IO tutorial (28)		
Java JSON tutorial (12)		
Java multithreading Tutorials (54)		
Java Programming Tutorials (18)		
Java xml tutorial (16)		
JDBC (29)		
jsp-servlet (37)		
online resources (78)		
Categories		
SQL (53)		
linux (36)		
database (30)		
courses (29)		
Eclipse (28)		
JVM Internals (22)		
Java Certification OCPJP SCJP (22)		
JQuery (16)		
REST (16)		
Testing (11)		
Maven (10)		
general (10)		

5) The wait() method is called on an Object on which the synchronized block is locked, while sleep is called on the Thread. See <u>Core Java, Volume 1 9th Edition</u> by Cay S. Horstmann for more details on how to use wait() and notify method in Java.



Difference between yield and sleep in Java

The major difference between yield and sleep in Java is that yield() method pauses the currently executing thread temporarily for giving a chance to the remaining waiting threads of the same priority to execute. If there is no waiting thread or all the waiting threads have a lower priority then the same thread will continue its execution. The yielded thread when it will get the chance for execution is decided by the thread scheduler whose behavior is vendor dependent. Yield method doesn't guarantee that current thread will pause or stop but it guarantee that CPU will be relinquished by current Thread as a result of a call to Thread.yield() method in java. See Java Concurrency in Practice for more details.

Blog Archive

- ▶ 2018 (84)
- **2017 2017 (858)**
 - ▶ December (101)
 - November (39)
 - October (52)
 - ► September (47)
 - ► August (62)
 - **▶** July (60)
- ▶ June (65)
- ► May (49)
- ► April (80)
- **▼** March (104)

How to use EnumSet in Java with Example

Failed to connect to queue manager - WebSphere $\mbox{MQ} \dots$

Private in Java: Why should you always keep fields...

What is Effectively Final variable of Java 8

How to Compare two String in Java - String Compari...

10 Tips on working fast in UNIX or Linux

How to format Date in SQL Server and Sybase Exampl...

Hibernate NullPointerException due to Space in HQL...

How to loop ArrayList in Java - List Itrator Trave...

What is Assertion in Java - Java Assertion Tutoria...


2 Scenario Based Data Structure and Algorithm Desi...

Sleep method in Java has two variants one which takes millisecond as sleeping time while other which takes both mill and nanosecond for sleeping duration.

```
sleep(long millis)
or
sleep(long millis,int nanos)
```

Causes the **currently executing thread to sleep** for the specified number of milliseconds plus the specified number of nanoseconds.

Here is nice diagram which shows how thread transition happen to different thread states by calling the wait(), sleep() and yield() methods.



- How to Convert and Print Byte array to Hex String ...
- Parsing Large JSON Files using Jackson Streaming A...
- 3 ways to Find First Non Repeated Character in a S...
- Difference between Stack and Queue Data Structure ...
- How to Reverse Array in Place in Java? Solution Wi...
- Difference between WeakReference vs SoftReference ...
- Java 1.5 Generics Tutorial: How Generics in Java w...
- 10 Exception handling Best Practices in Java Progr...
- Difference between start and run method in Thread ...
- Difference between Wait and Sleep, Yield in Java
- Top 10 Servlet Interview Question Answers J2EE
- Difference between Stack and Heap memory in Java
- Why use PreparedStatement in Java JDBC Example T...
- SimpleDateFormat in Java is not Thread-Safe Use Ca...
- How to find file and directory size in Unix with $\ensuremath{\text{E...}}$
- How to Reverse a Linked List in Java Using Recursi...
- How Garbage Collection works in Java
- 10 difference between Java and JavaScript for Prog...
- Difference between transient and volatile keyword ...

Example of Thread.sleep() method in Java

Here is sample code example of Sleep <u>Thread in Java</u>. In this example, we have put Main thread in Sleep for 1 second.

```
* Example of Thread Sleep method in Java
public class SleepTest {
       public static void main(String... args) {
              System.out.println(Thread.currentThread().getName() + "
is going to sleep for 1 Second");
              try {
                     Thread.currentThread().sleep(1000);
              } catch (InterruptedException e) {
                     // TODO Auto-generated catch block
                     e.printStackTrace();
              System.out.println("Main Thread is woken now");
Output:
main is going to sleep for 1 Second
Main Thread is woken now
```

- How to fix java.io.FileNotFoundException: (Access ...
- Top 10 basic networking commands in linux/unix
- How to Reverse an Array in Java Integer and Stri...
- Top 30 Scala and Functional Programming Interview ...
- Binary Search vs Contains Performance in Java List...
- How to check if two String are Anagram in Java P...
- How to Generate MD5 Hash in Java String Byte Arr...
- What is difference between SQL, T-SQL and PL/SQL?
- 5 ways to Convert Java 8 Stream to List Example,...
- 2 Examples of Streams with Collections in Java 8
- Difference between First and Second Level Cache in...
- How to enclose a list of values into single quotes...
- Can You Overload or Override Static methods in
- Java Synchronization Tutorial : What, How and Why?...
- How to Check if a Number is Binary in Java Progr...
- What is Daemon thread in Java and Difference to No...
- How to get ServletContext in Servlet, JSP, Action ...
- How to Convert an Array to Comma Separated String ...
- Top 15 Data Structures and Algorithm Interview Que...

10 points about Thread sleep() method in Java

I have listed down some important and worth to remember points about Sleep() method of Thread <u>Class in Java</u>:

- 1) Thread.sleep() method is used to pause the execution, relinquish the CPU and return it to thread scheduler.
- 2) Thread. The sleep() method is a <u>static method</u> and always *puts the current thread to sleep*.
- 3) Java has two variants of sleep method in Thread class one with one argument which takes milliseconds as the duration of sleep and another method with two arguments one is millisecond and other is the nanosecond.
- 4) Unlike <u>wait() method in Java</u>, sleep() method of Thread class **doesn't relinquish the lock** it has acquired.
- 5) sleep() method **throws Interrupted Exception** if another thread interrupts a sleeping thread in java.
- 6) With sleep() in Java it's not guaranteed that when sleeping thread woke up it will definitely get CPU, instead it will go to Runnable state and fight for CPU with other thread.
- 7) There is a **misconception** about sleep method in Java that calling t.sleep() will put Thread "t" into sleeping state, that's not true because Thread.sleep method is a static method it always put the current thread into Sleeping state and not thread "t".

That's all on **Sleep method in Java**. We have seen the **difference between sleep and wait** along with **sleep and yield in Java**. In Summary, just keep in mind that both sleep() and yield()

- Why character array is better than String for Stor...
- JDBC java.lang.ClassNotFoundException:
 com.mysql...
- How to find Largest Prime Factor of a Number in Ja...
- Mixing static and non static synchronized method
- Why use Underscore in Numbers from Java SE 7 Und...
- What is Method References in Java 8? An Example
- Difference between Struts 1 and Struts 2 Web Devel...
- 10 Hibernate Interview Questions and Answers for J...
- How to delete a directory with files in Java Exa...
- Bitwise and BitShift Operators in Java AND, OR,
- How to Clone Collection in Java Deep copy of $$\operatorname{\Delta rr}$$
- How to Remove First and Last Character of String i...
- Difference between Singleton Pattern vs Static Cla...
- What is GET and POST method in HTTP and HTTPS Prot...
- Top 5 Advanced SQL Books for Experienced Programme...
- What is Static and Dynamic binding in Java with Ex...
- 10 points on finalize method in Java Tutorial Ex...
- What is Encapsulation in Java and OOPS with Exampl...
- 10 example of chmod command in UNIX Linux

operate on the current thread.

Further Learning

Multithreading and Parallel Computing in Java

Java Concurrency in Practice - The Book

Applying Concurrency and Multi-threading to Common Java Patterns

Java Concurrency in Practice Course by Heinz Kabutz

Java Tutorial you may like:

Difference between ArrayList and Vector in Java

How SubString works in Java

Difference between SynchronizedCollection and ConcurrentCollection in Java

Why the main method is Static in Java

How Volatile keyword works in Java

Difference between Comparator and Comparable in Java

<u>Difference between ClassNotFoundException and NoClassDefFoundError in Java</u>

By Javin Paul at March 24, 2017

Labels: core java, Java multithreading Tutorials, thread interview questions

Location: United States

19 comments:

Java Tutorial said...

Moreover, developers can look at the java source for these methods to get more insight into <u>java multithreading</u> <u>tutorial</u>

January 8, 2012 at 8:53 AM

Anonymous said...

Thread.currentThread().sleep(1000);

Java 8 Date Time - 20 Examples of LocalDate, Local...

Top 50 Java Thread Interview Questions Answers for...

How to Increase Console Buffer Size in Eclipse IDE...

How to Implement Stack in Java Using Array and Gen...

Top 10 EJB Interview Question and Answer asked in ...

How to Find Largest and Smallest Number in Given I...

java.lang.UnsatisfiedLinkError: no dll in java.lib...

ReentrantLock Example in Java, Difference between ...

Why we use Threads in Java?

How to read Properties File in Java - XML and Text...

Top 20 FIX Protocol Interview Questions

Top 10 MQ Series Interview Questions Answers - Web...

How to add or list certificates from keystore or t...

10 Examples of curl Command in UNIX and Linux

How to create Immutable Class and Object in Java -...

Tibco tutorial: Tibco RV tips and commands

Tibco Tutorial: Fundamentals of Tibco RV messaggi...

TIBCO Tutorial: TIBCO Rendezvous or TIBCO RV me...

What is the use of class "java.lang.Class" in Java...

Why Comparing Integer using == in Java 5 is Bad?

should be written as

Thread.sleep(1000);

since sleep is a static method

June 4, 2012 at 8:34 PM

Javin @ Semaphore Example Java said...

Hi @Anonymous, yes it Thread.sleep() is absolutely Ok and static method should be called like that but I still like Thread.currentThread().sleep() because its much clearer on saying that current thread is going to sleep.

June 5, 2012 at 5:28 AM

Bhuneswar said...

Don't rely on Thread.yield method, in one JVM yield method may produce desired result but may not work on other JVM. Instead of using yield method use Thread.sleep(1) but don't use Thread.sleep(0) which will return immediately.

August 7, 2012 at 10:09 PM

Anonymous said...

What is the state of Thread, when we call sleep(), wait() or yeild() methods? This questions was asked to me on JP Morgan Interview.

April 16, 2013 at 8:12 PM

Pushkar said...

A thread can be in WAITING or TIMED_WAITING state, due to a call to wait() or sleep() method. If you call wait and sleep without timeout then Thread will be in WAITING (ThreadState.WAITING) state, while a call to sleep() and wait() without timeout will leave thread in TIMED_WAITING state. Difference between WAITING and TIMED_WAITING state is timeout, which means thread will come out once timeout is expired.

April 16, 2013 at 8:21 PM

Anonymous said...

i got confused in wait and sleep..please clarify more..

June 14, 2013 at 1:16 AM

sj_said...

- What is Abstraction in Java? Abstract Class or Int...
- Fundamentals of Object Oriented Programming in Jav...
- How to check if a thread holds lock on a particula...
- Why String is Immutable or Final in Java
- Difference between map() and flatMap() in Java 8 S...
- How to avoid deadlock in Java Threads
- Covariant Method Overriding of Java 5 Coding Bes...
- 10 Singleton Pattern Interview Questions in Java -...
- What is difference between Enumeration and Iterato...
- What is difference between HashMap and Hashtable i...
- java.lang.NoSuchMethodError: main Exception in thr...
- How to create and execute JAR file in Java Comma...
- ► February (88)
- ► January (111)
- ▶ 2016 (135)

References

- 1. Oracle's Java Tech Network
- 2. jQuery Documentation
- 3. Microsoft SQL Server Documentation
- 4. Java SE 8 API Documentation
- 5. <u>Spring Documentation</u>
- 6. Oracle's JAva Certification

Does using Thread.sleep(few minutes) puts a load on CPU?

I mean i am executing a method that consumes CPU heavily (actually it will zip a large text file).

So, after that method i want current thread to sleep for few minutes before calling the method again to archive another file. I am doing this so that other programs can also run smoothly.

November 26, 2014 at 1:54 AM

Anonymous said...

i need to execute a job like it has to run execute for one minute and other minute on idle, while it was on idle other function has to run.it works for 24/7, can you please help on this?

January 10, 2015 at 11:21 AM

Anonymous said...

Please, could you explain this statement further:

"... There is a misconception about sleep method in Java that calling t.sleep() will put Thread "t" into sleeping state, that's not true because Thread.sleep method is a static method it always put current thread into Sleeping state and not thread "t""

April 26, 2015 at 11:53 AM

Anonymous said...

Balvinder said,

But if the thread which executes yield is not release the lock then how it allows the other thread to execute? Because without acquiring the lock no one thread can allowed to execute.

May 3, 2015 at 1:31 PM

sarath said...

Please, could you explain this statement further:

"... There is a misconception about sleep method in Java that calling t.sleep() will put Thread "t" into sleeping state, that's not true because Thread.sleep method is a static method it always put current thread into Sleeping state and not thread "t""

There is no use in writing t1.sleep or t2.sleep, since t1.sleep/t2.sleep always puts the current thread.sleep. i.e. Asking t2.sleep from t1's code is meaningless.

<u>September 25, 2015 at 8:04 PM</u>

Javin Paul said...

7. Spring Security 5 Documentation

Pages

Privacy Policy

Copyright by Javin Paul 2010-2018. Powered by Blogger.

@Sarath, right way to call sleep() method is Thread.currentThread().sleep(), it's not advised to call static method on instances, even thought compiler allows it, it's not recommended because of confusion it creates.

September 25, 2015 at 9:34 PM

Anonymous said...

Ηi,

Thanks for the post. In the thread lifecylce diagram, there is an issue. From 'sleeping' state to 'ready-t-run' state transition will happen by interruption or after completion of sleep time. However, it is incorrectly written as notify.

June 26, 2016 at 11:14 AM

Javin Paul said...

@Anonymous, good catch. You are right a thread will go to sleeping to ready to run state after sleep duration finished or interruption.

June 27, 2016 at 5:10 AM

Jason Huang said...

the diagram shows the sleeping thread is wake up by "object.notify or object.notifyAll" ??? so a notify could wake up a sleep thread ?

May 8, 2017 at 8:18 AM

Javin Paul said...

@Jason, no, if it is sleeping due to Thread.sleep() it cannot wake it up.

May 9, 2017 at 5:54 AM


Aniket Thakur said...

You have yourself mentioned - "waiting thread can be awake by calling notify and notifyAll while sleeping thread can not be awakened by calling notify method". However your diagram says otherwise. Need to correct that. Since sleep() does not release lock - notify() or notifyAll() does not come into picture.

May 14, 2017 at 8:56 AM

Javin Paul said...

@Aniket, the diagram is incorrect on that front, sleep() doesn't release lock hence no need to call notify or notifyall to inform other waiting threads.



Newer Post <u>Home</u> <u>Older Post</u>

Subscribe to: Post Comments (Atom)

Search This Blog

Search