בכל העמודים.

SCAN-MASTER

UT INSPECTION REPORT

Report ~~Document~~ No: -
Report ~~Revision~~ manifcater No:
Date: Feb 28, 2026

Page no: 1 of —

שכבה רבה בקבר הדוגמאות, הבחון בעדיפות.

DOCUMENT SUMMARY

Customer	-	PO Number	-
Part Number	-	Part Name	-
Material	-	Cast/Heat N°	-
Document N°	-	Revision	0
Test Standard	-	Test Method	UT
Issue Date	Feb 28, 2026	Results	-

PART INFORMATION

Description: -
Drawing N°: -
Lot N°: -
Batch N°: -
Heat Treatment: -
Thickness: -
Surface Roughness: - ≤ 6.3 Um
Surface Condition: - ~~≤ 6.3 Um~~ ~~Roughness~~

QUANTITY & SERIAL NUMBERS

Work Order: -
Quantity: -
Serial Numbers: -

TESTING DETAILS

Test Methods: ☐ RT ☐ MT ■ UT ☐ PT ☐ OT
Scan Type: immersion
Equipment: -
~~TCG Applied:~~ No
Technique Sheet: -

OBSERVATIONS & RESULTS

No recordable indications detected during ultrasonic examination.

CONFORM

Report issued By	Approved By	Autorzed By (customer or manifacturer)
Date	Date	Date

בכל העמודים.

Scanned with CamScanner

תיקון בגלל הבדיקה.

OBSERVATIONS & RESULTS

Part inspected	Conforming Parts	Non Conforming Part
3	—	—

Test results

S/N	Scan direction	indication Amplitude	indication size	Location	Assesment
			depth - type - Length		

if needed → ☐ Add C-Scan image result.

אפשרות להכלל תמונה של הסריקה עם הסימנים בה.

Scanned with CamScanner

EQUIPMENT DETAILS

Ultrasonic Generator

Make: SM - Model: 2000 - Serial N°: 2001 -

Calibration Date: - 2/26

~~Transducers~~

Immersion:

Model: Olympus - Serial N°: - ~~Cal. Date:~~ -

Contact:

Model: - Serial N°: - Cal. Date: -

Scan ~~Parameters~~ Ditail

Frequency: - Probe Diameter: - Water Path: -

Software

Name: - Version: - Config: -

Calibration Block ~~(ASTM E127)~~

Serial N°: - Material: -

Thickness: - Valid Until: -

☐ NIST Traceable

לבצע בל התאמה של הסרגל עם הנתונים
מתוך הטבלה Scan Ditails

לבצע הרמלה של הבמאי כולל.
נרמל / בגיה. כולל הטבלה של ה- FBH

Scanned with CamScanner

AEROSPACE FORGING UT PARAMETERS

Per AMS-STD-2154 / ASTM E2375 / ASTM A388

Test Location & Timing

Location:	-	Facility:	-	Test Date:	2026-02-28
Start Time:	-	End Time:	-	Duration:	-

Environmental Conditions

Ambient Temp:	-	Part Temp:	-
~~Humidity:~~	-	~~Lighting:~~	-

Couplant Details (AMS-STD-2154)

Type:	-	Manufacturer:	-	Batch:	-
~~Sulfur Content:~~	~~< 250 ppm~~		~~Halide Content:~~	~~< 250 ppm~~	

Forging Information

Type:	ring	Grain Flow:	-	Ratio:	-

Inspection Directions: ■ Axial ■ Radial ☐ Circumf. ☐ Angle Beam

Sensitivity & Reference (AMS-STD-2154)

Ref FBH Size:	3/64"	FBH Depth:	-	Ref Level:	-
Scanning Sens:	+6 dB	Recording Level:	20%	Rejection Level:	100%

Transfer Correction

Cal Block BWE:	80%	Part BWE:	-	Correction:	-

Back Wall Echo Monitoring (ASTM A388)

Threshold:	50%	Loss Recorded:	-
Gate Start:	-	Gate End:	-

Scan Index & Coverage

Index:	-	Overlap:	10%	Coverage:	100%

Scanned with CamScanner

REMARKS

No additional remarks.

RESULTS SUMMARY

Parts Inspected:	0	**Conforming:**	-	**Non-Conforming:**	-

INSPECTOR CERTIFICATION

Level:	-	**Standard:**	EN 4179
Certificate N°:	-	**Expiry Date:**	-

APPROVAL SIGNATURES

PREPARED BY	APPROVED BY	WITNESS
Date:	Date:	Date:

Scanned with CamScanner