

Heat Shrink Thin Wall Tubes - Suitable upto 3.3 kV



AEX Heat Shrink Thin Wall Tubes are suitable for following applications:

- Wire harnessing for electrical & electronic applications.
- Provides electrical insulation and protection for in-line components.
- Used as strain relief for electrical wire connection.
- Bus-bar insulation for switchgear.
- Color coding for wires, cables, terminals and components.

KEY FEATURES AND BENEFITS:

- Halogen free, Flame retardant and self-extinguishing
- For Electrical Insulation up to 3.3 kV
- Standard Colors: Black, White, Yellow, Red, Blue, Green and Yellow/Green.
- Shrink ratio 2:1
- UV stabilized
- Meets RoHS Compliance

Technical Properties

Test Description	Typical Value	Test Method
Tensile Strength	15 N/mm ² (Min.)	ASTM D638
Elongation	300% (Min.)	ASTM D638
Density	1.4	ASTM D792
Longitudinal Change	- 10% (Max.)	ASTM D2671
Water Absorption	0.15% (Max.)	ASTM D570
Low Temp. Flexibility (-55°C for 4 Hrs.)	No Cracking	ASTM D2671
Heat Shock (250°C for 4 Hrs.)	No Cracking	ASTM D2671
Continuous Operating Temp.	-55°C to 125°C	IEC 216
Flammability	Pass	UL 224 VW1
Copper Corrosion Resistance	Good	ASTM D2671
Chemical Resistance	Good	ASTM D2671
Volume Resistance	1x10 ¹³ Ohm.cm (Min.)	ASTM D257
Di-electric Strength	20 kV/mm (Min.)	ASTM D149

Selection Chart

Product Code	Supplied I.D. (mm)	Recovered I.D. (mm)	Recovered Wall Thick. (mm)	Spools Mtr./Spool
ATW 1.0/0.5	1.0	0.5	0.28	200
ATW 1.5/0.75	1.5	0.75	0.32	200
ATW 2.0/1.0	2.0	1.0	0.35	200
ATW 2.5/1.25	2.5	1.25	0.44	200
ATW 3.0/1.5	3.0	1.5	0.44	200
ATW 4.0/2.0	4.0	2.0	0.44	200
ATW 5.0/2.5	5.0	2.5	0.56	100
ATW 6.0/3.0	6.0	3.0	0.56	100
ATW 7.0/3.5	7.0	3.5	0.56	100
ATW 8.0/4.0	8.0	4.0	0.56	100
ATW 10.0/5.0	10.0	5.0	0.56	100
ATW 12.7/6.35	12.7	6.35	0.56	100
ATW 14.0/7.0	14.0	7.0	0.69	100
ATW 15.0/7.5	15.0	7.5	0.69	100
ATW 16.0/8.0	16.0	8.0	0.69	100
ATW 18.0/9.0	18.0	9.0	0.69	100
ATW 20.0/10.0	20.0	10.0	0.78	100
ATW 25.0/12.5	25.0	12.5	0.78	50
ATW 30.0/15.0	30.0	15.0	0.87	50
ATW 35.0/17.5	35.0	17.5	0.97	50
ATW 40.0/20.0	40.0	20.0	0.97	50
ATW 50.0/25.0	50.0	25.0	0.97	25
ATW 60.0/30.0	60.0	30.0	0.96	25
ATW 70.0/35.0	70.0	35.0	1.10	25
ATW 80.0/40.0	80.0	40.0	1.27	25
ATW 100/50.0	100.0	50.0	1.17	25
ATW 120.0/60.0	120.0	60.0	1.17	25

Product Code for Yellow Green Shall be ATW-YG

