

"श्री कृष्ण गोविंद हरे मुरारी, हे नाथ नारायण वासुदेवा"

Data Structure and Algorithm

By

Malay Tripathi

BINARY
SEARCH³

FIRST AND LAST OCCURENCES IN ARRAY + COUNT OCCURENCES

Q. find the first and last occurrence of element x .

arr = [2, 4, 6, 8, 8, 8, 11, 13]

ind → 0 1 2 3 4 5 6 7

So, we have to find first and last occurrence index of x .

$x=8$

first index of occur. → { 3, 5 } → last index of occur.

$x=10$

first index of occur. → { -1, -1 } → last index of occur.

$x=11$

first index of occur. → { 6, 6 } → last index of occur.

LINEAR SEARCH

arr = [2 4 6 8 8 8 11 13]
 0 1 2 3 4 5 6 7
→ When we find $x=8$
first = -1 last = -1
3 -----> last = 5
3 -----> 5

{ 3, 5 }

first = -1, last = -1

for ($i=0$ to $n-1$)

{ if (arr[i] == x)

{ if (first == -1)

first = i

last = i

}

}

TIME COMPLEXITY = $O(N)$

“श्री कृष्ण गोविंद हरे मुरारी, हे नाथ नारायण वासुदेवा”

Data Structure and Algorithm

By

Malay Tripathi

As we know that the given array is sorted, we can apply Binary Search for first and last Occurrence.

arr = [2, 4, 6, 8, 8, 8, 11, 13]

as we know about upper bound and lower bound.

lower bound \rightarrow that it is smallest index, $A[\text{index}] \geq x$

upper bound $\rightarrow A[\text{index}] > x$

given me lower bound of (8) $\rightarrow A[\text{ind}] \geq 8 \rightarrow$ it will point at index 3

give me upper bound of (8) $\rightarrow A[\text{index}] > 8 \rightarrow$ it will point at index 6

arr = [2, 4, 6, 8, 8, 8, 11, 13]

lower bound

upper bound

$[\text{upperbound}(8) - 1]$

it will not covering all the cases, if the value is not in array

for $x=10$,

since 10 is not in array, you will get 11 as the lower bound.

$x=14$

$\text{lb}(14)$

\rightarrow it is start pointing hypothetical index of 8.

if $(\text{lb} == n \ || \ (arr[\text{lb}] != x))$ return $\{-1, -1\}$;

means element is not present in the array.
return $\{\text{lb}, \text{upperBound}(arr, n, x) - 1\}$;

Data Structure and Algorithm

Malay Tripathi

TIME COMPLEXITY = $2 * O(\log_2 n)$

USE SIMPLE BINARY SEARCH

$$\therefore \text{mid} = \frac{0+7}{2} = 3.5 \approx 3$$
$$\text{arr} = [2, 8, 8, 8, 8, 8, 11, 13]$$
$$\text{arr} = [2, 8, 8, 8, 8, 8, 11, 13]$$

low mid high

$$\text{first} = -1/31$$


```
arr = [2, 8, 8, 8, 8, 8, 11, 13]
```

$\uparrow \uparrow$
too high \rightarrow this element is not equal to x , thus we have to move
in the right search space.

“श्री कृष्ण गोविंद हरे मुरारी, हे नाथ नारायण वासुदेवा”
Data Structure and Algorithm

By
Malay Tripathi

arr = [2, 8, 8, 8, 8, 8, 11, 13]




low crosses high, thus first = ~~3~~ 1

FIRST OCCURENCE = 1

// FIND LAST OCCURENCE. 0 1 2 3 4 5 6 7
arr = [2, 8, 8, 8, 8, 8, 11, 13]

last = -1

Last = ~~3~~



$$* \text{ mid} = \frac{4+7}{2} = 5$$

arr[mid] = 8 = 8, last = ~~3~~ 5

$$* \text{ mid} = \frac{6+7}{2} = 6$$

arr[mid] = arr[6] = 11

8 ≠ 11. So we can't find 8 on the right.

Last occurrence = 5

"श्री कृष्ण गोविंद हरे मुरारी, हे नाथ नारायण वासुदेवा"

Data Structure and Algorithm

By

Malay Tripathi

Pseudo Code for first Occurrence.

```
fn(arr, n, x)
{
    low = 0, high = n-1
    first = -1
    while (low <= high)
    {
        mid = (low + high) / 2
        if (arr[mid] == x)
            first = mid, high = mid-1
        else if (arr[mid] < x)
            low = mid + 1
        else
            high = mid-1
    }
```

Pseudo Code for last Occurrence.

```
fn(arr, n, x)
{
    low = 0, high = n-1;
    last = -1;
    while (low <= high)
    {
        mid = (low + high) / 2
        if (arr[mid] == x)
            last = mid;
            low = mid + 1;
        else if (arr[mid] < x)
            low = mid + 1
        else
            high = mid-1;
    }
```

pair <int, int> firstAndLastPosition (vector <int> &arr, int n, int k)

```
{
    int first = firstOccurrence(arr, n, k);
    if (first == -1) return {-1, -1};
    int last = lastOccurrence(arr, n, k);
    return {first, last};
}
```

“श्री कृष्ण गोविंद हरे मुरारी, हे नाथ नारायण वासुदेवा”

Data Structure and Algorithm

By

Malay Tripathi

COUNT TOTAL NUMBER OF OCCURENCE OF X.

$(\text{last occurrence} - \text{first occurrence}) + 1 = \text{total no. of } x \text{ element in the array.}$

```
int count (vector<int> &arr, int n, int x) {  
    pair<int, int> ans = firstAndLastPosition (arr, n, x);  
    if (ans.first == -1) return 0;  
    return ans.second - ans.first + 1;  
}
```