

Katana Pay API v2

Create an order, send the customer to pay, get told the result. Two endpoints, one webhook, four statuses.

Webhooks are notifications; they can fail or retry. Always confirm order status by calling GET `/v2/orders/{id}` before fulfilling.

1. Keys and modes
2. Create an order
3. Read an order
4. The four statuses
5. Webhooks
6. Verify the signature
7. Retries, resend and test events
8. Errors
9. If you are on v1 today

1. Keys and modes

Every request carries your API key in a header, over HTTPS:

```
Authorization: Bearer sk_live_...
```

Create keys in the portal under **Webhooks & keys**. A key is shown once, when it is made.

Key	Orders it creates
sk_test_...	Test orders. No money moves. Use amounts ending <code>.99</code> to get a success, <code>.13</code> a failure and <code>.11</code> an expiry (for example <code>10099</code> , <code>10013</code> , <code>10011</code>).
sk_live_...	Live orders. Available once live mode is activated for your account.

The key decides the mode. A test key cannot read a live order, and a live key cannot read a test one.

2. Create an order

```
POST https://katanapay.co/v2/orders
Authorization: Bearer sk_live_...
Content-Type: application/json

{
  "amount": 200000,
  "currency": "INR",
  "reference": "inv-1001",
  "callback_url": "https://your-server.example/katana/webhook",
  "metadata": { "cart": "42" }
}
```

Field		Meaning
amount	required	An integer in minor units (paise). 200000 is ₹2,000.00.
currency	optional	INR , the default and the only value accepted.
reference	required	Your own id for the order, up to 60 characters, unique within your account. Sending the same reference again returns the same order, so a retry after a timeout is safe.
callback_url	optional	Where this order's webhook goes. Without it, the callback URL saved in the portal is used.
return_url	optional	Where the customer's browser is sent after paying.
flow	optional	P2P or INTENT . Leave it out: your account's own setting is used.
metadata	optional	Up to 20 keys of your own notes. Given back when you read the order.

Answer, 201 for a new order and 200 for a reference you already used:

```
{
  "order_id": "KTN_3f2b8c1e9a4d4e6f8b7a0c1d2e3f4a5b",
  "reference": "inv-1001",
  "status": "PENDING",
  "checkout_url": "https://katanapay.co/pay/3f2b8c1e-9a4d-4e6f-8b7a-0c1d2e3f4a5b",
  "expires_at": "2026-10-02T14:15:00.000Z"
}
```

Send the customer's browser to checkout_url . Keep order_id or your own reference ; either reads the order back.

3. Read an order

```
GET https://katanapay.co/v2/orders/inv-1001
GET https://katanapay.co/v2/orders/KTN_3f2b8c1e9a4d4e6f8b7a0c1d2e3f4a5b
Authorization: Bearer sk_live_...
```

The path takes Katana's `order_id` or your own `reference` . The answer is the same object a webhook carries, so one piece of code handles both, plus `checkout_url` , `expires_at` , `created_at` , `livemode` and your `metadata` .

```
{
  "event": "payment.success",
  "event_id": "evt_9c1d...",
  "order_id": "KTN_3f2b8c1e9a4d4e6f8b7a0c1d2e3f4a5b",
  "reference": "inv-1001",
  "status": "SUCCESS",
  "amount": 200000,
  "currency": "INR",
  "rrn": "123456789012",
  "rrn_is_synthetic": false,
  "paid_at": "2026-10-02T14:32:00.000Z",
  "gateway": null,
  "checkout_url": null,
  "expires_at": null,
  "created_at": "2026-10-02T14:00:00.000Z",
  "livemode": true,
  "metadata": { "cart": "42" }
}
```

While an order is `PENDING` , `event` and `event_id` are `null` .

4. The four statuses

Status	Meaning	Can it still change?
PENDING	The order was created and is waiting for the payment.	Yes.
SUCCESS	The payment is confirmed.	No. This is final.
FAILED	The payment was declined, or failed in a way that cannot be recovered.	Only to <code>SUCCESS</code> , if the customer tries again on the same order and pays.

`EXPIRED` No payment was confirmed in time.

Only to `SUCCESS` : a payment the bank authorised late still counts.

The customer has 15 minutes to pay. `expires_at` is when a `PENDING` order is given up on and you are told `EXPIRED` . For an order paid on a payment processor's page that can be later than the 15 minutes: once the customer's time is over the order may be kept `PENDING` for a further period while the payment is confirmed, and in that period the customer cannot start a new payment on it. `expires_at` already includes that period, so wait for it, or for the webhook, before you treat the order as unpaid.

An order told `EXPIRED` or `FAILED` can become `SUCCESS` afterwards. You are then sent `payment.success` with `"previous_status": "EXPIRED"` (or `"FAILED"`). Do not treat an expiry as the last word on money: read the order before you refuse to deliver.

`rrn` is the bank's reference for the payment. When `rrn_is_synthetic` is `true` , the bank gave Katana no reference and the value was made by Katana: it identifies the payment to Katana support, but it does not appear on a bank statement.

`gateway` is always `null` .

5. Webhooks

When an order reaches `SUCCESS` , `FAILED` or `EXPIRED` , Katana sends an HTTP `POST` to the order's `callback_url` :

```
POST /katana/webhook
Content-Type: application/json
X-Katana-Event: payment.success
X-Katana-Signature: t=1790951520,v1=5f8a...c2
X-Katana-Event-ID: evt_9c1d...

{
  "event": "payment.success",
  "event_id": "evt_9c1d...",
  "order_id": "KTN_3f2b8c1e9a4d4e6f8b7a0c1d2e3f4a5b",
  "reference": "inv-1001",
  "status": "SUCCESS",
  "previous_status": "EXPIRED",
  "amount": 200000,
  "currency": "INR",
  "rrn": "123456789012",
  "rrn_is_synthetic": false,
  "paid_at": "2026-10-02T14:32:00.000Z",
  "gateway": null
}
```

Event	Status	Sent when
payment.success	SUCCESS	The payment is confirmed.
payment.failed	FAILED	The payment failed.
payment.expired	EXPIRED	The order's time ran out with no payment.

- `previous_status` is present only when a `SUCCESS` follows an `EXPIRED` or a `FAILED`.
- `rrn` and `paid_at` are `null` unless the status is `SUCCESS`.
- Answer with any `2xx` within 8 seconds. Anything else is a failed delivery and is retried.
- Use `event_id` to ignore a delivery you have already processed: every retry of an event carries the same id.

In the portal you choose which outcomes you are sent: **Receive all outcomes** (the default) or **Receive paid only**, which sends `payment.success` alone and leaves you to read the status of the other orders.

6. Verify the signature

The signature proves the delivery came from Katana and was not altered. Your webhook secret (`whsec_...`) is shown once in the portal when you move to v2 or replace it.

```
signed_payload = "{t}.{raw request body}"
v1              = hex( HMAC-SHA256( key = webhook secret, message = signed_payload ) )
```

Sign the body exactly as it arrived, before parsing it. Refuse a delivery whose `t` is more than 300 seconds from your clock.

Node.js

```
const [t, v1] = req.headers["x-katana-signature"].split(",").map((p) => p.split("=")[1]);
const expected = crypto.createHmac("sha256",
WEBHOOK_SECRET).update(`${t}.${rawBody}`).digest("hex");
const fresh = Math.abs(Date.now() / 1000 - Number(t)) <= 300;
const valid = fresh && crypto.timingSafeEqual(Buffer.from(v1), Buffer.from(expected));
if (!valid) return res.status(400).end();
```

PHP

```
parse_str(str_replace(",", "&", $_SERVER["HTTP_X_KATANA_SIGNATURE"]), $sig);
$raw      = file_get_contents("php://input");
$expected = hash_hmac("sha256", $sig["t"] . "." . $raw, $WEBHOOK_SECRET);
$valid    = abs(time() - (int) $sig["t"]) <= 300 && hash_equals($expected, $sig["v1"]);
if (!$valid) { http_response_code(400); exit; }
```

Python

```
sig = dict(p.split("=", 1) for p in request.headers["X-Katana-Signature"].split(","))
expected = hmac.new(WEBHOOK_SECRET.encode(), f"{sig['t']}".encode() + raw_body,
hashlib.sha256).hexdigest()
fresh = abs(time.time() - int(sig["t"])) <= 300
if not (fresh and hmac.compare_digest(expected, sig["v1"])):
    abort(400)
```

7. Retries, resend and test events

A delivery your server does not answer with `2xx` is tried again: 7 attempts in all over about 31 hours, the first at once and the rest 1 minute, 5 minutes, 15 minutes, 1 hour, 6 hours and 24 hours after the attempt before. Every attempt carries the same `event_id`. After the last one the delivery is marked as given up and Katana's operations team is told.

In the portal:

- **Orders** finds any order by its order id, your reference or the bank reference, and shows each status change and every delivery attempt: when it was sent, what your server answered and how long it took.
- **Resend**, on a delivery, queues the same event again. It is a new delivery, so it has a new `event_id`.
- **Send test event** sends a sample of each event to your saved callback URL. A sample has the reference `test-event` and belongs to no order.
- **API log** lists your requests of the last 7 days with their status and latency.

8. Errors

Every `4xx` and `5xx` answer has the same shape:

```
{ "code": "ORDER_NOT_FOUND", "message": "no order with that id or reference", "reference": "req_5b1c..." }
```

Branch on `code`; `message` is for a person. `reference` is the id of the request, also in the `X-Request-Id` header: quote it to Katana support. Send your own `X-Request-Id` and it is used instead.

Code	HTTP	Meaning
<code>HTTPS_REQUIRED</code>	400	The request was not made over HTTPS.
<code>INVALID_REQUEST</code>	400	A field is missing or malformed; the message names it.
<code>UNSUPPORTED_CURRENCY</code>	400	Only INR is accepted.
<code>UNAUTHORIZED</code>	401	The API key is missing, unknown or revoked.
<code>MERCHANT_BLOCKED</code>	403	The account is blocked and takes no orders.
<code>MERCHANT_SUSPENDED</code>	403	The account is suspended or terminated.
<code>PAYIN_NOT_ENABLED</code>	403	The account is set up for payouts only and takes no pay-in orders.
<code>LIVE_MODE_NOT_ACTIVATED</code>	403	A live key was used before live mode was activated.
<code>ORDER_NOT_FOUND</code>	404	No order with that id or reference belongs to this key.
<code>REFERENCE_REUSED</code>	409	The reference already belongs to an order with a different amount.
<code>FLOW_NOT_SELECTED</code>	409	No pay-in flow has been selected for the account yet.
<code>FLOW_NOT_ENABLED</code>	409	The requested flow is not enabled for the account.
<code>FLOW_NOT_READY</code>	409	The account's flow cannot take this payment yet.

SETUP_INCOMPLETE	409	The account has no way to take this payment; contact Katana support.
ACCOUNT_NOT_LIVE	409	Live payments on the account are still being verified.
AMOUNT_BELOW_MIN	422	The amount is under the minimum.
AMOUNT_ABOVE_MAX	422	The amount is over the account's maximum.
UPI_LIMIT_EXCEEDED	422	The amount is over the limit for one UPI payment.
DAILY_LIMIT_EXCEEDED	422	The order would pass the account's limit for the day.
RATE_LIMITED	429	Too many orders in one second; retry after the Retry-After header.
PROCESSOR_ERROR	502	The payment processor did not accept the request; retry with the same reference.
INTERNAL_ERROR	500	Something failed on Katana's side; retry with the same reference.

After a `5xx` , or a timeout, send the same request again with the same `reference` : you get the order that was created, never a second one.

9. If you are on v1 today

Nothing changes for you until you choose to. The v1 endpoints and the v1 callback keep working as they are.

- The webhook version is a setting on your account, in the portal under **Webhooks & keys**: `v1` or `v2` . Existing accounts stay on v1 until they switch; new accounts start on v2. You can switch back.
- The setting decides the callback for every order of the account, whichever API created it.
- v2 has no request signature and no Salt: the API key in the header is the credential, and the webhook is verified with the webhook secret.
- Amounts are integers in paise in v2, not rupee strings.
- In v2 the paid status is the word `SUCCESS` , in the request log, the status API and the webhook alike.