

Quiz 1

Consider the following code snippet.

```
z = torch.matmul(w,x) + b
```

```
y = z * z
```

```
y.backward()
```

Question 1

1.0/1.0 point (graded)

Let x , w are rank-one tensors of same dimension and b is rank-zero tensor. Required grad for w is true, and x is false. Consider the code snippet given above. Then the value of $w.grad$ is equal to?

$2 * (\text{torch.matmul}(w,x) + b)$


$2 * (x + b)$

$2 * (\text{torch.matmul}(w,x) + b) * x$ ✓

$2 * (w * x + b) * x$

Submit

You have used 1 of 2 attempts



Question 2

0.0/1.0 point (graded)

You have to learn a classification model for the above two-dimensional dataset. Orange points belong to class zero, and blue points belong to class one, which of the following model has the potential to learn?

Single-layer perceptron with linear activation

Single-layer perceptron with ReLU activation ✖

Multi-layer perceptron with linear activation.

None of the above

Submit You have used 2 of 2 attempts

Question 3

1.0/1.0 point (graded)

Which of the following loss function is more robust to outliers?

Mean Square Error

Mean Absolute Error ✔

Both are equivalent

Nothing can be said before training.

Submit You have used 2 of 2 attempts

Question 4

1.0/1.0 point (graded)

Suppose you are solving an image 3-class classification problem. During the data exploration, you found that the ratio of the number of images for classes 0, 1, and 2 is 3:2:1. Which of the following loss function is best suited for the problem?


Root Mean Square

Absolute Error

Cross-Entropy

Cross-Entropy with Weight ✓

Submit You have used 1 of 2 attempts



Question 5

1.0/1.0 point (graded)

If the weight is properly initialized and inputs are normalized (with mean and std), which of the following statement is true?

Sigmoid is more prone to vanishing gradient problem compare to Tanh. ✓

Tanh is more prone to vanishing gradient problem compare to Sigmoid.

Sigmoid and Tanh, both are equally prone to vanishing gradient problem.

Just looking at the above graph and given information, it is not possible to jump to the conclusion.

Submit You have used 2 of 2 attempts

Question 6

0.0/1.0 point (graded)

The input image size is (28, 28, 3) (colored image with RGB channel), and the convolution layers with eight filters that kernel size is (3, 3) with no bias. What is the total number of weights parameters in the convolution layers?


28 x 28 x 3 x 3 x 3 x 8

28 x 28 x 3 x 3 x 8 ✗

3 x 3 x 3 x 8

3 x 3 x 8

Submit You have used 2 of 2 attempts



Question 7

1.0/1.0 point (graded)

We have an input image and two filters, $kernel_a$ and $kernel_b$. The image is convolved through these two filters, and we have two output images corresponds to these two filters.

$$kernel_a = \begin{bmatrix} 1 & 0 & -1 \\ 1 & 0 & -1 \\ 1 & 0 & -1 \end{bmatrix}$$

$$kernel_b = \begin{bmatrix} 1 & 1 & 1 \\ 0 & 0 & 0 \\ -1 & -1 & -1 \end{bmatrix}$$

Which of the following combinations for filters and output images are correct?

$(kernel_a, \text{output image 1})$ and $(kernel_b, \text{output image 2})$ ✓

$(kernel_a, \text{output image 2})$ and $(kernel_b, \text{output image 1})$

$(kernel_a, \text{output image 1})$ and $(kernel_b, \text{output image 1})$

$(kernel_a, \text{output image 2})$ and $(kernel_b, \text{output image 2})$

Submit You have used 2 of 2 attempts

Let's assume the following NumPy arrays:

```
x = [0, 0, 0]

y = [[1],
      [1],
      [1],
      [1]]

z = [[1, 1],
      [1, 1],
      [1, 1],
      [1, 1]]
```

Question 8

0.75/1.0 point (graded)

For the above NumPy arrays - x, y and z, which of the following operations are valid (assuming arrays are broadcastable)?

x + y

y + z

z + x

np.matmul((x+y), z)



Submit

You have used 2 of 2 attempts

Question 9

0.75/1.0 point (graded)

Which of the following operations have learnable parameters?

ReLU

Convolution 2D

Batch Norm

Max Pool



Submit

You have used 2 of 2 attempts

Question 10

0.5/1.0 point (graded)

The two main advantages of Convolutional Networks over Feed Forward networks are

☐ Have fewer parameters☐ Computation speed☐ Translation invariance☐ Rotation invariance

Submit

You have used 2 of 2 attempts

Discussion

[Hide Discussion](#)**Topic:** Quiz 1 / Topic-Level Student-Visible Label[Add a Post](#)

Show all posts ▼

by recent activity ▼

There are no posts in this topic yet. ✕

About Us

[About OpenCV](#)[Privacy](#)[Terms of services](#)

Courses

[Find a course](#)

Contact us

[✉ courses@opencv.org](mailto:courses@opencv.org)

Follow us



© OpenCV - all rights reserved