

1. Write a C program to read an array of 10 integers and count the total number of even and odd elements. Sample Output: Enter 10 integers: 1 2 3 4 5 6 7 8 9 10 Total even numbers: 5 Total odd numbers: 5

```
#include <stdio.h>

int main()
{
    int arr[10];
    int i;
    int even = 0, odd = 0;

    printf("Enter 10 integers: ");

    for (i = 0; i < 10; i++)
    {
        scanf("%d", &arr[i]);
    }

    for (i = 0; i < 10; i++)
    {
        if (arr[i] % 2 == 0)
        {
            even++;
        }
        else
        {
            odd++;
        }
    }

    printf("Total even numbers: %d\n", even);
    printf("Total odd numbers: %d\n", odd);

    return 0;
}
```

```
● PS C:\Users\STUDENT\Desktop\Amit\C> gcc arr.c -o arr
● PS C:\Users\STUDENT\Desktop\Amit\C> ./arr
Enter 10 integers: 1
2
3
4
5
6
7
8
9
10
Total even numbers: 5
Total odd numbers: 5
● PS C:\Users\STUDENT\Desktop\Amit\C> █
```

2. WAP that reads two arrays, calculates the sum of corresponding elements, and stores the result in a third array. Sample Output: Enter 5 elements for the first array: 1 2 3 4 5 Enter 5 elements for the second array: 6 7 8 9 10 Sum of the arrays: 7 9 11 13 15

```
#include <stdio.h>

int main()
{
    int arr1[5], arr2[5], sum[5];
    int i;

    printf("Enter 5 elements for the first array: ");

    for (i = 0; i < 5; i++)
    {
        scanf("%d", &arr1[i]);
    }

    printf("Enter 5 elements for the second array: ");

    for (i = 0; i < 5; i++)
    {
        scanf("%d", &arr2[i]);
    }
}
```

```

    for (i = 0; i < 5; i++)
    {
        sum[i] = arr1[i] + arr2[i];
    }

    printf("Sum of the arrays: ");

    for (i = 0; i < 5; i++)
    {
        printf("%d ", sum[i]);
    }

    return 0;
}

```

```

● PS C:\Users\STUDENT\Desktop\Amit\C> gcc arra.c -o arra
● PS C:\Users\STUDENT\Desktop\Amit\C> ./arra
Enter 5 elements for the first array: 1 2 3 4 5
Enter 5 elements for the second array: 9 8 7 6 5
Sum of the arrays: 10 10 10 10 10
○ PS C:\Users\STUDENT\Desktop\Amit\C> 

```

```

#include <stdio.h>

int main()
{
    int n;
    printf("Enter size of array: ");
    scanf("%d", &n);
    int arr[n];
    printf("Enter %d elements:\n", n);

    for (int i = 0; i < n; i++)
    {
        scanf("%d", &arr[i]);
    }

    printf("Original array:\n");
}

```

```

    for (int i = 0; i < n; i++)
    {
        printf("%d ", arr[i]);
    }

    printf("\nReverse array:\n");

    for (int i = n - 1; i >= 0; i--)
    {
        printf("%d ", arr[i]);
    }

    return 0;
}

```

```
PS C:\Users\STUDENT\Desktop\Amit\C> ./array
```

```

1
2
3
4
5
Original array:
1 2 3 4 5
Reverse array:
5 4 3 2 1

```

```

#include <stdio.h>

int main()
{
    int marks[5];
    int total = 0;
    float average;
    printf("Enter marks of 5 subjects:\n");
    for(int i = 0; i < 5; i++)
    {
        scanf("%d", &marks[i]);
    }
}

```

```
for(int i = 0; i < 5; i++)
{
    total = total + marks[i];
}

average = (float)total / 5;

printf("Total = %d\n", total);
printf("Average = %.2f\n", average);

return 0;
}
```

```
● PS C:\Users\STUDENT\Desktop\Amit\C> gcc marks.c -o marks
● PS C:\Users\STUDENT\Desktop\Amit\C> ./marks
Enter marks of 5 subjects:
1
2
3
4
5
Total = 15
Average = 3.00
```