

Assignment 1

Identify if the following statements can be executed in parallel

Exercise 1

a=1;

b=2;

Exercise 2

a=1;

b=a;

Exercise 3

b = a;

a = 1;

Exercise 4

a = 1;

a = 2;

Exercise 5

for(i=0; i<100;i++)

a[i] = i

Ex 7

for(i=0; i<100; i++) {

a[i] = i;

```
b[i] = 2*i;  
}
```

Ex 8

```
for(i=0;i<100;i++) a[i] = i;  
for(i=0;i<100;i++) b[i] = 2*i;
```

Ex 9

```
for(i=0; i<100; i++)  
a[i] = a[i] + 100;
```

Ex 10

```
for( i=0; i<100; i++ )  
a[i] = f(a[i-1]);
```

Ex 11

```
for(i=0; i<100; i++ )  
for(j=0; j<100; j++ )  
a[i][j] = f(a[i][j-1]);
```

Ex 12

```
for( j=0; j<100; j++ )  
for( i=0; i<100; i++ )  
a[i][j] = f(a[i][j-1]);
```

Ex 13

```
printf("a");
```

```
printf("b");
```

Ex 14

```
a = f(x);
```

```
b = g(x);
```

Ex 15

```
for(i=0; i<100; i++)
```

```
a[i+10] = f(a[i]);
```

Ex 16

```
for( i=1; i<100;i++ ) {
```

```
a[i] = ...;
```

```
... = a[i-1];
```

```
}
```

Ex 17

```
for( i=0; i<100; i++ )
```

```
a[i] = f(a[indexa[i]]);
```

