TECHNICAL EVALUATION REPORT

SIMPLECLEAN WASHING MACHINE

Evaluation reference	991A386D 30 October 2026
Test report evaluated	STUESO0520024332206LM Guangzhou STU Hengchuang Testing Service Co. Ltd Apr.10.2026
Report file	washing_machine_STUESO0520024332206LM.pdf (83 pages)
Product declared	SIMPLECLEAN washing machine, model EC/27FW, 240 V, 50 Hz, 400 W, Class I, Type Y supply-cord attachment.
Standards claimed	IEC 60335-1:2010, IEC 60335-2-7:2012
Standards evaluated	IEC 60335-1:2010 (Part 1); IEC 60335-2-7:2012 (Part 2 2-7)

FINAL VERDICT

REPORT CORRECTION / REPLACEMENT REQUIRED PRODUCT COMPLIANCE NOT DETERMINED CERTIFICATION HOLD

The report does not provide an adequate basis to conclude compliance. It contains incorrect test conditions, contradictory ratings and results, and substantial missing evidence for washing-machine-specific requirements.

Prepared by	Reviewed and approved by	Date
Complify Evaluation Engine	Name / signature: _____	30.10.2026

1. Evaluation Summary

Item	Detail
Report number	STUESO0520024332206LM | Guangzhou STU Hengchuang Testing Service Co. Ltd | Apr.10.2026
Product declared	SIMPLECLEAN washing machine, model EC/27FW, 240 V, 50 Hz, 400 W, Class I, Type Y supply-cord attachment.
Standards claimed	IEC 60335-1:2010, IEC 60335-2-7:2012
Evaluation basis	The supplied US IEC 60335-2-7:2012 cover and national foreword identify a 2012 adoption, but its reproduced IEC title pages and technical text identify IEC 60335-2-7:2008, Edition 7.0 (standard PDF pages 3 6). This evaluation uses the actual technical provisions supplied, applying Part 2 modifications over Part 1. Confirmation or a corrected standard copy is needed before making an edition-specific certification decision.
Final verdict	REPORT CORRECTION / REPLACEMENT REQUIRED PRODUCT COMPLIANCE NOT DETERMINED CERTIFICATION HOLD
Reason	The report does not provide an adequate basis to conclude compliance. It contains incorrect test conditions, contradictory ratings and results, and substantial missing evidence for washing-machine-specific requirements.

2. Report-Validity Decision Points

Priority	Decision point	Finding	Required resolution
P0	Resolve sample identity	240 V/400 W versus 2,500 W versus the photographed 380 V three-phase equipment.	Resolve sample identity: 240 V/400 W versus 2,500 W versus the photographed 380 V three-phase equipment.
P0	Correct and substantiate power and heating tests	, including ambient, load, programme, duration and material-specific temperature limits.	Correct and substantiate power and heating tests, including ambient, load, programme, duration and material-specific temperature limits.
P1	Complete the applicable Part 2 assessment	, particularly overflow/foaming, endurance, interlocks, unbalance and door/lid strength.	Complete the applicable Part 2 assessment, particularly overflow/foaming, endurance, interlocks, unbalance and door/lid strength.
P1	Provide traceable supporting evidence	markings, instructions, schematics, component identification, earthing tests, insulation measurements and heat/fire test records.	Provide traceable supporting evidence: markings, instructions, schematics, component identification, earthing tests, insulation measurements and heat/fire test records.
P1	Reissue consistent verdicts	, replacing unsupported Pass/N/A entries with justified findings.	Reissue consistent verdicts, replacing unsupported Pass/N/A entries with justified findings.

3. Critical Findings

Clause / concern	Report condition	Evaluation comments	Required verdict	Required action	Reference
Incorrect power-input assessment (P1 10.1, P2 10.1)	Declared input is 400 W, but the results table uses 2,500 W rated / 2,580 W measured, while the clause assessment is N/A.	The actual deviation between the table values is +3.2%, not the listed +6.7%, +7.3% or +10.0%. The +20% criterion is also incorrect for a motor-operated appliance above 300 W. For the declared 400 W motor-operated appliance, Table 1 permits +15% or 60 W, whichever is greater: maximum 460 W. The table cannot support the declared model s compliance.	**HOLD / CORRECT**	Correct the assessment and repeat the test under the specified conditions.	PDF pp.2,4,11,77
Heating-test ambient outside the specified conditions (P1 5.7, P2 5.7)	Ambient is 45 C.	P1 specifies 20 5 C, or 23 2 C where the stated doubt conditions apply. P2 does not authorize 45 C. No applicable exception or equivalent-test justification is provided. A higher ambient cannot automatically be substituted for the prescribed method.	**HOLD / CORRECT**	Correct the assessment and repeat the test under the specified conditions.	PDF p.77
Incorrect series-motor overspeed test voltage (P1 19.10)	The test is marked Pass at 1.06 240 V = 254.4 V.	Clause 19.10 requires 1.3 rated voltage for 1 minute at the lowest possible load: 312 V for the declared 240 V rating. If the motor is not a series motor, applicability must instead be corrected and substantiated.	**HOLD / CORRECT**	Correct the assessment and repeat the test under the specified conditions.	PDF p.24
IP marking incorrectly treated as inapplicable (P1 7.1, P2 6.2)	IP marking is N/A and no IP classification is stated.	P2 requires at least IPX4, and P1 requires marking of the water-protection IP number other than IPX0. Thus, the report s N/A assessment is incorrect. Whether the actual appliance carries the required marking remains unverified.	**HOLD / CORRECT**	Correct the assessment and repeat the test under the specified conditions.	PDF p.4
Applicable marking/language requirements excluded or replaced with unrelated text (P1 7.13, 7.14, 7.15, P2 7.15)	Instruction language and positioning of mandatory ratings are N/A.	The entry under 7.14 addresses a hot-surface triangle instead of the required legibility/durability verification. These entries do not correctly assess the supplied standards. No washing-machine amendment in the supplied P2 replaces the durability requirement this way.	**HOLD / CORRECT**	Correct the assessment and repeat the test under the specified conditions.	PDF p.9
Tested appliance identity and electrical configuration are unresolved (P1 7.1, 5.8.1, 5.8.2, P2 1)	Ratings state 240 V, 50 Hz, 400 W; the power table uses 2,500 W; the photograph visibly carries "380V 3Phase" and a three-phase terminal diagram.	Supply/test applicability cannot be established. Provide the tested sample s nameplate, complete photographs and connection details. Also confirm household/similar use rather than exclusively industrial use.	**INSUFFICIENT DETAIL**	Supply/test applicability cannot be established. Provide the tested sample s nameplate, complete photographs and connection details.	PDF pp.2,4,77,83
Normal-operation load and heating duration undocumented (P1 11.1, 11.3, 11.5, 11.8, P2 3.1.9, 11.7)	Clause 11 and its table are N/A, despite populated temperatures and a separate Pass statement.	No textile mass, water quantity/temperature, full-versus-half-load assessment, selected programme or required cycle/rest-period record is supplied. The reported temperatures cannot be accepted as a demonstrated P2 heating test.	**INSUFFICIENT DETAIL**	Provide the missing test records and applicability justification.	PDF pp.12 13,77

Clause / concern	Report condition	Evaluation comments	Required verdict	Required action	Reference
Temperature limits and thermal verdict are unsupported (P1 11.3, 11.8)	Internal-wire rise is 61.9 K, exceeding the report s own stated 35 K limit, yet page 13 states temperatures are within tolerance.	Page 79 separately lists internal wire rated 250 C, making the chosen 35 K criterion unclear. Winding rise is 97.8 K, with an unexplained 120 K limit and no insulation thermal class. Resolve material/rating identification and apply the correct Table 3 limits; do not simply retain the Pass.	**INSUFFICIENT DETAIL**	Resolve material/rating identification and apply the correct Table 3 limits; do not simply retain the Pass.	PDF pp.13,77,79
IPX4 test configuration not demonstrated (P1 15.1, 15.1.1, 15.1.2, P2 6.2)	Generic IPX1 IPX7 entries are marked Pass, but the IPX4 positioning/movement entry is N/A.	No identifiable IPX4 test setup, selected method or supporting inspection record establishes the washing machine s required protection.	**INSUFFICIENT DETAIL**	Provide the missing test records and applicability justification.	PDF pp.4,15 18
Washing-machine spillage/overflow procedure missing (P2 15.2)	Only a generic requirement and Pass appear.	No record identifies manual filling versus automatic filling, the applicable overflow procedure, the required top spill containing salt and rinsing agent, control operation, or the linked post-test insulation results.	**INSUFFICIENT DETAIL**	Provide the missing test records and applicability justification.	PDF pp.18,15
Foaming-resistance test omitted (P2 15.101, 5.3)	No 15.101 assessment is provided.	Evidence is needed for the doubled-detergent, longest-programme cycle, subsequent electric-strength test and prescribed waiting period before humidity treatment.	**INSUFFICIENT DETAIL**	Provide the missing test records and applicability justification.	PDF p.18
Operating-temperature leakage/electric strength not reliably established (P1 13.1, 13.2, 13.3, P2 13.2, 11.7)	The body specifies 1.06 rated voltage for a motor appliance, while the table records "1.15 240V" under heating appliances and leaves the motor/combined supply field blank.	Values 0.23 mA and 0.02 mA are shown, but test conditions and the second measurement path are unclear. No dedicated operating-temperature dielectric results identify application points and voltages.	**INSUFFICIENT DETAIL**	Provide the missing test records and applicability justification.	PDF pp.13 15,77
Door/lid and braking endurance omitted (P2 18.101, 18.102, 5.2, 5.3)	The report moves directly from Clause 17 to Clause 19.	No door/lid endurance assessment is given. Clause 18.101 generally specifies 10,000 opening/closing cycles, increased for drying appliances. Braking endurance under 18.102 must be assessed where its applicability conditions are met. Sample and sequence requirements are also unverified.	**INSUFFICIENT DETAIL**	Provide the missing test records and applicability justification.	PDF pp.20 21
Locked-rotor testing excluded without substantiated exemption (P1 19.7, P2 19.1, 19.7)	Motor abnormal tests and the locked-rotor table are N/A.	P2 exempts motors driving an oscillating agitator from 19.7, not every motor in a washing machine. Motor types, other driven functions and applicable durations must be identified.	**INSUFFICIENT DETAIL**	Provide the missing test records and applicability justification.	PDF pp.21,23,78
Washing-machine fault testing omitted (P2 19.1, 19.101, 19.102, 19.13)	No 19.101 or 19.102 results are supplied.	Establish timer/programmer presence and provide applicable fault simulations. For a cold-water-only appliance without heaters, address the 65 5 C wrong-water-supply test. Textile condition and post-fault interlock compliance are also undocumented.	**INSUFFICIENT DETAIL**	Establish timer/programmer presence and provide applicable fault simulations.	PDF pp.21 29
Electronic-circuit assessment inconsistent (P1 19.11, 19.11.4.8, 22.46)	Electronic fault testing is initially marked Pass, but detailed electronic-circuit and immunity assessments are N/A.	No schematic, low-power justification or protective-function identification resolves this conflict. Determine whether firmware protection and Annex R evaluation are relevant.	**INSUFFICIENT DETAIL**	Determine whether firmware protection and Annex R evaluation are relevant.	PDF pp.21,24 28

Clause / concern	Report condition	Evaluation comments	Required verdict	Required action	Reference
Unbalanced-load and drum-access protection omitted (P2 20.101, 20.102, 20.103, 20.104, 20.105)	Only generic stability/mechanical protection is assessed.	No unbalanced-load results, interlock defeat checks, drum kinetic-energy/peripheral-speed assessment, opening prevention or stopping-time measurements are supplied. Determine applicability from actual machine construction.	**INSUFFICIENT DETAIL**	Determine applicability from actual machine construction.	PDF pp.29 31
Washing-machine door/lid mechanical tests omitted (P2 21.101, 21.101.1, 21.101.2, 21.102, 5.2, 5.3)	General enclosure impact and insulation scratch tests do not replace the additional door/lid tests.	Provide applicable lid impact, door loading and lid-distortion evidence, including required sequence before endurance.	**INSUFFICIENT DETAIL**	Provide applicable lid impact, door loading and lid-distortion evidence, including required sequence before endurance.	PDF pp.31 33
Washing-machine construction safeguards omitted (P2 22.101, 22.102, 22.103, 22.104, 22.105)	No assessments address door opening with elevated water level, textile/heater contact, hot-water discharge from filter compartments, interlock forced-opening resistance, or tool-only access to emergency mechanical release.	Not every item necessarily applies, but none has an adequate applicability assessment.	**INSUFFICIENT DETAIL**	Provide the missing test records and applicability justification.	PDF pp.33 45
Leakage/condensation protection excluded without basis (P1 22.6, P2 22.6)	Clause 22.6 is N/A.	No construction evaluation or modified detergent-solution test is provided, and no Annex BB evidence supports an exemption for relevant liquid-containing parts. That exemption does not generally eliminate condensation protection.	**INSUFFICIENT DETAIL**	Provide the missing test records and applicability justification.	PDF p.35
Required instructions and marking evidence missing (P1 7.1, 7.8, 7.12, 7.12.5, 7.14, 7.15, P2 7.1, 7.12, 7.12.1, 7.15)	No complete nameplate or instructions are attached.	Maximum dry-cloth mass, applicable maximum-water-level/cold-water warning, base-ventilation instruction, general user safety text and Type Y cord-replacement instruction are unverified. Numerous entries concern immersion cleaning, cooking vessels and glass-ceramic surfaces, which are not the supplied P2 washing-machine additions.	**INSUFFICIENT DETAIL**	Provide the missing test records and applicability justification.	PDF pp.4 9,83
Water-mains exclusions unsupported (P1 7.12.8, 22.47, 22.48, 24.7)	All relevant water-mains entries are N/A, but no manual-fill-only construction evidence is supplied.	Confirm connection type; otherwise supply pressure-withstand, backsiphonage, hose-set and instruction evidence as applicable.	**INSUFFICIENT DETAIL**	Confirm connection type; otherwise supply pressure-withstand, backsiphonage, hose-set and instruction evidence as applicable.	PDF pp.8 9,44,52
Safety components insufficiently identified and qualified (P1 24.1, 24.1.3, 24.1.4, P2 24.1.4, 24.101)	Manufacturers/models are "Various," component standards are blank, and generic conformity marks are insufficient to verify the installed components.	Switch testing is stated without endurance evidence. Programmer/interlock endurance requirements are omitted. The 220 V plug rating also needs reconciliation with the 240 V appliance. Identify protection used for the claimed 19.4 Pass and verify non-self-resetting operation where required.	**INSUFFICIENT DETAIL**	Identify protection used for the claimed 19.	PDF pp.48 52,78 79
Supply cord and anchorage verification incomplete (P1 25.1, 25.5, 25.7, 25.8, 25.13, 25.15, 25.17)	Type Y and 3 0.75 mm H05VV-F are declared, but reliable appliance current, cord qualification, appliance mass, applied pull/torque and resulting displacement are absent.	Cord-entry protection is N/A without justification. The conflicting power ratings prevent a reliable cord-sizing conclusion.	**INSUFFICIENT DETAIL**	Provide the missing test records and applicability justification.	PDF pp.3,53 57,78

Clause / concern	Report condition	Evaluation comments	Required verdict	Required action	Reference
Earthing evidence incomplete (P1 27.3, 27.5)	The cord-slip requirement live conductors becoming taut before the earth conductor is N/A despite the Class I cord-connected configuration.	Resistance is recorded as 0.027 , below 0.1 , but source voltage, test current and coverage of accessible earthed parts are absent. The resistance value alone does not establish the complete test.	**INSUFFICIENT DETAIL**	Provide the missing test records and applicability justification.	PDF p.64
Creepage/CTI and solid-insulation assessment missing (P1 29.1, 29.2, 29.3, P2 29.2)	P2 requires pollution degree 3 and CTI 250, unless protection/location justifies the exception.	The report reproduces the general pollution-degree-2 approach without justification and gives no CTI result. Creepage tables contain reference limits but no measured paths/distances. Solid-insulation options are all N/A despite an overall Pass. Clearance entries ">2" and ">3" also lack identified measurement locations.	**INSUFFICIENT DETAIL**	Provide the missing test records and applicability justification.	PDF pp.67 72,79 82
Heat/fire evidence does not substantiate overall Pass (P1 30.1, 30.2.1, 30.2.3.1, 30.2.3.2, 30.2.4, P2 30.2)	Ball-pressure results are blank/N/A despite Pass in the main checklist.	Only a 550 C switch-enclosure glow-wire Pass is populated. Applicable 850 C and 750 C/650 C testing, permitted material alternatives, flame-duration/consequential ignition assessment and PCB needle-flame evidence are not documented. Confirm timer/programmer configuration to select the proper P2 fire-test route.	**INSUFFICIENT DETAIL**	Confirm timer/programmer configuration to select the proper P2 fire-test route.	PDF pp.72 75,82
Permitted electric-shock protection class (P2 6.1)	Class I is a permitted classification.	Sufficiency of its implementation is subject to the missing evidence above.	**PASS WITH EVIDENCE**	Retain evidence with sample traceability.	PDF pp.3 4
Reported Clause 16 leakage measurement (P1 16.2)	0.23 mA at 254.4 V is below both the portable Class I limit of 0.75 mA and the stationary Class I motor-operated limit of 3.5 mA.	This supports the recorded measurement path, not all required paths or conditioning.	**PASS WITH EVIDENCE**	Retain evidence with sample traceability.	PDF p.78
Recorded dielectric test outcomes (P1 16.3)	No breakdown is recorded at 1,250 V input-to-metal-enclosure and 3,000 V input-to-knob; page 20 states the 1-minute, 50/60 Hz procedure.	These voltages align with basic and reinforced insulation respectively for the declared voltage range.	**PASS WITH EVIDENCE**	Retain evidence with sample traceability.	PDF pp.20,78
Starting test exclusion (P2 9)	N/A agrees with P2, which explicitly excludes this clause.	N/A agrees with P2, which explicitly excludes this clause.	**PASS OR JUSTIFIED N/A**	Retain N/A justification.	PDF p.11
Running-overload test exclusion (P2 19.9)	N/A agrees with the supplied washing-machine standard.	It does not justify excluding locked-rotor or other applicable abnormal tests.	**PASS OR JUSTIFIED N/A**	Retain N/A justification.	PDF p.24

4. Part 2-7 Coverage

Clause(s)	Safety area	Report status	Applicability rule	Required report outcome	Risk
10.1	Incorrect power-input assessment	Non-compliant	Applicable per supplied Part 2 unless justified	Correct the assessment and repeat the test under the specified conditions.	Critical
5.7	Heating-test ambient outside the specified conditions	Non-compliant	Applicable per supplied Part 2 unless justified	Correct the assessment and repeat the test under the specified conditions.	Critical
6.2	IP marking incorrectly treated as inapplicable	Non-compliant	Applicable per supplied Part 2 unless justified	Correct the assessment and repeat the test under the specified conditions.	Critical
7.15	Applicable marking/language requirements excluded or replaced with unrelated text	Non-compliant	Applicable per supplied Part 2 unless justified	Correct the assessment and repeat the test under the specified conditions.	Critical
1	Tested appliance identity and electrical configuration are unresolved	Missing evidence	Applicable per supplied Part 2 unless justified	Supply/test applicability cannot be established. Provide the tested sample s nameplate, complete photographs and connection details.	Medium
3.1.9 / 11.7	Normal-operation load and heating duration undocumented	Missing evidence	Applicable per supplied Part 2 unless justified	Provide the missing test records and applicability justification.	Medium
6.2	IPX4 test configuration not demonstrated	Missing evidence	Applicable per supplied Part 2 unless justified	Provide the missing test records and applicability justification.	Medium
15.2	Washing-machine spillage/overflow procedure missing	Missing evidence	Applicable per supplied Part 2 unless justified	Provide the missing test records and applicability justification.	Medium
15.101 / 5.3	Foaming-resistance test omitted	Missing evidence	Applicable per supplied Part 2 unless justified	Provide the missing test records and applicability justification.	High
13.2 / 11.7	Operating-temperature leakage/electric strength not reliably established	Missing evidence	Applicable per supplied Part 2 unless justified	Provide the missing test records and applicability justification.	Medium
18.101 / 18.102 / 5.2 / 5.3	Door/lid and braking endurance omitted	Missing evidence	Applicable per supplied Part 2 unless justified	Provide the missing test records and applicability justification.	High
19.1 / 19.7	Locked-rotor testing excluded without substantiated exemption	Missing evidence	Applicable per supplied Part 2 unless justified	Provide the missing test records and applicability justification.	Medium
19.1 / 19.101 / 19.102 / 19.13	Washing-machine fault testing omitted	Missing evidence	Applicable per supplied Part 2 unless justified	Establish timer/programmer presence and provide applicable fault simulations.	High
20.101 / 20.102 / 20.103 / 20.104 / 20.105	Unbalanced-load and drum-access protection omitted	Missing evidence	Applicable per supplied Part 2 unless justified	Determine applicability from actual machine construction.	High
21.101 / 21.101.1 / 21.101.2 / 21.102 / 5.2 / 5.3	Washing-machine door/lid mechanical tests omitted	Missing evidence	Applicable per supplied Part 2 unless justified	Provide applicable lid impact, door loading and lid-distortion evidence, including required sequence before endurance.	High
22.101 / 22.102 / 22.103 / 22.104 / 22.105	Washing-machine construction safeguards omitted	Missing evidence	Applicable per supplied Part 2 unless justified	Provide the missing test records and applicability justification.	High
22.6	Leakage/condensation protection excluded without basis	Missing evidence	Applicable per supplied Part 2 unless justified	Provide the missing test records and applicability justification.	Medium

Clause(s)	Safety area	Report status	Applicability rule	Required report outcome	Risk
7.1 / 7.12 / 7.12.1 / 7.15	Required instructions and marking evidence missing	Missing evidence	Applicable per supplied Part 2 unless justified	Provide the missing test records and applicability justification.	Medium
24.1.4 / 24.101	Safety components insufficiently identified and qualified	Missing evidence	Applicable per supplied Part 2 unless justified	Identify protection used for the claimed 19.	High
29.2	Creepage/CTI and solid-insulation assessment missing	Missing evidence	Applicable per supplied Part 2 unless justified	Provide the missing test records and applicability justification.	Medium
30.2	Heat/fire evidence does not substantiate overall Pass	Missing evidence	Applicable per supplied Part 2 unless justified	Confirm timer/programmer configuration to select the proper P2 fire-test route.	Medium
6.1	Permitted electric-shock protection class	Compliant	Applicable per supplied Part 2 unless justified	Retain evidence with sample traceability.	Low
9	Starting test exclusion	Not applicable	Applicable per supplied Part 2 unless justified	Retain N/A justification.	Low
19.9	Running-overload test exclusion	Not applicable	Applicable per supplied Part 2 unless justified	Retain N/A justification.	Low

5. Part 1 Corrections

Clause / issue	Evaluation finding	Evaluation comments	Required correction	Final status
19.10	Incorrect series-motor overspeed test voltage	The test is marked Pass at 1.06 240 V = 254.4 V. Clause 19.10 requires 1.3 rated voltage for 1 minute at the lowest possible load: 312 V for the declared 240 V rating. If the motor is not a series motor, applicability must instead be corrected and substantiated.	Correct the assessment and repeat the test under the specified conditions.	**REPORT HOLD**
11.3 / 11.8	Temperature limits and thermal verdict are unsupported	Internal-wire rise is 61.9 K, exceeding the report s own stated 35 K limit, yet page 13 states temperatures are within tolerance. Page 79 separately lists internal wire rated 250 C, making the chosen 35 K criterion unclear. Winding rise is 97.8 K, with an unexplained 120 K limit and no insulation thermal class. Resolve material/rating identification and apply the correct Table 3 limits; do not simply retain the Pass.	Resolve material/rating identification and apply the correct Table 3 limits; do not simply retain the Pass.	**COVERAGE NOT VERIFIED**
19.11 / 19.11.4.8 / 22.46	Electronic-circuit assessment inconsistent	Electronic fault testing is initially marked Pass, but detailed electronic-circuit and immunity assessments are N/A. No schematic, low-power justification or protective-function identification resolves this conflict. Determine whether firmware protection and Annex R evaluation are relevant.	Determine whether firmware protection and Annex R evaluation are relevant.	**COVERAGE NOT VERIFIED**
7.12.8 / 22.47 / 22.48 / 24.7	Water-mains exclusions unsupported	All relevant water-mains entries are N/A, but no manual-fill-only construction evidence is supplied. Confirm connection type; otherwise supply pressure-withstand, backsiphonage, hose-set and instruction evidence as applicable.	Confirm connection type; otherwise supply pressure-withstand, backsiphonage, hose-set and instruction evidence as applicable.	**COVERAGE NOT VERIFIED**

Clause / issue	Evaluation finding	Evaluation comments	Required correction	Final status
25.1 / 25.5 / 25.7 / 25.8 / 25.13 / 25.15	Supply cord and anchorage verification incomplete	Type Y and 3 0.75 mm H05VV-F are declared, but reliable appliance current, cord qualification, appliance mass, applied pull/torque and resulting displacement are absent. Cord-entry protection is N/A without justification. The conflicting power ratings prevent a reliable cord-sizing conclusion.	Provide the missing test records and applicability justification.	**COVERAGE NOT VERIFIED**
27.3 / 27.5	Earthing evidence incomplete	The cord-slip requirement live conductors becoming taut before the earth conductor is N/A despite the Class I cord-connected configuration. Resistance is recorded as 0.027 , below 0.1 , but source voltage, test current and coverage of accessible earthed parts are absent. The resistance value alone does not establish the complete test.	Provide the missing test records and applicability justification.	**COVERAGE NOT VERIFIED**

6. Final Technical Conclusion

The report does not provide an adequate basis to conclude compliance. It contains incorrect test conditions, contradictory ratings and results, and substantial missing evidence for washing-machine-specific requirements. This is not a blanket finding that the physical appliance fails every affected requirement. Where the available evidence is insufficient or contradictory, the classification below is Missing evidence. Non-compliant findings identify demonstrable deficiencies in the reported test method or assessment. Basis: Part 1, Clause 4 requires verification by all relevant tests; Part 2, Clause 4 retains that requirement. The report s omissions and contradictions are detailed below. Return the report for technical correction and supplementary testing; do not rely on it as demonstrated conformity in its current form.

Annex A Clause-by-Clause Register

236 clause rows extracted from the test report. Assessment uses a fixed vocabulary; clauses marked CRITICAL carry a specific verification note.

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
5	GENERAL CONDITIONS FOR THE TESTS	P	REVIEW PARENT	Sub-clause(s) under specific review	PDF p.4
6	CLASSIFICATION		REVIEW PARENT	Sub-clause(s) under specific review	PDF p.4
6.1	Protection against electric shock	P	REPORTED PASS NOT VERIFIED TO EC/27FW	Permitted electric-shock protection class	PDF p.4
6.2	Protection against harmful ingress of water	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: IP marking incorrectly treated as inapplicable; IPX4 test configuration not demonstrated	PDF p.4
7	MARKING AND INSTRUCTIONS		REVIEW PARENT	Sub-clause(s) under specific review	PDF p.4
7.1	Rated voltage or rated voltage range in volts... : 240V	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: IP marking incorrectly treated as inapplicable; Tested appliance identity and electrical configuration are unresolved; Required instructions and marking evidence missing; Required instructions and marking evidence missing	PDF p.4
7.2	Stationary appliances for multiple supply shall	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.5
7.3	Appliances having a range of rated values and	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.5
7.5	For appliances marked with more than one	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.5
7.6	[symbol IEC 60417-5041 (2002-10)] caution, hot	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.5
7.7	Appliances to be connected to more than two	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.6
7.9	Unless it is obviously unnecessary, switches	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.6
7.10	The different positions of switches on stationary 1,2,3,4	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.6
7.11	Controls intended to be adjusted during	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.6
7.12	Instructions for appliances incorporating	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Required instructions and marking evidence missing; Required instructions and marking evidence missing	PDF p.6
7.12.4	The instructions for built-in appliances shall	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.8
7.12.7	The instructions for fixed appliances shall state	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.8
7.12.8	The instructions for appliances connected to the	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Water-mains exclusions unsupported	PDF p.8

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
7.13	Instructions and other text required by this	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Applicable marking/language requirements excluded or replaced with unrelated text	PDF p.9
7.14	The markings requiredHeight of the triangle in	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Applicable marking/language requirements excluded or replaced with unrelated text; Required instructions and marking evidence missing	PDF p.9
7.15	The markings specified in 7.1 to 7.5 shall be on	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Applicable marking/language requirements excluded or replaced with unrelated text; Applicable marking/language requirements excluded or replaced with unrelated text; Required instructions and marking evidence missing; Required instructions and marking evidence missing	PDF p.9
8	PROTECTION AGAINST ACCESS TO LIVE PARTS		VERDICT NOT STATED TO CONFIRM		PDF p.9
8.1	Appliances shall be constructed and enclosed	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.9
8.1.1	The requirement of 8.1 applies for all positions	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.9
8.1.2	Test probe 13 of IEC 61032 is applied with a	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.10
8.1.3	Instead of test probe B and test probe 13, for	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.10
8.1.5	Live parts of built-in appliances, fixed	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.10
8.2	Class II appliances and class II constructions	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.11
9	STARTING OF MOTOR-OPERATED	N/A	REPORTED N/A APPLICABILITY TO CONFIRM	Starting test exclusion	PDF p.11
10	POWER INPUT AND CURRENT		REVIEW PARENT	Sub-clause(s) under specific review	PDF p.11
10.1	If an appliance is marked with rated power input, (see appended table)	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Incorrect power-input assessment; Incorrect power-input assessment	PDF pp.11,77
10.2	If an appliance is marked with rated current, the (see appended table)	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF pp.11,77
11	HEATING	N/A	REVIEW PARENT	Sub-clause(s) under specific review	PDF p.12
11.1	Appliances and their surroundings shall not	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Normal-operation load and heating duration undocumented	PDF p.12
11.3	Temperature rises, other than those of windings.	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Normal-operation load and heating duration undocumented; Temperature limits and thermal verdict are unsupported	PDF p.12
11.4	Heating appliances are operated under normal	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.13

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
11.5	Motor-operated appliances are operated under 1.06 240V=254.4V	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Normal-operation load and heating duration undocumented	PDF p.13
11.6	Combined appliances are operated under	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.13
11.8	During the test, the temperature rises are	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Normal-operation load and heating duration undocumented; Temperature limits and thermal verdict are unsupported	PDF pp.13,77
13	LEAKAGE CURRENT AND ELECTRIC STRENGTH AT OPERATING		REVIEW PARENT	Sub-clause(s) under specific review	PDF p.13
13.1	At operating temperature, the leakage current of	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Operating-temperature leakage/electric strength not reliably established	PDF p.13
13.2	The leakage current is measured by means of (see appended table)	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Operating-temperature leakage/electric strength not reliably established; Operating-temperature leakage/electric strength not reliably established	PDF pp.14,77
13.3	The appliance is disconnected from the supply	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Operating-temperature leakage/electric strength not reliably established	PDF p.14
14	TRANSIENT OVERVOLTAGES	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.15
15	MOISTURE RESISTANCE		REVIEW PARENT	Sub-clause(s) under specific review	PDF p.15
15.1	The enclosure of the appliance shall provide the	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: IPX4 test configuration not demonstrated	PDF p.15
15.1.1	Appliances other than those classified IPXO are	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: IPX4 test configuration not demonstrated	PDF p.16
15.1.2	Hand-held appliances are turned continuously	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: IPX4 test configuration not demonstrated	PDF p.16
15.2	Appliances shall be constructed so that spillage	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Washing-machine spillage/overflow procedure missing	PDF p.18
15.3	Appliances shall be proof against humid	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.18
16	LEAKAGE CURRENT AND ELECTRIC STRENGTH		VERDICT NOT STATED TO CONFIRM		PDF p.18
16.1	The leakage current of the appliance shall not	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.18
16.2	An a.c. test voltage is applied between live parts	P	REPORTED PASS NOT VERIFIED TO EC/27FW	Reported Clause 16 leakage measurement	PDF pp.19,78
16.3	Immediately after the test of 16.2. the insulation	P	REPORTED PASS NOT VERIFIED TO EC/27FW	Recorded dielectric test outcomes	PDF pp.20,78
17	OVERLOAD PROTECTION OF TRANSFORMERS AND ASSOCIATED	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.20
19	ABNORMAL OPERATION	P	REVIEW PARENT	Sub-clause(s) under specific review	PDF p.21

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
19.2	Appliances with heating elements are tested	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.22
19.4	The appliance is tested under the conditions	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.22
19.5	The test of 19.4 is repeated on class 0l	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.22
19.6	Appliances with PTC heating elements are	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.23
19.7	The appliance is operated under stalled	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Locked-rotor testing excluded without substantiated exemption; Locked-rotor testing excluded without substantiated exemption	PDF pp.23,78
19.8	One phase of appliances incorporating	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.24
19.9	A running overload test is carried out on	N/A	REPORTED N/A APPLICABILITY TO CONFIRM	Running-overload test exclusion	PDF p.24
19.10	Appliances incorporating series motors are 1.06 240V=254.4V	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Incorrect series-motor overspeed test voltage	PDF p.24
19.11	Electronic circuits are checked by evaluation of	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Electronic-circuit assessment inconsistent	PDF p.24
19.11.1	Fault conditions a) to g) specified in 19.11.2 are	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.25
19.11.3	If the appliance incorporates a protective	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.26
19.11.4	Appliances having a device with an off position	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.26
19.11.4.1	The appliance is subjected to electrostatic	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.26
19.11.4.2	The appliance is subjected to radiated fields in	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.26
19.11.4.3	The appliance is subjected to fast transient	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.27
19.11.4.4	The power supply terminals of the appliance are	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.27
19.11.4.5	The appliance is subjected to injected currents	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.27
19.11.4.6	For appliances having a rated current not	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.27
19.11.4.7	The appliance is subjected to mains signals in	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.28
19.11.4.8	The appliance is supplied at rated voltage and	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Electronic-circuit assessment inconsistent	PDF p.28

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
19.13	During the tests, the appliance shall not emit	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Washing-machine fault testing omitted	PDF p.28
19.14	Appliances are operated under the conditions of	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.29
19.15	For appliances incorporating a mains voltage	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.29
20	STABILITY AND MECHANICAL HAZARDS		REVIEW PARENT	Sub-clause(s) under specific review	PDF p.29
20.1	Appliances, other than fixed appliances and	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.29
20.2	Moving parts of appliances shall, as far as is	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.30
21	MECHANICAL STRENGTH		REVIEW PARENT	Sub-clause(s) under specific review	PDF p.31
21.1	Appliances shall have adequate mechanical	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.31
21.2	Accessible parts of solid insulation shall have	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.32
22	CONSTRUCTION		REVIEW PARENT	Sub-clause(s) under specific review	PDF p.33
22.2	For stationary appliances, means shall be provided to ensure all-pole	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.33
22.3	Appliances with pins for insertion into	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.34
22.4	Appliances for heating liquids and appliances	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.34
22.5	Appliances intended to be connected to the	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.34
22.6	Appliances shall be constructed so that their	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Leakage/condensation protection excluded without basis; Leakage/condensation protection excluded without basis	PDF p.35
22.7	Appliances containing liquid or gases in normal	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.35
22.8	For appliances having compartments to which	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.35
22.9	Appliances shall be constructed so that parts	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.36
22.10	It shall not be possible to reset	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.36
22.11	Non-detachable parts that protect against	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.36
22.12	Handles. knobs, grips, levers and similar parts	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.37

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
22.13	Appliances shall be constructed so that when	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.38
22.14	Appliances shall have no ragged or sharp	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.38
22.15	Storage hooks and similar devices for flexible	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.38
22.16	Automatic cord reels shall be constructed so	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.38
22.17	Spacers intended to prevent the appliance from	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.39
22.18	Current-carrying parts and other metal parts, the	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.39
22.19	Driving belts shall not be relied upon to provide	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.39
22.20	Direct contact between live parts and thermal	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.39
22.21	Wood. cotton, silk, ordinary paper and similar	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.39
22.22	Appliances shall not contain asbestos.	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.39
22.23	Oils containing polychlorinated biphenyl (PCB)	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.39
22.24	Bare heating elements, other than those in class	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.39
22.25	Appliances shall be constructed so that sagging	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.40
22.26	Appliances having parts of class Ill construction	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.40
22.27	Parts connected by protective impedance shall	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.40
22.28	For class II appliances connected in normal use	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.40
22.29	Class II appliances intended to be permanently	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.40
22.30	Parts of class II construction which serve as	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.40
22.31	Neither clearances nor creepage distances over	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.41
22.32	Supplementary insulation and reinforced	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.41

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
22.33	Conductive liquids that are or may become	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.41
22.34	Shafts of operating knobs. handles, levers and	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.42
22.35	For constructions other than those of class III.	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.42
22.36	For appliances other than those of class III,	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.42
22.37	For class II appliances, capacitors shall not be	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.43
22.38	Capacitors shall not be connected between the	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.43
22.39	Lampholders shall be used only for the	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.43
22.40	Motor-operated appliances and combined	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.43
22.41	Appliances shall not incorporate components,	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.43
22.42	Protective impedance shall consist of at least	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.43
22.43	Appliances which can be adjusted for different	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.44
22.44	Appliances shall not have an enclosure that is	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.44
22.45	When air is used as reinforced insulation. the	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.44
22.47	Appliances intended to be connected to the	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Water-mains exclusions unsupported	PDF p.44
22.48	Appliances intended to be connected to the	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Water-mains exclusions unsupported	PDF p.44
22.49	For remote operation, the duration of operation	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.45
22.50	Controls incorporated in the appliance, if any,	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.45
22.51	A control on the appliance shall be manually	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.45
22.52	Socket-outlets on appliances accessible to the	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.45
23	INTERNAL WIRING		VERDICT NOT STATED TO CONFIRM		PDF p.45
23.1	Wireways shall be smooth and free from sharp	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.45

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
23.2	Beads and similar ceramic insulators on live	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.46
23.3	Different parts of an appliance that can move	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.46
23.4	Bare internal wiring shall be rigid and fixed so	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.47
23.5	The insulation of internal wiring that is subjected	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.47
23.6	When sleeving is used as supplementary	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.47
23.7	Conductors identified by the colour combination	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.47
23.8	Aluminium wires shall not be used for internal	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.48
23.9	Stranded conductors shall not be consolidated	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.48
23.10	The insulation and sheath of internal wiring,	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.48
24	COMPONENTS		REVIEW PARENT	Sub-clause(s) under specific review	PDF p.48
24.1	Components shall comply with the safety	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Safety components insufficiently identified and qualified	PDF pp.48,78
24.1.1	The relevant standard for capacitors likely to be	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.49
24.1.2	The relevant standard for safety isolating	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.50
24.1.5	The relevant standard for appliance couplers is	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.50
24.1.6	The relevant standard for small lampholders	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.50
24.1.7	If the remote operation of the appliance is via a	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.50
24.1.8	The relevant standard for thermal links is IEC	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.50
24.1.9	Contactors and relays, other than motor starting	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.51
24.2	Appliances shall not be fitted with	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.51
24.3	Switches intended to ensure all-pole	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.51

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
24.4	Plugs and socket-outlets for extra-low voltage	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.51
24.5	Capacitors in auxiliary windings of motors shall	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.51
24.6	The working voltage of motors directly	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.52
24.7	Detachable hose-sets for the connection of	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Water-mains exclusions unsupported	PDF p.52
24.8	Motor running capacitors in appliances for which	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.52
25	SUPPLY CONNECTION AND EXTERNAL FLEXIBLE CORDS		REVIEW PARENT	Sub-clause(s) under specific review	PDF p.53
25.2	Appliances, other than stationary appliances for	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.53
25.3	Appliances intended to be permanently	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.53
25.4	For appliances intended to be permanently	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.54
25.8	Conductors of supply cords shall have a	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Supply cord and anchorage verification incomplete	PDF p.54
25.9	Supply cords shall not be in contact with sharp	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.54
25.10	The supply cord of class I appliances shall have	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.54
25.11	Conductors of supply cords shall not be	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.55
25.12	The insulation of the supply cords shall not be	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.55
25.13	Inlet openings for supply cords shall be	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Supply cord and anchorage verification incomplete	PDF p.55
25.14	Appliances provided with a supply cord and that	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.55
25.15	Appliances provided with a supply cord, and	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Supply cord and anchorage verification incomplete	PDF p.56
25.16	Cord anchorages for type X attachments shall	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.57
25.17	For type Y attachment and type Z attachment,	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Supply cord and anchorage verification incomplete	PDF p.57
25.18	Cord anchorages shall be arranged so that they	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.57
25.19	For type X attachment, glands shall not be used	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.57

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
25.20	The insulated conductors of the supply cord for	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.57
25.21	The space for the connection of supply cords	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.58
25.22	Appliance inlets shall	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.58
25.23	Interconnection cords shall comply with the	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.59
25.24	Interconnection cords shall not be detachable	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.59
25.25	The dimensions of pins of appliances that are	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.59
26	TERMINALS FOR EXTERNAL CONDUCTORS		VERDICT NOT STATED TO CONFIRM		PDF p.60
26.1	Appliances shall be provided with terminals or	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.60
26.2	Appliances having type X attachment, except	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.60
26.3	Terminals for type X attachment and those for	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.60
26.4	Terminals for type X attachment, except type X	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.61
26.5	Terminals for type X attachment shall be located	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.61
26.6	Terminals for type X attachment and for the	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.62
26.7	Terminals for type X attachment, other than	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.62
26.8	Terminals for the connection of fixed wiring,	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.62
26.9	Terminals of the pillar type shall be constructed	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.62
26.10	Terminals with screw clamping and screwless	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.62
26.11	For appliances having type Y attachment or	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.63
27	PROVISION FOR EARTHING		REVIEW PARENT	Sub-clause(s) under specific review	PDF p.63
27.1	Accessible metal parts of Class 0I and I	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.63
27.2	Clamping means adequately secured against	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.63

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
27.3	For appliances with supply cord,	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Earthing evidence incomplete	PDF p.64
27.4	No risk of corrosion resulting from contact	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.64
27.5	Low resistance of connection between earthing	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Earthing evidence incomplete	PDF p.64
27.6	The printed conductors of printed circuit boards	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.65
28	SCREWS AND CONNECTIONS		VERDICT NOT STATED TO CONFIRM		PDF p.65
28.1	Fixings. the failure of which may impair	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.65
28.2	Electrical connections and connections	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.66
28.3	Space-threaded (sheet metal) screws shall only	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.66
28.4	Screws and nuts that make a mechanical	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.67
29	CLEARANCES CREEPAGE DISTANCES AND SOLID INSULATION	P	REVIEW PARENT	Sub-clause(s) under specific review	PDF p.67
29.1	Clearances shall not be less than the values	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Creepage/CTI and solid-insulation assessment missing	PDF pp.67,79
29.1.1	The clearances of basic insulation shall be	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.68
29.1.2	Clearances of supplementary insulation shall be	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.68
29.1.3	Clearances of reinforced insulation shall be not	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.68
29.1.4	The clearances for functional insulation are the	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.69
29.1.5	For appliances having higher working voltages	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.69
29.2.1	Creepage distances of basic insulation shall not	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.70
29.2.2	Creepage distances of supplementary	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.70
29.2.3	Creepage distances of reinforced insulation	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.70
29.2.4	Creepage distances of functional insulation	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.71
29.3	Supplementary insulation and reinforced	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Creepage/CTI and solid-insulation assessment missing	PDF p.71

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
29.3.1	The thickness of the insulation shall be at least	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.71
29.3.2	Each layer of material shall withstand the	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.72
29.3.3	The insulation is subjected to the dry heat test	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.72
29.3.4	The thickness of the accessible parts of	N/A	REPORTED N/A APPLICABILITY TO CONFIRM		PDF p.72
30	RESISTANCE TO HEAT AND FIRE		REVIEW PARENT	Sub-clause(s) under specific review	PDF p.72
30.1	External parts of non-metallic material, parts of	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Heat/fire evidence does not substantiate overall Pass	PDF pp.72,82
30.2	Parts of non-metallic material shall be resistant	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Heat/fire evidence does not substantiate overall Pass	PDF pp.72,82
30.2.1	The glow-wire test is also not carried out on	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Heat/fire evidence does not substantiate overall Pass	PDF p.73
30.2.3	Appliances that are operated while unattended	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.74
30.2.3.1	Parts of non-metallic material supporting	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Heat/fire evidence does not substantiate overall Pass	PDF p.74
30.2.3.2	Parts of non-metallic material supporting	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Heat/fire evidence does not substantiate overall Pass	PDF p.75
30.2.4	The base material of printed circuit boards is	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Heat/fire evidence does not substantiate overall Pass	PDF p.75
31	RESISTANCE TO RUSTING	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.76
32	RADIATION, TOXICITY AND SIMILAR HAZARDS	P	REPORTED PASS NOT VERIFIED TO EC/27FW		PDF p.76
29.2	TABLE: Creepage distances, basic, supplementary and reinforced insulation	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Creepage/CTI and solid-insulation assessment missing; Creepage/CTI and solid-insulation assessment missing	PDF pp.79,81