TECHNICAL EVALUATION REPORT

SUBMERSIBLE PUMP

Evaluation reference	3B2E931D — 01 November 2026
Test report evaluated	EN201222034S — EMTEK(NINGBO) CO., LTD. — Dec 28, 2025
Report file	submersible_pump_EN201222034S.pdf (89 pages)
Product declared	Submersible pump
Standards claimed	IEC 60335-1:2010+A1:2013+A2:2016; IEC 60335-2-41:2025 on page 2; IEC 60335-2-41:2012 on page 3
Standards evaluated	IEC 60335-1:2010 (Part 1); IEC 60335-2-41:2021 (Part 2 2-41)

FINAL VERDICT

REPORT CORRECTION / REPLACEMENT REQUIRED — PRODUCT COMPLIANCE NOT DETERMINED — CERTIFICATION HOLD

The tested model and electrical ratings cannot be reconciled with the declared pump, and several applicable safety assessments lack reliable evidence. The claimed 2025 particular standard and Part 1 amendments were not supplied for evaluation.

Prepared by	Reviewed and approved by	Date
Complify Evaluation Engine	Name / signature: _____	01.11.2026

1. Summary

Item	Detail
Report	EN201222034S | EMTEK(NINGBO) CO., LTD. | Dec 28, 2025
Product declared	Submersible pump
Standards claimed	IEC 60335-1:2010+A1:2013+A2:2016; IEC 60335-2-41:2025 on page 2; IEC 60335-2-41:2012 on page 3
Standards evaluated	US IEC 60335-1:2010; IEC 60335-2-41:2012 as endorsed in ILNAS-EN IEC 60335-2-41:2021
Final verdict	REPORT CORRECTION / REPLACEMENT REQUIRED — PRODUCT COMPLIANCE NOT DETERMINED — CERTIFICATION HOLD
Reason	The tested model and electrical ratings cannot be reconciled with the declared pump, and several applicable safety assessments lack reliable evidence. The claimed 2025 particular standard and Part 1 amendments were not supplied for evaluation.
Findings	Critical 5, High 13, Medium 1, Low 0
Evidence check	Report quotes found 19/19; standard quotes found 19/19; not found (needs review) 0
Conclusion	The report does not demonstrate compliance of SPC55068 with the supplied 2010 general requirements and 2012 pump particular requirements. A traceable replacement report, supported by applicable test records and the relevant claimed standards, is required before a certification decision can be made.

2. Findings

'(code)' = the values in this row were also checked by code against the report. Evidence = the AI's verbatim quotes searched by code in the report and standard PDFs; NOT FOUND means the row needs human review.

Severity	Clause	Finding	Reason	Required action	Pages	Evidence
Critical	4; 5.2	SPC55068 is declared, but full testing is stated to have been performed on model 4TSC4.0-96-110/1000. No relationship between the models is established.	The test results cannot be attributed reliably to the declared model.	Provide a replacement report identifying the tested sample and substantiating any model relationship.	PDF pp.2,3	Report: verified p.3 Standard: verified in IEC 60335-1:2010 p.26
Critical	7.1 (code)	The declared rating is 220–240 V, but the marking assessment records 96 V.	The voltage record is inconsistent, preventing identification of the applicable rated-voltage test basis.	Verify the sample marking and correct the rating throughout the report.	PDF pp.2,3,6	Report: verified p.6 Standard: verified in IEC 60335-1:2010 p.29
Critical	10.1 (code)	The declared input is 550 W, but the test table uses 1,000 W at 72 V and records 995.2 W.	The power-input assessment is based on a different rating and voltage; it does not demonstrate compliance for the declared pump.	Test and report power input against the verified rating of SPC55068.	PDF pp.2,3,79	Report: verified p.79 Standard: verified in IEC 60335-1:2010 p.38
Critical	5.8; 11.5; 13.1; 16.2; 19.7	The report records DC supply, 76.3 V for heating and leakage tests, and 116.6 V DC for locked rotor, rather than conditions traceable to the declared 220–240 V, 50 Hz rating.	The specified tests depend on rated supply and voltage; the recorded conditions cannot substantiate the declared rating.	Establish the actual supply and repeat or substantiate the affected tests at the applicable conditions.	PDF pp.2–4, 79–81	Report: verified p.81 Standard: verified in IEC 60335-1:2010 p.41
Critical	4	The photograph page depicts a pump labelled 750 W, whereas the declared model is rated 550 W; the image does not establish tested-sample identity.	The discrepancy further prevents reliable attribution of test evidence to the declared product.	Provide traceable photographs of the tested sample and its actual marking plate.	PDF pp.2–3,88	Report: verified p.88 Standard: verified in IEC 60335-1:2010 p.26
High	5.101; 25.14	Portable and fixed classifications are not established; the portable-pump cord-flexing test is marked N/A without a construction-based justification.	Pumps are tested as portable unless fixed, and applicable portable pumps require the cord-flexing test.	Establish the pump classification and perform the cord-flexing test if applicable.	PDF pp.4,6,43	Report: verified p.43 Standard: verified in IEC 60335-2-41:2021 p.13
High	7.1	The copied marking plate omits maximum operating depth, maximum liquid temperature and IP marking; the report records maximum depth as N/A despite declaring a 550 W submersible pump.	The supplied standards require these markings for the declared classification and rating.	Provide verified markings showing the required depth, liquid temperature and IP designation.	PDF pp.3,4,7	Report: verified p.4 Standard: verified in IEC 60335-2-41:2021 p.14
High	7.12.1	Maximum total head is marked P with a reference to marking detail, but no head value or installation instructions are supplied in the report.	Installation instructions must state maximum total head for pumps exceeding 50 W.	Provide the installation instructions and the verified maximum total head.	PDF pp.3,10	Report: verified p.10 Standard: verified in IEC 60335-2-41:2021 p.14
High	3.1.9; 5.7; 11.7; 19.101	Passing verdicts are given without recorded liquid temperature, total head or actual dry-running test conditions; the summary only states liquid temperature below 45 °C.	Normal operation uses the head producing highest input, and heating and dry-running tests require specified liquid and operating conditions.	Provide the test records identifying liquid temperature, head, duration and sample for each applicable test.	PDF pp.3,6,14,25,79	Report: verified p.3 Standard: verified in IEC 60335-2-41:2021 p.15
High	15.1.2	The immersion test is marked P, but maximum depth and actual pressure are not recorded; the report references 5 m rather than the supplied standard's 15 m alternative.	The 24 h test pressure depends on maximum operating depth and, where applicable, the 15 m alternative.	Document the marked depth and actual immersion pressure and repeat the test if the specified conditions were not met.	PDF pp.4,17	Report: verified p.17 Standard: verified in IEC 60335-2-41:2021 p.16

Severity	Clause	Finding	Reason	Required action	Pages	Evidence
High	24.1.4	The particulars show a self-resetting thermal cut-out, but automatic-control and thermal-motor-protector assessments are marked N/A, with no explanation of whether protection is required for compliance.	Applicable controls require assessment; a thermal motor protector necessary for compliance is tested with its motor.	Identify the cut-out and provide its applicable component and motor-protector assessment.	PDF pp.4,38, 62,82	Report: verified p.4 Standard: verified in IEC 60335-1:2010 p.77
High	24.5; 19.7	The report marks auxiliary-winding capacitor requirements P but marks capacitor open- and short-circuit locked-rotor tests N/A; the component list does not identify a capacitor.	Where an auxiliary-winding capacitor is present, the specified locked-rotor fault tests apply, subject to the stated P2 exception.	Confirm whether an auxiliary-winding capacitor is fitted and provide its identification and applicable test results.	PDF pp.20,40,82	Report: verified p.40 Standard: verified in IEC 60335-1:2010 p.54
High	25.1; 25.3	The general plug row is P, while the specific non-class-III submersible-pump plug and flexible-cord rows are N/A; the particulars do not confirm a fitted plug.	The particular part requires a supply cord fitted with a plug for a non-class-III submersible pump.	Verify and document the supplied cord and plug for the tested pump.	PDF pp.4,40–41	Report: verified p.40 Standard: verified in IEC 60335-2-41:2021 p.19
High	25.7; 25.8	The pump is identified for outdoor use, but cord type, length and conductor cross-section are not recorded; the relevant assessments are N/A.	Outdoor non-class-III submersible pumps have specified cord construction and length requirements, and conductor area is subject to Table 11.	Identify and assess the cord type, length and conductor cross-section against the applicable requirements.	PDF pp.4,42–43	Report: verified p.42 Standard: verified in IEC 60335-2-41:2021 p.19
High	25.10; 27.3; 27.5	The class I pump's green/yellow supply-cord core and conductor arrangement are marked N/A; the earth-continuity row is P without a measured resistance or test current.	Class I earthing and the specified low-resistance verification require evidence for the actual construction.	Document the protective conductor, its arrangement and measured earth-continuity results.	PDF pp.4,43,49	Report: verified p.49 Standard: verified in IEC 60335-1:2010 p.91
High	29.1; 29.2	Clearance and creepage tables assess a 500 V impulse basis and working voltage not exceeding 50 V, inconsistent with the declared 220–240 V rating; material group and measured paths are not identified.	The applicable distances depend on rated impulse voltage, working voltage, pollution degree and material group.	Reassess and record each relevant insulation path using the verified voltage and material data.	PDF pp.2,54, 83–85	Report: verified p.83 Standard: verified in IEC 60335-1:2010 p.97
High	30.1; 30.2	Heat and fire resistance is marked N/A throughout, and the results table is blank, although the component list identifies an insulating bushing. No part-specific exclusion or material evidence is provided.	Relevant insulating and non-metallic parts require assessment; the particular part specifies the applicable fire-test route for pumps.	Assess the relevant parts and provide test results, material evidence or justified exclusions.	PDF pp.55–59,82,87	Report: verified p.55 Standard: verified in IEC 60335-1:2010 p.102
High	4	The report claims IEC 60335-2-41:2025 on page 2 and IEC 60335-2-41:2012 on page 3; the claimed Part 1 amendments are not supplied.	The 2025 particular edition and claimed amendments cannot be checked against the documents supplied.	Provide the claimed editions and amendments and issue a consistent statement of the assessment basis.	PDF pp.2–3	Report: verified p.2 Standard: verified in IEC 60335-2-41:2021 p.8
Medium	29.2	The functional-creepage table continuation bears report number EN200622010S rather than EN201222034S.	The provenance of the continuation page and associated assessment is uncertain.	Replace the page with the verified continuation for this report.	PDF pp.85–86	Report: verified p.86 Standard: verified in IEC 60335-1:2010 p.37