TECHNICAL EVALUATION REPORT

SUBMERSIBLE PUMP

Evaluation reference	F030C9D4 — 31 October 2026
Test report evaluated	EN201222034S — EMTEK(NINGBO) CO., LTD. — 28 December 2025
Report file	submersible_pump_EN201222034S.pdf (89 pages)
Product declared	Submersible pump
Standards claimed	IEC 60335-1:2010+A1:2013+A2:2016; IEC 60335-2-41:2025 on page 2; IEC 60335-2-41:2012 in the conclusion on page 3
Standards evaluated	IEC 60335-1:2010 (Part 1); IEC 60335-2-41:2021 (Part 2 2-41)

FINAL VERDICT

REPORT CORRECTION / REPLACEMENT REQUIRED — PRODUCT COMPLIANCE NOT DETERMINED — CERTIFICATION HOLD

The tested model, ratings and recorded test voltages do not consistently match the declared product. Essential immersion, earthing, cord and heat-and-fire evidence is also missing or inadequately attributable.

Prepared by	Reviewed and approved by	Date
Complify Evaluation Engine	Name / signature: _____	31.10.2026

1. Summary

Item	Detail
Report	EN201222034S | EMTEK(NINGBO) CO., LTD. | 28 December 2025
Product declared	Submersible pump
Standards claimed	IEC 60335-1:2010+A1:2013+A2:2016; IEC 60335-2-41:2025 on page 2; IEC 60335-2-41:2012 in the conclusion on page 3
Standards evaluated	IEC 60335-1:2010; IEC 60335-2-41:2012 as endorsed in EN IEC 60335-2-41:2021
Final verdict	REPORT CORRECTION / REPLACEMENT REQUIRED — PRODUCT COMPLIANCE NOT DETERMINED — CERTIFICATION HOLD
Reason	The tested model, ratings and recorded test voltages do not consistently match the declared product. Essential immersion, earthing, cord and heat-and-fire evidence is also missing or inadequately attributable.
Findings	Critical 8, High 15, Medium 0, Low 0
Gaps	Part 2: 16, Part 1: 0
Conclusion	The report does not demonstrate compliance of SPC55068 against the supplied IEC 60335-1:2010 and IEC 60335-2-41:2012 requirements. No measured product failure is established by the supplied records; a replacement, traceable assessment and the missing claimed standard editions or amendments are required before a compliance decision can be made.

2. Findings

Rows marked 'code' were computed by code from the report values and override the AI text.

Severity	Clause	Finding	Reason	Required action	Pages
Critical	7.1 (code)	Rated voltage: declared rating vs Clause 7.1 marking: Declared rating 220-240 V; Clause 7.1 records 96 V.	Marking entry contradicts the declared rating; the report may describe a different sample.	Provide the actual nameplate and align all ratings across the report.	PDF pp.2,6
Critical	10.1 (code)	Rated power: declared marking vs Clause 10 test basis: Declared rated power input 550 W; Clause 10 table uses 1000 W as rated basis.	Test basis does not correspond to the declared product. Downstream test results cannot be attributed to the declared model until reconciled.	Reconcile rating and tested sample; re-test at the declared rating or document equivalence.	PDF pp.2,6,79
Critical	5.1; 7.1	The declared model is SPC55068, but the test summary identifies the fully tested model as 4TSC4.0-96-110/1000; the photograph depicts a 750 W pump, while the declared rating is 550 W.	Type-test results must be attributable to the appliance under evaluation; no relationship between the models or the pictured pump is established.	Provide a replacement report identifying the tested sample and substantiating its relationship to SPC55068.	PDF pp.1,2,3,88
Critical	7.1	Inconsistent: The declared rating is 220–240 V, 50 Hz, 550 W, but clause 7.1 records 96 V and the particulars state DC.	The required voltage marking and supply characteristics cannot be verified against contradictory records.	Reconcile the actual nameplate, supply type and tested rating in a replacement report.	PDF pp.2,3,4,6,7
Critical	10.1	Inconsistent: The declared rated power is 550 W, but the power-input table uses 1,000 W at 72 V and records 995.2 W.	Clause 10.1 requires measurement against the appliance’s rated power at rated voltage and normal operation; the recorded basis does not establish compliance for the declared rating.	Provide power-input measurements for the identified 550 W sample at the applicable rated-voltage conditions.	PDF pp.2,3,13,79
Critical	5.8.1; 11.5; 11.7	The heating test records 76.3 V, while the declared appliance is rated 220–240 V, 50 Hz; the actual liquid test temperature is not recorded.	Heating must be assessed at the applicable supply conditions and with liquid maintained at the temperature marked on the pump.	Provide heating results and test conditions attributable to the declared sample and its marked liquid temperature.	PDF pp.2,14,79
Critical	19.7; 19.101	The locked-rotor table records 116.6 V DC and 106.3 °C against a stated 240 °C limit; the dry-running test is marked P without its actual test voltage or head.	These tests require operation at rated voltage, and the recorded DC locked-rotor condition does not match the declared 220–240 V, 50 Hz rating.	Provide traceable abnormal-operation records for the declared sample at the applicable rated supply.	PDF pp.2,20,25,81
Critical	5.1	The specification cites IEC 60335-2-41:2025, while the conclusion cites the 2012 edition; the supplied Part 1 does not include the claimed 2013 and 2016 amendments.	The claimed assessment basis is inconsistent and the unavailable editions and amendments cannot be verified against the supplied standards.	Confirm the intended standards and provide the cited editions and amendments with a corrected assessment.	PDF pp.2,3
High	13.2; 16.2	Both leakage tests record 76.3 V and 0.05 mA; their stated limits are 0.35 mA peak and 0.25 mA, respectively, although the appliance is declared class I.	The tests require the applicable voltage and class-dependent leakage assessment; the recorded voltage does not correspond to the declared 220–240 V rating.	Provide leakage-current results at the applicable voltage using the correct class-I assessment.	PDF pp.2,4,15, 18,79,80
High	7.1	The 550 W submersible pump’s maximum operating depth is recorded as N/A, and the marking-plate copy does not show a maximum liquid temperature.	Part 2 requires a maximum operating depth in metres for submersible pumps over 50 W and a maximum liquid temperature of at least 35 °C.	Provide the verified appliance markings and correct the clause verdicts.	PDF pp.3,4,7
High	7.12.1	The maximum total head is marked P with "See marking detail," but no value in metres appears on the supplied marking copy or in the report.	Installation instructions for pumps over 50 W must state the maximum total head.	Provide the applicable installation instructions and record the maximum total head.	PDF pp.3,10
High	15.1.2	The report marks a 24 h immersion and a 1.3-times pressure condition P, but gives no operating depth or actual pressure and refers to 5 m rather than 15 m.	The supplied Part 2 specifies pressure based on operating depth, including 1.3 times the pressure at 15 m if higher, and requires specified water and pump temperatures.	Provide the actual immersion pressure, depth and temperature records and reassess them against Part 2.	PDF pp.4,16,17
High	24.1.3	The photograph shows a float-like device, but level-switch testing is N/A and no switch is identified in the component list.	If the device is a level switch, Part 2 requires 50,000 operating cycles.	Identify the pictured device and provide the applicable level-switch evaluation.	PDF pp.38,82,88

Severity	Clause	Finding	Reason	Required action	Pages
High	24.1.4; 19.7	A self-resetting thermal cut-out is identified, but automatic-control and thermal-motor-protector evaluations are marked N/A.	Applicable control cycling or Annex D testing depends on the device's function and whether it is necessary for compliance; that determination is not recorded.	Identify the protective device and document its compliance evidence or justify the exclusions.	PDF pp.4,38,62
High	24.5; 19.7	The report marks auxiliary-winding capacitor checks P, but the particulars do not identify a motor capacitor, the component list contains none, and capacitor fault tests are N/A.	Where such a capacitor is fitted, its ratings and applicable locked-rotor fault conditions must be assessed.	Clarify whether a capacitor is fitted and provide the applicable component and fault-test evidence.	PDF pp.4,20,40,82
High	25.1; 25.3	The general supply-cord-and-plug entry is P, but the specific class-I submersible-pump plug and flexible-cord entries are N/A; the plug box in the particulars is unchecked.	Part 2 requires a non-class-III submersible pump to have a supply cord fitted with a plug.	Verify the supplied connection and correct the applicable entries.	PDF pp.4,40,41
High	25.7; 25.8	Outdoor use is indicated, but cord type, conductor cross-section and cord length are not recorded and the applicable entries are N/A.	Part 2 specifies cord construction and, for outdoor submersible pumps, a length of at least 10 m or 3 m beyond marked operating depth, whichever is greater; Part 1 specifies minimum conductor area.	Identify and measure the supplied cord and assess it against the applicable requirements.	PDF pp.4,41,42
High	5.101; 25.14	Both portable and fixed classifications are unselected; testing as a portable pump and cord flexing are marked N/A.	Pumps are tested as portable unless fixed, and portable pumps other than the specified exceptions undergo cord-flexing testing.	Establish the pump classification and provide the applicable flexing-test evidence.	PDF pp.4,6,43
High	25.10; 27.3; 27.5	The class-I cord earthing-core and earthing-conductor arrangement are marked N/A; earth continuity is marked P without a measured resistance or test current.	A class-I supply cord requires a green/yellow protective conductor, and earth continuity must be tested with resistance not exceeding 0.1 Ω under the specified conditions.	Provide protective-conductor inspection and earth-continuity test records.	PDF pp.4,43,49
High	29.1; 29.2	The spacing assessment uses a 500 V rated impulse voltage and a working-voltage row of ≤50 V, with basic clearance and creepage reported as >2.0 mm; the declared rating is 220–240 V and pollution degree 3 is recorded.	For category II, Part 1 derives a 2,500 V rated impulse voltage for a 220–240 V rating; creepage depends on the applicable working voltage, pollution degree and material group.	Reassess and document each relevant insulation path using the verified rating, working voltage and material group.	PDF pp.2,54,68,83
High	29.3; 25.13	The report marks the inlet bushing as supplementary insulation and claims compliance by measurement, but gives no insulation thickness and marks the individual assessment routes N/A.	Supplementary insulation must be assessed by an applicable route under 29.3.	Provide the bushing's measured thickness or evidence for another permitted assessment route.	PDF pp.43,54,55
High	30.1; 30.2	Heat and fire resistance are marked N/A and the associated results table is empty, despite an insulating bushing being listed.	Applicable non-metallic parts require heat and fire assessment; Part 2 specifies the applicable fire-test route for pumps.	Identify the relevant parts and provide test or qualifying material evidence for the applicable route.	PDF pp.55–58,82,87
High	29.2	The footer of the final creepage-table page bears report number EN200622010S rather than EN201222034S.	The differing identifier prevents reliable attribution of that page to the report under evaluation.	Replace or authenticate the affected page in a controlled report.	PDF pp.2,86

3. Gaps — standard clauses not covered by the report

Clause lists read by code from the supplied standards and compared with the report's clause table.

Part	Clause	Requirement (from the standard)	Reason	Required action	Pages
Part 2	5.101	Reported N/A: Pumps are tested as portable appliances, unless they are fixed appliances.	The report marks this Part 2 (IEC 60335-2-41:2021) clause N/A without stating why it does not apply.	State why the clause does not apply to this product, or provide the test result.	PDF p.6
Part 2	5.102	Reported N/A: Stationary pumps having a three-phase motor that does not incorporate a protective device are installed with an appropriate device, in accordance with the instructions.	The report marks this Part 2 (IEC 60335-2-41:2021) clause N/A without stating why it does not apply.	State why the clause does not apply to this product, or provide the test result.	PDF p.6
Part 2	15.1.2	Reported N/A: Pumps classified IPX4 are tested with the inlet connected to the outlet by means of a tube filled with water. The pump is supplied at rated voltage and the tube is positioned so th	The report marks this Part 2 (IEC 60335-2-41:2021) clause N/A without stating why it does not apply.	State why the clause does not apply to this product, or provide the test result.	PDF p.16
Part 2	15.3	Reported N/A: Submersible pumps are not subjected to the test.	The report marks this Part 2 (IEC 60335-2-41:2021) clause N/A without stating why it does not apply.	State why the clause does not apply to this product, or provide the test result.	PDF pp.18,65,69
Part 2	19.102	Reported N/A: Pumps marked with a maximum period of operation are supplied at rated voltage and operated under normal operation until steady conditions are established.	The report marks this Part 2 (IEC 60335-2-41:2021) clause N/A without stating why it does not apply.	State why the clause does not apply to this product, or provide the test result.	PDF p.25
Part 2	20.1	Reported N/A: Submersible pumps are not subjected to the test.	The report marks this Part 2 (IEC 60335-2-41:2021) clause N/A without stating why it does not apply.	State why the clause does not apply to this product, or provide the test result.	PDF p.25
Part 2	22.40	Reported N/A: The requirement is not applicable to submersible pumps and vertical wet pit pumps. ILNAS-EN IEC 60335-2-41:2021	The report marks this Part 2 (IEC 60335-2-41:2021) clause N/A without stating why it does not apply.	State why the clause does not apply to this product, or provide the test result.	PDF p.32
Part 2	22.105	Reported N/A: Class I submersible pumps having a plastic enclosure shall be constructed so that leakage of liquid into the motor does not result in a hazard. Compliance is checked by the followi	The report marks this Part 2 (IEC 60335-2-41:2021) clause N/A without stating why it does not apply.	State why the clause does not apply to this product, or provide the test result.	PDF p.34
Part 2	22.106	Reported N/A: Shower-boost pumps shall be constructed so that they can be permanently connected to the water supply. Shower-boost pumps for wall mounting shall be constructed so that they can be	The report marks this Part 2 (IEC 60335-2-41:2021) clause N/A without stating why it does not apply.	State why the clause does not apply to this product, or provide the test result.	PDF p.35
Part 2	24.1.3	Reported N/A: Level switches are subjected to 50 000 cycles of operation.	The report marks this Part 2 (IEC 60335-2-41:2021) clause N/A without stating why it does not apply.	State why the clause does not apply to this product, or provide the test result.	PDF p.38
Part 2	25.3	Reported N/A: Submersible pumps, other than class III pumps, shall be provided with a flexible cord.	The report marks this Part 2 (IEC 60335-2-41:2021) clause N/A without stating why it does not apply.	State why the clause does not apply to this product, or provide the test result.	PDF p.40
Part 2	25.7	Reported N/A: For pumps intended for outdoor use and pumps intended for use in swimming pools, other than class III pumps, the supply cord shall be polychloroprene sheathed or equivalent synthet	The report marks this Part 2 (IEC 60335-2-41:2021) clause N/A without stating why it does not apply.	State why the clause does not apply to this product, or provide the test result.	PDF p.41
Part 2	25.8	Reported N/A: The supply cord of submersible pumps intended for outdoor use, other than class III pumps, shall have a length of 10 m or at least 3 m in excess of the maximum operating depth mark	The report marks this Part 2 (IEC 60335-2-41:2021) clause N/A without stating why it does not apply.	State why the clause does not apply to this product, or provide the test result.	PDF p.42
Part 2	25.14	Reported N/A: Portable pumps, except table fountain pumps and aquarium pumps, are subjected to the test.	The report marks this Part 2 (IEC 60335-2-41:2021) clause N/A without stating why it does not apply.	State why the clause does not apply to this product, or provide the test result.	PDF p.43
Part 2	30	Reported N/A: Resistance to heat and fire	The report marks this Part 2 (IEC 60335-2-41:2021) clause N/A without stating why it does not apply.	State why the clause does not apply to this product, or provide the test result.	PDF p.55

Part	Clause	Requirement (from the standard)	Reason	Required action	Pages
Part 2	30.2	Reported N/A: For submersible pumps if their live parts are completely contained within an enclosure of metal or porcelain and the instructions state that the pump shall be supplied through a re	The report marks this Part 2 (IEC 60335-2-41:2021) clause N/A without stating why it does not apply.	State why the clause does not apply to this product, or provide the test result.	PDF pp.56,62

Annex A — Clause-by-Clause Register

276 clause rows extracted from the test report. Assessment uses a fixed vocabulary; clauses marked CRITICAL carry a specific verification note.

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
5	GENERAL CONDITIONS FOR THE TESTS	P	REVIEW—PARENT	Sub-clause(s) under specific review	PDF p.6
5.7	Temperature of liquid maintained between 0 °C and –	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF pp.6,67,69
5.101	Pumps tested as portable appliances, unless	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Both portable and fixed classifications are unselected; testing as a portable pump and cord flexing are marked N/A.	PDF p.6
5.102	Stationary pumps having a three-phase motor that	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.6
6	CLASSIFICATION	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.6
6.1	Protection against electric shock	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.6
6.2	Submersible pumps are IPX8 (IEC 60335-2-41)	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.6
7	MARKING AND INSTRUCTIONS	P	REVIEW—PARENT	Sub-clause(s) under specific review	PDF p.6
7.1	Rated voltage or voltage range (V) 96	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Rated voltage; The declared model is SPC55068, but the test summary identifies the fully tested model as 4TSC4.0-96-110/1000; the photo; Inconsistent; The 550 W submersible pump's maximum operating depth is recorded as N/A, and the marking-plate copy does not show a maxi	PDF pp.6,60,64,69…
7.2	Warning for stationary appliances for multiple	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.7,78
7.3	Range of rated values marked with the lower and 220-240V	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF pp.7,68,78
7.4	Appliances adjustable for different rated voltages,	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.7,78
7.5	Appliances with more than one rated voltage or one	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.8,78
7.6	Correct symbols used (IEC 60335-2-41)	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF pp.8,60,76
7.7	Connection diagram fixed to appliances to be	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.8
7.8	Except for type Z attachment, terminals for connection to the supply mains indicated P	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.8
7.9	Marking or placing of switches which may cause a	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.8

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
7.10	Indications of switches on stationary appliancesand	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.8
7.11	Indication for direction of adjustment of controls	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.8
7.12	Instructions for safe use provided	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF pp.8,61,69,76
7.12.1	Sufficient details for installation supplied	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: The maximum total head is marked P with "See marking detail," but no value in metres appears on the supplied marking cop	PDF p.9
7.12.2	Stationary appliances not fitted with means for	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.10
7.12.3	Insulation of the fixed wiring in contact with parts	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.10
7.12.4	Instructions for built-in appliances	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.10
7.12.5	Replacement cord instructions, type X attachment	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.11
7.12.6	Caution in the instructions for appliances	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.11
7.12.7	Instructions for fixed appliances stating how the	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.11
7.12.8	Instructions for appliances connected to the water mains	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.11
7.12.9	Instructions specified in 7.12 and from 7.12.1 to	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.11
7.13	Instructions and other texts in an official language English	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.11
7.14	Marking clearly legible and durable, rubbing test as	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.11
7.15	Markings on a main part	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF pp.11,61
7.16	Marking of a possible replaceable thermal link or	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.12
8	PROTECTION AGAINST ACCESS TO LIVE PARTS	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.12
8.1	Adequate protection against accidental contact with	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF pp.12,66
8.1.1	Requirement applies for all positions, detachable	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.12
8.1.2	Use of test probe 13 of IEC 61032, with a force not	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.12

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
8.1.3	For appliances other than class II, use of test	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.12
8.1.4	Accessible part not considered live if	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.12
8.1.5	Live parts protected at least by basic insulation before installation or assembly: P	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.13
8.2	Class II appliances and constructions constructed Class I	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.13,61
9	STARTING OF MOTOR-OPERATED APPLIANCES	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.13
10	POWER INPUT AND CURRENT	P	REVIEW—PARENT	Sub-clause(s) under specific review	PDF p.13
10.1	Power input at normal operating temperature, rated (see appended table)	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Rated power; Inconsistent	PDF pp.13,69,79
10.2	Current at normal operating temperature, rated (see appended table)	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF pp.14,69,79
11	HEATING	P	REVIEW—PARENT	Sub-clause(s) under specific review	PDF p.14
11.1	No excessive temperatures in normal use	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.14
11.2	The appliance is held, placed or fixed in position as	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.14
11.3	Temperature rises, other than of windings,	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF pp.14,66
11.4	Heating appliances operated under normal	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.14
11.5	Motor-operated appliances operated under normal	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: The heating test records 76.3 V, while the declared appliance is rated 220–240 V, 50 Hz; the actual liquid test temperat	PDF pp.14,76
11.6	Combined appliances operated under normal	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.14
11.7	Pumps operated with liquid maintained at	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: The heating test records 76.3 V, while the declared appliance is rated 220–240 V, 50 Hz; the actual liquid test temperat	PDF pp.14,61
11.8	Temperature rises monitored continuously and not (see appended table)	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF pp.15,61,66,69…
13	LEAKAGE CURRENT AND ELECTRIC STRENGTH AT OPERATING	P	REVIEW—PARENT	Sub-clause(s) under specific review	PDF p.15
13.1	Leakage current not excessive and electric strength	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.15
13.2	For class 0, class II and class III appliances, Class I	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Both leakage tests record 76.3 V and 0.05 mA; their stated limits are 0.35 mA peak and 0.25 mA, respectively, although t	PDF pp.15,69,79

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
13.3	The appliance is disconnected from the supply	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF pp.15,79
14	TRANSIENT OVERVOLTAGES	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.16,80
15	MOISTURE RESISTANCE	P	REVIEW—PARENT	Sub-clause(s) under specific review	PDF p.16
15.1	Enclosure provides the degree of moisture	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF pp.16,65
15.1.1	Appliances, other than IPX0, subjected to tests as IP68	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.16
15.1.2	Hand-held appliance turned continuously through	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: The report marks a 24 h immersion and a 1.3-times pressure condition P, but gives no operating depth or actual pressure	PDF p.16
15.2	Spillage of liquid does not affect the electrical	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.17,65
15.3	Appliances proof against humid conditions	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.18,65,69
16	LEAKAGE CURRENT AND ELECTRIC STRENGTH	P	REVIEW—PARENT	Sub-clause(s) under specific review	PDF p.18
16.1	Leakage current not excessive and electric strength	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.18
16.2	Single-phase appliances: test voltage 1,06 times	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: Both leakage tests record 76.3 V and 0.05 mA; their stated limits are 0.35 mA peak and 0.25 mA, respectively, although t	PDF pp.18,69,80
16.3	Electric strength tests according to table 7 (see appended table) P	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF pp.18,66,80
17	OVERLOAD PROTECTION OF TRANSFORMERS	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.19,80
18	ENDURANCE	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.19
19	ABNORMAL OPERATION	P	REVIEW—PARENT	Sub-clause(s) under specific review	PDF p.19
19.1	The risk of fire, mechanical damage or electric	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF pp.19,61,66,76
19.2	Test of appliances with heating elements with	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.20,81
19.3	Test of 19.2 repeated; test voltage (V), power input	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.20,81
19.4	Test conditions as in clause 11, any control limiting	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.20,81
19.5	Test of 19.4 repeated on class 0I and I appliances	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.20,81

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
19.6	Appliances with PTC heating elements tested at	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.20,81
19.7	Stalling test by locking the rotor if the locked rotor	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: The locked-rotor table records 116.6 V DC and 106.3 °C against a stated 240 °C limit; the dry-running test is marked P w; A self-resetting thermal cut-out is identified, but automatic-control and thermal-motor-protector evaluations are marked; The report marks auxiliary-winding capacitor checks P, b	PDF pp.20,81
19.8	Multi-phase motors operated at rated voltage with	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.21,81
19.10	Series motor operated at 1,3 times rated voltage for	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.21,61,81
19.11	Electronic circuits, compliance checked by	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.21
19.11.1	Fault conditions a) to g) in 19.11.2 are not applied to circuits or parts of circuits N/A	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.22
19.11.2	Fault conditions applied one at a time, the appliance operating under conditions N/A	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.22,81
19.11.3	If the appliance incorporates a protective electronic	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.22
19.11.4	Appliances having a device with an off position	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.22
19.11.4.1	The appliance is subjected to electrostatic	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.23
19.11.4.2	The appliance is subjected to radiated fields in	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.23
19.11.4.3	The appliance is subjected to fast transient bursts in	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.23
19.11.4.4	The power supply terminals of the appliance	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.23
19.11.4.5	The appliance is subjected to injected currents in	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.23
19.11.4.6	Appliances having a rated current not exceeding	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.23
19.11.4.7	The appliance is subjected to mains signals in	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.23
19.11.4.8	The appliance is supplied at rated voltage and	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.23,81
19.12	If the safety of the appliance for any of the fault	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.23

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
19.13	During the tests the appliance does not emit flames,	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF pp.24,61,70,76…
19.14	Appliances operated under the conditions of	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.24
19.15	For appliances with a mains voltage selector switch,	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.25
19.101	Pump supplied at rated voltage and operated at	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: The locked-rotor table records 116.6 V DC and 106.3 °C against a stated 240 °C limit; the dry-running test is marked P w	PDF p.25
19.102	Pumps marked with maximum period of operation	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.25
20	STABILITY AND MECHANICAL HAZARDS	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.25
20.1	Appliances having adequate stability	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.25
20.2	Moving parts adequately arranged or enclosed as to	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.25
21	MECHANICAL STRENGTH	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.26
21.1	Appliance has adequate mechanical strength and is	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF pp.26,82
21.2	Accessible parts of solid insulation having strength	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.26
22	CONSTRUCTION	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.26
22.1	Appliance marked with the first numeral of the IP IP68	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.26
22.2	Stationary appliance: means to ensure all-pole disconnection from the supply being N/A	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.26
22.3	Appliance provided with pins: no undue strain on	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.26,62
22.4	Appliance for heating liquids and appliance causing	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.27
22.5	No risk of electric shock when touching the pins of	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.27
22.6	Electrical insulation not affected by condensing	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.27
22.7	Adequate safeguards against the risk of excessive	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.28
22.8	Electrical connections not subject to pulling during	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.28

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
22.9	Insulation, internal wiring, windings, commutators	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.28
22.10	Not possible to reset voltage-maintained	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.28
22.11	Reliable fixing of non-detachable parts that provide	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.28
22.12	Handles, knobs etc. fixed in a reliable manner, if	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.28
22.13	Unlikely that handles, when gripped as in normal	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.29
22.14	No ragged or sharp edges creating a hazard for the	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.29
22.15	Storage hooks and the like for flexible cords smooth	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.29
22.16	Automatic cord reels cause no undue abrasion or	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.29
22.17	Spacers not removable from the outside by hand or	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.29
22.18	Current-carrying parts and other metal parts	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.29
22.19	Driving belts not relied upon to provide the required	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.29
22.20	Direct contact between live parts and thermal	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.29
22.21	Wood, cotton, silk, ordinary paper and fibrous or	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.29
22.22	Appliances not containing asbestos	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.29
22.23	Oils containing polychlorinated biphenyl (PCB) not	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.29
22.24	Bare heating elements, except in class III	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.29
22.25	Sagging heating conductors, except in class III	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.30
22.26	For class III constructions the insulation between	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.30
22.27	Parts connected by protective impedance separated	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.30
22.28	Metal parts of class II appliances conductively	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.30

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
22.29	Class II appliances permanently connected to fixed	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.30
22.30	Parts serving as supplementary or reinforced	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.30
22.31	Neither clearances nor creepage distances over	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.30
22.32	Supplementary and reinforced insulation	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.30
22.33	Conductive liquids that are or may become	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.31
22.34	Shafts of operating knobs, handles, levers etc. not	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.31
22.35	For other than class III constructions, handles,	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.31
22.36	For appliances other than class III, handles	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.32
22.37	Capacitors in class II appliances not connected to	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.32
22.38	Capacitors not connected between the contacts of a	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.32
22.39	Lamp holders used only for the connection of lamps	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.32
22.40	Motor-operated appliances and combined	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.32
22.41	No components, other than lamps, containing	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.32
22.42	Protective impedance consisting of at least two	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.32
22.43	Appliances adjustable for different voltages,	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.32
22.44	Appliances not having an enclosure that is shaped	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.32
22.45	When air is used as reinforced insulation,	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.33
22.46	For programmable protective electronic circuits	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.33
22.47	Appliances connected to the water mains withstand	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.33
22.48	Appliances connected to the water mains	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.33

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
22.49	For remote operation, the duration of operation is to	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.33
22.50	Controls incorporated in the appliance take priority	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.33
22.51	There is a control on the appliance manually	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.33
22.52	Socket-outlets on appliances accessible to the user	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.33
22.53	Class II appliances and class III appliances that	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.33
22.54	Button cells and batteries designated R1 not	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.34
22.56	Detachable power supply part provided with the part	—	VERDICT NOT STATED—TO CONFIRM		PDF p.34
22.57	The properties of non-metallic materials do not	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.34
22.101	Pumps withstand the static pressure occurring in	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.34
22.102	Material of pump not be affected by liquid for which	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.34
22.103	Submersible pumps and vertical wet pit pumps so	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.34
22.104	Submersible pumps and vertical wet pit pumps	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.34
22.105	Class I submersible pumps with plastic enclosure so	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.34
22.106	Shower-boost pumps constructed so that they can be	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.35
23	INTERNAL WIRING	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.35
23.1	Wireways smooth and free from sharp edges	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.35
23.2	Beads etc. on live wires cannot change their	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.35
23.3	Electrical connections and internal conductors	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.35
23.4	Bare internal wiring sufficiently rigid and fixed	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.36
23.5	The insulation of internal wiring subjected to the	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.36

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
23.6	Sleeving used as supplementary insulation on	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.36
23.7	The colour combination green/yellow only used for	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.36
23.8	Aluminium wires not used for internal wiring No aluminium wires	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.36
23.9	Stranded conductors not consolidated by soldering	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.36
23.10	The insulation and sheath of internal wiring,	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.36
24	COMPONENTS	P	REVIEW—PARENT	Sub-clause(s) under specific review	PDF p.36
24.1	Components comply with safety requirements in	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF pp.36,82
24.1.1	Capacitors likely to be permanently subjected to the	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.37
24.1.2	Transformers in associated switch mode power	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.38
24.1.3	Switches complying with IEC 61058-1, the number	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: The photograph shows a float-like device, but level-switch testing is N/A and no switch is identified in the component l	PDF p.38
24.1.4	Automatic controls complying with IEC 60730-1 with the relevant part 2. The number N/A	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: A self-resetting thermal cut-out is identified, but automatic-control and thermal-motor-protector evaluations are marked	PDF p.38
24.1.5	Appliance couplers complying with IEC 60320-1	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.39
24.1.6	Small lamp holders similar to E10 lampholders	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.39
24.1.7	For remote operation of the appliance via a	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.39
24.1.8	The relevant standard for thermal links is	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.39
24.1.9	Contactors and relays, other than motor starting	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.39
24.2	Appliances not fitted with	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.39
24.3	Switches intended for all-pole disconnection of	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.39
24.4	Plugs and socket-outlets for extra-low voltage	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.39

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
24.5	Capacitors in auxiliary windings of motors marked	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: The report marks auxiliary-winding capacitor checks P, but the particulars do not identify a motor capacitor, the compon	PDF p.40
24.6	Working voltage of motors connected to the supply	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.40
24.7	Detachable hose-sets for connection of appliances	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.40
24.8	– the capacitors are of class of safety protection P2	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.40
25	SUPPLY CONNECTION AND EXTERNAL FLEXIBLE CORDS	P	REVIEW—PARENT	Sub-clause(s) under specific review	PDF p.40
25.1	Appliance not intended for permanent connection to fixed wiring, means for	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: The general supply-cord-and-plug entry is P, but the specific class-I submersible-pump plug and flexible-cord entries ar	PDF p.40
25.2	Appliance not provided with more than one means	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.40
25.3	Appliance intended to be permanently connected to fixed wiring provided with one of N/A	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: The general supply-cord-and-plug entry is P, but the specific class-I submersible-pump plug and flexible-cord entries ar	PDF p.40
25.4	Cable and conduit entries, rated current of	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.41
25.5	Method for assembling the supply cord to the appliance	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF pp.41,77
25.6	Plugs fitted with only one flexible cord	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.41
25.7	-Halogen-free, low smoke, thermoplastic insulated and sheathed	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Outdoor use is indicated, but cord type, conductor cross-section and cord length are not recorded and the applicable ent	PDF p.41
25.8	Nominal cross-sectional area of supply cords not	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Outdoor use is indicated, but cord type, conductor cross-section and cord length are not recorded and the applicable ent	PDF p.42
25.9	Supply cords not in contact with sharp points or	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.43
25.10	Supply cord of class I appliances have a	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: The class-I cord earthing-core and earthing-conductor arrangement are marked N/A; earth continuity is marked P without a	PDF p.43
25.11	Conductors of supply cords not consolidated by	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.43
25.12	Insulation of the supply cord not damaged when	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.43
25.13	Inlet openings so constructed as to prevent damage	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: The report marks the inlet bushing as supplementary insulation and claims compliance by measurement, but gives no insula	PDF pp.43,62,77

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
25.14	Supply cords moved while in operation adequately	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Both portable and fixed classifications are unselected; testing as a portable pump and cord flexing are marked N/A.	PDF p.43
25.15	For appliances with supply cord and appliances to	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.44
25.16	Cord anchorages for type X attachments constructed and located so that	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.44
25.17	Adequate cord anchorages for type Y and Z	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.45
25.18	Cord anchorages only accessible with the aid of a	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.45
25.19	Type X attachment, glands not used as cord	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.45
25.20	The insulated conductors of the supply cord for Type Y	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.45
25.21	Space for supply cord for type X attachment or for connection of fixed wiring N/A	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.45
25.22	Appliance inlets	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.45
25.23	– for class III construction, interconnection cords of	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.46
25.24	Interconnection cords not detachable without the	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.46
25.25	Dimensions of pins that are inserted into	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.46
26	TERMINALS FOR EXTERNAL CONDUCTORS	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.46
26.1	Appliances provided with terminals or equally	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.46
26.2	Appliances with type X attachment and appliances	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.46
26.3	Terminals for type X attachment and for connection	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.47
26.4	Terminals for type X attachment, except those	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.47
26.5	Terminals for type X attachment so located or	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.47,77
26.6	Terminals for type X attachment and for connection	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.47
26.7	Terminals for type X attachment, except in class III	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.47

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
26.8	Terminals for the connection of fixed wiring,	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.47
26.9	Terminals of the pillar type constructed and located	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.48
26.10	Terminals with screw clamping and screwless	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.48
26.11	For type Y and Z attachment, soldered, welded, Type Y	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.48
27	PROVISION FOR EARTHING	P	REVIEW—PARENT	Sub-clause(s) under specific review	PDF p.48
27.1	Accessible metal parts of class 0I and I appliances	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.48
27.2	Clamping means of earthing terminals adequately	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.48
27.3	For a detachable part having an earth connection	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: The class-I cord earthing-core and earthing-conductor arrangement are marked N/A; earth continuity is marked P without a	PDF p.49
27.4	No risk of corrosion resulting from contact between	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.49
27.5	Low resistance of connection between earthing	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: The class-I cord earthing-core and earthing-conductor arrangement are marked N/A; earth continuity is marked P without a	PDF p.49
27.6	The printed conductors of printed circuit boards not	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.49
28	SCREWS AND CONNECTIONS	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.49
28.1	Fixings, electrical connections and connections	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF pp.50,82
28.2	Electrical connections and connections providing	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.50
28.3	Space-threaded (sheet metal) screws only used for	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.50
28.4	Screws and nuts that make mechanical connection	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.51
29	CLEARANCES, CREEPAGE DISTANCES AND SOLID INSULATION	P	REVIEW—PARENT	Sub-clause(s) under specific review	PDF p.51
29.1	Clearances not less than the values specified in (see appended table)	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: The spacing assessment uses a 500 V rated impulse voltage and a working-voltage row of ≤50 V, with basic clearance and c	PDF pp.51,83
29.1.1	Clearances of basic insulation withstand the	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.52

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
29.1.2	Clearances of supplementary insulation not less (see appended table)	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.52
29.1.3	Clearances of reinforced insulation not less than (see appended table)	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.52
29.1.4	Clearances for functional insulation are the largest values determined from	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.52
29.1.5	Appliances having higher working voltages than rated voltage, clearances for basic N/A	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.53
29.2	Creepage distances not less than those appropriate (see appended table)	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: The spacing assessment uses a 500 V rated impulse voltage and a working-voltage row of ≤50 V, with basic clearance and c; The footer of the final creepage-table page bears report number EN200622010S rather than EN201222034S.	PDF pp.53,83,85
29.2.1	Creepage distances of basic insulation not less than (see appended table)	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.54
29.2.2	Creepage distances of supplementary insulation at (see appended table)	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.54
29.2.3	Creepage distances of reinforced insulation at least (see appended table)	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.54
29.2.4	Creepage distances of functional insulation not less (see appended table)	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.54
29.3	Supplementary and reinforced insulation have	P	CRITICAL / SPECIFIC REVIEW	CRITICAL: The report marks the inlet bushing as supplementary insulation and claims compliance by measurement, but gives no insula	PDF pp.54,64
29.3.1	Supplementary insulation have a thickness of at	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.55
29.3.2	Each layer of material withstand the electric	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.55
29.3.3	The insulation is subjected to the dry heat test Bb of	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.55
29.3.4	Thickness of accessible parts of reinforced	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.55
30	RESISTANCE TO HEAT AND FIRE	N/A	REVIEW—PARENT	Sub-clause(s) under specific review	PDF p.55
30.1	External parts of non-metallic material,	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Heat and fire resistance are marked N/A and the associated results table is empty, despite an insulating bushing being l	PDF p.55
30.2	Parts of non-metallic material resistant to ignition	N/A	CRITICAL / SPECIFIC REVIEW	CRITICAL: Heat and fire resistance are marked N/A and the associated results table is empty, despite an insulating bushing being l	PDF pp.56,62
30.2.1	Parts of non-metallic material subjected to the	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.56

Clause	Report row / topic	Verdict	Assessment	Required verification	Page
30.2.2	Appliances operated while attended, parts of	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.57
30.2.3	Appliances operated while unattended, tested as	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.57
30.2.3.1	Parts of non-metallic material supporting	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.57
30.2.3.2	Parts of non-metallic material supporting	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF pp.58,77
30.2.4	Base material of printed circuit boards subjected to	N/A	REPORTED N/A—APPLICABILITY TO CONFIRM		PDF p.59
31	RESISTANCE TO RUSTING	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.59
32	RADIATION, TOXICITY AND SIMILAR HAZARDS	P	REPORTED PASS—NOT VERIFIED TO SPC55068		PDF p.59